

8-8-2015

## Small Satellite Verification and Assessment Test Facility with Space Environments Effects Ground-testing Capabilities

Eric Stromberg  
*Utah State University*

Crystal Frazier  
*Utah State University*

Lisa Montierth Phillipps  
*Utah State University*

Alex Souvall  
*Utah State University*

JR Dennison  
*Utah State University*

James S. Dyer  
*Space Dynamics Laboratory, Utah State University*

Follow this and additional works at: [https://digitalcommons.usu.edu/mp\\_presentations](https://digitalcommons.usu.edu/mp_presentations)

 Part of the [Condensed Matter Physics Commons](#)

---

### Recommended Citation

Erik Stromberg, Crystal Frazier, Lisa Phillipps, Alex Souvall, JR Dennison, and James S. Dyer, "Small Satellite Verification and Assessment Test Facility with Space Environments Effects Ground-testing Capabilities," 29th Annual AIAA/USU Conference on Small Satellites, (Logan, UT, August 8-13, 2015).

This Presentation is brought to you for free and open access by the Materials Physics at DigitalCommons@USU. It has been accepted for inclusion in Presentations by an authorized administrator of DigitalCommons@USU. For more information, please contact [digitalcommons@usu.edu](mailto:digitalcommons@usu.edu).



**29<sup>th</sup> Annual AIAA/USU Conference on Small Satellites**

Logan, UT

August 8-13, 2015

***Small Satellite Verification and Assessment Test Facility with Space Environments Effects Ground-testing Capabilities***

Erik Stromberg,<sup>1</sup> Crystal Frazier,<sup>1</sup> Lisa Phillipps,<sup>2,3</sup>  
Alex Souvall,<sup>2,3</sup> JR Dennison<sup>3</sup> and James S. Dyer<sup>1</sup>

<sup>1</sup> *Space Dynamics Laboratory, Utah State University*

<sup>2</sup> *Mechanical Engineering Department, Utah State University*

<sup>3</sup> *Materials Physics Group, Physics Department, Utah State University*

***Abstract***

The Utah State University Space Dynamics Laboratory (SDL) and Materials Physics Group (MPG) have developed an extensive versatile and cost-effective pre-launch test capability for verification and assessment of small satellites, system components, and spacecraft materials. The facilities can perform environmental testing, component characterization, system level hardware in-the-loop testing, and qualification testing to ensure that each element is functional, reliable, and working per its design. Unique capabilities of SDL's Nano-Satellite Operation Verification and Assessment (NOVA) test facility include: (i) mass and moment of inertia testing using a high resolution mass measurement table to determine the center of gravity and an inverted pendulum table; (ii) dynamic magnetic field environment capable of simulating varying magnetic fields and interorbital variations in field strength accomplished using a large Helmholtz cage; (iii) *ex situ* solar simulation and solar array testing using a solar simulator light source; (iv) speed, jitter, and torque measurements of attitude control systems and small satellites weighing <10 kg; (v) attitude control sensor calibration and characterization using a combination of a zero-gauss chamber for magnetometer calibration, an Earth horizon simulator for horizon crossing sensors, and illumination sources for sun/moon recognition sensors; and (vi) communications protocol testing. Additional SDL environmental test facilities for small satellites include: (i) vacuum chambers for simulating the near-vacuum environments of space; (ii) thermal chambers for temperature bakeout and thermal swing characterization; (iii) outgassing measurement capabilities for screening new materials and (iv) a vibration table capable of a suite of sinusoidal and random vibration profiles to simulate environments seen on launch vehicles. Complimentary testing for potential environmental-induced modifications of small satellites, components, and materials are conducted at the MPG's Space Environment Effects Materials (SEEM) test facility in their new Space Survivability Test (SST) high vacuum chamber; this provides long-duration exposure of these elements to simulated space environment conditions. The facility simulates critical environmental components including the neutral gas atmosphere/vacuum, the far UV through near IR solar spectrum, electron plasma fluxes, and temperature with exposure to within <5% uniformity over the area of a cubesat face at intensities for 5X or greater accelerated testing. A Sr<sup>90</sup> β-radiation source produces a high-energy (~100 keV to >2 MeV) spectrum similar to the GEO spectrum for testing of radiation damage, single event interrupts, and COTS parts. An automated data acquisition system periodically monitors and records the real-time environmental conditions—along with *in situ* monitoring of key satellite/component/sample performance metrics and characterization of material properties and calibration standards—during the sample exposure cycle. A wide array of results for a prototypical 1U cubesat—including performance of solar arrays, electronics, sensor and memory components, radiation damage, *basic* communication responses, structural integrity, etc.—acquired at the NOVA and the SST facilities are presented to demonstrate their combined test capabilities.

\*Supported through funding from the USU Space Dynamics IR&D program.