

## New insights into the early reaction of alkali activated slag cements

Puertas, F.<sup>1)</sup>, Gismera, S.<sup>1)</sup>, Alonso, M. M.<sup>1)</sup>, Blanco-Varela, M.T.<sup>1)</sup>, Hoyos-Montilla, A.<sup>2)</sup>, Lanzón, M.<sup>3)</sup>, Moreno, R.<sup>4)</sup>, Lothenbach, B.<sup>5)</sup>, Palacios, M.<sup>1)</sup>

<sup>1)</sup> Eduardo Torroja Institute for Construction Sciences (IETcc-CSIC), C/ Serrano Galvache 4, 28033 Madrid, Spain

<sup>2)</sup> Universidad Nacional de Medellín, 223 Campus Robledo, 050034 Medellín, Colombia

<sup>3)</sup> Universidad Politécnica de Cartagena, Paseo Alfonso XIII 50, 30203 Cartagena, Spain

<sup>4)</sup> Ceramic and Glass Institute (ICV-CSIC), C/ Kelsen 5, Campus Cantoblanco 28049, Madrid, Spain

<sup>5)</sup> EMPA, Überland Str. 129, 8600 Dübendorf, Switzerland

Corresponding author: Palacios, M., email: [marta.palacios@ietcc.csic.es](mailto:marta.palacios@ietcc.csic.es)

In the recent years, there is an increasing interest to reduce the environmental impact of concrete. One of the most studied strategies is the use of Portland clinker-free cement, such as alkali-activated materials, which are obtained by mixing aluminosilicates with a highly alkaline solution. Alkali-activated slag (AAS) cements are reported to have excellent engineering properties and durability, mainly when waterglass (WG) is used as activating solution.

Previous studies have addressed the influence of the composition of the activating solution and slag, on the microstructure of AAS cements, and consequently on the composition and structure of the main hydration product (C-A-S-H) [1], [2]. Most of these studies have been performed on already hardened samples, however, very few have been focused on the first minutes of slag reaction that can affect properties such as rheology of AAS mortars and concrete.

In this study, a deep characterization of the early hydration products of WG-AAS pastes has been performed. WG-AAS pastes have been characterized from 0 to 20 minutes of hydration by different techniques such as laser diffraction, XRD, FTIR, TG-MS, SEM-EDX, nitrogen adsorption or ICP-OES. Moreover, the early hydration has been modelled using the Gibbs free energy minimization program, GEMS. Results have confirmed the formation of an initial C-A-S-H, with an increasing Al content with curing time.

### References

- [1] F. Puertas, M. Palacios, H. Manzano, J.S. Dolado, A. Rico, J. Rodríguez, A model for the C-A-S-H gel formed in alkali-activated slag cements, *J. Eur. Ceram. Soc.* 31 (2011) 2043–2056.
- [2] M. Ben Haha, G. Le Saout, F. Winnefeld, B. Lothenbach, Influence of activator type on hydration kinetics, hydrate assemblage and microstructural development of alkali activated blast-furnace slags, *Cem. Concr. Res.* 41 (2011) 301–310.