

GROUND IMPROVEMENT FOR RING BEAM TANK FOUNDATION  
COMPARED BETWEEN VIBRO REPLACEMENT AGAINST COMBINATION  
OF DYNAMIC TECHNIQUES WITH NUMERICAL MODELS

ADIL KHAN

A project report submitted in partial fulfillment of the  
requirements for the award of the degree of  
Master of Engineering (Geotechnics)

School of Civil Engineering  
Faculty of Engineering  
Universiti Teknologi Malaysia

DECEMBER 2019

## **DEDICATION**

This thesis is dedicated to my father, who taught me that the best kind of knowledge to have is that which is learned for its own sake. It is also dedicated to my mother, who taught me that even the largest task can be accomplished if it is done one step at a time.

## **ACKNOWLEDGEMENT**

First and foremost, all praises be to Allah S.W.T., the Almighty. In preparing this thesis, I was in contact with many people, researchers, academicians, and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my thesis supervisor, Professor Dr. Nazri Ali, for encouragement, guidance, critics and friendship. Without his continued support and interest, this thesis would not have been the same as presented here.

## **ABSTRACT**

Construction of large tanks are often carried out implementing a ring beam foundation. Majority of the load is transferred the ground, therefore, in areas of poor ground conditions, additional measures are taken to avoid geotechnical failure. Various methods exist for ground improvement, however, techniques such as piling and Vibro-Replacement are commonly implemented, due to their deep depth of improvement and flexibility of applicability for a wide range of soil profiles. However, alternative techniques may be implemented which could prove more efficient and even cost effective. Dynamic techniques, due to their fast rate of production, reduced operation costs and impressive efficiency prove as viable options. But since dynamic techniques have limitations with soil type and depth of improvement, for stratified geotechnical profiles, they may only be carried out in a combination with one another, which may deter engineers for opting to implement them. In the current study, the efficiency of ground improvement for a ring beam tank foundation shall be compared between Vibro-Replacement against combination of dynamic techniques with numerical models, to provide an insight between their capabilities and preliminary cost estimations shall also be carried out to a lesser extent to get an idea of the economic factors that affect decision making for ground improvement operations.

## ABSTRAK

Pembinaan tangki besar adalah berkait rapat dengan pelaksanaan asas alang cincin. Oleh sebab kebanyakan bebanan akan disalurkan ke permukaan tanah, pada permukaan tanah yang berkeadaan tidak baik, langkah keselamatan tambahan akan diambil bagi mengelakkan dari berlakunya kegagalan secara geoteknikal. Terdapat banyak kaedah bagi pembaikpulihan tanah, akan tetapi, teknik pencerucukan (piling) dan Vibro-Replacement adalah teknik yang biasanya dilakukan disebabkan kedalaman pembaikpuliannya yang tinggi dan fleksibiliti kebolehgunaannya untuk pelbagai jenis profil tanah. Walau bagaimanapun, teknik alternatif lain juga boleh digunapakai memandangkan terbuhtinya lebih efisien dan lebih kos efektif. Teknik dynamic menjadi pilihan yang baik kerana ia memberi kesan kepada kadar produksi yang lebih tinggi, pengurangan kos operasi dan bukti kecekapan yang mengagumkan. Akan tetapi, memandangkan teknik dynamic mempunyai kelemahan pada jenis tanah dan kedalaman pembaikpulihan, bagi profil geoteknikal berstrata, ianya hanya dilakukan dengan gabungan teknik lain, menyebabkan ahli jurutera tidak memilih untuk menggunakan teknik ini. Dalam penyelidikan semasa, kadar kecekapan bagi pembaikpulihan tanah dengan pelaksanaan asas alang cincin perlu dibandingkan antara Vibro-Replacement dan kombinasi teknik dynamic serta model berangka untuk memberi gambaran tentang kebolehan dan anggaran kos permulaan perlu dilaksanakan bagi memberi idea akan faktor ekonomikal yang memberi impak untuk membuat keputusan dalam operasi pembaikpulihan tanah.

## TABLE OF CONTENTS

	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	<b>iii</b>
	<b>DEDICATION</b>	<b>iv</b>
	<b>ACKNOWLEDGEMENT</b>	<b>v</b>
	<b>ABSTRACT</b>	<b>vi</b>
	<b>ABSTRAK</b>	<b>vii</b>
	<b>TABLE OF CONTENTS</b>	<b>viii</b>
	<b>LIST OF TABLES</b>	<b>xi</b>
	<b>LIST OF FIGURES</b>	<b>xii</b>
	<b>LIST OF ABBREVIATIONS</b>	<b>xiv</b>
	<b>LIST OF APPENDICES</b>	<b>xv</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Overview	1
	1.2 Background	2
	1.3 Problem Statement	3
	1.4 Aims and Objectives of the Study	3
	1.5 Scope of the Study	4
	1.6 Hypothesis of the Study	4
<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	<b>5</b>
	2.1 Introduction	5
	2.2 Suitability of Improvement Technique	5
	2.3 Description of Improvement Techniques considered	6
	2.3.1 Dynamic Compaction	7
	2.3.2 Rapid Dynamic Compaction	8
	2.3.3 Dynamic Replacement	9
	2.3.4 Vibro-Replacement (or Stone Columns)	10
	2.4 Design of Improvement Works	12

2.5	Expected degree of improvement from compaction works	14
2.6	Ring Beam Foundation for Large Tanks	15
2.7	Summary of important previous studies	17
2.8	Preliminary Assessment of Design Criteria	18
2.9	Basis of the Spreadsheet	18
2.9.1	Ground Improvement Reinforcement Parameters	18
2.9.2	Assessment Sheet Estimations	20
2.10	Three Dimensional Numerical Modelling	22
2.10.1	PLAXIS software for Finite Element Modelling	22
<b>CHAPTER 3</b>	<b>METHODOLOGY</b>	<b>23</b>
3.1	Introduction	23
3.2	Stages of the Study	23
3.2.1	Initial Review of the Present Literature	24
3.2.2	Study Definition and Planning	24
3.2.3	Main Literature Review	24
3.2.4	Data Collection	24
3.2.5	Preliminary Assessment	25
3.2.6	Approximate Cost Estimations	25
3.2.7	Numerical Modeling	25
3.2.8	Results Generation and Analysis	25
3.3	Geotechnical Profile	26
3.4	Methodology of Construction	28
3.5	Pre-modeling Stage	32
3.6	Generation of Numerical Models	32
3.7	Working Schedule	33
<b>CHAPTER 4</b>	<b>DATA COLLECTION</b>	<b>35</b>
4.1	Introduction	35
4.2	In-depth Interview Candidates	35
4.3	Important Information gained In-depth Interviews	36
4.3.1	In-depth Interview with Louai Al-Jannoun	36
4.3.2	In-depth Interview with Syed Muhammad Ali	37

<b>CHAPTER 5</b>	<b>ANALYSIS</b>	<b>41</b>
5.1	Introduction	41
5.1.1	Empirical Assessment Sheet	41
5.2	Analysis of Design Criteria	42
5.2.1	Deduction of Operation Parameters	47
5.2.2	Achievement of Design Criteria assessed by Empirical Methods	50
5.2.3	Achievement of Design Criteria assessed by Finite Element Method	50
5.3	Economic Analysis of performing Improvement Strategies	54
5.3.1	Case 1: Combination of Dynamic Techniques Project Cost	54
5.3.2	Case 2: Improvement primarily by Vibro-Replacement Project Cost	56
5.3.3	Project Duration Analysis	57
<b>CHAPTER 6</b>	<b>RESULTS</b>	<b>61</b>
6.1	Introduction	61
6.2	Techniques Operations Parameters Determination	61
6.3	Design Criteria Achievement Analysis Results	62
6.4	Results of Economic Analysis and Project Time Duration	64
<b>CHAPTER 7</b>	<b>CONCLUSION</b>	<b>67</b>
<b>REFERENCES</b>		<b>69</b>



## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Table 2.1	Suitability of soil type and typical energy required for Dynamic Compaction (Hussin, 2006)	12
Table 2.2	Typical Energy Applied for Rapid Dynamic Compaction (Han, 2015)	13
Table 2.3	Previous studies and important aspects observed	17
Table 2.4	Vibro-Replacement Parameters Boundary Limit Values	19
Table 2.5	Dynamic Replacement Parameters Boundary Limit Values	19
Table 4.1	Rates for items involved in the study as gained from the interviews	38
Table 5.1	Material Properties Taken	43
Table 5.2	Reinforcement Layers Material Properties Taken	45
Table 5.3	Roller Compaction Parameters (Kadivar, 2016)	49
Table 5.4	Empirical Analysis Results	50
Table 5.5	Points of Interest Selected for Analysis	51
Table 5.6	Summary of Induced Settlements from modelling results	52
Table 5.7	Verification of Design Criteria from Plaxis 3D Results	53
Table 5.8	Summary of Project Cost for Case 1 Project	55
Table 5.9	Summary of Project Cost for Case 2 Project	57
Table 6.1	Parameters for Compaction based Improvement Techniques	61
Table 6.2	Parameters for Inclusion based Improvement Techniques	62
Table 6.3	Parameters for Roller Compaction	62
Table 6.4	Parameters for Hydraulic Excavation	62
Table 6.5	Results of Empirical Analysis	63
Table 6.6	Results of Finite Element Analysis	63

## LIST OF FIGURES

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 2.1	Compatibility of techniques based on soil type (Han, 2015)	5
Figure 2.2	Improvement technique suggestion based on soil type and depth of improvement (Braiek, 2017)	6
Figure 2.3	Dynamic Compaction Sketch (Hussin, 2006)	7
Figure 2.4	Square Pattern of Impact Points (Han, 2015)	7
Figure 2.5	Rapid Dynamic Compaction Schematic (Han, 2015)	9
Figure 2.6	Dynamic Replacement Operation (Han, 2015)	10
Figure 2.7	Vibro-Replacement Operation (Han, 2015)	11
Figure 2.8	Tank with Ring Beam Foundation and structural elements relevant to current study as understood from Shockley and Borov (2010)	15
Figure 2.9	Tank modes of failure (Hamidi et al., 2017)	16
Figure 3.1	Summary of the steps to be carried out in the current study	26
Figure 3.2	Geotechnical Soil Profile for the current study	27
Figure 3.3	Chart illustrating the sequence of operations for dynamic techniques	29
Figure 3.4	Chart illustrating the sequence of operations for Vibro-Replacement	31
Figure 3.5	Pre-modelling planning	32
Figure 3.6	Work sequence	33
Figure 3.7	Work schedule	33
Figure 5.1	Assessment when no deep improvement is applies	42
Figure 5.2	Sample of Geometry Model and Displacement Model (Case 1)	50
Figure 5.3	Bearing Pressure vs Settlement charts for both models	52
Figure 5.4	Dynamic Replacement Improvement Plan	54
Figure 5.5	Vibro-Replacement Improvement Plan	56
Figure 5.6	Case 1: Project Duration Chart	58
Figure 5.7	Case 2: Project Duration Chart	59
Figure 6.1	Combination of Dynamic Techniques Project Duration Gantt Chart	65



## LIST OF ABBREVIATIONS

E.G.L.	-	Existing Ground Level
F.B.L.	-	Foundation Base Level
V.R.	-	Vibro-Replacement
D.R.	-	Dynamic Replacement
D.C.	-	Dynamic Compaction

## LIST OF APPENDICES

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
Appendix A	Boussinesq Partial Factors	73
Appendix B	Empirical Assessment Results	75
Appendix C	Plaxis 3D Results	78
Appendix D	Informed Consent Form	82
Appendix E	Interview Transcripts	84

# CHAPTER 1

## INTRODUCTION

### 1.1 Overview

In countries with abundance of soft/compressible soil profiles, a great demand for ground improvement exists. Prior to any construction work, geotechnical properties of the ground are assessed to verify its capability of sustaining loads after construction. In the case of a storage tank, however, the geotechnical properties are critical during different stages of storage and operation which shall be discussed in upcoming chapters. The crucial aspect is that the ground should sustain the tanks during these stages and if geotechnical properties are deemed insufficient or poor, ground improvement must be carried out. Many improvement techniques of different types exist and it is not uncommon to opt for a combination of improvement techniques. A prominent method of improvement is stone columns or Vibro-Replacement, as will be detailed in further chapters, it can be implemented on almost all soil types which makes it a commonly chosen technique over others. Alternative techniques such as Dynamic Compaction, Rapid Dynamic Compaction and Dynamic Replacement, have limitations with either depth or soil type, but, in a combination these dynamic techniques can carry out the improvement as well (Han, 2015). In the current study, improvement implementing Vibro-Replacement shall be compared against a combination of dynamic techniques for the rehabilitation of a ground where a storage tank placed on a ring beam foundation shall rest. Detailed aspects of all techniques involved, such as operation parameters and expected improvement, shall be deduced with viable justifications. Improvement efficiency for both strategies shall be analyzed primarily and economic factors (in terms of overall project cost and duration) shall be discussed lightly.

## 1.2 Background

Large storage of liquids in fields such as petrochemical, oil and gas industry or reverse osmosis sewage treatment plants, prompt the construction of large tanks. Apart from the load of the structure, the foundation design should take into consideration the tank liquid load, wind and seismic loads. Only a fraction of the load (approximately 10% of the tank shell load), is received by the foundation and the majority of the bearing pressure is directly transferred to the ground and therefore, the ground must be competent enough to sustain the load. The total settlement, differential settlement and edge settlement are common criteria that should be assessed by the geotechnical engineer to ensure constructability and avoid failure (Nagesh and Sasidhar, 2017).

To improve the engineering properties of the ground, many methods and techniques exist, depending on the soil type, economic factors or just personal preference. For the purpose of the current study, ground improvement implementing a single technique i.e. Vibro-Replacement shall be compared against a combination of dynamic techniques, in terms of efficiency and economic factors for the improvement of a ground on which a ring beam foundation shall be constructed.

Realistic geometry are well represented implementing Finite Element Method (FEM). With the ability to work with general boundary conditions and account for heterogeneous and anisotropic material properties, it increases the reliability and accuracy of the method. This implies that arbitrary shapes (which are more representative of real world geometry) can be made up of combined continuum of different material property regions i.e. property of inter-connected elements would vary with spatial location similar to what would be found in a natural setting (Akin, 2005). Owing to the attractive qualities of FEM, numerical models shall be used to perform deformation analysis and estimate settlements more accurately, using the software PLAXIS.

### **1.3 Problem Statement**

Failure of large tanks due to settlement are dictated by the ground, as it takes the load that is transmitted to it (Nagesh and Sasidhar, 2017). In an attempt to avoid failure, ground improvement proves a cost-effective method, as opposed to deep foundation or conventional excavation and replacement, especially if the thickness of soft soil is substantial (Braiek, 2017). Vibro-Replacement, due to being compatible with a large range of soils and deep improvement depth is a commonly chosen improvement technique. As shall be detailed in later chapters, improvement can be carried out in multiple ways implementing multiple techniques, but it is difficult to find a technique as material flexible and deep improvement as Vibro-Replacement. However, a combination of other techniques, like dynamic techniques, may be carried out in multiple stages and due to their low cost, cheap operations (no requirement of electricity or water), ease to use and higher energy implemented (Han, 2015; Hussin, 2006), may actually prove more efficient and cost effective compared to Vibro-Replacement technique. In the current study a comparative analysis shall be drawn.

### **1.4 Aims and Objectives of the Study**

The aim of current study is to assess and compare the performance of Vibro-Replacement against a combination of dynamic techniques in improvement of a ground for a large tank with ring beam foundation. Thus, the objectives of current study shall be as given below.

- a) Design ground improvement operations for both Vibro-Replacement and combination of dynamic techniques for ground improvement for a large tank with a ring beam foundation.
- b) Compare the efficiency of both operations in achieving the design criteria.
- c) Assess the economic factors and compare approximate cost estimates for carrying out both operations.



## **1.5 Scope of the Study**

To achieve the aim and objectives mentioned in Section 1.4, the scope of the study shall involve the tasks mentioned below.

- a) Defining improvement parameters which involve, grid spacing, number of pillars to construct (for ground reinforcement techniques) and energy parameters (more prominent in dynamic techniques which involve height of drop, weight of drop, etc.).
- b) Preliminary assessment using empirical methods to assess technique suitability.
- c) Numerical Models made using PLAXIS to verify design criteria.
- d) Comparison between both operations in terms of efficiency in reducing settlement and discussion regarding economic factors with rough estimated costs of both operations.

## **1.6 Hypothesis of the Study**

An analysis of the performance of ground improvement carried out by Vibro-Replacement and combination of dynamic techniques will aid in understanding the efficiency of both techniques when implemented for a large tank ring beam foundation. With results from both operations, a comparison can be drawn and acquiring data regarding costs will also enhance existing knowledge regarding economic factors and cost effect from carrying out both operations for a similar scenario which can aid in understanding decision making for choosing techniques implemented in ground improvement operations.

## REFERENCES

- Al-Jannoun, L. Interviewed by: Khan, A. (21<sup>st</sup> August 2019)
- Ali, M. Interviewed by: Khan, A. (1<sup>st</sup> September 2019)
- Akin, J. E. (2005). *Finite Element Analysis With Error Estimators: An Introduction to the FEM and Adaptive Error Analysis for Engineering Students*. Butterworth-Heinemann.
- American Petroleum Institute (1998). *API Standard 650: Welded Steel Tanks for Oil Storage*. American Petroleum Institute.
- Braiek, A. (2017). Cost effective solution for improving highly heterogeneous soil. In: *19th International Conference on Soil Mechanics and Geotechnical Engineering*. Seoul.
- Bouassida, M., & Said, I. (2010). About estimation of settlement by the oedometric and pressuremeter methods, 2nd Int. Conf. on Geotech. Eng. *October 25-27, Hammamet-Tunisia, 1*, 777-786.
- Brinkgreve, R. B. J., Kumarswamy, S., Swolfs, W. M., Waterman, D., Chesaru, A., & Bonnier, P. G. (2016). Plaxis 2014. *PLAXIS bv, the Netherlands*.
- Brinkgreve, R. B. J., Swolfs, W. M., Engin, E., Waterman, D., Chesaru, A., Bonnier, P. G., & Galavi, V. (2010). *PLAXIS 2D 2010. User manual Part 3: PLAXIS Material Models CONNECT Edition V20, Plaxis bv*.
- CEN (2004). EN 1997-1:2004. *Eurocode 7 Geotechnical design - Part 1: General rules*. Brussels, European Committee for Standardization.
- CEN (2007). EN 1997-1:2007. *Eurocode 7 Geotechnical design - Part 2: Ground investigation and testing*. Brussels, European Committee for Standardization.
- Cividini, A. (2014). *Application of Numerical Methods to Geotechnical Problems*. Vienna: Springer Wien.
- Cheng, X., Chen, W., Jing, W., Yin, C. and Shi, A. (2015). Influence of Area Replacement Ratio on Settlement and Stability of Oil Storage Tank Composite Foundation Treated With Compaction Piles. *Electronic Journal of Geotechnical Engineering*, 20.
- Chu, J., Varaksin, S., Klotz, U., & Mengé, P. (2009). Construction processes. In *Proceedings of the International Conference on Soil Mechanics and Geotechnical Engineering, Alexandria, Egypt*.

- Das, B. and Sobhan, K. (2018). *Principles of geotechnical engineering*. 9th ed. Boston: Cengage Learning.
- Han, J. (2015). *Principles and Practice of Ground Improvement*. Hoboken: Wiley.
- Hamidi, B., & Varaksin, S. (2017). Ground Improvement of Tank Foundations in the Middle East. In *International Congress and Exhibition" Sustainable Civil Infrastructures: Innovative Infrastructure Geotechnology"* (pp. 194-209). Springer, Cham.
- Helwany, S. (2007). *Applied soil mechanics with ABAQUS applications*. John Wiley & Sons.
- Hussin, James D. (2006). "Methods of Soft Ground Improvement." *The Foundation Engineering Handbook*: pp. 529-565.
- Kadivar, H. (2016). Case Study on Output/Productivity of Pneumatic Tired Vibratory Roller (Earth Compaction Equipment) under Different Job and Management Conditions. *International Journal of Science Technology & Engineering*, 03(04).
- Killeen, M. M., & McCabe, B. A. (2014). Settlement performance of pad footings on soft clay supported by stone columns: a numerical study. *Soils and Foundations*, 54(4), 760-776.
- Kirsch, F., & Kirsch, K. (2016). *Ground improvement by deep vibratory methods*. CRC Press.
- Limsiri, C. (2008). *Very soft organic clay applied for road embankment*. Leiden: Taylor & Francis.
- Lukas, R. G. (1995). Geotechnical Engineering Circular No. 1: Dynamic Compaction. Washington: U.S. Department of transportation.
- Mostafa, K. (2010). *NUMERICAL MODELING OF DYNAMIC COMPACTION IN COHESIVE SOILS*. Ph.D. University of Akron.
- Nagesh, D. and Sasidhar, C. (2017). Design and Analysis of Tank Ring Wall Foundation by using STAAD Pro V8i. *International Journal of Scientific Research in Science and Technology*, 3(8), pp.1264-1266.
- Narayanan, P. S., & Jeyapriya, S. P. (2015). Numerical Modeling and Development of Empirical Correlations for Prediction of Plane Strain Properties of Cohesionless Soils. *Electron J Geotech Eng*, 20, 6169-6184.

- NAVFAC (1982a). *DM-7.1 Soil Mechanics*. Facilities Engineering Command, U.S. Dept. of the Navy, Alexandria, VA, 364p.
- Navfac, D. M. (1982b). Foundations and earth structures. *Design manual*, 7. Alexandria, VA
- Ng, K. S., & Tan, S. A. (2015). Simplified homogenization method in stone column designs. *Soils and Foundations*, 55(1), 154-165.
- Obrzud, R., & Truty, A. (2012). The hardening soil model-a practical guidebook z soil. *PC100701 Report*.
- Petyt, Maurice (2015). *Introduction to finite element vibration analysis*. New York: Cambridge University Press.
- Rao, L., & Madhira, M. (2010, December). Evaluation of optimum spacing of stone columns. In *Indian Geotechnical Conference. GEOTrendz. December* (pp. 16-18).
- Raison, C. A. (2004). *Ground and soil improvement*. Thomas Telford.
- Rouaiguia, A. and Al-Zahrani, R. (2002). Simulation of Soil Dynamic Compaction. In: *The 6th Saudi Engineering Conference*. pp. 223-231.
- Shockley, L. R., & Borov, V. G. (2010). *U.S. Patent Application No. 12/342,476*.
- Sękowski, J., Kwiecień, S., & Kanty, P. (2018). The influence of dynamic replacement method on the adjacent soil. *International Journal of Civil Engineering*, 16(10), 1515-1522.
- Selvaraju, S., Wei He, Z., & Weng Leong, K. (2017). Vibro replacement stone columns for large steel storage tanks in Vietnam. In *Proc. of the 19th Intern. Conf. on Soil Mechanics and Geotechnical Engineering (Sep. 17–22, 2017/COEX, Seoul, Korea)*—ed. by W. Lee, J.-S. Lee, H.-K. Kim, D.-S. Kim.—Seoul (pp. 2651-2654).
- Swiss Standard (1999), “S. N. 670 010b : *Characteristics Coefficients of Soils*”, *Association of Swiss Road and Traffic Engineers*.
- Tarawneh, B., Bodour, W. A., Shatnawi, A., & Al Ajmi, K. (2019). Field evaluation and behavior of the soil improved using dynamic replacement. *Case Studies in Construction Materials*, 10, e00214.
- Von Soos, P. (1991). *Grundbau-Taschenbuch. Part 4*. Ernst & Sohn, Berlin.
- Wieland, M., Ren, Q., & Tan, J. S. (Eds.). (2014). *New Developments in Dam Engineering: Proceedings of the 4th International Conference on Dam Engineering, 18-20 October, Nanjing, China*. CRC Press.