

PERFORMANCE INDEX FOR PALM OIL MILL EFFLUENT MANAGEMENT

BEH ZHIKUAN

A dissertation submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering

Faculty of Chemical and Energy Engineering
Universiti Teknologi Malaysia

DECEMBER 2017

ACKNOWLEDGEMENTS

First and foremost, I would like to express my utmost appreciation and highest gratitude to my supervisor, Dr. Lim Jeng Shiun for their myriad constructive comments and unwavering support to the completion of this research. Their guidance and encouragement are gratefully acknowledged.

Moreover, I would like to thank Professor Ir. Dr. Sharifah Rafidah Wan Alwi and Dr. Norulhuda bt Ismail for their kind assistance in providing me valuable and useful information while preparing my thesis. Their valuable guidance and kindness as the host for the research visit in their research centre are also very much appreciated. I also acknowledge the efforts from Dr. Rashidah bt Ahmad for many timely discussions, which emerged into some of the useful ideas for this study. I would also like to thank the Engineer team in IOI Pamol Kluang Palm Oil Mill (M) Sdn. Bhd., who helped in the data extraction of the industrial case study. In addition, I would like to take this golden opportunity to thank my parents and family members for their unconditional continuous support and encouragements. Also, I wish to express my great appreciation for Nabila Farhana bt Jamaludin for valuable guidance and precious information. I would also like to recognise the tremendous financial support granted by Ministry of Education Malaysia through MyMaster scholarship.

ABSTRACT

The world is currently facing an energy crisis. This issue rises society concerns about the environment and energy and it urged the scientists and engineers to incorporate in sustainability process design or by retrofit of the existing or traditional process plant. There is much consideration needed to be considered environmental sustainability. Due to these issue, a systematic and structural sustainability evaluation tools are needed to help in the process of engineering design, analysis, improvement, retrofit and decision making. This research proposed a performance index for palm oil mill effluent management. Firstly, the assessment was performed with ratio normalization calculation method to measure and compare the current sustainability performance of a related palm oil mill. The feature has presented in more detail parameters to indicators for further extensive evaluation. Moreover, the weights of the parameters were determined by expert opinion survey. Based on the result evaluated, the poor performer indicators were determined, and suitable improvement method was proposed. The improvement method was chosen by comparing and evaluate various improvement methods that were suitable to enhance the weak perform indicator. This POME management model will benefit the company by assess sustainability performance of their industry and further improve it. This study is significant as it will bring an influential impact and improvement to the current palm oil industry in POME management.

ABSTRAK

Dunia sedang menghadapi krisis tenaga. Isu ini meningkatkan kebimbangan masyarakat tentang alam sekitar dan tenaga dan ia menggesa saintis dan jurutera untuk meningkatkan prestasi reka bentuk proses kemampunan atau dengan mengubahsuai loji proses sedia ada atau tradisional. Terdapat banyak pertimbangan yang perlu dipertimbangkan di dalam issue ini. Oleh demikian, alat penilaian kelestarian sistematik dan struktur diperlukan untuk membantu dalam proses reka bentuk kejuruteraan, analisis, penambahbaikan, retrofit dan membuat keputusan. Makalah ini membentangkan indeks kemampunan untuk proses sisa-sisa kilang kelapa sawit. Pertama, penilaian dilakukan dengan kaedah pengiraan nisbah normalisasi untuk mengukur dan membandingkan prestasi kemampunan semasa bagi kilang minyak sawit yang berkaitan. Aspek ini telah membahagikan kepada parameter yang lebih terperinci kepada petunjuk untuk penilaian lebih lanjut. Berdasarkan keputusan yang dinilai, indikator yang berpresrasi lemah telah ditentukan, dan kaedah penambahbaikan yang sesuai telah dicadangkan. Model kerangka sistematik ini akan memberi manfaat kepada syarikat dengan menilai prestasi kemampunan industri mereka dan terus memperbaikinya. Kajian ini adalah penting kerana ia akan membawa impak dan peningkatan yang berpengaruh kepada industri minyak sawit semasa.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	ACKNOWLEDGEMENTS	iii
	ABSTRACT	iv
	ABSTRAK	v
	TABLE OF CONTENTS	vi
	LIST OF TABLES	x
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xiii
	LIST OF SYMBOLS	xvi
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Research Background	1
	1.3 Problem Statement	3
	1.4 Research Objective	4
	1.5 Scope of Study	5

2	LITERATURE REVIEW	
2.1	Introduction	6
2.2	Current Sustainability Assessment of Palm Oil	7
2.2.1	Roundtable on Sustainable Palm Oil (RSPO)	7
2.2.2	Malaysia Sustainable Palm Oil (MSPO)	8
2.2.3	Indonesia Sustainable Palm Oil (ISPO)	8
2.2.4	Environmental Index for Palm Oil	9
2.3	Environmental and Sustainable Assessment Method in Others Field	10
2.3.1	Assessment of Sustainable Development of Hard Coal Mining Industry	10
2.3.2	Life Cycle Assessment	11
2.3.3	Developing a Framework for Sustainable Development Indicators for the Mining and Mineral Industry	12
2.3.4	Debottlenecking of Palm Oil Biorefinery	12
2.3.5	Multi-criteria strategy For Assessment at Early Stage	13
2.3.6	Process Reaction Routes Selection	15
2.3.7	Engineering for Sustainable Development (ESD)	16
2.3.8	Sustainability Indicators	16
2.4	Other Methods	17
2.5	Environment Sustainability Index	18
2.6	Review of Index Method	19
2.6.1	Ratio Normalization	19
2.6.2	Proximity to Target (PTT)	19
2.7	Weight Development	20
2.7.1	Review of Analytic Hierarchy Process (AHP)	20
2.7.2	Decision Tree	21

	2.7.3 Paired Comparison Analysis	21
	2.7.4 Expert Opinion	22
	2.8 Aggregation	22
	2.9 Research Gap	23
3	METHODOLOGY	26
	3.1 Introduction	26
	3.2 POME Performance Index Assessment Framework	26
	3.3 Framework Part 1	28
	3.3.1 Review on Current Practice	28
	3.3.2 Identify Parameter and Indicator	28
	3.3.3 POME Performance Parameter and Indicator	29
	3.3.4 Raw Data Collection	30
	3.3.5 Data Gathering and Establishment of Standard or Target	30
	3.4 Framework Part2	30
	3.4.1 Development of Weight	31
	3.4.2 Normalization and Index Calculation	32
	3.4.2.1 Normalization of General Indicators	32
	3.4.2.2 Normalization of pH Indicator	33
	3.4.2.3 Index Values Collection	34
	3.4.3 Analyse Index Score	36
	3.4.4 Pre-Screening of General Improvement Methods	37
	3.4.5 Propose Improvement to Weak Point	38
4	RESULT	39
	4.1 Introduction	39
	4.2 Database of Palm Oil Mill	39
	4.3 Data of Indicators Score	40
	4.4 Weight Distribution	44

4.5	Parameter Score Data	45
4.6	Parameter Aggregation Score Data	46
4.7	Total Index Score of POME Performance of Mills	47
4.8	POME Performance Analysis and Improvement	48
4.9	Pre-Screening of General Improvement Methods	48
	4.9.1 Covered Lagoon Bio-digester	48
	4.9.2 Anaerobic Digester Tank System	49
	4.9.3 Zero Discharge Treatment Technology	50
	4.9.4 Open Ponding System	52
	4.9.5 Evaluation of Selected Parameter for Improvement	53
4.10	Propose Improvement Method	55
5	CONCLUSION AND RECOMMENDATIONS	57
5.1	Summary	57
5.2	Recommendations	58
	REFERENCES	59
	APPENDIX A: QUESTIONNAIRE	64

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Comparison of Assessment Method for Palm Oil and Other Industry	24
3.1	Palm Oil Mill Data Collection Table for Environmental Assessment (Jamaludin <i>et al.</i> , 2016)	29
3.2	Level of Achievement Table	36
4.1	Palm Oil Mill Data and Standard Collected for POME Performance Assessment	42
4.2	Palm Oil Mill Data and Standard Collected for POME Performance Assessment after Ratio Normalization	43
4.3	Parameters Weight Distribution	44
4.4	Parameter Score of the Assessment	46
4.5	Parameter Aggregation Score of the Assessment	47
4.6	Economy Analysis of Covered Lagoon Bio-digester	49
4.7	Economy Analysis of Anaerobic Tank-Digester	50
4.8	Economy Analysis of Zero Discharge Treatment Technology	51
4.9	Economy Analysis of Open Ponding System	52
4.10	Comparison of EN1 and EN2 through Different Improvement Methods	53
4.11	Improvement Methods Economy Parameters	54
4.12	Total Improvement Methods Index Score	54

4.13	Palm Oil Mills EN1 and EN2 Before and After Improvement Result	56
4.14	Palm Oil Mills Before and After Improvement Result	56

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Overall Methodology of Environmental Index for Palm Oil Mill (Jamaludin <i>et al.</i> , 2016)	9
2.2	The Structure of the Hierarchical Model of Sustainable Development (Kopacz <i>et al.</i> , 2017)	11
2.3	Heuristic Framework to Debottlenecking of a Palm Oil-Based Integrated Biorefinery (Kasivisvanathan <i>et al.</i> , 2014)	13
2.4	Overview of the Multi-criteria Strategy Assessment (Patel <i>et al.</i> , 2012)	14
2.5	Routes Selection Pathway (Zheng <i>et al.</i> , 2012)	15
3.1	Overall Methodology of Environmental Index for Palm Oil Mill Adoption Framework	27
3.2	pH Indicator Index Score Interpolation Chart	33
4.1	Parameters Weight Distribution Pie Chart	45
4.2	Index Score for Palm Oil Mill A, B, C and D Bar Chart	47
4.3	Schematic Diagram of a Zero Discharge Process of Palm Oil Mill Effluent (POME) (Zheng <i>et al.</i> , 2013)	51
4.4	Bar chart of Total Improvement Methods Index Score	55

LIST OF ABBREVIATIONS

AHP	-	Analytic Hierarchy Process
BBIS	-	Bioenergy Based Industrial Symbiosis
BOD	-	Biochemical oxygen demand
CAPEX	-	Capital Expenditure
COD	-	Chemical Oxygen Demand
CPO	-	Crude Palm Oil
DOE	-	Department of Environment
EFB	-	Empty Fruit Bunches
EHS	-	Environment, Health and Safety
EN	-	Environment
EP	-	Economic Performance
EPL	-	Economic Performance Lower
EPU	-	Economic Performance Upper
ESD	-	Engineering for Sustainable Development
ESD	-	Engineering for Sustainable Development
FLDA	-	Federal Land Development Authority
FFA	-	Free Fatty Acid
FFB	-	Fresh Fruit Bunches
FTA	-	Fault Tree Assessment

DP	-	Gross Domestic Product
GHG	-	Greenhouse Gases
GREENSCOPE	-	Gauging Reaction Effectiveness for the Environmental Sustainability of Chemistries with a Multi-Objective Process Evaluator
GRI	-	Global Reporting Initiative
GRI	-	Global Reporting Initiative
GRI	-	Global Reporting Initiative
HEN	-	Heat Exchanger Networks
HEN	-	Heat Exchanger Networks
IIM	-	Inoperability Input–output Model
ILUC	-	Indirect Land Use Change
IS	-	Industrial Symbiosis
ISO	-	International Organization for Standardization
LCA	-	Life-cycle Assessment
MINLP	-	Mixed Integer Nonlinear Programming
MPOB	-	Malaysian Palm Oil Board
NKEA	-	National Key Economic Area
OPEX	-	Operating Expense
PEI	-	Potential Environment Impact
PFD	-	Process Flow Diagram
POME	-	Palm Oil Mill Effluent
PTT	-	Proximity to Target
ROR	-	Rate of Return
RSPO	-	Roundtable on Sustainable Palm Oil

WAR	-	Waste Reduction
BOD	-	BOD ₃ (Mg/L)
COD	-	COD (mg/L)
IIS	-	Index Indicator Score
MRE	-	Mixed Raw Effluent (ton/ton)
O&G	-	Oil and grease content (mg/L)
PC	-	Production cost (Rm/ton)
pH	-	Potential of Hydrogen
RNI	-	Ratio Normalization Indicator score
SUS	-	Suspended Solid (mg/L)
UOW	-	Use of fresh water (m ³ /ton)

LIST OF SYMBOLS

\bar{x}_{ci}^M	-	Mean of x Data for Compared Items ci
x_i^T	-	Target/Standard Value of x for Indicator i
$Mark_c$	-	Mark of the Related Class
$PAS_{m,p}$	-	Parameter Aggregation Score of Parameter p for Mill m
$PS_{m,p}$	-	Parameter Score of Parameter p for Mill m
TIS_m	-	Total Index Score of Mill m
$TIIS_{m,p}$	-	Total Indicator Index Score of Parameter p for Mill m
$TIMIS_{im}$	-	Total Improvement Methods Index Score for Related Improvement Method (im)
VS_p	-	Voted Score for a Parameter p
W_p	-	Weight for Parameter p
$IIS_{m,i}$	-	Indicator Index Score of Indicator i for Mill m
$Mark^{max}$	-	Maximum Mark of the Class
$N_{c,p}$	-	Voted Number of a Class c for a Parameter p
N^{max}	-	Maximum Voter Number
$N_{p,i}$	-	Number of Indicator i for Parameter p
EPS_{im}	-	Economy Parameters Score for related Improvement Method (im)
$RNI_{im,ci}$	-	Ratio Normalization Index of Compared Items ci for Related Improvement Method (im)
$RNI_{m,i}$	-	Ratio Normalization Index Indicator i for Mill m
x_i^L	-	Lower Limit of Indicator i
x_i^U	-	Upper Limit of Indicator i

x_i^{mid}	-	Midpoint of Indicator i
$x_{im,ci}$	-	x data of Compared Item (ci) for Related Improvement Method (im)
$x_{m,i}$	-	x data of Indicator i for Mill m
c	-	Class
im	-	Improvement Methods
i	-	Indicator
ep	-	Economy Parameters
m	-	Mill
N	-	Number
p	-	Parameter

CHAPTER 1

INTRODUCTION

1.1 Introduction

Palm oil is one of the vegetable oil, which acts as an important role in many commercial food industries. This chapter provides an overview of the current palm oil mill industry. This is followed by an introduction of the problem background, problem statement, research objectives and the scope of work for this study, which aims to develop new methodologies to assess current palm oil mill industry and palm oil mill effluent management.

1.2 Research Background

The primary product of palm oil mill is crude palm oil. There are 5 major steps in palm oil milling processes which are bunch reception, sterilisation, stripping, digestion and oil extraction (Gunstone *et al.*, 1987). The first process is bunch reception. Bunches are transported to the mills by trucks or cages on a narrow-gauge railway system or by road with a motor lorry or tractor trailer. After reception process, it is followed by sterilisation. The purpose of sterilisation is to the prevention of any further rise in FFA (Free Fatty Acid) due to enzyme action by inactivation of the lipolytic enzymes. Hence, this procedure also to loosen the fruit still attached to the bunch stalk, by providing sufficient heat to penetrate the points of attachment of the fruits to the spikelets to bring about hydrolysis at these points. Next process is the

stripping processes. The object of stripping, sometimes called 'threshing', is to separate the sterilised fruits together with the associated calyx leaves from the sterilised bunch stalks. After the stripping process, it is followed by the digestion process. After the bunch has been stripped, the sterilised fruit must be reheated purpose to loosen the pericarp from the nuts and further prepared for the pressing process. The process is carried out in steam-heated vessels provided with stirring arms to be known as digester or kettles. Final step is an oil extraction process. Although many systems, both wet and dry, have been used over the years to extract the crude oil from the digested fruit mash, it is common practice nowadays to use screw presses, especially when general palm fruits must be processed (Othman *et al.*, 2010).

However, with huge development of this industry in country has the result of some negative impact from the effluents or by products. The impact under the fossil fuels category came from the production of the fertilizers used as well as diesel usage for transportation and harvesting in the nursery and plantation phases. Results show that there are several impact categories with significant impacts from crude palm oil production. These factors have resulted in, decrease in air quality and climate change. The impact categories of climate change and a decrease in air quality came from upstream activities and the palm oil mill effluent (POME) in the mill (Subramaniam *et al.*, 2010).

Sustainable development has been popularly defined as development that meets the needs of the present without compromising the ability of future generations to meet their own needs (Von Schirnding *et al.*, 2005). Recently, there are lots of studies of sustainability of palm oil mill process, but there still contain room for improvement in palm oil mill effluent (POME) assessment and treatment. The environmental sustainable assessment process still considered insufficient amount. Moreover, a sustainable assessment with the integration of the palm oil mill process is seen still has a large potential to grow and improve. The palm oil mill index approach is used in this research to measure sustainability practice in palm oil mill process.

1.3 Problem Statement

Malaysia with 19.67 million metric tons of total crude palm oil production, placed second after the Indonesia in worldwide crude palm oil production rank. This corresponds to 100.4 million metric tons of fresh fruit bunch processed per year (Malaysian Palm Oil Board, 2014). Nonetheless, with this huge amount of annual production, there is a bigger responsibility to ensure the sustainability of palm oil production to protect humans and conserve the environment, while achieving economic viability. Moreover, in the palm oil mills process, it produces a large amount of organic waste which commonly known as palm oil mill effluent (POME). In the palm oil milling process, the process produced large amounts of this organic waste. Data proposed from Thailand in the year 1993 shows that on a weight basis, such wastes amount to nearly 80% of inputs (Preasertsan *et al.*, 1996).

In palm oil mill process about 1.5 m^3 of water is needed to process 1 ton of fresh fruit bunch (FFB). From all the water user about half of this water amount ends up as waste (palm oil mill effluent (POME)). POME is an unwanted wastewater produced from the palm oil milling process. This wastewater is thick, brownish with a distinct offensive odour, and has a high organic matter content and highly pollution (Ahmad *et al.*, 2009). The thick brownish raw POME in the viscous colloidal form is discharged at a temperature between 80°C and 90°C . If the untreated POME is discharged into watercourses, it certainly will cause considerable environmental problems due to its high biological oxygen demand (BOD) and high chemical oxygen demand (COD). This assessment tool will act as a guide to assess their mill. In addition, this type of assessment method has done by “Environmental Index for Palm Oil Mill” (Jamaludin *et al.*, 2016), which conducted a complete assessment including environmental assessment. However, the study used proximity to target method for the assessment. PTT is a good normalization formula, but it need more than one mill or sample data to do the calculation. A lone mill data will not be able to use the formula. Moreover, the study also did not consider of financial issue in the improvement section.

1.4 Research Objectives

The main objective of this research is to improve the POME management of palm oil mill. The research objectives are detailed as below:

1. To improve an existing framework and adopt in the context of POME management by using ratio normalization method to generate improvement method.
2. To evaluate palm oil mill effluent management in index score format in industry.
3. To construct weight values, which emphasize the importance of certain parameters and propose an improvement method with the consideration of the interactive relationship between POME index and economy feature.

1.5 Scope of Study

In orders to achieve the listed objectives, the scopes of study are stated below:

- i. Reviewing of the current management procedure, practice and identifying the research gap on the assessment on palm oil mill effluent treatment process.
- ii. Studying the parameters used to set the weighting index on each of the processes, and determine the weighting index on related environmental parameter.
- iii. Performance database is structured based on environmental and palm oil mill effluent related features. All the indicators, criteria and regulations are limited in palm oil mill.
- iv. Palm oil mill standard data collection is collected from previous study. Weight data is collected from IOI Pamol Kluang Palm Oil Mill.

REFERENCES

- Ahmad, S., & Polley, G. T. (1990). Debottlenecking of heat exchanger networks. *Heat Recovery Systems and CHP*, 10(4), 369-385. doi: [http://dx.doi.org/10.1016/0890-4332\(90\)90087-Z](http://dx.doi.org/10.1016/0890-4332(90)90087-Z)
- Alshekhli, O., Foo, D. C. Y., Hii, C. L., & Law, C. L. (2011). Process simulation and debottlenecking for an industrial cocoa manufacturing process. *Food and Bioproducts Processing*, 89(4), 528-536. doi: <http://dx.doi.org/10.1016/j.fbp.2010.09.013>
- Azapagic, A. (2004). Developing a framework for sustainable development indicators for the mining and minerals industry. *Journal of Cleaner Production*, 12(6), 639-662. doi: [https://doi.org/10.1016/S0959-6526\(03\)00075-1](https://doi.org/10.1016/S0959-6526(03)00075-1)
- Beasley, J. (1996). OR-notes. *Accessed March*, 22.
- Chandrasekharan, I., Kumar, R. S., Raghunathan, S., & Chandrasekaran, S. (2013). Construction of environmental performance index and ranking of states. [Article]. *Current Science (00113891)*, 104(4), 435-439.
- Chin, M. J., Poh, P. E., Tey, B. T., Chan, E. S., & Chin, K. L. (2013). Biogas from palm oil mill effluent (POME): Opportunities and challenges from Malaysia's perspective. *Renewable and Sustainable Energy Reviews*, 26, 717-726. doi: <http://dx.doi.org/10.1016/j.rser.2013.06.008>
- Gunstone, F. D., & Society of Chemical, I. (1987). *Palm oil*. Chichester [West Sussex]:Published for the Society of Chemical Industry by Wiley.
- Harsh, M. G., Saderne, P., & Biegler, L. T. (1989). A mixed integer flowsheet optimization strategy for process retrofits—the debottlenecking problem. *Computers & Chemical Engineering*, 13(8), 947-957. doi: [http://dx.doi.org/10.1016/0098-1354\(89\)85067-7](http://dx.doi.org/10.1016/0098-1354(89)85067-7)

- Hechinger, M., Voll, A., & Marquardt, W. (2010). Towards an integrated design of biofuels and their production pathways. *Computers & Chemical Engineering*, 34(12), 1909-1918. doi: <http://dx.doi.org/10.1016/j.compchemeng.2010.07.035>
- Hsu, A., Lloyd, A., & Emerson, J. W. (2013). What progress have we made since Rio? Results from the 2012 Environmental Performance Index (EPI) and Pilot Trend EPI. *Environmental Science & Policy*, 33, 171-185. doi: <https://doi.org/10.1016/j.envsci.2013.05.011>
- Huang, H.-Z., Gu, Y.-K., & Du, X. (2006). An interactive fuzzy multi-objective optimization method for engineering design. *Engineering Applications of Artificial Intelligence*, 19(5), 451-460. doi: <http://dx.doi.org/10.1016/j.engappai.2005.12.001>
- Jamaludin, N. F., Ab Muis, Z., Hashim, H., & Ahamad, R. (2016). Environmental index for palm oil mill. In *Chemical Engineering Transactions* (Vol. 52, pp. 1177-1182). (Chemical Engineering Transactions; Vol. 52). Italian Association of Chemical Engineering
- Kasisvisvanathan, H., Ng, R. T. L., Tay, D. H. S., & Ng, D. K. S. (2012). Fuzzy optimisation for retrofitting a palm oil mill into a sustainable palm oil-based integrated biorefinery. *Chemical Engineering Journal*, 200–202, 694-709. doi: <http://dx.doi.org/10.1016/j.cej.2012.05.113>
- Kasisvisvanathan, H., Tan, R. R., Ng, D. K. S., Abdul Aziz, M. K., & Foo, D. C. Y. (2014). Heuristic framework for the debottlenecking of a palm oil-based integrated biorefinery. *Chemical Engineering Research and Design*, 92(11), 2071-2082. doi: <http://dx.doi.org/10.1016/j.cherd.2014.02.024>
- Kopacz, M., Kryzia, D., & Kryzia, K. (2017). Assessment of sustainable development of hard coal mining industry in Poland with use of bootstrap sampling and copula-based Monte Carlo simulation. *Journal of Cleaner Production*, 159, 359-373. doi: <https://doi.org/10.1016/j.jclepro.2017.05.038>
- Li, S., & Hu, C. (2009). Satisfying optimization method based on goal programming for fuzzy multiple objective optimization problem. *European Journal of Operational Research*, 197(2), 675-684. doi: <http://dx.doi.org/10.1016/j.ejor.2008.07.007>
- Liew, W. H., Hassim, M. H., & Ng, D. K. S. Sustainability assessment framework for

- chemical production pathway: Uncertainty analysis. *Journal of Environmental Chemical Engineering*. doi: <http://dx.doi.org/10.1016/j.jece.2016.05.003>
- Lim, C. I., Biswas, W., & Samyudia, Y. (2015). Review of Existing Sustainability Assessment Methods for Malaysian Palm Oil Production. *Procedia CIRP*, 26, 13-18. doi: <http://dx.doi.org/10.1016/j.procir.2014.08.020>
- Madaki, Y. S. (2013). PALM OIL MILL EFFLUENT (POME) FROM MALAYSIA PALM OILMILLS: WASTE OR RESOURCE. *International Journal of Science, Environment and Technology*, 2(6).
- Man, E. L., & Baharum, A. (2011). A qualitative approach of identifying major cost influencing factors in palm oil mills and the relations towards production cost of crude palm oil. *American Journal of Applied Sciences*, 8(5), 441.
- Miranker, W. L., & Pan, V. Y. (1980). Methods of aggregation. *Linear Algebra and its Applications*, 29, 231-257. doi: [http://dx.doi.org/10.1016/0024-3795\(80\)90245-1](http://dx.doi.org/10.1016/0024-3795(80)90245-1)
- Narayanan, D., Zhang, Y., & Mannan, M. S. (2007). Engineering for Sustainable Development (ESD) in Bio-Diesel Production. *Process Safety and Environmental Protection*, 85(5), 349-359. doi: <http://dx.doi.org/10.1205/psep07016>
- Narayanan, D., Zhang, Y., & Mannan, M. S. (2007). Engineering for Sustainable Development (ESD) in Bio-Diesel Production. *Process Safety and Environmental Protection*, 85(5), 349-359. doi: <http://dx.doi.org/10.1205/psep07016>
- National Key Economic Areas (NKEA). (2011) *National Biogas Implementation (epp5)* (pp. 1-28). Malaysia: Biogas Capture and CDM Project Implementation for Palm Oil Mills.
- Ng, R. T. L., Ng, D. K. S., Tan, R. R., & El-Halwagi, M. M. (2014). Disjunctive fuzzy optimisation for planning and synthesis of bioenergy-based industrial symbiosis system. *Journal of Environmental Chemical Engineering*, 2(1), 652-664. doi: <http://dx.doi.org/10.1016/j.jece.2013.11.003>
- Othman, M. R., Repke, J.-U., Wozny, G., & Huang, Y. (2010). A Modular Approach to Sustainability Assessment and Decision Support in Chemical Process Design. *Industrial & Engineering Chemistry Research*, 49(17), 7870-7881. doi: [10.1021/ie901943d](http://dx.doi.org/10.1021/ie901943d)
- Panjeshahi, M. H., & Tahouni, N. (2008). Pressure drop optimisation in debottlenecking

- of heat exchanger networks. *Energy*, 33(6), 942-951. doi: <http://dx.doi.org/10.1016/j.energy.2007.09.013>
- Patel, A. D., Meesters, K., den Uil, H., de Jong, E., Blok, K., & Patel, M. K. (2012). Sustainability assessment of novel chemical processes at early stage: application to biobased processes. [10.1039/C2EE21581K]. *Energy & Environmental Science*, 5(9), 8430-8444. doi: 10.1039/c2ee21581k
- Prasertsan, S., & Prasertsan, P. (1996). Biomass residues from palm oil mills in Thailand: An overview on quantity and potential usage. *Biomass and Bioenergy*, 11(5), 387-395. doi: [http://dx.doi.org/10.1016/S0961-9534\(96\)00034-7](http://dx.doi.org/10.1016/S0961-9534(96)00034-7)
- Ruiz-Mercado, G. J., Gonzalez, M. A., & Smith, R. L. (2013). Sustainability Indicators for Chemical Processes: III. Biodiesel Case Study. *Industrial & Engineering Chemistry Research*, 52(20), 6747-6760. doi: 10.1021/ie302804x
- Shabbir, Z., Tay, D. H. S., & Ng, D. K. S. (2012). A hybrid optimisation model for the synthesis of sustainable gasification-based integrated biorefinery. *Chemical Engineering Research and Design*, 90(10), 1568-1581. doi: <http://dx.doi.org/10.1016/j.cherd.2012.02.015>
- Subramaniam, V., May, C. Y., Muhammad, H., Hashim, Z., Tan, Y. A., & Wei, P. C. (2010). Life cycle assessment of the production of crude palm oil (Part 3). *J. Oil Palm Res*, 22, 895-903.
- Tan, R. R., Ballacillo, J.-A. B., Aviso, K. B., & Culaba, A. B. (2009). A fuzzy multiple-objective approach to the optimization of bioenergy system footprints. *Chemical Engineering Research and Design*, 87(9), 1162-1170. doi: <http://dx.doi.org/10.1016/j.cherd.2009.04.004>
- Tan, R. R., Lam, H. L., Kasivisvanathan, H., Ng, D. K. S., Foo, D. C. Y., Kamal, M., Klemeš, J. J. (2012). An algebraic approach to identifying bottlenecks in linear process models of multifunctional energy systems. [journal article]. *Theoretical Foundations of Chemical Engineering*, 46(6), 642-650. doi: 10.1134/s004057951206022x
- Tay, D. H. S., Ng, D. K. S., Sammons, N. E., & Eden, M. R. (2011). Fuzzy Optimization Approach for the Synthesis of a Sustainable Integrated Biorefinery. *Industrial & Engineering Chemistry Research*, 50(3), 1652-1665. doi: 10.1021/ie1011239

- Temeng, A. A. (2010). *Industrial Architecture; a Determinant of Efficiency in The Palm Oil Mill*. College of Architecture and Planning.
- Theo, W. L., Lim, J. S., Ho, W. S., Hashim, H., Lee, C. T., & Muis, Z. A. (2017). Optimisation of oil palm biomass and palm oil mill effluent (POME) utilisation pathway for palm oil mill cluster with consideration of BioCNG distribution network. *Energy*, *121*, 865-883. doi: <https://doi.org/10.1016/j.energy.2017.01.021>
- von Schirnding, Y. (2005). The World Summit on Sustainable Development: reaffirming the centrality of health. [journal article]. *Globalization and Health*, *1*(1), 8. doi: [10.1186/1744-8603-1-8](https://doi.org/10.1186/1744-8603-1-8)
- Young, D. M., & Cabezas, H. (1999). Designing sustainable processes with simulation: the waste reduction (WAR) algorithm. *Computers & Chemical Engineering*, *23*(10), 1477-1491. doi: [http://dx.doi.org/10.1016/S0098-1354\(99\)00306-3](http://dx.doi.org/10.1016/S0098-1354(99)00306-3)
- Zhang, Z., Choo, Y. M., & Loh, S. K. (2013). Zero discharge treatment system of palm oil mill effluent (pome): Google Patents.
- Zheng, K., Lou, H. H., Gangadharan, P., & Kanchi, K. (2012). Incorporating Sustainability into the Conceptual Design of Chemical Process-Reaction Routes Selection. *Industrial & Engineering Chemistry Research*, *51*(27), 9300-9309. doi: [10.1021/ie3002952](https://doi.org/10.1021/ie3002952)