The Impact of Carbon Sink Uncertainty on Mitigation Strategies

Wolf Heinrich Reuter*, Sabine Fuss, Jana Szolgayová, Michael Obersteiner

Ecosystems Services and Management Program (ESM), International Institute for Applied Systems Analysis (IIASA), Laxenburg, Austria * Corresponding author: Tel: +43 2236 807 518, Fax: +43 2236 807 299, E-mail: reuter@iiasa.ac.at

Objectives

- Optimal composition of a mitigation portfolio given the uncertainty surrounding key variables
- Natural sink modelled stochastically and as a function of atmospheric Greenhouse Gas (GHG) concentration accounting for possible climate feedbacks

BECCS

 Bio-energy in combination with carbon capture and storage





- Analyze different emissions targets and identify best hedging strategies in the technosphere given the uncertainty in the biosphere with explicit focus on their interrelation
- Examine the role of bioenergy with carbon capture and storage (BECCS) when accounting for natural sinks and the potential climate feedbacks

Model

- A global decision maker plans abatement and negative emission technology (NET) deployment bound by a cumulative emission target over the 21st century
- Three periods: 1) Short-term (2010-2030), 2) Medium-term (2030-2050), and 3) Long-term (2050-2100)
- Select most cost-effective policy plan with two available options: (1) abatement and (2) deployment of NETs consisting of BECCS and direct air capture (DAC). The technologies differ in their cost structure and mitigation levels.
- CO_2 sink modelled similar to Friedlingstein et al. (2006): feedback between atmospheric CO_2 concentration and the sink, with additional stochastic shocks representing extreme events like forest fires, pests, etc. (Probability of shock occurrence modelled as being positively dependent on the cumulative emissions)

Sink Sensitivity to Atmospheric CO₂

- Deployment of BECCS (and DAC) very much dependent on sink's sensitivity to atmospheric CO₂ (β)
- For high CO₂ fertilization effect: NETs are a relatively stable share in the mitigation portfolio, which is equal to the maximum BECCS potential.
- For a lower effect: amount of CO₂ abated with NETs increases, i.e. deployment of DAC starts

- Using biomass to produce bio-energy, then capturing and diverting the CO_2 produced during combustion/processing into a long-term geological storage facility
- CO_2 fixation by photosynthesis (i.e. bio-energy under certain criteria, is considered to be carbon neutral) plus capture and storage of CO_2 from biomass combustion (negative emissions)

DAC

- Direct Air Capture
- Using chemical reactions to remove CO₂ directly from the air
- Currently expensive, i.e. DAC is much higher on the abatement curve than BECCS and will only be deployed if all other potentials are exploited

Feedstock Feedstock + CO2 ≈ 0 < 0</p>



Cumulative Emission Target

- Least stringent cumulative emissions target (2,900 GtCO₂): NETs are not part of the optimal portfolio anymore.
- Most stringent target (88 GtCO₂): in last period maximum amount of BECCS (1,605 GtCO₂) plus 1,035 GtCO₂ of DAC, as so much abatement in the last period needed that DAC becomes cheaper than marginal unit of abatement

and increases.

Result as expected because "free" mitigation through uptake by natural sinks decreases and NETs have to make up for the difference



BECCS potential

- Even though BECCS is used only in the third period, its potential has direct impact on the optimal abatement already in the first and second periods.
- Increase of 50% in potential of BECCS is reflected in an over 40% (20%) decrease in the first (second) period abatement.
- If BECCS potentials are higher than in our baseline the present value (PV) of the portfolio costs decrease relatively little, as we deploy more BECCS.

- Abatement need in first period similar with different targets (140 GtCO₂ for the 88 and 880 GtCO₂ targets to only 80 GtCO₂ for the 1,500 and 2,900 GtCO₂ targets)
- The present value (PV) of the portfolio cost increases exponentially with the stricter cumulative emissions targets



Shocks to the Carbon Sink

- With increasing shock size, more mitigation needs to be carried out to meet the target in the last period in total.
- The larger part of this increase is achieved through NETs deployment. As the potential of BECCS is already fully exploited in the baseline case, the increase can here only happen via a deployment in DAC.
- With a higher probability of a shock to the sink, this increase gets steeper with the shock size
- If BECCS potential is lower than in the baseline, however, the PV of the costs almost doubles because of the increased deployment of DAC



