

HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

Conference Paper, Published Version

Boyer, Aude; Guyot, Grégory; Vermeulen, Julien; Viard, Thomas
Benchmark FLOW3D Shallow water/TELEMAC2D on a river
70 km long including 2 dams

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:
TELEMAC-MASCARET Core Group

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/107199>

Vorgeschlagene Zitierweise/Suggested citation:

Boyer, Aude; Guyot, Grégory; Vermeulen, Julien; Viard, Thomas (2019): Benchmark FLOW3D Shallow water/TELEMAC2D on a river 70 km long including 2 dams. In: XXVIth TELEMAC-MASCARET User Conference, 15th to 17th October 2019, Toulouse.

Standardnutzungsbedingungen/Terms of Use:

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

Benchmark FLOW3D Shallow water/TELEMAC2D on a river 70 km long including 2 dams

Aude Boyer¹, Grégory Guyot¹, Julien Vermeulen¹, Thomas Viard¹

¹ Electricité de France (EDF), Centre d'Ingénierie Hydraulique (CIH), 73370 La Motte-Servolex, France
julien.vermeulen@edf.fr

Abstract:

Past floods have shown important differences in flow estimation going through 2 dams. Those dams are built on a plain river and are separated by 30 km. A tributary converge downstream the first dam but its supply can't explain the differences in flow estimation.

It is expected that the differences come from a lack of integration of the downstream water level in the flow estimation of the downstream dam. A 70 km modelling including the 2 dams and their reservoirs and 20 km of downstream river has been decided.

The main complexity of this model was to properly integrate the dams' discharge capacity in the model:
Two solutions were implemented:

- A TELEMAC2D model using a FORTRAN program to represent the dams discharge capacity previously defined with parametrical local FLOW3D models of the dams
- A FLOW3D Shallow water model of the 70km of river including 3D portions for the dams

The benchmark compares:

- the global investment in hours of engineer for the 2 solutions
- the calculation capacities and duration
- the hydraulic accuracy

Proposed session: *River and urban floods, flood forecasting and management*

Key words: 2D model, 3D model, dam

Speaker: Julien Vermeulen