## TECHNIQUES IN MAKING MASTER MODEL FOR SPIN CASTING TECHNOLOGY

#### THESIS

Submitted as Partial Fulfill of the Requirements to Obtain the Bachelor of International Industrial Engineering Degree



Arranged by:

DAHANA PAMUNGKAS Student Number: 04 14 04272

INTERNATIONAL INDUSTRIAL ENGINEERING PROGRAM
FACULTY OF INDUSTRIAL TECHNOLOGY
UNIVERSITAS ATMA JAYA YOGYAKARTA
YOGYAKARTA
2009

#### STATEMENT OF WORK'S ORIGINALITY

I honestly declare that this thesis which I wrote does not contain the works or parts of the works of other people, except those cited in the quotations and bibliography, as a scientific paper should



# A BACHELOR OF INTERNATIONAL INDUSTRIAL ENGINEERING THESIS On

### TECHNIQUES IN MAKING MASTER MODEL FOR SPIN CASTING TECHNOLOGY

Has been Examined and Approved On June, 2009

Adviser, Co-Adviser,

T.B. Hanandoko, S.T., M.T. A. Tonny Yuniarto, S.T., M.Eng.

Board of Examiners, Chairman,

T.B. Hanandoko, S.T., M.T.

Member, Member,

P. Wisnu Anggoro, S.T., M.T. Ir. B. Kristyanto, M.Eng., Ph.D

Yogyakarta, June, 2009 Dean of Faculty of Industrial Technology Universitas Atma Jaya Yogyakarta

Paulus Mudjihartono, S.T., M.T.

#### **ACKNOWLEDGEMENT**



Dedicated for:
My parents
MY siblings
Myself



#### **FOREWORD**

This final report is one of the prerequisite to finish the undergraduate study program in Industrial Engineering Department, Industrial Technology Faculty, Atmajaya Yogyakarta University.

I am so grateful to many people who encouraged, and help me to finish this final report. On this opportunity, I would like to thank:

- 1. Jesus Christ, for His blessing and guidance.
- 2. Mr. Paulus Mudjihartono, S.T., M.T, as the Dean of Industrial Technology Faculty, Atmajaya Yogyakarta University.
- 3. Mr. Parama Kartika Dewa SP, S.T., M.T., as the Head of Industrial Engineering Department, Industrial Technology Faculty, Atmajaya Yogyakarta University.
- 4. Mr. Hadi Santono, S.T., M.T., as the Head of International Class of Industrial Engineering, with those never ending break through.
- 5. Mr. Theodorus B. Hanandoko, S.T., M.T., as first adviser, who had spent plenty of time to give guidance, direction, inputs and correction in writing this final report.
- 6. Mr. A. Tonny Yuniarto, S.T., M.Eng., as first adviser, who had inputs and correction in writing this final report .
- 7. Mr. Paulus Wisnu Anggoro, S.T., M.T., thanks for all those advice and jokes.
- 8. Mr. Ir. B. Kristyanto, M.Eng., Ph.D as head of LPPM, thanks for supports.

- 9. Mr. Ashari and his crews at Hari Mukti Teknik Workshop, thank you for the input, the idea of machine construction, and warm welcome.
- 10. Mas Budi who always help me at process production laboratory.
- 11. Friends at thesis research, Eko, Geovanni, and William. We had struggled for obtaining quality thesis report. Thanks for the input, support, and togetherness.
- 12. My parents, thanks for supporting my life. Dad, your junior now ready to take over you.
- 13. My siblings who always support me. Thanks for everything.
- 14. My friends TIKI Batch 2004, finally, we're in the same level. Thank you.
- 15. All those who haven't mentioned, thank you.

I realize that this final report has not perfect but I hope that this final report can be useful and can be developed in a further research.

Yoqyakarta, June 2009

#### CONTENTS

COVER	i
STATEMENT OF WORK'S ORIGINALITY	ii
AUTHORIZATION	
ACKNOWLEDGEMENT	iv
FOREWORD	vi
CONTENTS	riii
TABLE CONTENTS	Х
FIGURE CONTENTS	хi
APPENDIX CONTENT	xv
ABSTRACT	xvi
S	
CHAPTER 1 INTRODUCTION	
1.1 Background	1
1.2 Problem Statement	3
1.3 Research Objectives	
1.4 Scope of Research	3
1.5 Research Methodology	
1.6 Report Outline	5
CHAPTER 2 LITERATURE REVIEW	6
CHAPTER 3 BASIC THEORY	
3.1 Spin Casting	8
3.2 Silicone Rubber	13
3.2.1 Silicone Rubber Classification	16
3.2.2 Room Temperature Vulcanizing	
(RTV) Rubbers	16
3.2.3 Advantages	17

3.2.4 Disadvantages	18
3.2.5 Flexibility	18
3.3 Resin	19
3.3.1 Resin Uses	19
3.4 Process Decision Program Charts	20
3.5 The Cause and Effect Diagram (Fishbone Diagram)	25
3.6 Arrow Diagram	27
	29
3.7.1 Physical and allotropes	30
3.7.2 Chemistry and compounds	31
3.8 Machine Cost	32
3.9 Casting Defects	33
$\mathcal{O}$	
CHAPTER 4 SETTING EXPERIMENTS	
4.1 Equipments and Materials	34
4.1.1 Mold Making Peripherals	34
4.1.2 Supporting Materials for Experiments	35
4.1.3 Master Model Machine Specification	3
4.2 Parameter	38
4.3 Experiments Steps	38
4.4 Material and Components Price	3.9
CHAPTER 5 ANALYSIS AND DISCUSSION	
5.1 Identification of Problems during	
Reproducing Master Model	41
5.1.1 Reproducing Using Roland MDX 40	41
5.1.2 Reproducing by Carving	41
5.1.3 Reproducing by Casting	42
5.1.3.1 Using Silicone Rubber Seal	42
5.1.3.2 Using RTV Silicone Rubber	43
5.1.3.3 Using Resin	44

5.1.3.4 Using Bench Vise	45
5.1.3.5 Using C-Clamp	46
5.1.3.6 By Heating the mold	47
5.1.3.7 Using Prototype Machine	48
5.1.3.7.1 Prototyping Machine	49
5.1.3.7.2 Using Vertical Sprue Mold	50
5.1.3.7.3 Using Horizontal Sprue Mold	51
5.1.3.7.4 Using Horizontal Long Sprue Mold	52
5.2 Performance Test	54
5.3 Analysis of Production Time	57
5.4 Analysis of Master Model Machine Cost	58
CHAPTER 6 MANUAL INSTRUCTION	
	59
6.2 The Operation Procedure	60
CHAPTER 7 CONCLUSION	П
7.1 Conclusion	66
7.2 Suggestion	67

REFERENCES

APPENDIX

#### TABLE CONTENTS

Table	2.1	Comparison of Previous and	
		Present Research	7
Table	3.1	Silicone Rubber	
		Mechanical Properties	16
Table	4.1	Mold Making Peripherals	34
Table	4.2	Supporting Materials for Experiments	35
Table	4.3	Master Model Machine Specification	37
Table	4.4	Material and Components Price	38
Table	5.1	Performance Test	54
Table	5.2	Production Time	58
Table	5.3	Machine Cost	58
Table	6.1	Specification.	60
Table	7.1	Comparison Result	66

#### FIGURE CONTENTS

Figure	1.1 Research Methodology Flow Chart	4
Figure	3.1 Parts are arranged on silicone rubber	8
Figure	3.2 Mold is assembled with	
	locknuts and sprayed	9
Figure	3.3 Vulcanization	Ç
Figure	3.4 Gating and Venting	10
Figure	3.5 Spinning	10
Figure	3.6 Pouring	11
Figure	3.7 Pouring illustration inside	
7	spin casting machine	11
Figure	3.8 Removal Parts	12
Figure	3.9 Symbolic Shorthand Souvenir Life Cycle	12
Figure	3.10 Silicone Rubber Chain	15
Figure	3.11 Silicone Rubber Bonding	15
Figure	3.12 Oil resistant grades of silicone	П
	rubber with (left) nitride functional	//
	groups and (right) fluorine functional	7
	groups	19
Figure	3.13 Names and Meanings of Symbols	22
Figure	3.14 Possible Relative Positions of	
	Start and Goal	23
Figure	3.15 Feedback Loops	23
Figure	3.16 PDPC	25
Figure	3.17 Illustration of Fishbone Diagram	26
Figure	3.18 Example of Arrow Diagram	27
Figure	4.1 Master Model Machine	37
Figure	4.2 Experiments Steps	38
Figure	5.1 Roland MDX 40	41
Figure	5.2 Analysis of unaccomplished patterns	42

Figure	5.3 Unaccomplished patterns	42
Figure	5.4 Analysis of blow defects	43
Figure	5.5 Blow defects	43
Figure	5.6 Analysis of obtain the broken mold	44
Figure	5.7 The broken mold	44
Figure	5.8 Using Bench Vise	45
Figure	5.9 Analysis of blow defects emerge the result	45
Figure	5.10 Blow defects emerge on the result	45
46	5.11 Using C-Clamp	46
	5.12 Analysis of blow defects on	
2	the product	46
Figure	5.13 Blow defects on the product	47
Figure	5.14 Oven the mold	47
Figure	5.15 Analysis of blow and pin holes defects	
	on the product	48
Figure	5.16 Blow and pin holes defects on	П
	the product	48
Figure	5.17 Prototype Machine	49
Figure	5.18 Vertical Sprue	50
Figure	5.19 Analysis of blow defects at center on	
	the product	50
Figure	5.20 Blow defects at center on the product	50
Figure	5.21 Horizontal Sprue	51
Figure	5.22 Analysis of cold shut defect	51
Figure	5.23 Cold shut defects on product surface	52
Figure	5.24 Mold Frame	52
Figure	5.25 Analysis of accomplished details	52
Figure	5.26 Product Result	53
Figure	5.27 Arrow Diagram of Casting Process	57
Figure	6.1 Machine Specification	5.9

Figure	6.2 Open Top Enclosure	60
Figure	6.3 Load silicone rubber	61
Figure	6.4 Fasten the mold frame	61
Figure	6.5 Close Top Enclosure	61
Figure	6.6 Connect machine to regulator	62
Figure	6.7 Plug the electrical plug	62
Figure	6.8 Turn the switch on	62
Figure	6.9 Set the regulator at maximum voltage to	
	activate electric motor	63
Figure	6.10 Set the regulator at 125 volt to get	
	constant speed	63
Figure	6.11 Pour the molten metal	63
Figure	6.12 Set the regulator at 0 volt	64
	6.13 Pull the plug out	
Figure	6.14 Turn the switch off	64
Figure	6.15 Open Top Enclosure	65
Figure	6.16 Remove mold frame	65
Figure	6.17 Open silicone rubber mold	65

#### APPENDIX CONTENT

iens in lumine

Master Model Machine

Master Model Machine Component

Process Decision Program Chart

#### ABSTRACT

A master model is required before a product is actually processed in a machine. One technique to produce this master model is using Roland MDX 40 machine which is already used in ADTC. However, duplicating master model by using this machine is not recommended because : (1) Producing a master model using a Roland MDX 40 machine consumes a long time (depend on product complexity) due to metal material used for producing the master model is a heat resistant material, hence requires more time to shape; (2) Roland MDX 40 machine are high costly to use. The time consumption in the process of making the master model would burden the cost of electricity and replacing the cutter all the time when it is not sharp anymore; (3) A Roland MDX 40 machine also requires a machine operator to always stand by to frequently giving the machine and cutter oil lubricant during the process.

This research use PDPC (Process Decision Program Chart) to depict all of the techniques that did in ordering to obtain the best technique in making master model. Fishbone diagram used to analyze the problems that occur on every technique. Arrow diagram used to detect the sequence of production process and obtain production time.

By the end of the research, A prototype machine was built to produce a master model of UAJY keychain. This machine operates at 1400 rpm, with power of 187,5 watt, price of IDR 4.500.000,00 and machine cost per hour is IDR 1.650,00.