

# Effects of Soret diffusion on premixed counterflow flames

Wang Han and Zheng Chen\*

SKLTCS, Department of Mechanics and Engineering Science, College of Engineering, Peking University, Beijing 100871, China

## Abstract

Soret diffusion is a secondary mass diffusion and it affects laminar flames with very light or heavy species and large temperature gradient. To get a general understanding of Soret effects on stretched flame, we conduct theoretical analysis on premixed counterflow flame with Soret diffusion. A deliberately idealized premixed counterflow flame model is analyzed asymptotically within the framework of large activation energy, potential flow, and thermaldiffusive model. A correlation among flame stretch rate, flame position, and flame temperature is derived and is used to assess the effects of Soret diffusion on counterflow flame structure, Markstein length, and extinction stretch rate. Results show that Soret diffusion quantitatively affects the premixed counterflow flame and that the influence of Soret diffusion strongly depends on Lewis number and stretch rate. For light fuel, the premixed counterflow flame becomes stronger after including Soret diffusion. The opposite trend occurs for heavy fuel. The influence of Soret diffusion is found to increase with the stretch rate. A linear change between normalized Markstein length and Soret diffusion coefficient is observed, indicating that flame becomes more sensitive to stretch rate after including Soret diffusion. Furthermore, Soret diffusion is shown to greatly increase the extinction stretch rate of light fuels. These results indicate that for highly-stretched premixed flames containing very light species, the impact of Soret diffusion cannot be neglected.

Keywords: Soret diffusion; premixed counterflow flame; Lewis number; extinction stretch rate

Paper accepted by *Combustion Science and Technology* on Feb. 11, 2015

<sup>\*</sup> Corresponding author. E-mail address: cz@pku.edu.cn (Z. Chen). Tel: 86-10-6276-6232.

# **1. Introduction**

Mass diffusion is extremely important in laminar flames since it drives reactants into reaction zone in which chemical energy is converted into heat (Law, 2006). There are two main modes of mass diffusion in combustion process: one is Ficikan diffusion driven by concentration gradient and the other one is Soret diffusion driven by temperature gradient (Hirschfelder et al., 1954). Fickian diffusion is the dominant mode of mass transport and it is always considered in laminar flame modelling. Compared to Fickian diffusion, Soret diffusion is a secondary mass diffusion and it is only important for very light or very heavy species. In most studies on laminar flame structure and fundamental properties of laminar flames (e.g., laminar flame speed, extinction stretch rate, etc.), mass transport was merely represented by Fickian diffusion while little attention was paid to Soret diffusion. However, Soret diffusion is expected to be important for cases with sufficiently light or heavy species and strong temperature gradients (Hirschfelder et al., 1954).

In the literature, the effects of Soret diffusion have been mainly studied through numerical simulation. For examples, Rosner and coworkers (Gomez and Rosner, 1993; Rosner et al., 2000) investigated the Soret diffusion of heavy species such as particle and soot; Ern and Giovangigli (Ern and Giovangigli, 1998; Ern and Giovangigli, 1999) studied the influence of Soret diffusion on the extinction of hydrogen/air and methane/air flames; Law and coworkers (Xin et al., 2012; Yang et al., 2010) found that extinction stretch rate can be greatly affected by Soret diffusion; and Bongers and de Goey (Bongers and De Goey, 2003), Yang et al. (Yang et al., 2010; Yang et al., 2011) and Liang et al. (Liang et al., 2013) assessed the effects of the Soret diffusion on laminar flame speed. These numerical studies (Bongers and De Goey, 2003; Ern and Giovangigli, 1998; Ern and Giovangigli, 1999; Gomez and Rosner, 1993; Liang et al., 2013; Rosner et al., 2000; Xin et al., 2012; Yang et al., 2010; Yang et al., 2011) indicated discernible effects of Soret diffusion in laminar flames containing very light or very heavy species. Unfortunately, numerical simulations are usually limited to specific fuel and hence the conclusions are lack of generality. To get a general understanding of Soret effects in combustion and to develop appropriate physical insight into the problem, analytical studies need to be conducted.

There are only a few theoretical studies on Soret effects in the literature. Garcia-Ybarra et al. (Garcia-Ybarra and Clavin, 1981; Garcia-Ybarra et al., 1984) considered Soret diffusion in their theoretical analysis and showed that thermo-diffusive stability limits and Markstein lengths are affected by Soret diffusion. Arias-Zugasti and Rosner (Arias-Zugasti and Rosner, 2008) assessed the influence of Soret diffusion on counterflow diffusion flames. They found that, besides the non-unity fuel Lewis number, the Soret diffusion induces additional shifts of

flame temperature and position (Arias-Zugasti and Rosner, 2008). Fong et al. (Fong et al., 2012) investigated the Soret diffusion effects on laminar diffusion flame residing in a counterflow of a fluid fuel stream and a gaseous oxidant. The flame temperature and position were found explicitly as a function of Soret diffusion coefficient (Fong et al., 2012). In these studies (Arias-Zugasti and Rosner, 2008; Fong et al., 2012; Garcia-Ybarra and Clavin, 1981; Garcia-Ybarra et al., 1984), the premixed counterflow flame was not considered. To our knowledge, in the literature there is no theoretical analysis on Soret diffusion effects on premixed counterflow flame.

Therefore, the present work aims to provide a general theoretical description of premixed counterflow flame with Soret diffusion and to assess the effects of Soret diffusion on counterflow flame structure, Markstein length, and extinction stretch rate. In the next section, theoretical model and analytical solutions are presented. Then in Section 3, the effects of Soret diffusion are examined. Finally, the conclusions are given in Section 4.

## 2. Theoretical analysis

## 2.1 Mathematical model

One-dimensional, adiabatic, premixed counterflow flame is studied in the present theoretical analysis. Because of the symmetry in twin premixed counterflow flames, we only need consider the half region of  $0 \le x \le \infty$ . Figure 1 shows the schematic diagram of the premixed counterflow flame. For simplicity, we assume potential flow with velocity being  $\tilde{u} = -\tilde{k}\tilde{x}$  and  $\tilde{v} = -\tilde{k}\tilde{r}/2$  (where  $\tilde{k}$  is the stretch rate) without considering the boundary layer on the stagnation surface. One-step, first-order, global reaction model is used and thereby the effects of radical (Zhang and Chen, 2011) and the coupling between Soret diffusion and chemical reaction (Liang et al., 2013) are not included in the present model. The mixture is assumed to be deficient in fuel and thus only fuel concentration needs to be considered. For the one-dimensional, premixed, steady, counterflow flame, the governing equations for temperature  $\tilde{T}$  and fuel mass fraction  $\tilde{Y}$  are

$$\tilde{\rho}\tilde{C}_{p}\tilde{u}\frac{d\tilde{T}}{d\tilde{x}} = \frac{d}{d\tilde{x}}\left(\tilde{\lambda}\frac{d\tilde{T}}{d\tilde{x}}\right) + \tilde{q}\tilde{\omega}$$
(1)

$$\tilde{\rho}\tilde{u}\frac{d\tilde{Y}}{d\tilde{x}} = -\frac{d}{d\tilde{x}}\left(\tilde{j}_{Y}\right) - \tilde{\omega}$$
<sup>(2)</sup>

For the sake of simplicity, we employ the diffusive-thermal model, according to which the density  $\tilde{\rho}$ , heat capacity  $\tilde{C}_p$ , and heat conductivity  $\tilde{\lambda}$  of the mixture are all assumed to be constant. The parameter,  $\tilde{q}$ , in Eq. (1) denotes the reaction heat-release per unit mass of fuel.

The reaction rate of the one-step global reaction is  $\tilde{\omega} = \tilde{\rho}\tilde{A}\tilde{Y}\exp(-\tilde{E}/\tilde{R}^{\,0}\tilde{T})$ , in which  $\tilde{A}$  is the pre-factor of Arrhenius law,  $\tilde{E}$  the activation energy, and  $\tilde{R}^{\,0}$  the universal gas constant. The mixture-averaged diffusion model (Bongers and De Goey, 2003; Fong et al., 2012; Hirschfelder et al., 1954) is employed and the diffusive mass flux in Eq. (2) is

$$\tilde{j}_{Y} = -\tilde{\rho}\tilde{D}\left(\frac{d\tilde{Y}}{d\tilde{x}} + \alpha\tilde{Y}\frac{d\tilde{T}}{\tilde{T}d\tilde{x}}\right)$$
(3)

in which the first term on the right hand side represents mass flux due to Fickian diffusion while the second one due to Soret diffusion. Here  $\tilde{D}$  denotes the molecular diffusivity of fuel and  $\alpha$ is the Soret diffusion coefficient. Since Soret diffusion drives light/heavy molecules towards hot/cold region, the coefficient  $\alpha$  is typically negative for light species (e.g., atomic and molecular hydrogen) and positive for heavy fuels (e.g., n-heptane, n-decane) (Bongers and De Goey, 2003; Fong et al., 2012; Hirschfelder et al., 1954).

We introduce the following non-dimensional variables

$$x = \frac{\tilde{x}}{\tilde{\delta}_{f}^{0}}, \quad u = \frac{\tilde{u}}{\tilde{S}_{L}^{0}}, \quad T = \frac{\tilde{T} - \tilde{T}_{u}}{\tilde{T}_{ad} - \tilde{T}_{u}}, \quad Y = \frac{\tilde{Y}}{\tilde{Y}_{u}}, \quad \omega = \frac{\tilde{\omega}\tilde{\delta}_{f}^{0}}{\tilde{\rho}\tilde{S}_{L}^{0}\tilde{Y}_{u}}, \quad k = \tilde{k}\frac{\tilde{\delta}_{f}^{0}}{\tilde{S}_{L}^{0}}$$
(4)

where  $\tilde{T}_u$  and  $\tilde{Y}_u$  denote the temperature and fuel mass fraction in the fresh mixture. The characteristic speed  $\tilde{S}_L^0$ , characteristic length  $\tilde{\delta}_f^0 = \tilde{\lambda}/(\tilde{\rho}\tilde{C}_p\tilde{S}_L^0)$ , and characteristic temperature  $\tilde{T}_{ad} = \tilde{T}_u + \tilde{Y}_u\tilde{q}/\tilde{C}_p$  are, respectively, the laminar flame speed, flame thickness, and flame temperature of an adiabatic, unstretched, planar flame. The non-dimensional governing equations are

$$\frac{d^2T}{dx^2} + kx\frac{dT}{dx} + \omega = 0$$
(5)

$$\frac{d^2Y}{dx^2} + kLex\frac{dY}{dx} + \alpha \frac{d}{dx}(Yf) - \omega = 0$$
(6)

in which  $Le = \tilde{\lambda} / (\tilde{\rho} \tilde{C}_P \tilde{D})$  is the Lewis number of fuel. The boundary conditions are

$$x = 0$$
:  $dT / dx = 0$ ,  $Y = 0$  (7)

$$x \to +\infty$$
:  $T = 0$ ,  $Y = 1$  (8)

In Eq. (6), *f* represents the so-called "driving force" of Soret diffusion (Yang et al., 2010; Yang et al., 2011):

$$f = \frac{1}{\tilde{T}} \frac{d\tilde{T}}{d\tilde{x}} = \frac{1}{\gamma + T} \frac{dT}{dx} \quad \text{with} \quad \gamma = \frac{\tilde{T}_{\infty}}{\tilde{T}_{ad} - \tilde{T}_{\infty}}$$
(9)

In the limit of large activation energy, chemical reaction occurs within a very thin zone of

high temperature and the reaction rate can be replaced by the following Delta function (Joulin and Clavin, 1979; Veeraragavan and Cadou, 2011; Wu and Chen, 2012)

$$\omega = \left[\sigma + (1 - \sigma)T_f\right]^2 \exp\left[\frac{Z}{2}\frac{T_f - 1}{\sigma + (1 - \sigma)T_f}\right] \cdot \delta(x - x_f)$$
(10)

where  $\sigma = \widetilde{T}_u / \widetilde{T}_{ad}$  is the thermal expansion ratio and  $Z = \widetilde{E}(1-\sigma)/(\widetilde{R}^0 \widetilde{T}_{ad})$  the Zel'dovich number.

By integrating Eq. (6) from the flame front to the fresh region, we have

$$\frac{dY}{dx}\Big|_{x=x_f^+} = Le \int_{x_f^+}^{\infty} \left(kx \frac{dY}{dx}\right) dx$$
(11)

It is seen that the integration of Soret term in Eq. (6) is equal to zero in the fresh region. However, this does not mean that the Soret effect does not affect the propagation of a strained premixed flat flame. It is noticed that there is an x before dY/dx in the convective term in Eq. (6). Therefore, the integration of this convection term is not a constant and it depends on the distribution of fuel mass fraction. After Soret diffusion of fuel is considered, the distribution of fuel mass fraction changes and so does the integration of convection term in Eq. (6). Therefore, for a strained premixed flat flame, the integration of convection term in Eq. (6) in the fresh region does depend on the value of Soret diffusion coefficient. This is unlike the unstrained, 1-D, premixed planar flame, for which the integration of the convection term is equal to a constant and it does not depends on the value of Soret diffusion coefficient. Therefore, as shown in other numerical analysis (Xin et al., 2012; Yang et al., 2010), the stained premixed flat flame is affected by Soret diffusion.

Integrating Eqs. (5) and (6) around the flame interface  $x=x_f$  yields the following jump relations

$$\frac{dT}{dx}\Big|_{x_{f}^{+}} - \frac{dT}{dx}\Big|_{x_{f}^{+}} = \frac{1}{Le}\left(\frac{dY}{dx}\Big|_{x_{f}^{+}} - \frac{dY}{dx}\Big|_{x_{f}^{-}}\right) = [\sigma + (1-\sigma)T_{f}]^{2} \exp\left[\frac{Z}{2}\frac{T_{f}-1}{\sigma + (1-\sigma)T_{f}}\right]$$
(12)

#### 2.2 Analytical solution

Without the nonlinear reaction term, Eqs. (5-6) subjected to conditions given by Eqs. (7, 8, 12) can be solved analytically in the unburned  $(x \ge x_f)$  and burned  $(0 \le r \le x_f)$  zones. The analytical solution for the temperature distribution is

$$T(x) = \begin{cases} T_f & \text{for } 0 \le x \le x_f \\ T_f I(x,k) / I(x_f,k) & \text{for } x \ge x_f \end{cases}$$
(13)

where  $I(x,k) = \int_{x}^{\infty} \exp(-ks^2/2) ds$  and  $T_f$  is the flame temperature to be determined later.

For fuel-lean case, fuel is completely consumed in flame front and it appears only in the unburned zone. It is noted that we always have f < 0 since the temperature gradient is always negative in the unburned zone (see Eqs. 13 and 9). Since Soret diffusion is usually one-order smaller than Fickian diffusion, Eq. (6) can be solved asymptotically. By neglecting the second and higher order terms of  $O(\alpha^2)$ , we obtain the following expression for fuel mass fraction in the unburned zone ( $x \ge x_f$ )

$$Y(x) = Y_0(x) + \alpha Y_1(x)$$
(14)

$$Y_0(x) = 1 - I(x, kLe) / I(x_f, kLe)$$
(15)

$$Y_{1}(x) = 1 - \frac{I(x, kLe)}{I(x_{f}, kLe)} \int_{x_{f}}^{\infty} \frac{F(s)Y_{0}(s)}{dY_{0}(s)/ds} ds + \int_{x}^{\infty} \frac{F(s)[Y_{0}(s) - Y_{0}(x)]}{dY_{0}(s)/ds} ds$$
(16)

where  $F(x) = -d(Y_0 f) / dx$  and f(x) is defined in Eq. (9).

Substituting Eqs. (13-16) into the jump relations in Eq. (12), we obtain the following algebraic system of equations for stretch rate k, flame position,  $x_f$ , and flame temperature,  $T_f$ ,

$$T_{f} \frac{e^{-kx_{f}^{2}/2}}{\int_{x_{f}}^{\infty} e^{-k\xi^{2}/2} d\xi} = \frac{1}{Le} \frac{e^{-kLex_{f}^{2}/2}}{\int_{x_{f}}^{\infty} e^{-kLe\xi^{2}/2} d\xi} \left[ 1 + \alpha \int_{x_{f}}^{\infty} G(\xi) d\xi \right]$$

$$= [\sigma + (1 - \sigma)T_{f}]^{2} \exp\left[ \frac{Z}{2} \frac{T_{f} - 1}{\sigma + (1 - \sigma)T_{f}} \right]$$
(17)

in which

$$G(x) = T_{f} \frac{I(x, kLe)}{I(x_{f}, kLe)} \times \left\{ \frac{kx \cdot e^{k(Le-1)x^{2}/2} [I(x_{f}, kLe) - I(x, kLe)] - e^{-kx^{2}/2}}{\gamma I(x_{f}, k) + T_{f}I(x, k)} - \frac{T_{f}e^{k(Le-2)x^{2}/2} [I(x_{f}, kLe) - I(x, kLe)]}{[\gamma I(x_{f}, k) + T_{f}I(x, k)]^{2}} \right\}$$
(18)

By numerically solving Eq. (17) using the Newton's iteration method, we can get the flame position (*x<sub>f</sub>*), flame speed ( $S_L=kx_f$ ) and flame temperature ( $T_f$ ) as a function of flame stretch (*k*) for different Lewis numbers (*Le*) and Soret diffusion coefficients ( $\alpha$ ). When the Soret diffusion is neglected (i.e.,  $\alpha=0$ ), Eq. (17) reduces to

$$T_{f} \frac{e^{-kx_{f}^{2}/2}}{\int_{x_{f}}^{\infty} e^{-k\xi^{2}/2} d\xi} = \frac{1}{Le} \frac{e^{-kLex_{f}^{2}/2}}{\int_{x_{f}}^{\infty} e^{-kLe\xi^{2}/2} d\xi} = \left[\sigma + (1-\sigma)T_{f}\right]^{2} \exp\left[\frac{Z}{2} \cdot \frac{T_{f} - 1}{\sigma + (1-\sigma)T_{f}}\right]$$
(19)

which is the same as the previous results on adiabatic premixed counterflow flame (Chen and Ju, 2008; Ju et al., 2000). Therefore, in the limit of  $\alpha$ =0 the present analysis is consistent with previous studies without considering Soret diffusion.

It is noted that the deliberately idealized theoretical analysis is constrained by the assumptions of one-step chemistry, large activation energy, constant thermal and transport properties, and potential flow field. Other factors such as thermal expansion, boundary layer on the stagnation surface, and temperature-dependent diffusivities are not taken into consideration. Therefore, the present theoretical analysis only provides qualitative information on the influence of Soret diffusion on premixed counterflow flame.

#### **3. Results and discussion**

In the present study, emphasis is placed on examining the Soret diffusion effects on stretched flame speed, Markstein length, extinction stretch rate, and flame structure of premixed counterflow flame. Results at different values of Soret diffusion coefficient and Lewis number are obtained from Eq. (17). The Zel'dovich number, Z=10, and thermal expansion ratio,  $\sigma=0.22$ , and  $\gamma=\sigma/(1-\sigma)=0.282$ , are fixed. We consider two Lewis numbers, Le=0.5 and Le=2.0, which represent light and heavy fuels, respectively. Since the Soret diffusion coefficient,  $\alpha$ , is negative/positive for light/heavy species, we have  $\alpha=-0.1$  for Le=0.5 and  $\alpha=+0.1$  for Le=2.0. The approximate value of Soret diffusion coefficient is  $\alpha=-0.29$  for hydrogen molecule at high temperature (Fristrom and Monchick, 1988) and its absolute value decreases for hydrogen in the low-temperature preheat zone. As mentioned before, the Soret diffusion coefficient is assumed to be a constant which is a limitation of the present analysis. Therefore, we choose an approximately averaged value of  $\alpha=-0.1$  for light fuels. It is noted that the value of  $\alpha$  is somewhat arbitrarily chosen. Nevertheless, the same conclusion can be drawn even when other values of  $\alpha$  are used since the theory works for all different values of  $\alpha$ .

Figure 2(a) shows the change of flame position,  $x_f$ , with the stretch rate, k. It is observed that the flame approaches to the stagnation surface as the stretch rate increases. For both cases, there is a critical value of the stretch rate, beyond which the flame cannot exist. The critical stretch rate is the so-called extinction stretch rate and it is denoted by  $K_{ext}$ . For Le=0.5, flame extinction occurs when the flame is close to the stagnation surface. However, for Le=2.0, flame extinction occurs at the turning point on the  $x_{f}$ -k curve. The completely different extinction behavior for different Lewis numbers is due to the coupling between positive stretch rate and non-unity Lewis number (preferential diffusion between fuel and heat). The readers are referred to Ref. (Law, 2006) for detailed explanation.

Figures 2(b) and 2(c) shows the influence of Soret diffusion on stretched flame speed,  $S_L$ , and flame temperature,  $T_f$ . The flame temperature is slightly affected by Soret diffusion and the influence becomes stronger as the extinction stretch rate is approached. Since the flame speed depends on flame temperature in the Arrhenius form with large activation energy, the stretched

flame speed is shown to be much more strongly affected by Soret diffusion than flame temperature.

For light fuel with Le=0.5, Fig. 2 shows that flame position, stretched flame speed, and flame temperature become larger after considering Soret diffusion (i.e., the Soret diffusion coefficient changes from  $\alpha=0$  to  $\alpha=-0.1$ ). This indicates that the premixed counterflow flame becomes stronger and more difficult to be extinguished after including Soret diffusion. This is reasonable since Soret diffusion facilitates mass transport of light fuel towards the hightemperature reaction zone (see Fig. 3) and thereby leads to approaching stoichiometry for the lean flame and increase of the burning intensity. On the other hand, for heavy fuel with Le=2.0, Fig. 2 indicates that the premixed counterflow flame becomes weaker after considering Soret diffusion ( $\alpha$  changes from  $\alpha=0$  to  $\alpha=+0.1$ ). This is because Soret diffusion inhibits mass transport of heave fuel towards the reaction zone (see Fig. 3) and thereby leads to further departure from stoichiometry. The theoretical results shown in Fig. 2 are compatible with those from simulation considering detailed chemistry and transport (Xin et al., 2012; Yang et al., 2010): for premixed counterflow flame of lean H<sub>2</sub>/air (the equivalence ratio is  $\phi$ =0.35), numerical simulation by Yang et al. (Yang et al., 2010) showed that the flame becomes stronger after considering the Soret diffusion of hydrogen molecule; and for lean nC<sub>7</sub>H<sub>16</sub>/air ( $\phi$ =0.6), numerical simulation by Xin et al. (Xin et al., 2012) showed that the flame becomes weaker after considering the Soret diffusion of heptane molecule.

In order to interpret the dependence of Soret diffusion influence on stretch rate, we examine the fuel transport to reaction zone due to Fickian diffusion and that due to Soret diffusion. These two mass fluxes are calculated according to the following expressions

$$J_{\text{Fickian}} = \frac{1}{Le} \frac{dY_0(x)}{dx} \bigg|_{x=x_f}, \quad J_{\text{Soret}} = \frac{\alpha}{Le} \frac{dY_1(x)}{dx} \bigg|_{x=x_f}$$
(20)

where  $Y_0(x)$  and  $Y_1(x)$  are respectively given in Eqs. (15) and (16). Figure 3 shows the ratio between  $J_{\text{Soret}}$  and  $J_{\text{Fickian}}$  as a function of stretch rate for Le=0.5 and Le=2. As expected, the mass flux due to Soret diffusion is much smaller than that due to Fickian diffusion. It is observed from Fig. 3 that the Soret effect on the net diffusive flux is merely a few percent, which is due to the factor Y/T in the Soret diffusion term (see Eq. 3) – as the mixture approaches the reaction zone, Y decreases and T increases. For light fuel with Le=0.5 and  $\alpha=-0.1$ , both  $J_{\text{Soret}}$  and  $J_{\text{Fickian}}$ are positive, indicating that Soret diffusion increases the equivalent mass diffusivity and thereby reduces the effective Lewis number. For heave fuel with Le=2.0 and  $\alpha=+0.1$ , we have  $J_{\text{Soret}}<0<J_{\text{Fickian}}$ , indicating that Soret diffusion reduces the equivalent mass diffusivity and thereby increases the effective Lewis number. It is well known that positively-stretched flame becomes stronger/weaker at smaller/larger Lewis number (Law, 2006). Therefore, Soret diffusion strengthens and weakens the premixed counterflow flame for *Le*=0.5 and *Le*=2.0, respectively.

Figure 3 also shows that the ratio,  $|J_{\text{Soret}}/J_{\text{Fickian}}|$ , increases with the stretch rate, indicating that Soret diffusion has stronger influence at higher stretch rate. This is consistent with results in Fig. 2. With the increase of stretch, the flame front moves toward the stagnation surface (see Fig. 2a) and the preheat zone become narrower. Consequently, the temperature gradient and thereby Soret diffusion increase with stretch rate. This is demonstrated by Fig. 4 which shows the temperature and fuel mass fraction distributions at different stretch rates for *Le*=0.5. At fixed stretch rate, Soret diffusion is shown to modify the distributions of temperature and fuel mass fraction and promotes the fuel transport to the reaction zone. When the stretch rate is increased from  $0.1K_{\text{ext}}$  to  $0.9K_{\text{ext}}$ , the flame becomes closer to the stagnation surface and both temperature and fuel mass fraction gradients are shown to increase.

The Markstein length/number is used to characterize the influence of external stretching on local flame speed. For weakly stretched flames, there is a linear relationship between the stretched flame speed,  $S_L$ , and stretch rate, k, (i.e.,  $S_L = S_L^0 - L \cdot k$ , where  $S_L^0$  is the flame speed at zero stretch rate). Therefore, Markstein length, L, can be obtained from linear extrapolation between  $S_L$  and K. The Markstein length at different Soret diffusion coefficients are obtained and the normalized results for Le=0.5 and Le=2.0 are shown in Fig. 5. It is seen that the normalized Markstein length increases linearly with the absolute value of Soret diffusion coefficient. This indicates that for both light and heavy fuels, the stretched flame speed becomes more sensitive to stretch rate after including Soret diffusion. This observation is also consistent with the previous discussion on the change of effective Lewis number by Soret diffusion. After including Soret diffusion, the effective Lewis number decreases/increases for Le=0.5/Le=2.0 and thereby the stretch effects become stronger. Furthermore, it is observed that the influence of Soret diffusion on Markstein length of light fuel with Le=0.5 is much stronger that on Markstein length of heavy fuel with Le=2.0. This is due to the fact that the higher flame temperature and temperature gradient at smaller Lewis number induces stronger Soret diffusion.

Besides the Markstein length, the influence of Soret diffusion on the extinction stretch rate is also studied. It is noted that the extinction strain rate is highly sensitive to the variations in the diffusive properties. The presence of Soret diffusion can decrease/increase the effective Lewis numbers of light/heavy fuels (Han and Chen, 2015). Therefore, it is expected that Soret diffusion can have relatively strong influence on the extinction strain rate for flames containing sufficiently light/heavy fuels. Figure 6 shows the normalized extinction stretch rate as a function of Soret diffusion coefficient for light fuel with Le=0.5 and heavy fuel with Le=2.0. Consistent with results in Fig. 2, Soret diffusion increases and decreases the extinction stretch rate for light fuel (*Le*=0.5) and heavy fuel (*Le*=2.0), respectively. Specially, the extinction stretch rate is increased by 38% for light fuel with *Le*=0.5 after  $\alpha$  is changed from 0 to -0.1 and it is reduced by 8.7% for heavy fuel with *Le*=2.0 after  $\alpha$  is changed from 0 to +0.1. Therefore, Soret diffusion should be considered when the extinction stretch rate is used in chemical mechanism validation and development. In fact, simulation with detailed chemistry (Xin et al., 2012; Yang et al., 2010) also indicated discernible effects of Soret diffusion on the extinction stretch rate: for premixed counterflow flame of lean H<sub>2</sub>/air (the equivalence ratio is  $\phi$ =0.35), Yang et al. (Yang et al., 2010) showed that extinction stretch rate is increased by 24% after considering the Soret diffusion of hydrogen molecule; and for lean nC<sub>7</sub>H<sub>16</sub>/air ( $\phi$ =0.6), Xin et al. (Xin et al., 2012) showed that the extinction stretch rate is reduced by 18% after considering the Soret diffusion of heptane molecule. Moreover, Fig. 6 indicates that the sensitivity of extinction stretch rate of light fuel to Soret diffusion is much stronger than that of heavy fuel. Therefore, Soret diffusion has strong influence on the extinction of lean premixed counterflow flames containing very light species such as atomic and molecular hydrogen.

# **4.** Conclusions

A simplified premixed counterflow flame model including Soret diffusion is analyzed within the framework of large activation energy and potential flow. A general correlation among flame stretch rate, flame position, and flame temperature is derived. It is used to assess the Soret diffusion effects on premixed counterflow flame structure, Markstein length, and extinction stretch rate at different Lewis numbers. It is found that Soret diffusion quantitatively affects the flame position, flame temperature, and stretched flame speed of premixed counterflow flame and that the influence of Soret diffusion greatly depends on Lewis number and stretch rate. For light fuel with Le<1, the premixed counterflow flame becomes stronger and more difficult to be extinguished after including Soret diffusion. The opposite trend occurs for heavy fuel with *Le>*1. This is due to the fact that Soret diffusion facilitates/inhabits mass transport of light/heavy fuel towards the reaction zone and thus modifies the local stoichiometry. With the increase of stretch rate, the mass transport due to Soret diffusion increases and thereby Soret diffusion has stronger influence at higher stretch rate. Furthermore, it is shown that the normalized Markstein length linearly increases with the Soret diffusion coefficients, indicating that for both light and heavy fuels, the stretched flame speed becomes more sensitive to stretch rate after including Soret diffusion. In term of extinction stretch rate, it is increased by Soret diffusion for light fuel. Therefore, for the extinction of lean premixed counterflow flames containing very light species, the Soret diffusion effects should be considered.

It is noted that near-limit combustion processes such as extinction and ignition are much more sensitive to Soret diffusion than normal flame propagation process. Besides, the Soret diffusion is important for cases with sufficiently light or heavy species and strong temperature gradients and it can be negligible for normal hydrocarbon fuels. As suggested by one of the anonymous reviewers, the uncertainties in diffusive coefficients in the case of detailed flame calculations might be much larger than the Soret diffusion coefficient which is difficult to be accurately estimated. Therefore, the importance of the Soret diffusion effect should not be overemphasized.

## Acknowledgments

This work was supported by National Natural Science Foundation of China (Nos. 51322602 and 51136005) and Doctoral Fund of Ministry of Education of China (Nos. 20120001110080 and 20100001120003). We thank Professor Chung K. Law and Mr. Wenkai Liang at Princeton University for helpful discussions.

# References

- Arias-Zugasti, M. and Rosner, D.E., 2008. Soret transport, unequal diffusivity, and dilution effects on laminar diffusion flame temperatures and positions. Combust. Flame, 153(1– 2): 33-44.
- Bongers, H. and De Goey, L.P.H., 2003. The effect of simplified transport modeling on the burning velocity of laminar premixed flames. Combust. Sci. Technol., 175(10): 1915-1928.
- Chen, Z. and Ju, Y., 2008. Combined effects of curvature, radiation, and stretch on the extinction of premixed tubular flames. Int. J. Heat Mass Transfer, 51(25–26): 6118-6125.
- Ern, A. and Giovangigli, V., 1998. Thermal diffusion effects in hydrogen-air and methane-air flames. Combust. Theor. Model., 2(4): 349-372.
- Ern, A. and Giovangigli, V., 1999. Impact of detailed multicomponent transport on planar and counterflow hydrogen/air and methane/air flames. Combust. Sci. Technol., 149(1-6): 157-181.
- Fong, D., Bechtold, J.K. and Law, C.K., 2012. Asymptotic structure of laminar diffusion flames at high pressure. Physics of Fluids, 24: 093602.
- Fristrom, R.M. and Monchick, L., 1988. Two simple approximations to the thermal diffusion factor and their applications to flame studies. Combust. Flame, 71(1): 89-99.
- Garcia-Ybarra, P. and Clavin, P., 1981. Cross-transport effects in nonadiabatic premixed flames. Proceedings of the 7th International Colloquium on Gasdynamics of Explosions and Reactive Systems: 463-481.
- Garcia-Ybarra, P., Ncoli, C. and Clavin, P., 1984. Soret and dilution effects on premixed flames. Combust. Sci. Technol., 42: 87-109.
- Gomez, A. and Rosner, D.E., 1993. Thermophoretic effects on particles in counterflow laminar diffusion flames. Combust. Sci. Technol., 89: 335-362.
- Han, W. and Chen, Z., 2015. Effects of Soret diffusion on spherical flame initiation and propagation. Int. J. Heat Mass Transfer, 82: 309-315.

- Hirschfelder, J.O., Curtiss, C.F. and Bird, R.B., 1954. Molecular theory of gases and liquids. John Wiley.
- Joulin, G. and Clavin, P., 1979. Linear-stability analysis of non-Adiabatic flames diffusionalthermal model. Combust. Flame, 35: 139-153.
- Ju, Y., Masuya, G., Liu, F., Hattori, Y. and Riechelmann, D., 2000. Asymptotic analysis of radiation extinction of stretched premixed flames. Int. J. Heat Mass Transfer, 43(2): 231-239.
- Law, C.K., 2006. Combustion Physics. Cambridge University Press.
- Liang, W., Chen, Z., Yang, F. and Zhang, H., 2013. Effects of Soret diffusion on the laminar flame speed and Markstein length of syngas/air mixtures. Proc. Combust. Inst., 34: 695-702.
- Rosner, D.E., Israel, R.S. and Mantia, B.L., 2000. "Heavy" species Ludwig-Soret transport effects in air-breathing combustion. Combustion and Flame, 123: 547-560.
- Veeraragavan, A. and Cadou, C.P., 2011. Flame speed predictions in planar micro/mesoscale combustors with conjugate heat transfer. Combust. Flame, 158: 2178-2187.
- Wu, Y. and Chen, Z., 2012. Asymptotic analysis of outwardly propagating spherical flames. Acta Mech. Sin., 28: 359-366.
- Xin, Y., Sung, C.-J. and Law, C.K., 2012. A mechanistic evaluation of Soret diffusion in heptane/air flames. Combust. Flame, 159(7): 2345-2351.
- Yang, F., Law, C.K., Sung, C.J. and Zhang, H.Q., 2010. A mechanistic study of Soret diffusion in hydrogen–air flames. Combust. Flame, 157(1): 192-200.
- Yang, F., Zhang, H.Q. and Wang, X.L., 2011. Effects of soret diffusion on the laminar flame speed of n-butane-air mixtures. Proc. Combust. Inst., 33(1): 947-953.
- Zhang, H. and Chen, Z., 2011. Spherical flame initiation and propagation with thermally sensitive intermediate kinetics. Combust. Flame, 158: 1520-1531.



Fig. 1 The schematic diagram of the premixed counterflow flame.



Fig. 2 Change of (a) flame position, (b) stretched flame speed, and (c) flame temperature with the stretch rate for premixed counterflow flame of light fuel (Le=0.5) and heavy fuel (Le=2.0).



Fig. 3 The ratio between fuel transportation to the reaction zone due to Soret diffusion,  $J_{\text{Soret}}$ , and that due to Fickian diffusion flux,  $J_{\text{Fickian}}$ , as a function of stretch rate for *Le*=0.5 and *Le*=2.0.



Fig. 4 Temperature and fuel mass fraction distributions with and without considering Soret diffusion.



Fig. 5 The normalized Markstein length as a function of Soret diffusion coefficient.  $L(\alpha=0)=-4.5$  for Le=0.5 and  $L(\alpha=0)=+3.8$  for Le=2.0.



Fig. 6 The normalized extinction stretch rate as a function of Soret diffusion coefficient.  $K_{\text{ext}}(\alpha=0)=53.58$  for Le=0.5 and  $K_{\text{ext}}(\alpha=0)=0.086$  for Le=2.0.