

Synthesis of Nanocrystalline Nickel-Zinc Ferrites via a Microemulsion Route

V. Uskoković¹ and M. Drofenik²

¹The Jožef Stefan Institute, Ljubljana ²Faculty of Chemistry and Chemical Engineering, Maribor

Keywords: Co-precipitation, CTAB, Ferrite, Nanomaterial, pH, Reverse Micelle

ABSTRACT

Nanostructured NiZn-ferrites were synthesized using a low-temperature co-precipitation method within the reverse micelles of ternary CTAB/1-hexanol/water microemulsions. The influence of pH on the precipitation reaction was investigated. It was found that a higher pH resulted in more crystalline particles. Subsequent oxidation of the ferrous ions and their precipitation, which leads to the formation of spinel ferrites, is discussed. Diffraction-lines broadening and specific surface area measurements revealed an average particle size of ~ 3 nm. The saturation magnetization of the samples was 20 times smaller than for traditionally synthesized NiZn-ferrites, while the coercivities were 10 - 100 times larger than for bulk NiZn-ferrites, which is consistent with the nanocrystalline nature of the synthesized magnetic material. TEM investigations were used to show the agglomerated nature of the synthesized samples, which is the reason why the samples do not show superparamagnetic behavior.

1. INTRODUCTION

Nickel-zinc ferrites [1] are of great interest to modern electronic industry since they have been used as electronic components [2] such as transformer cores, giant magneto-resistant materials, recording heads [3], antennas or loading coils. The main properties of NiZn-ferrites, which make them unique magnetic ceramic materials are their high electrical resistivity, which in turn lead to lower eddy current losses, the losses that become significant in EM fields of high frequencies. The main idea behind the production of nanostructured NiZn-ferrites is that their electrical resistivity might be pushed to higher values due to increased concentration of grain boundaries [4]. Deagglomerated nanosized and single-domain magnetic particles are constituent parts of magnetic fluids [5], which are used in novel dynamic speakers, acoustic devices [6] and "magnetic vs. non-magnetic" separators.

Different low-temperature routes (often called wet routes) for synthesis of ferrite powders, such as co-precipitation [7], sol-gel [8], hydrothermal syntheses [9] and others are described in the literature. All of these low-temperature methods were primarily invented in order to overcome difficulties arising out of the traditional high-temperature way of ferrites syntheses, which characterize weak control over the final composition, chemical inhomogeneity, broad distribution of particle sizes, and inevitable product's contamination with impurities during the stages of grinding and mixing. It is known that by using a relatively novel (21 years old [10]) reverse-micelle-microemulsion method of synthesis, particles of controllable and uniform sizes and shapes might be obtained [11]. Relatively low processing costs and low syntheses temperatures make the microemulsion-assisted synthesis of ferrite particles alluring for various applications. Multiple microemulsion approaches, where different reactants are closed inside the respective reverse micelles, are within previously mentioned class proven to be more successful route [12] compared

Licensed to Uskokovic (vuk.uskokovic@ijs.si) - Jožef Stefan Institute - Slovenia

All rights reserved. No part of the contents of this paper may be reproduced or transmitted in any form or by any means without the written permission of the publisher: Trans Tech Publications Ltd, Switzerland, <u>www.ttp.net</u>. (ID: 194.249.156.228-11/08/05,12:31:38)

to the single-microemulsion approach where the reactants are let to diffuse in water cores of reverse micelle where the chemical reactions of the synthesis take place.

2. EXPERIMENTAL

The ternary CTAB/water/1-hexanol microemulsion was used as a medium in which $Ni_{0.5}Zn_{0.5}Fe_2O_4$ was synthesized. The following chemicals were used: $FeSO_4 \cdot 7H_2O$ (>99%, Alfa Aesar), $NiSO_4 \cdot 7H_2O$ (99,7%, Podnart), $ZnSO_4 \cdot 7H_2O$ (>99%, Alfa Aesar) as precursor salts; CTAB (>99%, Alfa Aesar) as a surfactant; 1-hexanol (>98%, Merck-Schuchardt) as the oil phase; deionized water as the aqueous phase; (CH₃)₄NOH (25 wt %, 99,5% purity, Alfa Aesar) as a precipitating agent; H_2O_2 (30 wt %, Carlo Erba) as an oxidating agent; H_2SO_4 (99,8%, Carlo Erba) as an acidifying agent; ethanol (99,8%, Carlo Erba) and deionized water as washing substances. The chemical composition (CTAB:hexanol: $H_2O = 30.5:57:12.5$) of the templating reverse micellar microemulsion for *in situ* synthesis of NiZn-ferrite was chosen from the previous work [13]. When using a divalent iron salt as a precursor component, pH of the solution must be under 1.8 so as to avoid early oxidation of ferrous ions.



Fig. 1. Flow chart of the NiZn-ferrite nanopowder synthesizing procedure by using the microemulsion route.

The formation of NiZn-ferrite particles by hydrolysis and subsequent oxidation of the alkaline suspension of hydroxides $Fe(OH)_2$, $Ni(OH)_2$ and $Zn(OH)_2$ is based on Schikorr's reaction [14]. The reaction proceeds within the "water pools" of reverse micelles and is governed by oxidation of the mixture of metal hydroxides of an appropriate composition in an alkaline media. The synthesis route of the produced NiZn-ferrites is shown in Fig.1. Three separate microemulsions under controlled temperature in air were applied to obtain nanosized NiZn-ferrite. The first one comprised aqueous solution of precursor cations in total concentration of 0.237 M and with pH=1.6, the second microemulsion comprised aqueous 5 wt% (CH₃)₄NOH solution, while the third microemulsion carried aqueous 30 wt% H₂O₂ solution in its "water pools".

The obtained nanoparticles morphologies were investigated using TEM (JEOL JEM-2000FX). The powders were also characterized by X-ray diffraction analyses (D4 Endeavour), specific magnetization measurements (MANICS DSM10) and specific surface-area measurements (Micromeritics Gemini II analyzer).

3. RESULTS AND DISCUSSION

The X-ray diffraction patterns of the synthesized nanopowders at the precipitation pH values higher than 8 and below 8 are shown in Fig. 2.



Fig. 2. X-ray patterns of the sample synthesized at the precipitation pH below 8 (down) and above 8 (up). Spinel-derived peaks are denoted by S, while goethite-derived peaks are denoted by G.

During the oxidation of the microemulsion, two concurrent reactions depending on the hydroxide ion concentration take place. The first reaction is associated with the oxidation of iron(II) hydroxide and incorporation of Fe³⁺ into NiZn-ferrite spinel, while the second reaction leads to the formation of goethite (α -FeOOH), which might also persist as an intermediate compound in the formation of ferrite.

Simplified chemical reactions for the both processes can be written as:

 $\frac{1}{2Ni^{2+} + \frac{1}{2Zn^{2+} + 2Fe^{2+} + 6OH^{-} + \frac{1}{2O_2} \rightarrow Ni_{0.5}Zn_{0.5}Fe_2O_4 + 3H_2O}{2Fe^{2+} + 4OH^{-} + \frac{1}{2O_2} \rightarrow 2FeOOH + H_2O}$

At sufficiently high concentrations of hydroxyl ions, i.e. at pH > 8, NiZn-ferrite is formed, while at lower pH values, goethite appears as the main phase. In order to achieve a higher pH value when following a multi-microemulsion approach, the amount of the alkaline microemulsion was varied so that the parameter w, that is the molar ratio of water to surfactant, remains the same during the course of each experiment. This can be observed in Table I where the particle size is of the same order of magnitude for all samples, but slightly larger for the samples synthesized at higher pH values (11-13.5). It is well known that the main factor for regulating the average particle size of the synthesized samples is the parameter w, although dynamic intermicellar interaction has attracted

Table 1 Sample ID, pH of the precipitation, identified crystalline phases, specific surface area (A_s), average grain size obtained from the measured specific surface (d_s) and x-ray broadening

mediationents (ux), and sutaration magnetization (ivis)						
Sample ID	pН	Identified phases	As	ds	d_x	Ms
			(m^2/g)	(nm)	(nm)	(emu/g)
F	4	Goethite	-	-	-	0.8
G	4	Goethite	-	-	-	0.8
Н	8	Spinel	212	6	2	1.2
Ι	9	Spinel	305	4	3	0.9
J	10	Spinel	318	4	2	1.1
K	11	Spinel	303	4	4	4.2
L	12	Spinel	261	5	4	4.6
М	13	Spinel	350	4	4	4.6
N	13,5	Spinel	333	4	4	5.4

measurements (d_x) , and saturation magnetization (M_s)



Fig. 3. TEM images of the sample I (a) and the sample K (b).

significant attention recently. The calculated diameter of the water pools [15] for the given weight percentage of water (12.5 %) is equal to 2.4 nm, which is very close to the average particle size estimated from the broadening of diffraction lines (2 - 4 nm).

TEM images of the I and K powders are shown in Fig.3. The sample I, just as all the synthesized samples between the precipitation pH values of 8 and 10, is featured by acicular particles, and consequently, due to their high anisotropy, large values of coercivities. On the other hand, the samples synthesized at the precipitation pH values ≥ 11 consist of uniformly sized agglomerated particles. The agglomerated nature of the synthesized powders is the reason why they disobey the superparamagnetic model [16]. The measured coercivities varied from 24 to 1300 Oe, which is in the latter case about 100 times larger compared to bulk samples of the same chemical composition. Acicular particles in the samples synthesized at medium pH values might be derived from the acicular nature of a certain FeOOH phase, which is probably an intermediate ferric compound present during the process of formation of NiZn-ferrite. Otherwise, medium pH values might promote spherical-to-worm-like transition of CTAB reverse micelles, which might then serve as templates for the synthesis of acicular crystallites [17].

A typical hysteresis loop of the synthesized NiZn-ferrite nanopowder via microemulsion route is shown in Fig. 4a, while the dependence of the saturation magnetization of samples on the pH value of the precipitation is shown in Fig. 4b.



Fig. 4. a.) A hysteresis loop of the nanosized NiZn-ferrite powder N; b.) Saturation magnetization of samples versus pH of precipitation

The saturation magnetizations of samples have much lower values compared to the values characteristic of bulk-synthesized samples. It is well established that the size of magnetic particles has an influence on the resulting saturation magnetization of the material [18,19]. This phenomenon was observed in several ferrite systems [20] and was explained by a magnetically "dead" layer on the surface of particles [21], which is a consequence of non-collinear surface spins. Many other reasons such as crystal lattice defects, mass effects of absorbed water, chemical and physical changes on the surface, magnetic degradation of the surface or redistribution of cation sites in the lattice might be taken into account when considering a decrease in magnetization with reducing average particle size. Since the average particle sizes of the synthesized NiZn-ferrites are found to be in the range of 2-4 nm, about half of all the atoms in the material are positioned on the particles' surfaces. An increase in size of crystallite domains as determined from XRD-lines-broadening measurements, between precipitation pH values of 10 and 11 (Table 1) is reflected on a 4-fold increase in saturation magnetization between these two synthesizing pH values (Fig. 4b). Nevertheless, even at the precipitation $pH \ge 11$, the samples magnetizations are smaller by a factor of about 20 compared to bulk-synthesized NiZn-ferrites, and this ratio of magnetizations for NiZnferrites synthesized using traditional and microemulsion routes was already predicted in the literature [22].

Prolonging or shortening the time between the initiated precipitation reaction and the isolation of magnetic particles (which was usually 1 hour) did not leave any significant traces on magnetic or crystalline characteristics of the powder. It was only revealed that the coercivity of the samples decreases with the aging time (from 1300 to 800 to 400 Oe as the aging time was prolonged from 30 min to 1 h to 2 h for the sample H), which might be related to the refinement of the surface of the particles, so that they can more easily change the direction of magnetic moments. The purpose of the third, oxidating microemulsion is still not clear since there were no changes in crystallinity at H₂O₂-oxidized and H₂O₂-non-oxidized samples, whereas the H₂O₂-oxidized sample had for about 50 % higher magnetization than the H₂O₂-non-oxidized sample. Thus, completion of the dissolved oxygen or the decomposition of water-initiated [23] oxidation of ferrous ions, which along the way serve as spinel crystallization nuclei, and refinement of spinel particles initiated by exothermic reaction of oxidation might be taken into account to happen when using this step in the procedure.

4. CONCLUSIONS

The results presented here show that the performed low-temperature co-precipitation technique within the reverse micelles of the CTAB/1-hexanol/H₂O microemulsion system by using triplemicroemulsion procedure is appropriate for the synthesis of nanostructured NiZn-ferrite particles of uniform sizes. pH value of the precipitation should exceed 8 in order to yield spinel as the main phase, and should exceed 11 in order to gain particles of uniform morphology. With the increase in the precipitation pH, the magnetization increases too, while the XRD-determined average particle size remains at ~ 4 nm. TEM investigations revealed coral-like agglomerated nature of the nanoparticles synthesized at higher pH value, while the existence of acicular particles was observed within the sample synthesized at medium pH values. Increase in aging time leads to the decrease in large coercivities, which suggests refinement of particles in microemulsion in time.

REFERENCES

- [1] A. Goldman, Modern Ferrite Technology, Van Nostrand Reinhold (1990).
- [2] T. Abraham, Am. Cer. Soc. Bull. 73, 62 (1994).
- [3] J. A. Burg, T. C. Anthony, J. H. Nickel, Mater. Res. Bull. 21(9) 23-27(1996).
- [4] C. R. Hendricks, V. W. R. Amarakoon, D. Sullivan, Cer. Bull. 70 (5) 817 823 (1991).
- [5] K. Raj, B. Moskowitz, R. Casciari, J. Magn. Magn. Mater. 149, 174 180 (1995).
- [6] V. E. Fertman, Magnetic Fluids Guidebook, Hemisphere Publ. Corp., New York (1990).
- [7] Soft Ferrites, A Users's Guide; Magn. Mater. Producers Association, Chicago, IL, (1997).
- [8] A. Goldman and A.M. Laing, J. Phys. (Paris) 4 (38) C1-297-C1-301 (1977).
- [9] M. Rozman and M. Drofenik, J. Am. Ceram. Soc. 78 (9) 2449-55 (1995).
- [10] M. Boutonnet, J. Kizling, P. Stenius, Coll. & Surf. 5 (3), 209 225 (1982).
- [11] D. O. Yener, H. Giesche, J. Am. Cer. Soc. 84 (9) 1987-95 (2001).
- [12] J. Wang, P. F. Chong, S. C. Ng, L. M. Gan, Mater. Lett. 30, 217 221 (1997).
- [13] V. Uskoković, M. Drofenik, Mater. & Tech. 37 (3-4) 129 131 (2003).
- [14] G. Schicorr, Z. Allgem. Chem. 212, 33-38 (1938).
- [15] E. Rodenas, M. Valiente, Coll. & Surf. 62, 289 295 (1992).
- [16] C. P. Bean, J. D. Livingston, J. Appl. Phys. 30 (4) 120S 129S (1959).
- [17] S. Xu, H. Zhou, J. Xu, Y. Li, Langmuir 18, 10503 10504 (2002).
- [18] R. H. Kodama, J. Magn. Magn. Mater. 200, 359 372 (1999).
- [19] J. P. Chen, C. M. Sorenson et al, Phys. Rev. 54 (13), 9288-96 (1996).
- [20] T. Sato, T. Iijima, M. Seki, N. Inagaki, J. Magn. Magn. Mater. 65, 252 (1987).
- [21] A. E. Berkowitz, W. J. Schule, P. J. Flanders, J. Appl. Phys. 39, 1261 (1987).
- [22] S. Santra, R. Tapec, N. Theodoropoulou et al., Langmuir 17, 2900 2906 (2001).
- [23] H. Robbins, Proceedings of the ICF, Center for Academic Publications, Japan (1981).
- [24] Y. Todaka, M. Nakamura, S. Hattori et al., Mater. Trans. 44 (2) 277 284 (2003).