

1 Introduction

2 Total irrigated area in Mexico is 6.46 Mha. Corn crop covers 22% of this surface, with an
3 average yield around 7.33 Mg ha⁻¹; nevertheless, yields in Northern and Central Mexico
4 (semi-arid climate) decrease until 5.37 Mg ha⁻¹. Factors such as crop genetics, soil
5 characteristics, fertilizer application, and water requirements affect corn production. Tyagi
6 et al. (2003) showed yields and quality of maize declining due to inadequate water supply
7 and inappropriate irrigation scheduling. Kiziloglu et al. (2009) indicated that water stress
8 has an important effect on water consumption and yield of maize and reported a positive,
9 strong linear relationship between yield and water use. Improvement of irrigation water
10 management calls for an accurate knowledge of crop water requirements or crop
11 evapotranspiration (ET_c).

12 ET_c is generally calculated as the product of a crop coefficient (K_c) and the reference
13 evapotranspiration (ET_o) (Allen et al. 1998). K_c varies along the crop phenological
14 development, i.e. K_c can be plotted as a function of time during the crop season. Different
15 methodologies have been proposed to plot K_c curves. The Food and Agriculture
16 Organization of the United Nations (FAO) proposed defining four phenological stages
17 (initial, development, mid-season and late or final stages), estimating three K_c values (at
18 the initial, K_{Cini}, mid-season, K_{Cmid}, and late-season, K_{Cend}), and connecting straight line
19 segments through each of the four growth stages (Allen et al. 1998); horizontal lines are
20 drawn through K_c in the initial and mid-season stages, while diagonal lines are drawn
21 from K_{Cini} to K_{Cmid} within the course of the development stage and from K_{Cmid} to K_{Cend}
22 within the course of the late-season stage.

1 Applying the approach proposed by Allen et al. (1998) is quite simple. However, the
2 practical definition of the four crop growth stages is quite cumbersome for a great number
3 of crops because these stages are not based on standard phenological stages as used by
4 farmers or technicians. In addition, the approach proposed by Allen et al. (1998) requires
5 the crop growth stages and the general average meteorological conditions be defined in
6 advance at the beginning of the season. Thus, in practice, this leads to the use of a fixed K_c
7 curve along different years particularly for real time scheduling irrigation. Alternative
8 approaches estimate K_c as a continuous function of other parameters easier to determine
9 along the season allowing the K_c curve be modified as a function of the year-to-year
10 variability. Thus, K_c can be computed as a function of days after sowing (Ojeda-
11 Bustamante et al. 2004; Kang et al. 2003; Sepaskhah and Andam 2001) although this
12 approach show limitations for real-time crop water requirements estimation because they
13 do not take into account the environmental variations that occur year by year and the
14 effect of cultural factors on the rate of canopy development (Martínez-Cob 2008). Other
15 authors have proposed obtaining the K_c curve as a function of several other parameters:
16 leaf area index, percent ground cover and cumulative growing degree days (or thermal
17 units, TU). These approaches use variables that are more closely related to crop
18 development and they respond to the year-to-year variability. Temperature variability
19 prevails as one of the most important environmental factors affecting the growth and yield
20 of crops (Yan and Hunt 1999). That variability has a direct and strong influence on crop
21 development (Ritchie and NeSmith 1991). Several previous studies have developed
22 equations to estimate crop coefficients as a function of that variable, either using the
23 absolute values of cumulative thermal units (TU) or using the fraction of thermal units
24 (FTU, i.e the fraction of cumulative TU at a given period to the total seasonal cumulative

1 TU) (Martínez-Cob 2008; Kang et al. 2003; Grattan et al. 1998; Steele et al. 1996; Nielsen and
2 Hinkle 1996; Amos et al. 1989; Sammis et al. 1985). The use of thermal units is
3 recommended as it can be easily computed from readily available daily air temperature at
4 on-line weather station networks. The use of FTU is preferred over the use of TU as it
5 allows a general application of the crop coefficient curve across cultivars requiring
6 different TU totals from emergence or budbreak to harvest or physiological maturity
7 (Amos et al. 1989). The generalization of these types of equations would require their
8 validation for conditions different from which they were developed. This validation
9 studies should focus on the consequences on crop water management and crop
10 productivity of using those equations for irrigation scheduling as compared to using the
11 standard, worldwide applied procedure proposed by Allen et al. (1998).

12 A number of researches have evaluated yields for various crops under different
13 experimental irrigation doses expressed as percentages of ET_c computed using K_c
14 derived from the FAO or other alternative approaches (Bezerra et al. 2012; Dehghanisanij et
15 al. 2009; Dioudis et al. 2009; Ko and Piccinni 2009; López-Urrea et al. 2009; Vories et al.
16 2009; Kar et al. 2007; Ojeda-Bustamente et al. 2006). Nevertheless, there is a lack of studies
17 comparing several K_c approaches in terms of seasonal crop water requirements, yields
18 and water productivity.

19 The objectives of this work were: 1) to estimate daily corn K_c values from FAO
20 methodology as well as using the equation developed by Martínez-Cob (2008) to estimate
21 the corn K_c curve from the fraction of thermal units equation (FTU_{MC}); 2) to compare the
22 corn crop water requirements and irrigation doses estimated using both approaches; 3) to

1 evaluate the consequences of both irrigation approaches on the water use productivity and
2 the corn crop production.

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

1 **Material and methods**

2 The experimental work was conducted during the 2009 and 2010 growing seasons at a 5 ha
3 commercial farm located at Chupaderos aquifer, 18 km northeast from city of Zacatecas,
4 Mexico (22° 47' 46.7'' N latitude, 102° 25' 21.8'' W longitude, altitude 2077 m). The soil at
5 the experimental area is sandy clay loam (texture with 64.04 % sand, 21.96 % clay, and 14
6 % silt) with 3.2 % organic matter content, field capacity of 0.36 m³ m⁻³ % and permanent
7 wilting point of 0.18 m³ m⁻³. The climate is semiarid with minimum and maximum mean
8 monthly temperatures of 6.7 °C (December and January) and 27.3 °C (May), respectively.
9 Average annual precipitation is about 525 mm of which 80% occurs from June through
10 September.

11 Two treatments were established: a) treatment I: irrigation scheduling using the crop
12 coefficients estimated applying the FAO methodology adapted to the local conditions; b)
13 treatment II: irrigation scheduling using the crop coefficients estimated from the equation
14 developed by Martínez-Cob (2008). An experimental plot of 1 ha (50 m x 200 m) was
15 established within the abovementioned commercial plot. This plot was divided in two
16 subplots (50 m x 100 m), one for each treatment. Each subplot had three replications, 16.5
17 m x 100 m (about 22 rows within each replicate). At the end of the season, an area of 7.5 m
18 x 7.0 m, at the middle 10 rows of each replication, was sampled for yield determination.
19 The experimental plot was sown with corn (H-311 hybrid) on April 13 (2009) and April 3
20 (2010); harvesting dates were September 9 (2009) and August 30 (2010). Distance between
21 rows was 0.75 m and average seedling density was about 75,000 plants ha⁻¹. The hybrid H-
22 311 was obtained by the National Research Institute for Forestry, Agriculture and
23 Livestock of Mexico (INIFAP) as a cultivar suited for irrigated land in Mexico. It has been

1 proved for several years under different experimental and practical conditions showing
2 yield of grain that ranged between 6 to 10 Mg ha⁻¹ (Mojarro et al. 2012). Following INIFAP
3 recommendations, a fertilizer dose of 200-80-00 (N-P-K) was applied for both years.

4 An automated weather station (Vantage Pro2 Davis Instruments) located 280 m south of
5 the experimental field was used to measure daily rainfall, daily average wind speed at 2 m
6 above ground, daily average relative humidity, daily minimum and maximum air
7 temperature, and daily total solar radiation. These data were used to estimate ET_o by the
8 FAO Penman-Monteith method (Allen et al. 1998).

9 For each replication and treatment, the water productivity was obtained by dividing the
10 corresponding grain yield by the volume of irrigation water applied (IGD), and the
11 economic productivity was estimated as the product of grain yield and market price of
12 corn; according to the Ministry of Agriculture, Livestock, Rural Development, Fisheries
13 and Food of the Mexican government the annual average price of corn for 2009 and 2010
14 was 235 \$ Mg⁻¹, and 230 \$ Mg⁻¹, respectively. An analysis of variance (ANOVA) (single
15 factor) was conducted using the MSExcel 2007 program, and the significance of the
16 differences between treatments for grain yield, water productivity and economic
17 productivity were tested.

18 **Corn crop coefficients**

19 From 2005 to 2008, Mojarro et al. (2008) performed a study to estimate crop coefficients
20 following the FAO methodology adapted to the local conditions of the Calera aquifer of
21 the State of Zacatecas (Mexico). This aquifer is placed 45 km from commercial farm used in
22 this experiment. The K_c curves and length of stages recommended by these authors for
23 corn crop were used in this work to estimate the K_c values for treatment I (K_{cFAO}). The K_c

1 values for initial season, mid-season and late season were $K_{C_{ini}}=0.35$, $K_{C_{mid}}=1.22$, and
 2 $K_{C_{end}}=0.62$, with lengths of 45 days for initial stage, 30 days for development stage, 45 days
 3 for mid-season stage, and 30 days for late stage. The same curve was used for both
 4 seasons.

5 On the other hand, Martínez-Cob (2008) developed a corn crop coefficient curve as a
 6 function of fraction of thermal units (FTU) under the semiarid climatic conditions of
 7 Aragón (Spain). That equation was validated for the climatic conditions and cultivar used
 8 in that study but it should be validated for different conditions and cultivars. Climate
 9 conditions in Aragón (Spain) are different than those in Zacatecas (Mexico), with hotter
 10 and drier summer when most of the corn development occurs. Thus treatment II used Kc
 11 values estimated using the following equation developed by Martínez-Cob (2008):

$$K_{C_{FTU_i}} = -3.4245FTU_i^3 + 1.045FTU_i^2 + 2.4973FTU_i + 0.2389 \quad [1]$$

12 where $K_{C_{FTU_i}}$ is the crop coefficient value for day i and FTU_i is the fraction thermal unit
 13 for day i calculated as:

$$FTU_i = \frac{TU_i}{TTU} \quad [2]$$

15 where TTU is the total cumulative thermal units ($^{\circ}C$) and TU_i is the cumulative thermal
 16 units for day i ($^{\circ}C$); its values were computed as (Ritchie and NeSmith 1991):

$$TU_i = TU_{i-1} + (T_a - T_b)_i \quad \text{if } T_a > T_b$$

$$TU_i = TU_{i-1} \quad \text{if } T_a \leq T_b \quad [3]$$

19

1 where TU_{i-1} is the cumulative thermal units for day $i-1$ ($^{\circ}\text{C}$), T_a is the average
2 temperature for day i ($^{\circ}\text{C}$) and T_b is the basal temperature ($^{\circ}\text{C}$). Basal temperature was
3 assumed as 9°C (Ruiz-Corral et al. 2002) in this experiment.
4 Application of Eq. (1) requires a priori knowledge of the value of TTU adequate for the
5 cultivar and conditions under study. In this study, that value was not known at the onset
6 of the 2009 season. Thus TTU for 2009 corn season was considered as the average of TTU
7 computed for 2005-2008, between April 13 and September 9, the season length (150 days)
8 determined by Mojarro et al. (2008) as typical for corn in the area to apply the FAO
9 methodology. The average of these four values was 1661°C (coefficient of variation, 3%).
10 Temperature data for this period was taken from a weather station monitored by INIFAP
11 located around 15 km ($22^{\circ} 45' 26.1''$ N latitude, $102^{\circ} 30' 36.0''$ W longitude, altitude 2289
12 m) from the site of the experiment. Because an automatic weather station was available
13 next to the experimental plot during 2009, a TTU value was computed using the
14 temperature data registered at that station. Thus a value of 1768°C was obtained and used
15 for the 2010 season for treatment II. Considering that the abovementioned coefficient of
16 variation was 3 %, this TTU value of 1768°C was within the confidence interval ($P = 0.05$)
17 of the average TTU value of 1661°C .

18

19 **Net corn crop water requirements and irrigation scheduling**

20 During 2009, furrow irrigation was applied. A solid-set sprinkler irrigation system was
21 installed during that season and it became on operation for the 2010 season. Net corn crop
22 water requirements for both treatments were computed as follows:

$$CWR_s = ET_c - PEF_s \quad [4]$$

23

1 where CWR_s (mm) is the water required by corn crop to compensate the loss of water as
 2 evapotranspiration. ETC_s (mm) is the crop evapotranspiration (Eq. 5) and PEF_s (mm) is
 3 the effective precipitation (Eq. 6). Due to the different irrigation systems, Eq. (4) during
 4 2009 was applied for periods of varying length, ranging from 10 to 25 days, while during
 5 2010 was applied on a weekly basis. ETC_s and PEF_s were estimated as follows:

$$6 \quad ETC_s = \sum_{i=t}^{T_s} Kc_i ET_{o_i} \quad [5]$$

7
 8 where ET_{o_i} (mm) is the reference evapotranspiration for day i ; Kc_i is the crop coefficient
 9 for day i (either treatment I or treatment II); t and T_s are the first and last day of the
 10 considered period.

$$11 \quad PEF_s = 0.75 P_s \quad \text{if } P_s > 0.2 ET_{o_s}$$

$$12 \quad PEF_s = 0.00 \quad \text{if } P_s \leq 0.2 ET_{o_s} \quad [6]$$

13 where P_s (mm) and ET_{o_s} (mm) are the precipitation and reference evapotranspiration,
 14 respectively, for the considered period.

15
 16 Irrigation gross depth (mm) was calculated as follows

$$17 \quad IGD = \frac{CWR_s}{E_a} \quad [7]$$

18
 19 where E_a is the application efficiency.

20 For the 2009 season, an application efficiency of 70 % was assumed for the furrow
 21 irrigation system used. This assumption was based on previously experimentation years
 22 on the studied commercial field where soil physics and irrigation phases for a chili

1 (*Capsicum annuum* L.) crop were characterized as well as E_a was estimated using the
2 definition of Howell (2003) for application efficiency as the relation between irrigation
3 needed by the crop and water delivered to the field. Six inches gated pipe was used for the
4 application of irrigation water in furrows. The time consumed in each surface irrigation
5 event was calculated as:

$$T_r = \frac{V_a}{Q_g} \quad [8]$$

6
7 where V_a is the volume applied in each irrigation event (m^3), calculated as the product of
8 irrigation gross depth (m), furrow length (in this study, 100 m) and distance between
9 furrows (in this study, 0.75 m). Q_g is the water discharged by the gated pipe in each
10 furrow ($\text{m}^3 \text{h}^{-1}$); and T_r is the inflow time (h).

11 For the 2010 season, irrigation water was applied by a solid-set sprinkler irrigation system
12 with spacing between sprinklers of 12 m in rectangular arrangement; sprinklers model
13 WR-33 equipped with two nozzles (3.97 mm and 3.18 mm) manufactured by Waderain
14 Inc. (Portland, Oregon, USA) were used in the experiment. The system was operating at
15 200 kPa of hydraulic pressure. For this pressure and the rectangular framework used,
16 three preliminary experimental tests were performed to determine the coefficient of
17 uniformity (CU) (Christiansen, 1942) of the water application under different wind
18 conditions (0.6, 1.2, 2.1 and 3.9 m s^{-1}) following the criteria outlined by Merriam and Keller
19 (1978). Average CU values of 93 %, 91 %, 83 %, and 76 % were obtained for the wind
20 speeds tested (0.6, 1.2, 2.1 and 3.9 m s^{-1} , respectively). An application efficiency of 85% for
21 wind speeds lower than 2.0 m s^{-1} was claimed by the sprinkler nozzle producer. Recorded

1 average wind speeds during the irrigation events rarely exceeded that threshold value.

2 The duration of each solid-set sprinkler irrigation event was estimated as:

3

$$T_s = \frac{10 A IGD}{Q} \quad [9]$$

4

5 where T_s is the total operating hours of the sprinkler system (h), A is the irrigated area

6 (0.5 ha for each experimental plot), 10 is a constant for units transformation, IGD is the

7 irrigation gross depth between two irrigation events (mm), and Q is the discharge by the

8 sprinkler ($\text{m}^3 \text{h}^{-1}$). According to the Waderain Product Catalog, the discharge for WR-33

9 sprinkler is around $1.20 \text{ m}^3 \text{h}^{-1}$ for double nozzle operating at 200 kPa. Solid-set sprinkler

10 irrigation events were set for night time periods.

11

12

13

14

15

16

17

18

19

20

21

1 **Results and discussion**

2 The meteorological conditions for the 2009 and 2010 corn seasons (13 April to 9 September
3 in 2009, and 3 April to 30 August in 2010) are presented in Figure 1. Air temperature
4 averages were 19.6 °C for 2009 and 19.2 °C for 2010 respectively; minimum and maximum
5 air temperature values were 17.6 °C and 22.9 °C for 2009, and 17.2 °C and 22.9 °C for 2010.
6 Vapor pressure deficit (VPD) ranged between 0.38 to 1.98 kPa for 2009, and 0.33 to 1.80
7 kPa for 2010; averages values were 1.11 kPa and 1.05 kPa, respectively. Wind speed was
8 higher for 2010 than 2009; mean daily values were rarely above 2 m s⁻¹ although maximum
9 gusts of 4.9 m s⁻¹ (in 2009) and 6.1 m s⁻¹ (in 2010) were reached; seasonal average wind
10 speed was 0.8 m s⁻¹ for 2009, and 1.1 m s⁻¹ for 2010. In accordance with these differences in
11 the meteorological conditions, there also were some differences between the
12 corresponding estimates of ET_o (Figure 1). The ET_o ranged between 3.6 to 7.3 mm day⁻¹ for
13 2009, and 2.6 to 7.2 mm day⁻¹ for 2010; the average ET_o values were 4.8 mm day⁻¹ for 2009
14 and 4.7 mm day⁻¹ for 2010. The main difference in ET_o between both seasons was observed
15 during July and August when ET_o rates for 2010 were much lower. This difference was
16 mainly due to the lower VPD values observed for 2010 (Figure 1). The decrease in ET_o and
17 VPD observed for the summer period for both years was due to higher precipitation
18 amounts recorded during this period. Precipitation in summer is relatively high at the
19 study area, leading to slightly lower temperatures and a reduction of the dryness of the
20 air.

21 The crop coefficient curves used to estimate crop water requirements for both treatments
22 are plotted in Figure 2. The K_{CFTU} values estimated from Equation 1 led to different curves
23 for both corn seasons due to the different values of total cumulative thermal units (TTU).
24 The value of TTU used for 2009 was 6.1 % lower than that for 2010 resulting in smaller

1 values of crop coefficients at the end of the 2009 season. In addition, the 2010 season was
2 slightly cooler than the 2009 season, particularly in the second-half of the season (Fig. 1).
3 This situation led to a $K_{C_{TTU}}$ curve for 2010 slightly longer than that for 2009. Seasonal
4 average $K_{C_{FTU}}$ was about 7.1 % greater for 2010 (0.91 for 2009, and 0.98 for 2010), while
5 seasonal $K_{C_{FAO}}$ was 0.81 for both seasons. Figure 2 shows that the $K_{C_{FTU}}$ values were
6 greater for 2009 than those for 2010 when the Kc curve was rising (from beginning of crop
7 season to maximum Kc); the opposite occurred when the Kc curve was declining (from
8 maximum Kc to end of crop season). The equation (1) implies that a maximum value of
9 $K_{C_{FTU}} = 1.37$ will be reached when $FTU = 0.625$. In this work this occurred 84 and 88 days
10 after sowing for 2009 and 2010, respectively. Differences between $K_{C_{FTU}}$ (2009 and 2010)
11 and $K_{C_{FAO}}$ occurred mainly during the initial and development stages. This difference also
12 shows the importance of using local, real-time meteorological data for scheduling
13 irrigation. Thus the $K_{C_{FAO}}$ values used in this study were obtained at a location (Calera
14 Aquifer) with an average air temperature (18.2 °C for the period 2005 to 2008) lower than
15 that in the commercial plot where this study was performed (19.6 °C and 19.2 °C in 2009
16 and 2010). This lower temperature at the Calera Aquifer led to a longer initial and
17 development stages when using the $K_{C_{FAO}}$ curve as compared to the $K_{C_{FTU}}$ curve.

18

19 **Corn crop water requirements and irrigation scheduling**

20 Figure 3 shows 10-day values of estimated effective precipitation. The total effective
21 precipitation during 2009 (148 mm) was about 35% higher than that for 2010 (96 mm). A
22 great proportion of the effective precipitation occurred during the period June 21 to June
23 30 for both years: 34 % for 2009, and 26 % for 2010. Most of the remaining seasonal

1 effective precipitation occurred during the last third of the corn season: 45 % for 2009 and
2 68 % for 2010.

3 The values of the net crop water requirements (CWR_s , Eq. 4) estimated for each irrigation
4 event during each year of experimentation are presented on Figure 4. The number of
5 irrigation events was 8 for 2009 and 16 for 2010 because of the different irrigation system
6 used during those two seasons, furrow irrigation and solid-set sprinkler irrigation,
7 respectively. Subsequently, the average values of CWR_s per irrigation event were higher
8 for 2009, 53 mm (ranging from 25 to 79 mm) for treatment I ($K_{C_{FAO}}$), and 76 mm (ranging
9 from 40 to 131 mm) for treatment II ($K_{C_{FTU}}$). The corresponding average values of CWR_s
10 for 2010 were 28 mm (ranging from 12 to 59 mm) for treatment I, and 37 mm (ranging
11 from 13 to 69 mm) for treatment II.

12 Figure 4 shows that the values of CWR_s for both treatments were relatively similar for the
13 second half of the crop season, while CWR_s for treatment II was much higher during the
14 first half of the crop season. This was the consequence of the different crop coefficient
15 curves for both treatments (Fig. 3). The K_c curve for treatment I ($K_{C_{FAO}}$) was shifted with
16 respect to the curve for treatment II ($K_{C_{FTU}}$) and the peak values for treatment I were
17 delayed with respect to those for treatment II. The $K_{C_{FAO}}$ curve was applied using
18 information from previous works (Mojarro et al., 2008) and it may not completely
19 correspond to the current phenological development for the particular cultivar and
20 climatic conditions of this study. Martínez-Cob (2008) used the current phenological
21 development and climatic conditions of the particular cultivar used in his study, obtaining
22 a better similarity between the $K_{C_{FAO}}$ and the $K_{C_{FTU}}$ curves and a moderately higher
23 estimated CWR_s values for the FAO approach. In accordance with the abovementioned
24 results, the total irrigation gross depth (IGD, Eq. 7) applied was also higher for 2009 than

1 for 2010: 610 mm (treatment I) and 762 mm (treatment II) for 2009, and 527 mm (treatment
2 I) and 701 mm (treatment II) for 2010 (Table 1). Thus, IGD for 2009 was about 16 % higher
3 than that for 2010 for treatment I, and about 8 % higher for treatment II.

4 Table 2 shows the grain corn yield, the water productivity and the economic productivity
5 for the two treatments for both seasons. The grain yield was significantly ($P < 0.05$) higher
6 for treatment II than for treatment I for both years, about 37.5 % for 2009 and 28.8 % for
7 2010; agreeing with results obtained by previous researches (Ko and Piccinni 2009; Voires
8 et al. 2009; Payero et al. 2006) about yield increase with irrigation to the extent that crop
9 evapotranspiration is satisfied. For all cases, these grain yields exceeded the average yield
10 for the semi-arid climatic conditions of the state of Zacatecas (5.37 Mg ha^{-1}). The higher
11 yields obtained for treatment II indicate that actual crop evapotranspiration (consumptive
12 water use) was higher for that treatment as there is a strong positive relationship between
13 grain yield and evapotranspiration (Howell, 1990). In other words, treatment I led to an
14 underestimation of actual crop water requirements (and gross irrigation needs). Thus
15 these were not adequately met and the crop suffered water stress leading to lower grain
16 yields. Treatment II was able to meet more adequately those crop water requirements and
17 therefore grain yield was higher. This study used a $K_{C_{FAO}}$ curve described in the literature
18 (Mojarro et al., 2008) and therefore may not be adequately adjusted according to the
19 particular conditions (climatic and cultivar) of the experimental seasons. Martínez-Cob
20 (2008) used current phenological development and climatic conditions when estimating
21 the $K_{C_{FAO}}$ curve (after the end of the season) to be compared to the $K_{C_{FTU}}$ curve. For this
22 reason, the computed ET values with these two approaches by Martínez-Cob (2008)
23 showed a much lower difference (about 8 %) among them. This reflects the importance of
24 using crop coefficient curves that match more closely the particular conditions of each

1 season. For irrigation scheduling, the need for a previous knowledge of phenological
2 development implicit in the FAO approach as described by Allen et al. (1998) imposes an
3 important limitation for an accurate estimation of current crop water requirements. Use of
4 variables such as the FTU, which can be easily obtained as the season progresses, can
5 improve those estimations leading to higher grain yields.

6 On the other hand, during 2009, the average water productivity for treatment I was lower,
7 1.10 kg m⁻³ than that for treatment II, 1.21 kg m⁻³; nevertheless, in 2010, this indicator for
8 treatment I was slightly higher, 1.38 kg m⁻³ than that for treatment II, 1.34 kg m⁻³ (Table 2).
9 These differences were not significant (P>0.05). Kiziloglu et al. (2009) reported water
10 productivity for corn crop of 1.48 kg m⁻³ and 1.53 kg m⁻³ using irrigation doses of 352.8 mm
11 (the water needed to satisfy 100 % of actual crop evapotranspiration), and 282.2 mm
12 (irrigation water applied just to satisfy the 80 % of full irrigation) respectively. In addition,
13 the economic productivity was also significantly higher (P<0.05) for treatment II, 2162 \$
14 ha⁻¹ (during 2009 and 2010), than that for treatment I, 1575 \$ ha⁻¹ (during 2009) and 1679 \$
15 ha⁻¹ (during 2010). Table 2 also shows that the differences between years for treatment I, in
16 terms of water and economic productivity, were about 25 % and 7 % respectively while for
17 treatment II water productivity increased by about 11 % from 2009 to 2010; nevertheless
18 economic productivity remains equal. Comparing these same indicators but between
19 treatments results that water productivity was about 10 % higher for treatment II during
20 2009 and 3% lower during 2010 than that of treatment I while economic productivity in
21 both years was higher for treatment II than that of treatment I (37 % and 29 %
22 respectively). Therefore, the use of the FTU to estimate crop water requirements have led
23 to higher corn yields and lower year-to-year variability in terms of water and economic

1 productivity. Of course, two years of study is not too much and a longer and more
2 detailed analysis should be performed.

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

1 Conclusions

2 Two irrigation scheduling treatments were evaluated during two corn crop seasons, 2009
3 and 2010: treatment I, using Kc values computed using the FAO methodology; and
4 treatment II, using Kc values computed using an equation developed by Martínez-Cob
5 (2008) to estimate them from fraction of thermal units. Corn crop water requirements and
6 irrigation doses were estimated for the two treatments as well as water use productivity
7 and corn crop production. Total net crop water requirements estimated for each irrigation
8 event were 427 mm (2009), and 448 mm (2010) for treatment I; and 533 mm (2009), and 596
9 mm (2010) for treatment II. Nevertheless, the use of fraction of thermal units to estimate
10 corn crop coefficients provided better results against FAO methodology in terms of corn
11 production. Thus, grain yield was higher for treatment II than for treatment I for both
12 years, about 37.5 % for 2009 and 28.8 % for 2010. In addition, the economic productivity
13 was higher for treatment II, 2162 \$ ha⁻¹ (during 2009 and 2010), than that for treatment I,
14 1575 \$ ha⁻¹ (during 2009) and 1679 \$ ha⁻¹ (during 2010). On the other hand, water
15 productivity was 10 % lower for treatment I than for treatment II for 2009, but in 2010 was
16 3 % higher for treatment I than for treatment II.

17 These results confirm that the use of fraction of thermal units to estimate corn crop
18 coefficient has improved the yield, and the water management of this crop under the
19 conditions of this study. This improvement seemed to be somewhat higher when using
20 furrow irrigation system as compared to sprinkler irrigation. Because of the limitations of
21 the study (only two years and one experimental plot), further evaluations under other
22 conditions should be performed.

23

1 References

- 2 Allen, R. G., Pereira, L. S., Raes, D., and Smith, M. (1998). "Crop evapotranspiration:
3 guidelines for computing crop water requirements". FAO Irrigation and Drainage
4 Paper 56. FAO, Rome.
- 5 Amos, B., Stone, L. R., and Bark, L. D. (1989). "Fraction of thermal units as the base for
6 evapotranspiration crop coefficient curve for corn". *Agronomy Journal*, 81:713-717.
- 7 Bezerra, B. G., da Silva, B. B., Bezerra, J. R. C., and Sofiatti, V. (2012). "Evapotranspiration
8 and crop coefficient for sprinkler-irrigated cotton crop in Apodi Plateau semiarid
9 lands of Brazil". *Agricultural Water Management* 107:86-93.
- 10 Christiansen, J. E. (1942). "Irrigation by sprinkling". *Agric. Exp. Stn. Bull.* 670. Univ. of
11 California, Berkeley.
- 12 Dehghanisani, H., Nakhjavani, M. M., Tahiri, A. Z., and Anyoji, H. (2009). "Assessment of
13 wheat and maize water productivities and production function for cropping system
14 decisions in arid and semiarid regions". *Irrigation and Drainage* 58:105-115.
- 15 Dioudis, P., Filintas, A. T., Papadopoulos, A. H. (2009). "Corn yield response to irrigation
16 interval and the resultant savings in water and other overheads". *Irrigation and*
17 *Drainage* 58:96-104.
- 18 Grattan, S. R., Bowers, W., Dong, A., Snyder, R. L., Carroll, J. J., and George, W. (1998).
19 "New crop coefficients estimate water use of vegetables, row crops". *California*
20 *Agriculture*, 52(1):16-21.
- 21 Howell, T. A. (2003). "Irrigation Efficiency". *Encyclopedia of Water Science*, Marcel Dekker
22 Inc., New York, USA, 467-472.
- 23 Howell, T. A. (1990). "Relationships between crop production and transpiration,
24 evapotranspiration and irrigation". *Irrigation of agricultural crops*, Stewart B. A.,

1 Nielsen D. R., eds., Agronomy Series No 30. 391-434. ASA-CSSA-SSSA, Madison, WI,
2 USA.

3 Kang, S. Z., Gu, B. J., Du, T. S., and Zhang, J. H. (2003). "Crop coefficient and ratio of
4 transpiration to evapotranspiration of winter wheat and maize in a semi-humid
5 region". *Agricultural Water Management*, 59(3):239-254.

6 Kar, G., Kumar, A., and Martha, M. (2007). "Water use efficiency and crop coefficients of
7 dry season oilseed crops". *Agricultural Water Management* 87:73-82.

8 Kiziloglu, F. M., Sahin, U., Kuslu, Y., and Tunc, T. (2009). "Determining water-yield
9 relationship, water use efficiency, crop and pan coefficients for silage maize in a
10 semiarid region". *Irrigation Science*, 27:129-137

11 Ko, J., and Piccinn, G. (2009). "Corn yield responses under crop evapotranspiration-based
12 irrigation management". *Agricultural Water Management* 96:799-808.

13 López-Urrea, R., Montoro, A., López-Fuster, P., and Fereres, E. (2009). "Evapotranspiration
14 and responses to irrigation of broccoli". *Agricultural Water Management* 96:1155-
15 1161.

16 Martínez-Cob, A. (2008). "Use of thermal units to estimate corn crop coefficients under
17 semiarid climatic conditions". *Irrigation Science*, 26:335-345.

18 Merriam, J. L. and Keller, J. (1978). "Farm irrigation system evaluation: a guide for
19 management". Utah State University, Logan, Utah.

20 Mojarro, D. F., Bautista-Capetillo C., Ortiz, V. J. and Vázquez, F. E. (2012) "Comparing
21 water performance by two different surface irrigation methods". *Irrigation-Water*
22 *Management, Pollution and Alternative Strategies*, García-Garizabal, I. ed., Rijeka,
23 Croatia.

- 1 Mojarro, D. F., Gonzalez, T. J., Gutiérrez, N. J. A., Toledo, B. A., and Araiza, E. J. A. (2008).
2 "Software PIREZ (Proyecto Integral de Riego para el Estado de Zacatecas)"
3 Universidad Autónoma de Zacatecas, Mexico.
- 4 Nielsen, D. C., and Hinkle, S. E. (1996). "Field evaluation of basal crop coefficients for corn
5 based on growing degree days, growth stage, or time". Transactions of the ASAE,
6 39(1):97-103.
- 7 Ojeda-Bustamante, W., Sifuentes-Ibarra, E., Slack, D. S., and Carrillo, M. (2004).
8 "Generalization of irrigation scheduling parameters using the growing degree days
9 concept: application to a potato crop". Irrigation and Drainage, 53: 251-261.
- 10 Ojeda-Bustamante, W., Sifuentes-Ibarra, E., and Unland-Weiss, H. (2006). "Integral
11 programming for corn irrigation in Northern Sinaloa, Mexico". Agrociencia, 40:13-25.
- 12 Payero, J. O., Melvin, S. R., Irmak, S., and Tarkalson, D. (2006). "Yield response of corn to
13 deficit irrigation in a semiarid climate". Agricultural Water Management, 84(1-2):101-
14 112.
- 15 Ritchie, J. T., and NeSmith, D. S., (1991). "Temperature and crop development". Hanks, J.,
16 and Ritchie, J. T., eds. Modeling plant and soil systems. Series Agronomy No 31.
17 American Society of Agronomy, Crop Science Society of America, Soil Science Society
18 of America, Madison, pp 5-29.
- 19 Ruiz-Corral, J. A., Flores-López, H. E., Ramírez-Díaz, J. L., and González-Eguiarte, D. R.
20 (2002). "Cardinal temperatures and length of maturation cycle of maize hybrid H-311
21 under rainfed conditions". Agrociencia, 36:569-577.
- 22 Sammis, T. W., Mapel, C. L., Lugg, D. G., Lansford, R. R., and McGuckin, J. T. (1985).
23 "Evapotranspiration crop coefficients predicted using growing-degree-days".
24 Transactions of the ASAE, 28(3):773-780.

1 Sepaskhah, A. R., and Andam, M. (2001). "Crop coefficient of sesame in a semiarid region
2 of IR Iran". *Agricultural Water Management*, 49:51-63.

3 Steele, D. D., Sajid, A. H., and Prunty, L. D. (1996). "New corn evapotranspiration crop
4 curves for southeastern North Dakota". *Transactions of the ASAE*, 39(3):931-936.

5 Tyagi, N. K., Sharma, D. K., and Luthra, S. K. (2003). "Determination of evapotranspiration
6 for maize and berseem clover". *Irrigation Science*, 21:173-181.

7 Vories, E. D., Tacker, P. L., Lancaster, S. W., and Glover, R. E. (2009). "Subsurface drip
8 irrigation of corn in the United States Mid-South". *Agricultural Water Management*,
9 96:912-916.

10 Yan, W., and Hunt, L. A. (1999). "An equation for modelling the temperature response of
11 plants using only the cardinal temperatures". *Annals of Botany*, 84:607-614.

12

13

14

15

16

17

18

19

20

21

22

23

1 **List of Tables**

2 **Table 1.** *Crop water requirements (CWR), irrigation gross depth applied (IGD), and effective*
3 *precipitation (PEF) values for 2009 and 2010 corn seasons. Treatment I, scheduling irrigation*
4 *using a crop coefficient computed following Allen et al. (1998); treatment II, scheduling*
5 *irrigation using a crop coefficient computed following Martínez-Cob (2008).*

6
7 **Table 2.** *Performance indicators for 2009 and 2010 corn seasons. Treatment I, scheduling*
8 *irrigation using a crop coefficient computed following Allen et al. (1998); treatment II,*
9 *scheduling irrigation using a crop coefficient computed following Martínez-Cob (2008).*

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

1 **List of Figures**

2 **Figure 1.** *10-day averages of the daily mean meteorological conditions recorded at the nearby*
3 *station during the 2009 and 2010 corn seasons. Daily vapor pressure deficit (VPD) and*
4 *reference evapotranspiration computed following Allen et al. (1998).*

5

6 **Figure 2.** *Crop coefficient curves used to estimate crop water requirements for: treatment I, using a*
7 *crop coefficient (Kc) curve computed following Allen et al. (1998) (FAO); and treatment II,*
8 *using a Kc curve computed following Martínez-Cob (2008) (FTU).*

9

10 **Figure 3.** *Cumulative effective precipitation for 10-day periods occurred during the 2009 and 2010*
11 *corn seasons.*

12

13 **Figure 4.** *Net corn crop water requirements for: treatment I, crop coefficient computed following*
14 *Allen et al. (1998) (FAO); and treatment II, crop coefficient computed following Martínez-Cob*
15 *(2008) (FTU), during two seasons: 2009 and 2010.*

16

17

1 Table 1. *Crop water requirements (CWR), irrigation gross depth applied (IGD), and effective precipitation (PEF) values for 2009 and 2010 corn*
 2 *seasons. Treatment I, scheduling irrigation using a crop coefficient computed following Allen et al. (1998); treatment II, scheduling irrigation*
 3 *using a crop coefficient computed following Martínez-Cob (2008)*

4

5

Year	CWRs (mm)		IGD (mm)		PEFs (mm)
	I	II	I	II	
2009	427.1	533.3	610.1	761.8	148.1
2010	448.1	596.0	527.1	701.2	96.0

6

1 Table 2. Performance indicators for 2009 and 2010 corn seasons. Treatment I, scheduling irrigation using a crop coefficient computed following
 2 Allen et al. (1998); treatment II, scheduling irrigation using a crop coefficient computed following Martínez-Cob (2008)

3

Year	Grain yield [‡] (Mg ha ⁻¹)		Water productivity [‡] (Kg m ⁻³)		Economic productivity [‡] (\$ ha ⁻¹)	
	I	II	I	II	I	II
2009	6.70 ^a	9.20 ^b	1.10 ^a	1.21 ^a	1575 ^a	2162 ^b
2010	7.30 ^a	9.40 ^b	1.38 ^a	1.34 ^a	1679 ^a	2162 ^b

4

5 ‡ Different letters indicate that the treatments were significantly different and same letters indicate that the treatments were not
 6 significantly different (P<0.05).

7

Figure 1. 10-day averages of the daily mean meteorological conditions recorded at the nearby station during the 2009 and 2010 corn seasons. Daily vapor pressure deficit (VPD) and reference evapotranspiration computed following Allen et al. (1998).




Figure 2. Crop coefficient curves used to estimate crop water requirements for: treatment I, using a crop coefficient (K_c) curve computed following Allen et al. (1998) (FAO); and treatment II, using a K_c curve computed following Martínez-Cob (2008) (FTU)




Figure 3. Cumulative effective precipitation for 10-day periods occurred during the 2009 and 2010 corn seasons




Figure 4. Net corn crop water requirements for: treatment I, crop coefficient computed following Allen et al. (1998) (FAO); and treatment II, crop coefficient computed following Martínez-Cob (2008) (FTU), during two seasons: 2009 and 2010.

