

El-Ghazali Talbi

▶ To cite this version:

El-Ghazali Talbi. Machine learning into metaheuristics: A survey and taxonomy of data-driven metaheuristics. 2020. hal-02745295

HAL Id: hal-02745295 https://hal.inria.fr/hal-02745295

Preprint submitted on 3 Jun 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

EL-GHAZALI TALBI, University of Lille

During the last years, research in applying machine learning (ML) to design efficient, effective and robust metaheuristics became increasingly popular. Many of those data driven metaheuristics have generated high quality results and represent state-of-the-art optimization algorithms. Although various appproaches have been proposed, there is a lack of a comprehensive survey and taxonomy on this research topic. In this paper we will investigate different opportunities for using ML into metaheuristics. We define uniformly the various ways synergies which might be achieved. A detailed taxonomy is proposed according to the concerned search component: target optimization problem, low-level and high-level components of metaheuristics. Our goal is also to motivate researchers in optimization to include ideas from ML into metaheuristics. We identify some open research issues in this topic which needs further in-depth investigations.

CCS Concepts: • Computing methodologies → Search methodologies.

Additional Key Words and Phrases: Metaheuristics, Machine learning, Optimization, Data-driven metaheuristics

ACM Reference Format:

1 2

3

5 6

7

8

9

10

11

12

13

14 15

16

17

18

19

20

21 22

23

35

36

37

38

39

El-Ghazali TALBI. 2020. Machine learning into metaheuristics: A survey and taxonomy of data-driven metaheuristics. *ACM Comput. Surv.* 00, 00, Article 00 (2020), 30 pages. https://doi.org/00

1 INTRODUCTION

In the last decades, metaheuristics have shown their efficiency in solving various complex opti-24 mization problems in science and industry [195]. In general, metaheuristics do not use explicit 25 knowledge discovered during the search using advanced machine learning (ML) models. Meta-26 heuristics generate a lot of data in the search process. The data can be *static* when it concerns 27 the target problem and instance features to solve. Moreover several dynamic data are generated 28 during the iterative search process: solutions in the decision and the objective spaces, sequence of 29 solutions or trajectories, successive populations of solutions, moves, recombinations, local optima, 30 elite solutions, bad solutions, etc. Thus ML can be helpful in analyzing these data to extract useful 31 knowledge. This knowledge will guide and enhance the search performance of metaheuristics and 32 make them "smarter" and "well informed". Data-driven metaheuristics have been proven to be 33 advantageous in both convergence speed, solution quality and robustness. 34

In this paper, a survey of data-driven metaheuristics to solve difficult optimization problems is presented. A taxonomy is also proposed in an attempt to provide a common terminology and classification mechanisms. The goal of the general taxonomy given here is to provide a framework to allow comparison of data-driven metaheuristics in a qualitative way. In addition, it is hoped

40 Author's address: El-Ghazali TALBI, el-ghazali.talbi@univ-lille.fr, University of Lille, Polytech'Lille, Cité scientifique, 41 Villeneuve d'Ascq, 59655.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee
 provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and
 the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored.
 Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires
 prior specific permission and/or a fee. Request permissions from permissions@acm.org.

- ⁴⁶ © 2020 Association for Computing Machinery.
- 47 0360-0300/2020/00-ART00 \$15.00

48 https://doi.org/00

that the categories and their relationships to each other have been chosen carefully enough to indicate areas requiring research efforts as well as to help classify future work. We distinguish three hierarchical ways to use ML in metaheuristics (Fig.1):

- **Problem-level data-driven metaheuristics:** ML can help in modeling the optimization problem to solve (e.g. objective function, constraints). It can also assist landscape analysis and the decomposition of the problem.
- Low-level data-driven metaheuristics: a metaheuristic is composed of different search components. ML can drive any search component such as the initialization of solution(s), and the search variation operators (e.g. neighborhoods in local search, mutation and crossover in evolutionary algorithms). It may also be used to tune the various parameters of a metaheuristic.
 - **High-level data-driven metaheuristics:** this class of data-driven metaheuristics concerns the selection and generation of metaheuristics, and the design of hybrid and parallel cooperative metaheuristics.



Fig. 1. A general taxonomy of data-driven metaheuristics.

Other flat criteria are used in the taxonomy such as the learning time. In *offline* data-driven metaheuristics, the ML process occurs a priori before starting to solve the problem. In *online* data driven-metaheuristics, ML gather knowledge during the search while solving the problem.

The synergy between ML and optimization has received increasing attention. Most of the related works basically focus on the use of optimization algorithms in solving ML problems [24][192][126][42][51]. Indeed most of the ML problems can be formulated as optimization problems. In the last decade there was a considerable interest in the use of ML into optimization. Very few papers investigate the role of ML into exact optimization algorithms (e.g. branch and bound, dynamic programming), constraint programming, and mathematical programming [20]. To our knowledge there is no comprehensive survey which identifies in a unified way how ML can help the design of metaheuristics. In some outdated surveys [100][42][234], the authors enumerate some data-driven metaheuristics. In [33] the authors focus on dynamic combinatorial optimization problems. In [196], we have proposed a taxonomy of hybrid metaheuristics, in which the combination of metaheuristics with mathematical programming, constraint programming and ML has been addressed. In this

paper a more complete and general taxonomy of data-driven metaheuristics is proposed. More than
 125 references have been analyzed according to our taxonomy. The unified taxonomy is kept as
 small as possible by proceeding in a hierarchical way as long as possible; then a flat classification is
 presented according to other criteria.

The paper is structured as follows. In section 2, the main concepts of metaheuristics and ML are detailed in a general and unified way. Section 3 focuses on problem-level data-driven metaheuristics. In section 4, low-level data-driven metaheuristics are presented, while in section 5 we describe high-level data-driven metaheuristics. Finally, the last section presents the main conclusions and identifies some research perspectives.

2 MAIN CONCEPTS

103

104

105

106

107

108 109

110

113

123

111 This section presents in a unified way the main concepts used for metaheuristics and machine 112 learning.

114 2.1 Metaheuristics

115 An optimization problem consists in searching the optimal solution(s) x^* from a set of solutions 116 X which maximize (or minimize) an *objective function* f(x) while satisfying a set of *constraints*. 117 Metaheuristics represent a class of general-purpose heuristic algorithms that can be applied to any 118 optimization problem. Unlike exact methods, metaheuristics allow to tackle large scale problems by 119 delivering satisfactory solutions in a reasonable time. There is no guarantee to find global optimal 120 solutions or even bounded solutions. Metaheuristics have received more and more popularity in 121 the past 30 years. Indeed, their use in many applications shows their efficiency and effectiveness to 122 solve large and complex problems.

In the design of a metaheuristic, two contradictory criteria must be taken into account: *exploration* of the search space (*diversification*), and *exploitation* of the best solutions found (*intensification*). Promising regions are determined through the "good" solutions obtained. In intensification, the promising regions are explored more throughly with the hope to find better solutions. In diversification, non explored regions must be visited to be sure that all regions of the search space are evenly explored and that the search is not only confined to a reduced number of regions.

130 2.1.1 Single-solution based metaheuristics. Single-solution based metaheuristics (S-metaheuristics) 131 improve a single solution. They could be seen as "walks" through neighborhoods or search trajec-132 tories through the search space of the target problem [195]. S-metaheuristics iteratively apply the 133 generation and replacement procedures from the current solution. In the generation phase, a set of 134 candidate solutions are generated from the current solution s. This set C(s) is generally obtained 135 by local transformations of the solution. In the replacement phase¹, a selection is performed from 136 the candidate solution set C(s) to replace the current solution, i.e. a solution $s' \in C(s)$ is selected 137 to be the new solution. This process iterates until a defined stopping criteria. The generation and 138 the replacement phases may be *memoryless*. In this case, the two procedures are based only on the 139 current solution. Otherwise, some history of the search stored in a memory can be used in the gen-140 eration of the candidate list of solutions and the selection of the new solution. Popular examples of 141 such S-metaheuristics are local search, simulated annealing and tabu search. Algorithm1 illustrates 142 the high-level template of this family of metaheuristics. Their common search concepts are the 143 definition of the *neighborhood* structure and the generation of the *initial solution*. 144

145 146

147

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

¹Also named transition rule, pivoting rule and selection strategy.

	$s = s_0$; /* Generation of the initial solution */
i	t = 0;
]	Repeat
	$\tilde{/}^*$ Generate candidate solutions from s _t */
	Generate($C(s_t)$);
	/* Select a solution from $C(s_t)$ to replace the current solution $s_t */$
	$s_{t+1} = \operatorname{Select}(C(s_t));$
	t = t + 1;
1	Until Stopping criteria satisfied
(Output: Best solution found.

160

161 2.1.2 Population based metaheuristics. Population based metaheuristics (P-metaheuristics) could be 162 viewed as an iterative improvement of a population of solutions. P-metaheuristics start from an 163 initial population of solutions². Then, they iteratively apply the generation of a new population 164 and the replacement of the current population. In the generation phase, a new population of 165 solutions is created. In the replacement phase, a selection is carried out from the current and 166 the new populations. This process iterates until a given stopping criteria. Popular examples of 167 P-metaheuristics are evolutionary algorithms, ant colony optimization, scatter search, differential 168 evolution, particle swarm optimization, bee colony and artificial immune systems. Algorithm 2 169 illustrates the high-level template of P-metaheuristics. 170

lgorithm 2 : High-level template of P-metaheuristics	
$P = P_0$; /* Generation of the initial population */	
t = 0;	
Repeat	
Generate(P'_t); /* Generation a new population */	
P_{t+1} = Replace-Population($P_t \cup P'_t$); /* Select new population */	
t = t+1;	
Until Stopping criteria satisfied	
Output: Best solution(s) found.	

P-metaheuristics may be classified into two main categories:

• Evolutionary-based: in this category of P-metaheuristics, the solutions composing the population are selected and reproduced using variation operators (e.g. mutation, recombination³) acting *directly* on their representations. A new solution is constructed from the different attributes of solutions belonging to the current population. Evolutionary algorithms (EAs) and scatter search (SS) represent well-known examples of this class of P-metaheuristics.

• **Blackboard-based**⁴: It is based on the idea that the solutions of the population participate in the construction of a shared memory. This shared memory will be the main input in generating the new population of solutions. Ant colonies and estimation of distribution algorithms (EDA) belong to this class of P-metaheuristics. For the former, the shared memory

- ⁴A blackboard system is an artificial intelligence application based on the blackboard architectural model, where a shared
 knowledge, the "blackboard", is iteratively updated by a diverse group of agents [61].
- 196

181

182

183

184

185 186

187

188

189

190 191

²Some P-metaheuristics such as ant colony optimization start from partial or empty solutions.

⁹³ ³Also called crossover and merge.

is represented by the pheromone matrix while, in the latter strategy, it is represented by a
 probabilistic learning model. For instance, in ant colonies, the generated solutions by past ants
 will affect the generation of future ants via the pheromones. Then, the generated solutions
 participate in updating the pheromones.

2.2 Machine learning

201 202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

223

224

225

226

227

ML is one of the most salient research domain in artificial intelligence. ML has experienced an important development in the last decade and has become a powerful analysis tool in a wide range of applications related to big data. ML is the science of extracting useful and hidden patterns from a training dataset considered composed of multiple examples. Various ML tasks can be used depending on the desired outcome of the model. Usually a distinction is made between supervised, semi-supervised and unsupervised learning. The most common ML tasks used in this paper are (Fig. 2):

- **Regression and classification:** this is a supervised ML task in which we predict a predefined category or class from a given set of attributes (continuous variables for regression and discrete variables for classification) [8]. The following ML techniques are generally used for solving this family of problems: Gaussian process, linear regression, K-nearest neighbors, artificial neural networks (ANN), support vector machine (SVM), random forests, decision trees, logistic regression, naive Bayes and deep learning.
- Clustering: this unsupervised ML task partitions the input data set into subsets (clusters), so that data in each subset share common aspects [64]. The partitioning is often indicated by a similarity measure defined by a distance. The main used techniques for clustering are: hierarchical clustering, partitioning methods (e.g K-means, K-medoids, Mean-Shift), grid based clustering (e.g. CLIQUE, Sting, Wave Cluster), model based clustering (e.g. EM, COBWEB) and density based methods (e.g. DBSCAN, Optics, Denclue).
 - Association rules: association rule mining is a procedure which is meant to find frequent patterns, correlations, associations or causal structures from datasets found in various kinds of databases [67]. One of the most efficient used methods are Apriori, FP-growth and Eclat. Many measures of interestingness for rules have been proposed such as support, confidence, conviction, leverage, and lift (i.e. interest).
- **Feature selection:** the *feature selection* task consists in reducing the number of attributes (i.e. dimensionality of the dataset) [37]. It is an important task because selecting significant features would help to build simpler models of better accuracy and can reduce overfitting. The traditional techniques used for feature selection are: filter methods (e.g. Pearson's correlation, linear discriminant analysis (LDA), analysis of variance ANOVA, chi-square tests), wrapper methods (e.g. forward selection, backward selection, recursive feature elimination), and embedded methods (e.g. mRMR, Greedy).
- Reinforcement learning: reinforcement learning (RL) aims to learn optimal actions from a finite set of available actions through continuously interacting with an unknown environment [194]. The main components are: states, set of actions and rewards. From the current state, a RL agent takes an action, changes to a new state and receives a reward. The reward determines the quality of the carried action. RL is also referred to as *approximate dynamic programming* [155]. The goal of the agent is to maximize the accumulation of rewards over time. The main approaches for RL can be classified as follows:
- Model-free: the optimal control policy is learned without first learning an explicit model.
 Such schemes include: policy search (e.g. metaheuristics, policy gradient) and value-function
 based, related to dynamic programming principles (e.g. temporal fifference (TD) learning,
- 245

Q-learning [216], SARSA (State-Action-Reward-State-Action), DQN (Deep Q Network), DDPG (Deep Deterministic Policy Gradient, MCTS (Monte Carlo Tree Search)).

 Model-based: conversely model-based algorithm uses a reduced number of interactions with the real environment during the learning phase. Its aim is to construct a model based on these interactions, and then use this model to simulate further episodes, not in the real environment but by applying them to the constructed model and get the results from it.



Fig. 2. Main machine learning tasks and associated methods.

3 PROBLEM-LEVEL DATA-DRIVEN METAHEURISTICS

In this class of data-driven metaheuristics, ML techniques are carried out on the optimization problem at hand. Knowledge is obtained by the analysis of the landscape of the problem using selected features. Moreover, the problem model can be reformulated (e.g. objective function, constraints) or decomposed for a more efficient and effective solving.

290 3.1 Landscape analysis

Exploratory landscape analysis represent a number of techniques used to extract knowledge on the characteristics of a given optimization problem. The main questions for this scientific challenge are:

246

247

248

249

250

251

281 282 283

284

289

• Which features? high-level features specified by human experts such as the level of mul-295 timodality or separability have been introduced to reflect the problem characteristics [16]. 296 297 Other properties based on expert knowledge can be used such as: global basin structure, variable scaling, search space homogeneity, basin size homogeneity, global to local optima 298 contrast, and size of plateaus. Low-level features are automatically and numerically computed 299 to characterize the landscape of a given problem. The features can be grouped into five 300 classes related to: the characteristics of the distribution of the objective function values 301 302 (y-Distribution), the relative position of each objective value compared to the median of all values (Levelset), meta-modeling of the initial data set (Meta-Model), the estimated degree of 303 convexity of the function (Convexity) as well as the assessment of multimodality by local 304 searches starting from the initial design points (Local Search) [127]. 305

Which goal? those features are important for the design of efficient metaheuristics and understanding the behavior of the algorithms. This knowledge can be used for the selection of the best suited metaheuristic to solve a given problem by predicting the characteristics of the input instance [221][23]. It can also be used to tune the parameters of an algorithm [14], predict its runtime for solving a given benchmark instance [90], and generating hard benchmark instances [116].

• Which ML methods? many ML methods have been investigated to extract those features such as: Bayesian networks [151], support vector regression [23], random forest [90], Gaussian process [90], neural networks [189], regression trees [14], and ridge regression [221].

3.2 Data-driven objective function

Two different goals govern the use of ML in the objective function (Fig. 3):

- **Improving the convergence**: ML can help to transform the objective functions in order to better guide the metaheuristic through the search space. Those learnable objective functions include some knowledge extracted from the problem.
 - **Reducing the computational cost**: it consists in approximating the objective function. The approximation is evaluated much faster than the original function for expensive optimization problems.

3.2.1 Learnable objective function. The main issue in this family of methods is to generate automatically improved objective functions from exploiting some knowledge of the target optimization problem and features extracted from states visited during the search process. Those learnable objective functions can help guiding the search to improve solutions. For instance, this is an important issue for problems characterized by multimodality and neutrality. A representative of such an approach is Guided Local Search (GLS) which modifies the objective function when trapped on a local optima. The augmented objective function of the problem include a set of penalty terms [210]. Whenever the S-metaheuristic gets caught in a local optima, the penalties are modified and search is iterated to minimize the transformed objective function. The penalty gives the degree up to which the solution features is constrained.

Some approaches to construct learnable objective functions using reinforcement learning have been proposed. In [25], some features characterizing good solutions are defined for the given problem. The objective function is predicted by analyzing search trajectories of local search methods. A TD(λ) family of *temporal-difference reinforcement learning* algorithms is used. The learned evaluation function is then used to bias future search trajectories toward better solutions on the same problem. *Transfer learning* has also been used to transfer previously learned evaluation functions to new, similar optimization problems [66]. In [101], an *inverse reinforcement learning*

343

312

313

314 315

316 317

318

319

320

321

322

323

324 325

326

327

328

329

330

331

332

333

334

00:8



Fig. 3. Data-driven objective function.

(IRL) approach is proposed to learn the objective function in robotic problems. The main idea is to predict a suitable objective function given observations of optimal behavior. In many robotics problems, it is significantly easier to provide demonstrations of optimal behavior than it is to design an objective function that defines the required behavior. IRL is used to learn the observed behavior using features of solutions selected by L_1 regularization.

3.2.2 Objective approximation. Many optimization problems (e.g. engineering design) are concerned by extremely expensive objective functions. Those problems are generally characterized by black-box objective functions whose algebraic definitions are unknown (e.g. simulation based optimization). However, metaheuristics need to carry out a huge number of function evaluation in order to find good solutions. For such expensive optimization problems, the approximation of the objective function is an interesting alternative for designing efficient data-driven metaheuristics.

ML approaches can be used to build approximate models of the objective function [94]. In this context, previously evaluated solutions are learned by a ML approach to approximate the objective function of new generated solutions. The main issue here is to obtain a "good" approximation in terms of maximizing its quality and minimizing its computing time. Many questions arise in the design of this scheme such as: which proportion of the visited solutions are evaluated using the approximation, and at what time or in which component of the search algorithm the approximation is used. Objective approximation methods can be classified into two families (Fig.3):

• Similarity-based approximation: can be seen as Lazy learners or memory based learners. The most popular similarity-based approximation are objective inheritance, K-nearest neighbor, and clustering techniques. Objective inheritance methods⁵ are popular in P-metaheuristics.

⁵This scheme is also called fitness imitation or fitness inheritance.

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

In [188], the objective value of a new solution is computed as a linear weighted combina-393 tion of the parents, in which the weights depend on similarity with the parents. In [29], a 394 395 resampling technique is combined with an average combination to solve noisy problems. Other objective inheritance methods based on conditional probabilities tables and decision 396 trees are proposed in [149]. In the k-nearest neighbors method, the objective value of a 397 given solution is computed according to the k-nearest neighbors with known exact values 398 [233]. Similarity-based approximation can also be carried out by clustering algorithms. A 399 400 clustering algorithm is applied on a population of solutions to be evaluated. Each cluster will have a representative solution. Only the solution that represents the cluster is evaluated 401 [162][106][97][226]. Then, the objective function of other solutions of the cluster is estimated 402 with respect to its associated representative. Different clustering techniques may be used 403 such as K-means and fuzzy C-means. 404

405 • Functional-based approximation: it consists in a new model of the objective function being built. The model construction strategy is based on previous data obtained from the 406 original objective functions. Many ML algorithms have been investigated [94][13]: Polynomial 407 models (i.e. Response Surface) [74], Radial Basis Functions (RBF), Kriging (i.e. Gaussian 408 process) [28][107], Support Vector Machines (SVM) [186], Artificial Neural Networks (ANNs) 409 410 [86][193][70][83]. A recent approach consists to use an ensemble of surrogates in order to improve the performance of the approximation [73]. Multiple criteria have to be used 411 to compare the various models: number of samples provided to build the model, number 412 of parameters of the model, quality of the approximation, cost of the model building, and 413 cost of the model inference. In offline approximation, the model is built before the search 414 starts, whereas in online approximation (i.e. surrogate assisted), the model is constructed 415 416 and improved during the search.

Some hybrid approaches combining similarity-based and functional-based approximations have been proposed. An example of such a hybrid approache is a clustering approach applied in EAs in which we split the population into several clusters and then construct an approximate model for each cluster. Multiple approximate models are expected to use more local information about the search space and fit the original objective function better than a single global model [36][150][221].

3.2.3 Surrogate-assisted metaheuristics. Surrogate-assisted optimization⁶ is a popular approach to
 deal with the optimization of expensive problems [198]. These algorithms are iterative sampling
 procedures relying on surrogate models (i.e. metamodels) of the considered objective and constraint
 functions which are generally characterized by a negligible computational cost, in order to iteratively
 determine and explore the most promising locations of the design space, thus simultaneously
 refining the surrogate model and converging towards the problem optimum [95].

The main questions in designing surrogate-based metaheuristics are:

- **Surrogate building**: which ML approach is used to build the surrogate? Different approaches are used in the literature: Random Forest, Polynomial models, Gaussian Process [237], Neural Networks [211], radial basis functions [165], deep Gaussian processes [81], deep neural networks. A recent trend is to use multiple surrogates (i.e. ensembles of metamodels) to improve the accuracy of the surrogates [65].
- Surrogate incorporation: which solutions should be selected to be evaluated using the real objective function or the surrogate? *Evolution Control* uses jointly surrogates and original objective functions in a metaheuristic. The original objective functions are used to evaluate

440 441

439

417

418

419

420

421

422

429

430

431

432

433

434

⁶Also known as Bayesian Optimization

some/all solutions in some/all iterations, in a fixed or adaptive way [39]. In *direct approxi- mation*, the approximated objective function replaces the original one in the whole search
process [188][177]. In the *indirect approximation*, the metaheuristic use the approximation
in some search operators (e.g. neighborhood, population initialization, crossover, mutation)
[161][92].

• **Surrogate update**: When and how the surrogate is updated? the surrogate can be updated in a fixed (e.g. each iteration, given number of iterations) or an adaptive way (e.g. improvement of solutions). Different *infill criteria* have been used for updating the surrogate: lower confidence bound (LCB), upper confidence bound (UCB), probability of improvement, expected improvement (EI) [230]. They are based on a tradeoff between exploration, by searching where predicted variance is high and exploitation by searching where expected value is minimized.

One of the most popular Bayesian Optimization algorithms is the "Efficient Global Optimization" (EGO) algorithm [98]. It is based on Gaussian Process (GP) regression (also called Kriging). First, a set of solutions are generated using Design of Experiments (DoE). Then, it consists in sampling iteratively, using the prediction and uncertainty by the Gaussian model, the most promising solution based on an *infill sampling criterion*. This point is evaluated using the real objective function and the surrogate is updated using the new training set, and a new solution is sampled, and so on, until a given stopping criterion is satisfied (Fig.4).



Fig. 4. The EGO Bayesian optimization algorithm.

3.3 Constraint handling

For a given problem, there are usually domain specific constraints that can be exploited to construct efficient metaheuristics. The most popular constraint handling procedures in metaheuristics are the penalization and the repairing procedures. Different data-driven constraint handling approaches exist (Fig.5):

• **Constraint approximation**: the approximation strategies detailed in the previous section for the objective functions may also applied to constraints. Surrogates for constraints have been applied to problems with expensive black-box constraints [164][132]. Various ML models have been investigated such as: ANN [96], Kriging [206], RBF [166], and SVM [120]. Different infill sampling criteria are used to deal with constrained global optimization problems (e.g. expected improvement with Probability of Feasibility (PoF) [217], Expected Violation (EV), Mean Constraint (MC)) [156]. The infill criteria aims to balance between exploitation and exploration of the objective and all the constraint approximations [145].



Fig. 5. Data-driven constraints.

- Constraint transformation: in penalization strategies, adaptive strategies have been used for switching from lower complexity surrogates to higher complexity models (e.g. SVM [184]). For problems with many constraints, the search process will be very sensitive to accuracy of the surrogates which are built on the agregation of objective function and constraints. Hence, techniques that aggregate constraint's surrogates to one or a few have been proposed [235]. Dealing with constraints for many real-world problems requires incorporating domain knowledge into optimization algorithms. In the ART (Adaptive Reasoning Technique), a search memory is used to learn the behavior of a greedy algorithm [146]. Some constraints are added to the problem. Those constraints are generated from the non interesting visited solutions according to the values associated to their decision variables. Similar to the tabu list strategy in tabu search, those constraints are deleted after a given number of iterations. In [136], the authors use constraints to incorporate domain knowledge into Bayesian networks. They have formally proved that adding constraints reduces variance and improves generalization for machine learning problems.
- Constraint repairing: some ML approaches have been used to design repairing procedures • for constraint handling. In [236], Reinforcement Learning $TD(\Lambda)$ method and artificial neural networks are applied to design efficient repairing procedures for scheduling problems. In cultural algorithms, adaptive knowledge represented by belief cells (i.e. intervals) is used to avoid infeasible regions and for promoting the exploration of feasible regions [93]. Different constraint handling techniques can be effective during different steps of the search process. ML could also be applied to the online selection of the best constraint handling technique.
- **Problem decomposition** 3.4

505

506 507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

530

536

537

539

ML approaches can be used in breaking large scale optimization problems into smaller subproblems. 531 Those subproblems are then solved more efficiently by metaheuristics. Problem decomposition 532 approaches can be carried out in both hierarchical and flat ways. Hierarchical decomposition is used 533 when the problem can be successively refined. Flat decomposition generates separate subproblems 534 that can be solve in a parallel way. Three types of decomposition strategies may be carried out: 535

- Data space decomposition: partitioning of data input space can be applied to decompose the input space into subspaces. Metaheuristics are then used to solve simpler subproblems associated each partition. Then, a global solution is built using partial final solutions. For 538
 - ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

instance, in geographical problems such as vehicle routing [167][62][140] and covering [49],
clustering techniques exploiting the spatial properties can be applied to structure the set of
input nodes. Different clustering algorithms using geographical proximity have been used
such as K-means [72][68], density based clustering [62], and ANNs [154]. This approach
has been also applied to other families of problems such as scheduling [118][17], in which
clustering of jobs is carried out [3].

In stochastic and robust optimization, the clustering approach can also be applied for the set of input scenario [44][182]. In [119], a hierarchical clustering approach is proposed to select representative scenario clusters for a robust optimization in order to avoid redundant simulations and improve robustness in uncertain environments. In [44], clustering has been used to enhance a progressive hedging-based metaheuristic for a network design problem that models demand uncertainty with scenario. The metaheuristic solves successive multi-scenario subproblems associated to different clusters of scenario.

- Decision space decomposition: in this problem decomposition approach, the set of decision variables is divided into several subsets in order to remove the inter-relationship between subsets. The subproblems are assumed to be independent or loosely coupled. A popular decomposition technique is time-based decomposition in which the time horizon is used as a splitting criterion [110].
- ML can also be used to fix some variables to certain values and then solve the reduced associated subproblem. The fixed variables are selected using some knowledge (e.g. elite solutions, interdependance between variables). For instance, this approach is used in *coevolutionary algorithms* for global optimization problems [123][85], and *Benders decomposition* for mixed optimization problems (MIP) [207].
 - **Objective space decomposition:** in multi-objective optimization problems, reducing the number of objective is an important issue for the search efficiency. Indeed, the difficulties in solving many-objective optimization problems are the inefficiency of dominance relations, important computational cost and complexity in visualization of the objective space. Reducing the number of objectives using ML approaches represents a popular approach to handle this difficulty: *offline reduction* using *Principle Component Analysis (PCA)* [178] or *online reduction* based on the clustering of the Pareto front [27][142]. In [27], an unsupervised clustering algorithm is applied in the objective space at different iterations of the metaheuristic. For each cluster, only representative objectives are selected to guide the search during next iterations.

4 ML IN LOW-LEVEL COMPONENTS OF METAHEURISTICS

Although the effectiveness of metaheuristics has been demonstrated in solving difficult and largesize optimization problems in various areas, the design of the appropriate setting usually requires a deep expert knowledge in order to obtain competitive results. Here, ML can be used to find good designs for various search components or parameters of metaheuristics such as the initial solutions(s), neighborhoods, variation operators, stopping criteria and various parameters associated.

4.1 Initial solution(s)

The most commonly used method in the generation of initial solution(s) is randomness. In general, a population of random solutions is characterized by a bad quality and do not even ensure a good diversification in the search space. ML-assisted initialization techniques can improve the solution quality, reduce the computational costs, and improve the robustness in terms of the variation of the solutions found [102]. Hence, ML has been applied in the initialization of solution(s) following different methodologies (Fig.6):

588

563

564

565

566

567 568

569

570

571 572 573

574

575

576

577

578

579 580



Fig. 6. Data-driven initial solution(s) initialization.

- Incorporating a priori knowledge for intensification: knowledge extracted from previous problems solving can be used to generate solutions which integrate "good" patterns. ML can learn good properties of the obtained solutions and then help to generate good quality initial solutions in promising regions of the search space. The general learning methodology is shown in Figure 7. First, by selecting a set of training instances of the problem and obtaining a set of elite solutions for this set. Then, some features of the elite set of solutions are found using ML models. Finally, the obtained ML model is used to generate initial solutions for a new problem instance. Defining features and similarity metrics for a given problem are the main issues of this methodology. Such approaches have been proposed using case-based reasoning in EAs [121], association rules and attribute-oriented induction in P-metaheuristics [134], multi-label classification using decision trees [117], logistic regression [80][180] and neural networks [157] in S-metaheuristics. Recently, some deep architectures for neural networks have been explored. In [129], Convolution Neural Networks (CNNs) models learn the optimal solution for the traveling salesman problem as an image and extract the patterns (i.e. edges) to be included in a solution. This methodology can also be applied in solving similar problems by applying *transfer learning* approaches. There is an opportunity to exploit the structure of similar problems that have been already solved for which we have a lot of knowledge.
- Fixing positions for diversification: diversification is an important issue in metaheuristics. ML has been applied to improve diversification in P-metaheuristics by using for instance *orthogonal experimental design* [114], and in iterative S-metaheuristics by using for instance multi-armed bandits (epsilon-greedy Q-learning) [35]. Indeed, the problem of selecting a region to explore can be defined as a multi-armed bandit: a reinforcement learning problem that exemplifies the exploration-exploitation tradeoff dilemma, in which each arm is represented by a region of the search space [208].
- Generating initial solutions: ML can also help to generate "good" quality initial solution(s). An example of such approaches are:
- Opposition-based learning: using a one-to-one mapping function in the decision space, opposition-based learning (OBL) allows to obtain complementary solutions in order to improve the convergence of the search process and the coverage of the search space.



Fig. 7. Extracting knowledge from the history of the search and its use into initial solutions for intensification.(1) Selecting the training problem instances and obtaining the elite solutions (optimal or near-optimal solutions).(2) ML is applied using the elite set of solutions and the selected features of instances.(3) The extracted ML model will be used to generate the initial solutions(s) for solving a new problem instance.

Opposite solutions are generated during the initialization of a population using different types of mapping functions: Type-I opposition, Type-I Quasi-opposition, Type-I Super Opposition, Type-II opposition, Center-based sampling, Generalized OBL, and Quasireflection OBL [172]. This methodology has been carried out in Differential Evolution (DE) [5][202][159][214][18], Evolutionary Algorithms [224][53], Harmony Search [183][185], and Particle Swarm Optimization (PSO) [213][212][187][69]. It has also been applied for solving multi-objective optimization problems [113][122] and noisy problems [79].

- Artificial neural networks (ANN): different architectures of ANNs have been investigated to generate good quality solution for optimization problems: Hopfield neural networks (HNN) [223][197][218], Recurrent Neural Networks (RNN) [19][135], Pointer networks [209], Self Organizing Map (SOM) [131][40].
- Interpolation techniques: from a given population of solutions, new solutions can be generated using interpolation techniques such as quadratic interpolation [143][7]. Using a quadratic interpolation of three solutions, a new solution lying at the minimum of the quadratic curve crossing through the three solutions is obtained. It helps to improve the convergence rate of the algorithms.
- Reinforcement learning (RL): RL can be seen as a greedy optimization approach in which a complete solution is constructed by successive addition of decisions [104][103]. Recently, some deep architectures have been investigated such as Deep RL [125], and Deep Q Network [215].
- Transfer learning: transfer learning has been expoited for the population initialization in solving dynamic multi-objective optimization problems [91]. It allows to generate an initial population by reusing past experience to speed up the search process.

4.2 Search operators design

This section deals with the application of ML into the design of search operators: constructive (i.e. greedy) operators, unary operators (e.g. neighborhood in local search, mutation in EAs), binary

686

653

654

655

656 657 658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681 682

operators (e.g. crossover in EAs), indirect operators (e.g. probabilistic models in estimation of
 distribution algorithms), intensification, and diversification search operators:

- **Constructive operators:** some metaheuristics such as Ant Colony Optimization and GRASP use greedy operators to generate new solutions. Association rules and clustering (e.g.self-organizing maps) have been used to extract patterns that are incorporated into greedy procedures [170][45]. Reinforcement learning have been integrated into constructive operators, such as Q-learning in ant colony based optimization [54]. This approach is very popular in solving control problems such as mobile robots [75]. Indeed reinforcement learning is a natural framework for sequential learning in greedy procedures. This RL framework has also been applied to many combinatorial optimization problems such as the maximum cut, minimum vertex cover, and traveling salesman [104].
- Unary operators: one of the key issues in designing efficient unary operators is ensuring that they search in the appropriate neighborhood. Two different issues have been addressed using online learning:
- Size of the neighborhood: the size of the neighborhood can be learned online during search; for instance the step size in Evolution strategies (ES) [179].
- Sampling of the neighborhood: ML models can be extracted from a set of good generated 704 solutions to guide the generation of the candidate neighbors. Other than applying a random 705 or complete generation of the neighborhood, a reduced set of candidate neighbors are 706 generated. This methodology has been applied to many metaheuristics such as EAs [176], 707 and VNS [199]. In [176], probabilistic models are learned from the population in EAs. 708 New solutions are generated by sampling the probabilistic model. In [201] a linkage tree 709 genetic algorithm based on hierarchical clustering is proposed. It allows to identify the 710 problem variables that have a high mutual information in a population of good solutions. 711 In the generation of new solutions, these linked variables determine the neighborhood 712 where the metaheuristic searches for better solutions by sampling values for these problem 713 variables from the current population. This neighborhood learning is guided by the linkage 714 hierarchical clustering found so far during the search. 715
 - **Binary operators:** the knowledge extracted during the search can be incorporated into binary operators such as recombination operators in EAs for the generation of new solutions (Fig. 8). From a set of solutions (e.g. current population, elite solutions), some learning models are extracted, that will participate in:
 - Recombination of solutions: association rules [175], decision trees [99] are some examples of ML approaches that have been applied in the croosover operator in EAs. In [175], an elite set of solutions is maintained by an EA. The frequent itemsets are discovered using the Apriori algorithm of association rules. Then those frequent itemsets will guide the crossover operator by a greedy procedure. In [128], a set of decision rules describing the generated solutions are found, using the *AQ learning algorithm*. The extracted rules are incorporated into the crossover operator.
- Selection of solutions: in general, the selection of solutions to be recombined is based only on their qualities (e.g. roulette or tournament selection). The candidates for crossover can be chosen using some distance measures. Hence, hierarchical clustering has been proposed to select solutions in neighboring clusters [6][144]. Indeed, recombining only neighboring solutions may improve the efficiency of crossover operators.
- Indirect operators: in blackboard-based metaheuristics (e.g. EDA), ML models are used to generate new solutions: probabilistic models [148], Bayesian networks [152], incremental learning [11], dependency trees [12], and Markov random fields [181]. Similarly, *cultural*
 - ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

735

689

690

691

692

693

694

695

696

697

698

716

717

718

719

720

721

722

723

724

725

algorithms use good quality solutions to induce beliefs guiding the generation of solutions by
 evolutionary operators [168]. Cultural evolution allows populations to learn and adapt faster
 than biological evolution.



Fig. 8. Extracting knowledge from the search history and its use into search operators.

Other important search operators can be handled by ML:

- **Intensification**⁷: this approach uses a learning process to guide the underlying metaheuristic toward good regions of the search space. It allows to make deeper search aroud promising regions of the search space. The features of good solutions are extracted using online learning such as clustering [153] and frequent itemsets using association rules [48][169]. Then a deeper search is carried out around solutions characterized by those patterns.
- **Diversification**⁸: this approach uses a learning process to guide the underlying metaheuristic toward unvisited regions of the search space. A learning component keeps track of all visited solutions by storing some informations: spheres in the decision space [153], intervals for decision variables [191], Self-Organizing Maps (SOM) [9], binary space-partitioning (BSP) trees [228]. In order to guide the underlying metaheuristic toward unexplored regions, the learning component generate solutions far away from the visited solutions.

4.2.1 Operator selection. In many metaheuristics there exists a lot of alternatives in terms of search operators design: neighborhoods and more generally unary operators such as mutation in EAs, and binary operators such as crossover in EAs. ML can be used for the selection of the best suited search operator. Sequential learning approaches (e.g. reinforcement learning, multi-armed bandit) are well suited for the selection of search operators [56].

Reinforcement learning has been applied to learn the optimal search operator based on the
 performance of operators. The operator selection problem is formulated as reinforcement learning
 problem. It is applied to learn optimal policies by maximizing the accumulated rewards. According

^{782 &}lt;sup>7</sup>i.e. exploitation

⁷⁸³⁸i.e. exploration

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

to the calculated *Q* function value of each candidate operator, an optimal operator can be selected to
maximize the learned *Q* reward value. This approach has been used for various unary operators such
as mutation [231], and neighborhood selection in VNS (Variable Neighborhood Search) [1][55][109].
VNS integrate a set of different neighborhoods, which are explored in a predefined sequence. ML
approaches allows to select the most appropriate neighborhood at a given iteration.

Other sequential learning approaches have been proposed such as *multi-armed bandit* for operator selection in EA [47], and neighborhood selection in VNS [38], and *adaptive pursuit algorithm* [57]. *Ensemble methods* represent alternatives to sequential learning that have been investigated for this task [124].

4.3 Parameter tuning

790

791

792

793

794 795

796

797

798

799

800

801

802

803

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

Many quantitative parameters compose metaheuristics. Quantitative parameters represent numerical values to be initialized such as the probability of application of variation operators (e.g. mutation, crossover) in EAs, the tabu list size in tabu search, and the velocity is particle swarm optimization. The various parameters of metaheuristics have a significant impact on their efficiency [50]. In general, metaheuristics designers tune the parameters by hand, guided by their experience and some rules of thumb. Finding good parameter setting is a tedious and time-consuming task [60].

There are a lot of similarities between the parameter tuning problem and problems faced in ML [21] and Design of Experiments (DoE) [63]. Offline or static parameter tuning addresses the finding of good parameters before the execution of a metaheuristic [89]. Online or dynamic parameter tuning addresses the dynamic change of parameters during the search. A hybridization of both approaches is generally required for finding satisfactory solutions.

4.3.1 Offline parameter tuning. There is no general optimal parameter setting for metaheuristics. For any metaheuristic, an optimal parameter setting can vary considerably depending on the problem, and even between instances of the same problem. Three main ML methodologies can be applied:

• Unsupervised learning: unsupervised learning has been explored to improve the efficiency of factorial experimental design for parameter tuning. The main idea is to reduce the parameter space in order to reduce the computational complexity: Design of Experiments (DoE) [43], Taguchi fractional experimental design [2], fractional factorial design [76], correlation graph decomposition [111]. This methodology can be described in an unified way by the following three steps:

- Parameter selection: the main goal of this step is to select the significant parameters which influence the performance of the metaheuristic. Given the input set of parameters, the selection step tries to rank these parameters to determine the importance of parameters. This step allows to reduce the parameters space to be explored by eliminating some non significant parameters.
- Parameter space exploration: it consists in decomposing the parameter space in differ ent clusters. A model-based approximation (e.g. linear regression [43], response surface
 [88][76], logistic regression [160], decision tree [15]) is built to find relationship between
 the parameters and the objective function value. This step allows to find promising clusters
 in the parameters space.
- Parameter space exploitation: in each cluster, an optimization process is applied to find
 the best parameters. Any metaheuristic can be used for this step (e.g. local search [43],
 evolutionary algorithms [111]).
- 833

- Supervised learning: optimal parameters setting may differ function of the problem instances of the problem at hand. Supervised learning can be applied in order to predict the best parameters value for a given instance of the problem. Each instance is characterized by some features [163]. Two different steps can be considered (Fig.9):
 - Training and learning: for different set of initial parameter values, a metaheuristic is applied to generate solutions for a finite training set of problem instances. Then, the obtained performance data are carried out by ML to build a model.
- Prediction: supervised ML is trained with the data from the first stage in order to give
 recommendations for parameters for any new problem instance. ML is therefore used for
 the recognition of good initial parameter settings for new problem instances. Parameters
 values for new problem instances can be retrieved in real time using supervised learning,
 once the training phase is carried out. Different models have been used such as artificial
 neural networks (ANN) [52], Bayesian networks [147], linear regression [34], and SVM
 [112].
 - **Surrogate-based optimization:** parameters tuning can be formulated as an expensive optimization problem, in which the decision variables are the parameters, and the objective function is the solution quality obtained by the optimization algorithm. Hence, surrogate-based optimization techniques has been applied to reduce the complexity of the meta-optimization process [219].



Fig. 9. ML and parameter tuning: training, learning and prediction.

4.3.2 Online parameter tuning. In online tuning, the parameters are adapted during the search.
For instance, the initialization of the probability of application of a given search operator may
be adjusted adaptively by computing the progress of the last applications of the search operator
[203][82]. Hence, it becomes possible to determine the probabilities of application of a given
operator in an adaptive manner where the more efficient an operator is, the likelier is its application.
Knowledge extracted during the search may serve to dynamically change at run time the values of
parameters, using various learning methodologies:

Sequential learning approach: the most popular online approach is sequential learning: adaptive pursuit [200], multi-armed bandit [47], and reinforcement learning [59][4]. Multi-armed bandit strategies treat each parameter as a separate arm and fix their probabilities by

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

learning the expected rewards [47]. Reinforcement learning uses feedback from the search todefine states and actions which represent parameters values [59].

- Classification/regression approach: classifiers (e.g. SVM [229]) or regression models [112]
 can be used to predict effective parameters settings on the basis of the current status of the search and problem/instance informations.
 - **Clustering approach:** clustering approaches have also been applied. In [232], the distribution of the population in the search space is clustered at each iteration. Using the K-means algorithm, the parameters are adapted according to the knowledge extracted from clusters. Some rules based on the relative size of the cluster containing the best solution and the one containing the worst solution are used to adapt the probabilities of the application of variation operators in EAs.

5 ML IN HIGH-LEVEL COMPONENTS OF METAHEURISTICS

Metaheuristics can be seen as high-level algorithms composed of low-level search operators (e.g. greedy versus iterative). On one hand, many metaheuristic families exist in the literature (e.g. EAs, swarm intelligence, local search) and then various heuristics can be designed. On the other hand, for a given optimization problem, a heuristic can be automatically generated by fixing a configuration from the design space of low-level search operators. According to the nature of the design space of metaheuristics, one can consider the metaheuristic selection problem for selecting existing algorithms, and the metaheuristic generation problem for generating automatically algorithms from the search components of existing ones (Fig.10).



Fig. 10. ML in high-level components of metaheuristics.

5.1 Selection of metaheuristics

The design space of metaheuristics is very large. Moreover the steady development of new metaheuristics makes the selection of the best metaheuristic for a given problem or instance an important challenge [108]. The algorithm selection involves selecting an algorithm from a given portfolio of algorithms in order to take into account the varying performance of algorithms over a set of instances and problems [171]. It is well-known that a global best metaheuristic for all optimization problems does not exist. We have to accept that no single metaheuristic will produce the best performance on all problems and instances [220]. One is especially interested in giving metaheuristic recommendations for certain families of optimization problems which differ in the kind of exhibited problem features.

The research literature on the algorithm selection problem show the efficiency of using ML for the problem [22][26]. For the metaheuristic selection problem, one can distinguish between

offline and online learning. The advantage of online learning is an adaptive selection of algorithm,
 whereas the cost for this additional effectiveness is an important overhead:

- Offline learning: the idea is to gather knowledge from a set of training instances by using instance features, that will hopefully generalize to solve new instances. One can consider three approaches for the metaheuristic selection problem:
- Oclassification: a multi-class classifier predict the best performing metaheuristic over the *k* possible ones. A predictive model is trained on empirical performance data and metaheiristics. Many supervised ML techniques can be used such as ANN [204][77][205], Bayesian networks [78], nearest neighbors [71], support vector machines [84], decision trees [41], logistic regression [158], ensembles [190], and deep neural networks [46].
- Regression: the performance of each metaheuristic is predicted via a regression model and then selects the one with the best predicted performance. Several ML regression approaches have been proposed: linear regression [115], support vector regression [23], and Lasso regression [87].
 - Clustering: it consists in clustering the problem instances in feature space, then selects the best metaheuristic for each cluster and finally affects to each new instance the metaheuristic associated with the instance's predicted cluster.
 - Online learning: the learning takes place during the search. For instance, this idea has been widely explored in the *hyper-heuristic* framework [30]. The most used ML strategies are mainly based on sequential learning. In a reinforcement learning formulation of the problem, the metaheuristics represent actions, states correspond to solutions, and the value function (i.e. reward) represents the performance of the metaheuristic, while the environment is represented by the instance problem [173] (Fig.11). Most of the considered RL approaches usually use only a single instance [133][31][141][222]. For a problem domain (i.e. set of instances), the reward can be represented by the average performance over the set of instances. The main issue of different RL algorithms (e.g. temporal difference learning [173]) is to estimate the value functions.

Some hybrid approaches combining offline and online learning have been proposed [130]. By combining metaheuristic portfolios and online selection, the goal is to develop a problem-independent methodology with diverse problem solving capability.



Fig. 11. Online selection of a metaheuristic using a reinforcement learning approach.

5.2 Generation of metaheuristics

There are so many various characteristics of problem instances encountered in practice. An automated design of a metaheuristic can be performing well and cost effective for a given problem or instance. The generated metaheuristic can produce better solutions than those obtained by human created metaheuristics. Moreover, the automated process is less demanding on human time, and is

980

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962 963 964

965

966

967

968

969

970 971

972 973 974

therefore appealing. One can find offline and online learning strategies for the automatic generation 981 of heuristics: 982

- 983 • Offline learning: Genetic programming (GP) is the most widely used approach for that pur-984 pose [174][32][105]. The automated design of effective heuristics is carried out via evolution, 985 in which the heuristic is represented by a GP-tree. Other used methodologies for automati-986 cally generating a new heuristic for a given problem/instance are based on apprenticeship 987 learning [10], Learning Classifier Systems (LCS) [138], ANN [139] and logistic regression 988 [137].
- 989 • Online learning: the most used online ML approach is the reinforcement learning (RL) to 990 generate greedy [58] and iterative metaheuristics [225]. In [225], deep RL using graph neural 991 networks (GNN) has been used to generate local search heuristics to solve SAT problems. 992 Local search has been formalized as Markov decision process (MDP). Generating a good 993 heuristic consists to find an optimal policy π which maximizes the expected accumulated 994 reward obtained by a local search algorithm. This methodology is also popular in swarm of 995 robots, for which at each iteration the best metaheuristic is generated to perform a given 996 number of predefined actions [227]. 997

998 CONCLUSIONS AND PERSPECTIVES

999

1016

1017

1018

1019

1020

1021

1022

The fields of ML and metaheuristics are increasingly intertwined. In this paper we have investigated 1000 the different opportunities for applying ML into metaheuristics. We have defined in a unified way 1001 the various synergies that may be achieved. A detailed taxonomy has been proposed according to 1002 the concerned search component: target optimization problem, low-level and high-level search 1003 components of metaheuristics. Many of those data-driven metaheuristics have generated high 1004 quality results and represent state-of-the-art optimization algorithms. One has to keep the overhead 1005 of learning low. Indeed, the integration of ML techniques in metaheuristics incurs additional costs 1006 which have to be considered in the performance evaluation measures. 1007

Research in designing metaheuristics using ML techniques is witnessed to have an important 1008 impact in the future. We expect the interplay of metaheuristics and ML will increase. Indeed, 1009 data-driven metaheuristics opens up a wealth of perspectives. From the optimization point of 1010 view, investigating the integration of ML into exact optimization techniques (e.g. mathematical 1011 programming, branch and bound, dynamic programming, constraint programming) is an important 1012 research challenge. Solving more complex optimization problems such as multi-objective optimiza-1013 tion, dynamic optimization, optimization under uncertainty, and bi-level optimization, opens also 1014 many other research issues. 1015

From the machine learning perspective, the use of more sophisticated and modern ML techniques such as deep learning models will represent an interesting alternative to solve more complex problems. Transfer learning can help to reuse the past experience for speeding up the metaheuristic search process for dynamic and cross-domain optimization problems. Indeed, integrating transfer leaning in metaheuristics can improve performance and robustness in solving similar and evolving problems and instances.

It could also be interesting to explore the design and implementation of parallel models for data-1023 driven metaheuristics. High-performance computing is evolving toward Exascale supercomputers 1024 composed of millions of cores provided in heterogeneous devices mainly multi-core processors with 1025 various architectures, GPU (Graphics Processing Units) accelerators and TPUs (Tensor Processing 1026 Units) and other AI-dedicated ASICS (Application-Specific integrated Circuits). Finally, the coupling 1027 of software frameworks dealing with the two classes of algorithms (i.e. metaheuristics and ML 1028 1029

algorithms) is an important issue for the future. This enables to reduce the complexity of developingdata-driven metaheuristics approaches and makes them increasingly popular.

1034 REFERENCES

- [1] [n.d.]. A variable neighborhood search algorithm with reinforcement learning for a real-life periodic vehicle routing
 problem with time windows and open route. ([n. d.]).
- [2] Belarmino Adenso-Diaz and Manuel Laguna. 2006. Fine-tuning of algorithms using fractional experimental designs and local search. *Operations research* 54, 1 (2006), 99–114.
- [3] M. Adibi and J. Shahrabi. 2014. A clustering-based modified variable neighborhood search algorithm for a dynamic
 job shop scheduling problem. *The International Journal of Advanced Manufacturing Technology* 70 (02 2014).
- 1040[4] Arina Afanasyeva and Maxim Buzdalov. 2011. Choosing best fitness function with reinforcement learning. In 2011104110th International Conference on Machine Learning and Applications and Workshops, Vol. 2. 354–357.
- [5] Morteza Alinia Ahandani. 2016. Opposition-based learning in the shuffled bidirectional differential evolution algorithm. Swarm and Evolutionary Computation 26 (2016), 64–85.
- [6] Oswin Aichholzer, Franz Aurenhammer, B Brandstatter, Thomas Ebner, Hannes Krasser, Ch Magele, M Muhlmann,
 and W Renhart. 2002. Evolution strategy and hierarchical clustering. *IEEE transactions on magnetics* 38, 2 (2002),
 1045 1041–1044.
- 1046 [7] M. Ali, M. Pant, and A. Abraham. 2013. Unconventional initialization methods for differential evolution. *Appl. Math.* Comput. 219, 9 (2013), 4474–4494.
- [8] Ethem Alpaydin. 2014. *Introduction to machine learning*. MIT press.
- [9] Heni Ben Amor and Achim Rettinger. 2005. Intelligent exploration for genetic algorithms: using self-organizing maps
 in evolutionary computation. In *Proceedings of the 7th annual conference on Genetic and evolutionary computation*.
 1531–1538.
- [10] S. Asta, E. Özcan, A. Parkes, and A. Etaner-Uyar. 2013. Generalizing hyper-heuristics via apprenticeship learning. In
 European Conference on Evolutionary Computation in Combinatorial Optimization. 169–178.
- [11] S. Baluja. 1994. Population-based incremental learning. a method for integrating genetic search based function optimization
 and competitive learning. Technical Report. Carnegie-Mellon Univ Pittsburgh Pa Dept Of Computer Science.
- [12] Shumeet Baluja and Scott Davies. 1997. Using Optimal Dependency-Trees for Combinatorial Optimization: Learning the
 Structure of the Search Space. Technical Report. CARNEGIE-MELLON UNIV PITTSBURGH PA DEPT OF COMPUTER
 SCIENCE.
- 1057 [13] Thomas Bartz-Beielstein, Bogdan Filipič, Peter Korošec, and El-Ghazali Talbi. 2020. *High-Performance Simulation-Based Optimization*. Springer.
- [14] T. Bartz-Beielstein and S. Markon. 2004. tuning search algorithms for real-life applications: regression tree based
 approach. In *CEC'2004 Congress on Evolutionary Computation*. 1111–1118.
- [15] Thomas Bartz-Beielstein, Konstantinos E Parsopoulos, and Michael N Vrahatis. 2004. Design and analysis of
 optimization algorithms using computational statistics. *Applied Numerical Analysis & Computational Mathematics* 1,
 2 (2004), 413–433.
- [16] Thomas Bartz-Beielstein and Mike Preuß. 2014. Experimental analysis of optimization algorithms: Tuning and beyond.
 In Theory and Principled Methods for the Design of Metaheuristics. Springer, 205–245.
- [17] M. H. Bassett, J. F. Pekny, and G. V. Reklaitis. 1996. Decomposition techniques for the solution of large-scale scheduling
 problems. *AIChE Journal* 42, 12 (1996), 3373–3387.
- [18] M Basu. 2016. Quasi-oppositional differential evolution for optimal reactive power dispatch. International Journal of Electrical Power & Energy Systems 78 (2016), 29–40.
- [19] Irwan Bello, Hieu Pham, Quoc V Le, Mohammad Norouzi, and Samy Bengio. 2016. Neural combinatorial optimization
 with reinforcement learning. arXiv preprint arXiv:1611.09940 (2016).
- [20] K. P. Bennett and E. Parrado-Hernández. 2006. The interplay of optimization and machine learning research. *Journal of Machine Learning Research* 7, Jul (2006), 1265–1281.
- [21] M. Birattari. 2009. Tuning metaheuristics: A machine learning perspective. Springer.
- [22] B. Bischl, P. Kerschke, L. Kotthoff, M. Lindauer, Y. Malitsky, A. Fréchette, H. Hoos, F. Hutter, K. Leyton-Brown, and K. Tierney. 2016. Aslib: A benchmark library for algorithm selection. *Artificial Intelligence* 237 (2016), 41–58.
- [23] B. Bischl, O. Mersmann, H. Trautmann, and M. Preuß. 2012. Algorithm selection based on exploratory landscape anal ysis and cost-sensitive learning. In *Proceedings of the 14th annual conference on Genetic and evolutionary computation*.
 313–320.
- [24] Léon Bottou, Frank E Curtis, and Jorge Nocedal. 2018. Optimization methods for large-scale machine learning. *Siam Review* 60, 2 (2018), 223–311.
- 1078

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

- [25] J. Boyan and A. W. Moore. 2000. Learning evaluation functions to improve optimization by local search. *Journal of Machine Learning Research* 1, Nov (2000), 77–112.
- [26] P. Brazdil, C. Giraud-Carrier, C. Soares, and R. Vilalta. 2008. Metalearning: Applications to Data Mining.
- [27] Mihaela Elena Breaban and Adrian Iftene. 2015. Dynamic Objective Sampling in Many-objective Optimization. *Procedia Computer Science* 60 (2015), 178 – 187. Knowledge-Based and Intelligent Information & Engineering Systems 19th Annual Conference, KES-2015, Singapore, September 2015 Proceedings.
- [28] Dirk Buche, Nicol N Schraudolph, and Petros Koumoutsakos. 2005. Accelerating evolutionary algorithms with
 Gaussian process fitness function models. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications* and Reviews) 35, 2 (2005), 183–194.
- 1087 [29] Lam T Bui, Hussein A Abbass, and Daryl Essam. 2005. Fitness inheritance for noisy evolutionary multi-objective optimization. In *Proceedings of the 7th annual conference on Genetic and evolutionary computation*. ACM, 779–785.
- [30] E. Burke, M. Gendreau, M. Hyde, G. Kendall, G. Ochoa, E. Ozcan, and R. Qu. 2013. Hyper-heuristics: A survey of the state of the art. *Journal of the Operational Research Society* 64, 12 (2013), 1695–1724.
- [31] E. Burke, G. Kendall, and E. Soubeiga. 2003. A tabu-search hyperheuristic for timetabling and rostering. *Journal of heuristics* 9, 6 (2003), 451–470.
- [32] Edmund K Burke, Matthew Hyde, Graham Kendall, and John Woodward. 2010. A genetic programming hyperheuristic approach for evolving 2-D strip packing heuristics. *IEEE Transactions on Evolutionary Computation* 14, 6 (2010), 942–958.
- [33] Laura Calvet, Jésica de Armas, David Masip, and Angel A Juan. 2017. Learnheuristics: hybridizing metaheuristics
 with machine learning for optimization with dynamic inputs. *Open Mathematics* 15, 1 (2017), 261–280.
- [34] M. Caserta and E. Qui�onez Rico. 2009. A cross entropy-Lagrangean hybrid algorithm for the multi-item capacitated lot-sizing problem with setup times. *Computers and Operations Research* 36, 2 (2009), 530 548.
- [35] D. Catteeuw, M. Drugan, and B. Manderick. Ljubljana, Slovenia, 2014. Guided Restarts Hill-Climbing. In *PPSN'14 Parallel ProblemSolving from Nature*. 313–320.
- [36] D. Chafekar, L. Shi, K. Rasheed, and J. Xuan. 2005. Multiobjective GA Optimization Using Reduced Models. Systems,
 Man, and Cybernetics, Part C: Applications and Reviews, IEEE Transactions on 35 (06 2005), 261–265.
- [37] Girish Chandrashekar and Ferat Sahin. 2014. A survey on feature selection methods. *Computers & Electrical Engineering* 40, 1 (2014), 16–28.
- [38] Y. Chen, P. Cowling, F. Polack, and P. Mourdjis. 2016. A multi-arm bandit neighbourhood search for routing and scheduling problems. (2016).
- [39] T. Chugh, K. Sindhya, J. Hakanen, and K. Miettinen. 2019. A survey on handling computationally expensive
 multiobjective optimization problems with evolutionary algorithms. *Soft Computing* 23, 9 (2019), 3137–3166.
- 1106[40] EM Cochrane and JE Beasley. 2003. The co-adaptive neural network approach to the Euclidean travelling salesman1107problem. Neural Networks 16, 10 (2003), 1499–1525.
- [41] D. J. Cook and R. C. Varnell. 1997. Maximizing the benefits of parallel search using machine learning. In AAAI/IAAI. 559–564.
- [42] David Corne, Clarisse Dhaenens, and Laetitia Jourdan. 2012. Synergies between operations research and data mining:
 The emerging use of multi-objective approaches. *European Journal of Operational Research* 221, 3 (2012), 469–479.
- [43] Steven P Coy, Bruce L Golden, George C Runger, and Edward A Wasil. 2001. Using experimental design to find effective parameter settings for heuristics. *Journal of Heuristics* 7, 1 (2001), 77–97.
- [44] Teodor Gabriel Crainic, Mike Hewitt, and Walter Rei. 2014. Scenario grouping in a progressive hedging-based
 meta-heuristic for stochastic network design. *Computers & Operations Research* 43 (2014), 90–99.
- [45] J-C. Créput and A. Koukam. 2008. The memetic self-organizing map approach to the vehicle routing problem. *Soft Computing* 12, 11 (2008), 1125–1141.
- [46] C. Cummins, P. Petoumenos, Z. Wang, and H. Leather. 2017. End-to-end deep learning of optimization heuristics. In
 2017 26th International Conference on Parallel Architectures and Compilation Techniques (PACT). 219–232.
- [47] Luis DaCosta, Alvaro Fialho, Marc Schoenauer, and Michèle Sebag. 2008. Adaptive operator selection with dynamic multi-armed bandits. In *Proceedings of the 10th annual conference on Genetic and evolutionary computation*. 913–920.
- [48] FL Dalboni, LS Ochi, and LMA Drummond. 2003. On improving evolutionary algorithms by using data mining for
 the oil collector vehicle routing problem. In *International Network Optimization Conference*. 182–188.
- [49] M. R. de Holanda, A. Plastino, and U. dos Santos Souza. 2020. MineReduce for the minimum weight vertex cover problem. In *OLA'2020 Int. conf. on Optimization and Learning, Cadiz, Spain.*
- [50] Kenneth De Jong. 2007. Parameter setting in EAs: a 30 year perspective. In *Parameter setting in evolutionary algorithms*.
 1–18.
- 1124 [51] Clarisse Dhaenens and Laetitia Jourdan. 2016. *Metaheuristics for big data*. John Wiley & Sons.
- 1125[52] F. Dobslaw. 2010. A parameter tuning framework for metaheuristics based on design of experiments and artificial1126neural networks. In International Conference on Computer Mathematics and Natural Computing.
- 1127

El-Ghazali TALBI

- [53] Xiaojian Dong, Song Yu, Zhijian Wu, and Zhangxing Chen. 2010. A hybrid parallel evolutionary algorithm based on
 elite-subspace strategy and space transformation search. In *High Performance Computing and Applications*. Springer,
 139–145.
- [54] M. Dorigo and L. M. Gambardella. 1997. Ant colony system: a cooperative learning approach to the traveling salesman problem. *IEEE Transactions on evolutionary computation* 1, 1 (1997), 53–66.
- [55] J. dos Santos, J. D. de Melo, A. Neto, and D. Aloise. 2014. Reactive search strategies using reinforcement learning,
 local search algorithms and variable neighborhood search. *Expert Systems with Applications* 41, 10 (2014), 4939–4949.
- [56] M. Drugan. 2019. Reinforcement learning versus evolutionary computation: A survey on hybrid algorithms. *Swarm and evolutionary computation* 44 (2019), 228–246.
- [57] M. Drugan and E-G. Talbi. 2014. Adaptive Multi-operator MetaHeuristics for quadratic assignment problems. In EVOLVE-A Bridge between Probability, Set Oriented Numerics, and Evolutionary Computation V. 149–163.
- [58] G. Duflo, G. Danoy, E-G. Talbi, and P. Bouvry. 2020. Automated Design of Efficient Swarming Behaviours: a Q-Learning
 Hyper-Heuristic Approach. In OLA'2020 Int. conf. on Optimization and Learning, Cadiz, Spain.
- [59] AE Eiben, Mark Horvath, Wojtek Kowalczyk, and Martijn C Schut. 2006. Reinforcement learning for online control
 of evolutionary algorithms. In *International Workshop on Engineering Self-Organising Applications*. 151–160.
- [60] A. E. Eiben and S. K. Smit. 2011. Parameter tuning for configuring and analyzing evolutionary algorithms. Swarm and Evolutionary Computation 1, 1 (2011), 19–31.
- [61] R. S. Engelmore and A. Morgan. 1988. *Blackboard Systems*. Addison-Wesley.
- [62] S. Erdoğan and E. Miller-Hooks. 2012. A green vehicle routing problem. *Transportation Research Part E: Logistics and Transportation Review* 48, 1 (2012), 100–114.
- [63] L. Eriksson, E. Johansson, N. Kettaneh-Wold, C. Wikström, and S. Wold. 2000. Design of experiments. *Principles and Applications, Learn ways AB, Stockholm* (2000).
- [64] Adil Fahad, Najlaa Alshatri, Zahir Tari, Abdullah Alamri, Ibrahim Khalil, Albert Y Zomaya, Sebti Foufou, and Abdelaziz
 Bouras. 2014. A survey of clustering algorithms for big data: Taxonomy and empirical analysis. *IEEE Transactions on Emerging Topics in Computing* 2, 3 (2014), 267–279.
- [65] C. Fan, B. Hou, J. Zheng, L. Xiao, and L. Yi. 2020. A surrogate-assisted particle swarm optimization using ensemble
 learning for expensive problems with small sample datasets. *Applied Soft Computing* (2020), 106–142.
- [66] L. Feng, Y. Ong, M. Lim, and I. W. Tsang. 2015. Memetic Search With Interdomain Learning: A Realization Between CVRP and CARP. *IEEE Transactions on Evolutionary Computation* 19, 5 (2015), 644–658.
- [67] Philippe Fournier-Viger, Jerry Chun-Wei Lin, Bay Vo, Tin Truong Chi, Ji Zhang, and Hoai Bac Le. 2017. A survey of
 itemset mining. Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery 7, 4 (2017), e1207.
- [68] S. Gao, Y. Wang, J. Cheng, Y. Inazumi, and Z. Tang. 2016. Ant colony optimization with clustering for solving the
 dynamic location routing problem. *Appl. Math. Comput.* 285 (2016), 149–173.
- [69] Wei-feng Gao, San-yang Liu, and Ling-ling Huang. 2012. Particle swarm optimization with chaotic opposition-based population initialization and stochastic search technique. *Communications in Nonlinear Science and Numerical Simulation* 17, 11 (2012), 4316–4327.
- [70] António Gaspar-Cunha and Armando Vieira. 2004. A Hybrid Multi-Objective Evolutionary Algorithm Using an
 Inverse Neural Network.. In *Hybrid Metaheuristics*. 25–30.
- [71] C. Gebruers, A. Guerri, B. Hnich, and M. Milano. 2004. Making choices using structure at the instance level within a case based reasoning framework. In *International Conference on Integration of Artificial Intelligence (AI) and Operations Research (OR) Techniques in Constraint Programming*. 380–386.
- [72] S. Geetha, G. Poonthalir, and P. Vanathi. 2009. Improved k-means algorithm for capacitated clustering problem.
 INFOCOMP 8, 4 (2009), 52–59.
- [73] Tushar Goel, Raphael T Haftka, Wei Shyy, and Nestor V Queipo. 2007. Ensemble of surrogates. *Structural and Multidisciplinary Optimization* 33, 3 (2007), 199–216.
- [74] Tushar Goel, Rajkumar Vaidyanathan, Raphael T Haftka, Wei Shyy, Nestor V Queipo, and Kevin Tucker. 2007. Response surface approximation of Pareto optimal front in multi-objective optimization. *Computer methods in applied mechanics and engineering* 196, 4-6 (2007), 879–893.
- [75] P. Goyal, H. Malik, and R. Sharma. 2019. Application of evolutionary reinforcement learning (erl) approach in control
 domain: A review. In *Smart Innovations in Communication and Computational Sciences*. 273–288.
- [76] Aldy Gunawan, Hoong Chuin Lau, and Elaine Wong. 2013. Real-world parameter tuning using factorial design with
 parameter decomposition. In *Advances in Metaheuristics*. Springer, 37–59.
- [77] J. Gupta, R. Sexton, and E. Tunc. 2000. Selecting scheduling heuristics using neural networks. *INFORMS Journal on Computing* 12, 2 (2000), 150–162.
- [78] Haipeng H. Guo. 2003. Algorithm selection for sorting and probabilistic inference: a machine learning-based approach.
 Ph.D. Dissertation. Kensas State University.
- 1175
- 1176

00:24

- [79] Lin Han and Xingshi He. 2007. A novel opposition-based particle swarm optimization for noisy problems. In *Third IEEE International Conference on Natural Computation (ICNC 2007)*, Vol. 3. 624–629.
- [80] M. He, P. Kalmbach, A. Blenk, W. Kellerer, and S. Schmid. 2017. Algorithm-data driven optimization of adaptive communication networks. In *2017 IEEE 25th International Conference on Network Protocols (ICNP)*. 1–6.
- [81] Ali Hebbal, Loic Brevault, Mathieu Balesdent, El-Ghazali Talbi, and Nouredine Melab. 2019. Bayesian Optimization
 using Deep Gaussian Processes. arXiv preprint arXiv:1905.03350 (2019).
- [82] T-P. Hong, H-S. Wang, and W-C. Chen. 2000. Simultaneous applying multiple mutation operators in genetic algorithm.
 Journal of Heuristics 6, 4 (2000), 439–455.
- [83] Young-Seok Hong, Hungu Lee, and Min-Jea Tahk. 2003. Acceleration of the convergence speed of evolutionary algorithms using multi-layer neural networks. *Engineering Optimization* 35, 1 (2003), 91–102.
- [84] P. D. Hough and P. J. Williams. 2006. Modern Machine Learning for Automatic Optimization Algorithm Selection.
 Technical Report. Sandia National Lab.(SNL-CA), Livermore, CA (United States).
- [85] X-M. Hu, F-L. He, W-N. Chen, and J. Zhang. 2017. Cooperation coevolution with fast interdependency identification for large scale optimization. *Information Sciences* 381 (2017), 142–160.
- [86] J. Hunger and G. Huttner. [n.d.]. Optimization and analysis of force field parameters by combination of genetic algorithms and neural networks. *Journal of Computational Chemistry* 20, 4 ([n. d.]), 455–471.
- [87] F. Hutter, Y. Hamadi, H. Hoos, and K. Leyton-Brown. 2006. Performance prediction and automated tuning of randomized and parametric algorithms. In *International Conference on Principles and Practice of Constraint Programming*.
 Springer, 213–228.
- 1193[88] Frank Hutter, Holger H Hoos, and Kevin Leyton-Brown. 2011. Sequential model-based optimization for general1194algorithm configuration. In International Conference on Learning and Intelligent Optimization. 507–523.
- [89] Frank Hutter, Holger H Hoos, Kevin Leyton-Brown, and Thomas Stützle. 2009. ParamILS: an automatic algorithm configuration framework. *Journal of Artificial Intelligence Research* 36 (2009), 267–306.
- [90] Frank Hutter, Lin Xu, Holger H Hoos, and Kevin Leyton-Brown. 2014. Algorithm runtime prediction: Methods &
 evaluation. Artificial Intelligence 206 (2014), 79–111.
- [91] M. Jiang, Z. Huang, L. Qiu, W. Huang, and G. G. Yen. 2018. Transfer Learning-Based Dynamic Multiobjective
 Optimization Algorithms. *IEEE Transactions on Evolutionary Computation* 22, 4 (2018), 501–514.
- [92] Xuan Jiang, Deepti Chafekar, and Khaled Rasheed. 2003. Constrained multi-objective ga optimization using reduced models. In 2003 Genetic and Evolutionary Computation Conference. Workshop Program. 174–177.
 [20] Y. Yim, J. D. D. and J. K. Karakara, and Khaled Rasheed. 2003. Constrained multi-objective ga optimization using reduced models. In 2003 Genetic and Evolutionary Computation Conference. Workshop Program. 174–177.
- [93] X. Jin and R. Reynolds. 1999. Using knowledge-based evolutionary computation to solve nonlinear constraint
 optimization problems: a cultural algorithm approach. In *Proceedings of the 1999 congress on evolutionary computation- CEC*'1999, Vol. 3. 1672–1678.
- [94] Y. Jin. 2005. A comprehensive survey of fitness approximation in evolutionary computation. *Soft Computing* 9, 1 (2005), 3–12.
- [95] Y. Jin. 2011. Surrogate-assisted evolutionary computation: Recent advances and future challenges. *Swarm and Evolutionary Computation* 1 (06 2011), 61–70.
- [96] Y. Jin, M. Olhofer, and B. Sendhoff. 2002. A framework for evolutionary optimization with approximate fitness
 functions. *IEEE Transactions on evolutionary computation* 6, 5 (2002), 481–494.
- [97] Y. Jin and B. Sendhoff. 2004. Reducing fitness evaluations using clustering techniques and neural network ensembles.
 In *Genetic and Evolutionary Computation GECCO'2004, LNCS No.3102.* Springer, 688–699.
- [98] Donald R Jones, Matthias Schonlau, and W. J. Welch. 1998. Efficient global optimization of expensive black-box
 functions. *Journal of Global optimization* 13, 4 (1998), 455–492.
- [99] Laetitia Jourdan, David Corne, Dragan Savic, and Godfrey Walters. 2005. Preliminary investigation of the learnable
 evolution model for faster/better multiobjective water systems design. In *International Conference on Evolutionary* Multi-Criterion Optimization. 841–855.
- [100] L. Jourdan, C. Dhaenens, and E-G. Talbi. 2006. Using data mining techniques to help metaheuristics: A short survey. In *Hybrid Metaheuristics (HM'2006) (LNCS)*, Vol. 4030. Gran Canaria, Spain, 57–69.
- [101] Mrinal Kalakrishnan, Peter Pastor, Ludovic Righetti, and Stefan Schaal. 2013. Learning objective functions for
 manipulation. In 2013 IEEE International Conference on Robotics and Automation. 1331–1336.
- [102] B. Kazimipour, X. Li, and A. Qin. 2014. A review of population initialization techniques for evolutionary algorithms.
 In Evolutionary Computation (CEC), 2014 IEEE Congress on. 2585–2592.
- [103] Harshad Khadilkar. 2018. A Scalable Reinforcement Learning Algorithm for Scheduling Railway Lines. IEEE Transactions on Intelligent Transportation Systems 99 (2018), 1–11.
- [104] Elias Khalil, Hanjun Dai, Yuyu Zhang, Bistra Dilkina, and Le Song. 2017. Learning combinatorial optimization
 algorithms over graphs. In *Advances in Neural Information Processing Systems*. 6348–6358.
- 1223[105] E. Kieffer, G. Danoy, M. Brust, P. Bouvry, and A. Nagih. 2019. Tackling large-scale and combinatorial bi-level problems1224with a genetic programming hyper-heuristic. *IEEE Transactions on Evolutionary Computation* (2019).
- 1225

00:26

- [106] H-S. Kim and S-B. Cho. 2001. An efficient genetic algorithm with less fitness evaluation by clustering. In *Congress on Evolutionary Computation CEC'01*. IEEE Press, 887–894.
- [107] Joshua Knowles. 2006. ParEGO: a hybrid algorithm with on-line landscape approximation for expensive multiobjective optimization problems. *IEEE Transactions on Evolutionary Computation* 10, 1 (2006), 50–66.
- [108] L. Kotthoff. 2016. Algorithm selection for combinatorial search problems: A survey. In *Data Mining and Constraint Programming*. Springer, 149–190.
- [109] P. Laborie and D. Godard. 2007. Self-adapting large neighborhood search: Application to single-mode scheduling
 problems. *Proceedings MISTA-07, Paris* 8 (2007).
- [110] W. Laesanklang and D. Landa-Silva. 2017. Decomposition techniques with mixed integer programming and heuristics for home healthcare planning. *Annals of operations research* 256, 1 (2017), 93–127.
- [111] Hoong Chuin LAU and Fei Xiao. 2009. Enhancing the speed and accuracy of automated parameter tuning in heuristic design. (2009).
- [123 [112] Stefan Lessmann, Marco Caserta, and Idel Montalvo Arango. 2011. Tuning metaheuristics: A data mining based
 approach for particle swarm optimization. *Expert Systems with Applications* 38, 10 (2011), 12826–12838.
- [113] Shing Wa Leung, Xin Zhang, and Shiu Yin Yuen. 2012. Multiobjective differential evolution algorithm with oppositionbased parameter control. In 2012 IEEE Congress on Evolutionary Computation. 1–8.
- [114] Y-W. Leung and Y. Wang. 2001. An orthogonal genetic algorithm with quantization for global numerical optimization.
 IEEE Transactions on Evolutionary computation 5, 1 (2001), 41–53.
- [115] K. Leyton-Brown, E. Nudelman, and Y. Shoham. 2002. Learning the empirical hardness of optimization problems:
 The case of combinatorial auctions. In *International Conference on Principles and Practice of Constraint Programming*.
 556–572.
- 1244 [116] K. Leyton-Brown, E. Nudelman, and Y. Shoham. 2009. Empirical hardness models: Methodology and a case study on combinatorial auctions. *Journal of the ACM (JACM)* 56, 4 (2009), 1–52.
- [117] Xiaonan Li and Sigurdur Olafsson. 2005. Discovering dispatching rules using data mining. *Journal of Scheduling* 8, 6
 (2005), 515–527.
- [118] L. Liu and M. Dessouky. 2017. A decomposition based hybrid heuristic algorithm for the joint passenger and freight train scheduling problem. *Computers & Operations Research* 87 (2017), 165–182.
- [119] Zhe Liu and Fahim Forouzanfar. 2018. Ensemble clustering for efficient robust optimization of naturally fractured reservoirs. *Computational Geosciences* 22, 1 (2018), 283–296.
- [120] I. Loshchilov, M. Schoenauer, and M. Sebag. 2012. Self-adaptive surrogate-assisted covariance matrix adaptation
 evolution strategy. In *Proceedings of the 14th annual conference on Genetic and evolutionary computation*. 321–328.
- 1252[121] S. Louis and J. McDonnell. 2004. Learning with case-injected genetic algorithms. IEEE Transactions on Evolutionary1253Computation 8, 4 (2004), 316–328.
- [122] Xiaoliang Ma, Fang Liu, Yutao Qi, Maoguo Gong, Minglei Yin, Lingling Li, Licheng Jiao, and Jianshe Wu. 2014. MOEA/D with opposition-based learning for multiobjective optimization problem. *Neurocomputing* 146 (2014), 48–64.
- [1256 [123] S. Mahdavi, S. Rahnamayan, and M. E. Shiri. 2018. Incremental cooperative coevolution for large-scale global
 optimization. Soft Computing 22, 6 (2018), 2045–2064.
- [124] R. Mallipeddi and P. N. Suganthan. 2010. Ensemble of constraint handling techniques. *IEEE Transactions on Evolutionary Computation* 14, 4 (2010), 561–579.
- [125] Hongzi Mao, Mohammad Alizadeh, Ishai Menache, and Srikanth Kandula. 2016. Resource management with deep reinforcement learning. In *Proceedings of the 15th ACM Workshop on Hot Topics in Networks*. 50–56.
- 1261[126] S. Meisel and D. C. Mattfeld. 2007. Synergies of data mining and operations research. In System Sciences, 2007. HICSS12622007. 40th Annual Hawaii International Conference on. 56–56.
- [127] O. Mersmann, B. Bischl, H. Trautmann, M. Preuss, C. Weihs, and G. Rudolph. 2011. Exploratory landscape analysis.
 In Proceedings of the 13th annual conference on Genetic and evolutionary computation. 829–836.
- [128] R. S. Michalski. 2000. Learnable evolution model: Evolutionary processes guided by machine learning. *Machine Learning* 38, 1 (2000), 9–40.
- [129] Shoma Miki, Daisuke Yamamoto, and Hiroyuki Ebara. 2018. Applying Deep Learning and Reinforcement Learning to
 Traveling Salesman Problem. In 2018 International Conference on Computing, Electronics & Communications Engineering
 (iCCECE). 65–70.
- [130] M. Mısır, S. Handoko, and H. C. Lau. 2015. OSCAR: Online selection of algorithm portfolios with case study on memetic algorithms. In *International Conference on Learning and Intelligent Optimization*. 59–73.
- [131] Abdolhamid Modares, Samerkae Somhom, and Takao Enkawa. 1999. A self-organizing neural network approach for
 multiple traveling salesman and vehicle routing problems. *International Transactions in Operational Research* 6, 6
 (1999), 591–606.
- 1273

1274

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

- [1275 [132] J. Mueller and J. Woodbury. 2017. GOSAC: global optimization with surrogate approximation of constraints. *Journal of Global Optimization* 69 (01 2017).
- [133] Alexander Nareyek. 2003. Choosing search heuristics by non-stationary reinforcement learning. In *Metaheuristics: Computer decision-making*. Springer, 523–544.
- [134] M. M. Nasiri, S. Salesi, A. Rahbari, N. S. Meydani, and M. Abdollai. [n.d.]. A data mining approach for population-based
 methods to solve the JSSP. *Soft Computing* ([n.d.]).
- [135] Mohammadreza Nazari, Afshin Oroojlooy, Lawrence Snyder, and Martin Takác. 2018. Reinforcement learning for
 solving the vehicle routing problem. In *Advances in Neural Information Processing Systems*. 9839–9849.
- [136] R. S. Niculescu, T. Mitchell, and R. B. Rao. 2006. Bayesian network learning with parameter constraints. *Journal of machine learning research* 7, Jul (2006), 1357–1383.
- [137] J. Ortiz-Bayliss, H. Terashima-Marín, and S. Conant-Pablos. 2013. A supervised learning approach to construct hyper-heuristics for constraint satisfaction. In *Mexican Conference on Pattern Recognition*. 284–293.
- [138] J. Ortiz-Bayliss, H. Terashima-Marín, and S. Conant-Pablos. 2013. Using learning classifier systems to design selective
 hyper-heuristics for constraint satisfaction problems. In *Evolutionary Computation (CEC), 2013 IEEE Congress on*.
 2618–2625.
- [139] J. Ortiz-Bayliss, H. Terashima-Marín, P. Ross, and S. Conant-Pablos. 2011. Evolution of neural networks topologies and learning parameters to produce hyper-heuristics for constraint satisfaction problems. In *Proceedings of the 13th annual conference companion on Genetic and evolutionary computation*. 261–262.
- [140] A. Ostertag, K. Doerner, and R. Hartl. 2008. A variable neighborhood search integrated in the POPMUSIC framework
 for solving large scale vehicle routing problems. In *International Workshop on Hybrid Metaheuristics*. 29–42.
- [141] E. Özcan, M. Misir, G. Ochoa, and E. Burke. 2012. A Reinforcement Learning: Great-Deluge Hyper-Heuristic for Examination Timetabling. In *Modeling, Analysis, and Applications in Metaheuristic Computing: Advancements and Trends.* 34–55.
- [142] Monalisa Pal, Sriparna Saha, and Sanghamitra Bandyopadhyay. 2018. DECOR: Differential Evolution using Clustering
 based Objective Reduction for many-objective optimization. *Information Sciences* 423 (2018), 200 218.
- 1296[143] Millie Pant, Musrrat Ali, and Ved P Singh. 2009. Differential evolution using quadratic interpolation for initializing1297the population. In 2009 IEEE International Advance Computing Conference. 375–380.
- [144] So-Youn Park and Ju-Jang Lee. 2009. Improvement of a multi-objective differential evolution using clustering algorithm. In 2009 IEEE International Symposium on Industrial Electronics. IEEE, 1213–1217.
- [145] J. M. Parr, C. M. E. Holden, A. I. J. Forrester, and A. J. Keane. 2010. Review of efficient surrogate infill sampling criteria with constraint handling.
- 1301[146] R. Patterson, E. Rolland, and H. Pirkul. 1999. A memory adaptive reasoning technique for solving the capacitated1302minimum spanning tree problem. Journal of Heuristics 5 (1999), 159–180.
- [147] Reyes Pavon, Fernando Diaz, Rosalia Laza, and Victoria Luzon. 2009. Automatic parameter tuning with a Bayesian case-based reasoning system. A case of study. *Expert Systems with Applications* 36, 2, Part 2 (2009), 3407 3420.
- [148] M. Pelikan, D. Goldberg, and F. Lobo. 2002. A survey of optimization by building and using probabilistic models.
 Computational optimization and applications 21, 1 (2002), 5–20.
- 1306[149] Martin Pelikan and Kumara Sastry. 2004. Fitness inheritance in the Bayesian optimization algorithm. In Genetic and1307Evolutionary Computation Conference. 48–59.
- 1308 [150] M. Pelikan, K. Sastry, and D. Goldberg. 2005. Multiobjective hBOA, Clustering, and Scalability. GECCO 2005 Genetic and Evolutionary Computation Conference (03 2005).
- [151] J. Pena, J. Lozano, and P. Larranaga. 2005. Globally Multimodal Problem Optimization Via an Estimation of Distribution
 Algorithm Based on Unsupervised Learning of Bayesian Networks. *Evolutionary Computation* 13 (03 2005), 43–66.
- 1311[152] J. Peña, J. Lozano, and P. Larrañaga. 2005. Globally multimodal problem optimization via an estimation of distribution
algorithm based on unsupervised learning of Bayesian networks. *Evolutionary Computation* 13, 1 (2005), 43–66.
- 1313[153] Daniel Cosmin Porumbel, Jin-Kao Hao, and Pascale Kuntz. 2010. A search space cartography for guiding graph
coloring heuristics. Computers and Operations Research 37, 4 (2010), 769 778.
- [154] J-Y. Potvin and S R. S. Thangiah. 2020. Vehicle Routing through Simulation. Fusion of Neural Networks, Fuzzy Systems
 and Genetic Algorithms: Industrial Applications (2020).
- 1316[155] Warren B Powell. 2007. Approximate Dynamic Programming: Solving the curses of dimensionality. Vol. 703. John Wiley1317& Sons.
- [156] Rémy Priem, Nathalie Bartoli, and Youssef Diouane. 2019. On the Use of Upper Trust Bounds in Constrained Bayesian Optimization Infill Criteria. In AIAA Aviation 2019 Forum. 2986.
- ¹³¹⁹ [157] Paolo Priore, David de la Fuente, Javier Puente, and José Parreño. 2006. A comparison of machine-learning algorithms
 ¹³²⁰ for dynamic scheduling of flexible manufacturing systems. *Engineering Applications of Artificial Intelligence* 19, 3
 ¹³²¹ (2006), 247–255.
- 1322 1323

ACM Comput. Surv., Vol. 00, No. 00, Article 00. Publication date: 2020.

00:28

- [1324 [158] L. Pulina and A. Tacchella. 2007. A multi-engine solver for quantified boolean formulas. In *International Conference* on *Principles and Practice of Constraint Programming*. 574–589.
- [159] S. Rahnamayan, H. Tizhoosh, and M. Salama. 2008. Opposition-based differential evolution. *IEEE Transactions on Evolutionary computation* 12, 1 (2008), 64–79.
- [160] Iloneide CO Ramos, Marco César Goldbarg, Elizabeth G Goldbarg, and Adriao Duarte Dória Neto. 2005. Logistic regression for parameter tuning on an evolutionary algorithm. In 2005 IEEE Congress on Evolutionary Computation, Vol. 2. IEEE, 1061–1068.
- [161] Khaled Rasheed and Haym Hirsh. 2000. Informed operators: Speeding up genetic-algorithm-based design optimization
 using reduced models. In *Proceedings of the 2nd Annual Conference on Genetic and Evolutionary Computation*. 628–635.
- 1332 [162] K. Rasheed, S. Vattam, and X. Ni. 2002. Comparison of methods for developing dynamic reduced models for design optimization. In CEC'2002 Congress on Evolutionary Computation. 390–395.
- [133] [163] J. Rasku, T. Kärkkäinen, and N. Musliu. 2016. Feature extractors for describing vehicle routing problem instances.
 (133) OASICS; 50 (2016).
- 1335[164] Rommel G Regis. 2014. Constrained optimization by radial basis function interpolation for high-dimensional expensive1336black-box problems with infeasible initial points. Engineering Optimization 46, 2 (2014), 218–243.
- [165] Rommel G Regis. 2014. Evolutionary programming for high-dimensional constrained expensive black-box optimization using radial basis functions. *IEEE Transactions on Evolutionary Computation* 18, 3 (2014), 326–347.
- [166] Rommel G Regis and Christine A Shoemaker. 2004. Local function approximation in evolutionary algorithms for the
 optimization of costly functions. *IEEE transactions on evolutionary computation* 8, 5 (2004), 490–505.
- [167] M. Reimann, K. Doerner, and R. Hartl. 2004. D-ants: Savings Based Ants Divide and Conquer the Vehicle Routing
 Problem. 31 (04 2004), 563–591.
- [168] R. G. Reynolds, Z. Michalewicz, and B. Peng. 2005. Cultural algorithms: Computational modeling of how cultures learn to solve problems- an engineering example. *Cybernetics and Systems* 36, 8 (2005), 753–771.
- [169] Marcos Henrique Ribeiro, Alexandre Plastino, and Simone L Martins. 2006. Hybridization of GRASP metaheuristic
 with data mining techniques. *Journal of Mathematical Modelling and Algorithms* 5, 1 (2006), 23–41.
- [170] M. H. Ribeiro, V. Trindade, A. Plastino, and S. L. Martins. 2004. Hybridization of GRASP Metaheuristics with Data
 Mining Techniques. In *Hybrid Metaheuristics*.
- [171] J. R. Rice. 1976. The algorithm selection problem. Advances in Computers 15 (1976), 65–118.
- [172] Nicolás Rojas-Morales, María-Cristina Riff Rojas, and Elizabeth Montero Ureta. 2017. A survey and classification of
 opposition-based metaheuristics. *Computers & Industrial Engineering* 110 (2017), 424–435.
- [1349 [173] Thomas Philip Runarsson. 2011. Learning heuristic policies-a reinforcement learning problem. In International Conference on Learning and Intelligent Optimization. 423-432.
- [174] N. Sabar, M. Ayob, G. Kendall, and R. Qu. 2015. Automatic design of a hyper-heuristic framework with gene expression programming for combinatorial optimization problems. *IEEE Trans. Evolutionary Computation* 19, 3 (2015), 309–325.
- [175] Haroldo G Santos, Luiz Satoru Ochi, Euler Horta Marinho, and Lúcia Maria de A Drummond. 2006. Combining an
 evolutionary algorithm with data mining to solve a single-vehicle routing problem. *Neurocomputing* 70, 1-3 (2006),
 70–77.
- [176] Kumara Sastry and David E. Goldberg. 2004. Designing Competent Mutation Operators Via Probabilistic Model
 Building of Neighborhoods. In *Genetic and Evolutionary Computation GECCO 2004*, Kalyanmoy Deb (Ed.). 114–125.
- 1357 [177] Kumara Sastry, David E Goldberg, and Martin Pelikan. 2001. Don't evaluate, inherit. In Proceedings of the 3rd Annual Conference on Genetic and Evolutionary Computation. 551–558.
- [178] Dhish Kumar Saxena, João A. Duro, Ashutosh Tiwari, Kalyanmoy Deb, and Qingfu Zhang. 2013. Objective
 Reduction in Many-Objective Optimization: Linear and Nonlinear Algorithms. *Trans. Evol. Comp* 17, 1 (2013), 77–99.
- [179] Michèle Sebag, Marc Schoenauer, and Caroline Ravise. 1997. Inductive Learning of Mutation Step-Size in Evolutionary
 Parameter Optimization. In *Evolutionary Programming*.
- 1362 [180] Atif Shahzad and Nasser Mebarki. 2012. Data mining based job dispatching using hybrid simulation-optimization approach for shop scheduling problem. *Engineering Applications of Artificial Intelligence* 25, 6 (2012), 1173–1181.
- [181] S. Shakya and J. McCall. 2007. Optimization by estimation of distribution with DEUM framework based on Markov
 random fields. *International Journal of Automation and Computing* 4, 3 (2007), 262–272.
- [182] C. Shang and F. You. 2019. A data-driven robust optimization approach to scenario-based stochastic model predictive
 control. Journal of Process Control 75 (2019), 24–39.
- [183] G Shankar and V Mukherjee. 2016. Quasi oppositional harmony search algorithm based controller tuning for load frequency control of multi-source multi-area power system. *International Journal of Electrical Power & Energy Systems* 75 (2016), 289–302.
- [184] L. Shi and K. Rasheed. 2008. ASAGA: an adaptive surrogate-assisted genetic algorithm. In *Proceedings of the 10th annual conference on Genetic and evolutionary computation*. 1049–1056.
- 1371
- 1372

- [185] Chandan Kumar Shiva, G Shankar, and V Mukherjee. 2015. Automatic generation control of power system using a
 novel quasi-oppositional harmony search algorithm. *International Journal of Electrical Power & Energy Systems* 73
 (2015), 787–804.
- [186] Yang Shiyou, Qing Liu, Junwei Lu, S.L. Ho, Guangzheng Ni, Peihong Ni, and Suming Xiong. 2009. Application of Support Vector Machines to Accelerate the Solution Speed of Metaheuristic Algorithms. *Magnetics, IEEE Transactions* on 45 (04 2009), 1502 – 1505.
- [1378 [187] Tapas Si, Arunava De, and Anup Kumar Bhattacharjee. 2014. Particle swarm optimization with generalized opposi tion based learning in particle's pbest position. In 2014 International Conference on Circuits, Power and Computing
 Technologies [ICCPCT-2014]. 1662–1667.
- [188] Robert E Smith, Bruce A Dike, and SA Stegmann. 1995. Fitness inheritance in genetic algorithms. In *Proceedings of the 1995 ACM symposium on Applied computing*. 345–350.
- [189] K. Smith-Miles and J. van Hemert. 2011. Discovering the suitability of optimisation algorithms by learning from
 evolved instances. Annals of Mathematics and Artificial Intelligence 61, 2 (2011), 87–104.
- 1384[190] K. A. Smith-Miles. 2009. Cross-disciplinary perspectives on meta-learning for algorithm selection. ACM Computing1385Surveys (CSUR) 41, 1 (2009), 1–25.
- 1386 [191] Carlos Soza, Ricardo Landa Becerra, María Cristina Riff, and Carlos A Coello Coello. 2011. Solving timetabling problems using a cultural algorithm. *Applied Soft Computing* 11, 1 (2011), 337–344.
- ¹³⁸⁷ [192] Suvrit Sra, Sebastian Nowozin, and Stephen J Wright. 2012. *Optimization for machine learning*. Mit Press.
- [193] Sanjay Srivastava, Bhupendra Pathak, and Kamal Srivastava. 2008. Neural network embedded multiobjective genetic
 algorithm to solve non-linear time-cost tradeoff problems of project scheduling. *Journal of scientific and industrial research* 67 (01 2008), 124.
- [194] Richard S Sutton, Andrew G Barto, et al. 1998. *Introduction to reinforcement learning*. Vol. 135.
- [195] E-G. Talbi. 2009. Metaheuristics: from design to implementation. Wiley.
- [196] El-Ghazali Talbi. 2016. Combining metaheuristics with mathematical programming, constraint programming and
 machine learning. *Annals of Operations Research* 240, 1 (2016), 171–215.
- 1394[197] Kay Chen Tan, Huajin Tang, and Shuzhi Sam Ge. 2005. On parameter settings of Hopfield networks applied to1395traveling salesman problems. IEEE Transactions on Circuits and Systems I: Regular Papers 52, 5 (2005), 994–1002.
- 1396[198] Y. Tenne and C-K. Goh. 2010. Computational intelligence in expensive optimization problems. Vol. 2. Springer Science
& Business Media.
- [199] Simon Thevenin and Nicolas Zufferey. 2019. Learning Variable Neighborhood Search for a scheduling problem with
 time windows and rejections. *Discrete Applied Mathematics* 261 (2019), 344–353.
- [200] D. Thierens. 2005. An adaptive pursuit strategy for allocating operator probabilities. In *Proceedings of the 7th annual* conference on Genetic and evolutionary computation. 1539–1546.
- [201] Dirk Thierens and Peter A. N. Bosman. 2012. Learning the Neighborhood with the Linkage Tree Genetic Algorithm. In *Learning and Intelligent Optimization*, Youssef Hamadi and Marc Schoenauer (Eds.). 491–496.
- [202] Hamid R Tizhoosh, Mario Ventresca, and Shahryar Rahnamayan. 2008. Opposition-based computing. In *Oppositional Concepts in Computational Intelligence*. Springer, 11–28.
- [203] A. Tuson and P. Ross. 1998. Adapting operator settings in genetic algorithms. *Evolutionary Computation* 6, 2 (1998), 161–184.
- 1406 [204] D. Tuzun, M. A. Magent, and L. I. Burke. 1997. Selection of vehicle routing heuristic using neural networks. International Transactions in Operational Research 4, 3 (1997), 211–221.
- [205] R. Tyasnurita, E. Ozcan, and R. John. 2017. Learning heuristic selection using a time delay neural network for open vehicle routing. In 2017 IEEE Congress on Evolutionary Computation (CEC). 1474–1481.
- 1409[206] Holger Ulmer, Felix Streichert, and Andreas Zell. 2003. Evolution strategies assisted by Gaussian processes with1410improved preselection criterion. In *The 2003 Congress on Evolutionary Computation, 2003. CEC'03.*, Vol. 1. 692–699.
- 1411
 [207] François Vanderbeck and Laurence A Wolsey. 2010. Reformulation and decomposition of integer programs. In 50 Years of Integer Programming 1958-2008. 431–502.
- 1412[208] Joannes Vermorel and Mehryar Mohri. 2005. Multi-armed bandit algorithms and empirical evaluation. In European1413conference on machine learning. 437–448.
- 1414[209] Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. 2015. Pointer networks. In Advances in Neural Information1415Processing Systems. 2692–2700.
- [210] Christos Voudouris and Edward PK Tsang. 2003. Guided local search. In *Handbook of metaheuristics*. 185–218.
- [211] G Gary Wang and Songqing Shan. 2007. Review of metamodeling techniques in support of engineering design optimization. *Journal of Mechanical design* 129, 4 (2007), 370–380.
- 1418[212] Hui Wang, Hui Li, Yong Liu, Changhe Li, and Sanyou Zeng. 2007. Opposition-based particle swarm algorithm with1419Cauchy mutation. In 2007 IEEE Congress on Evolutionary Computation. 4750–4756.
- 1420
- 1421

00:30

- 1422[213] H. Wang, Z. Wu, S. Rahnamayan, Y. Liu, and M. Ventresca. 2011. Enhancing particle swarm optimization using1423generalized opposition-based learning. *Information Sciences* 181, 20 (2011), 4699–4714.
- 1424[214] Jing Wang. 2015. Enhanced differential evolution with generalised opposition-based learning and orientation1425neighbourhood mining. International Journal of Computing Science and Mathematics 6, 1 (2015), 49–58.
- [215] Bernd Waschneck, André Reichstaller, Lenz Belzner, Thomas Altenmüller, Thomas Bauernhansl, Alexander Knapp,
 and Andreas Kyek. 2018. Optimization of global production scheduling with deep reinforcement learning. *Procedia CIRP* 72 (2018), 1264–1269.
- 1428 [216] Christopher JCH Watkins and Peter Dayan. 1992. Q-learning. Machine learning 8, 3-4 (1992), 279-292.
- 1429 [217] William J. Welch and Matthias Schonlau. 1997. Computer experiments and global optimization.
- [218] Ue-Pyng Wen, Kuen-Ming Lan, and Hsu-Shih Shih. 2009. A review of Hopfield neural networks for solving mathematical programming problems. *European Journal of Operational Research* 198, 3 (2009), 675–687.
- [219] Martin Wistuba, Nicolas Schilling, and Lars Schmidt-Thieme. 2018. Scalable gaussian process-based transfer surrogates
 for hyperparameter optimization. *Machine Learning* 107, 1 (2018), 43–78.
- 1433[220] D. Wolpert and W. Macready. 1997. No free lunch theorems for optimization. IEEE transactions on evolutionary1434computation 1, 1 (1997), 67–82.
- 1435 [221] L. Xu, F. Hutter, H. Hoos, and K. Leyton-Brown. 2008. SATzilla: portfolio-based algorithm selection for SAT. Journal of artificial intelligence research 32 (2008), 565–606.
- [222] Yuehua Xu, David Stern, and Horst Samulowitz. 2009. Learning adaptation to solve constraint satisfaction problems.
 Proceedings of Learning and Intelligent Optimization (LION) (2009).
- 1438[223] T. Yalcinoz, B. J. Cory, and M. J. Short. 2001. Hopfield neural network approaches to economic dispatch problems. 231439(08 2001), 435-442.
- [224] Samaneh Yazdani and Jamshid Shanbehzadeh. 2015. Balanced Cartesian Genetic Programming via migration and opposition-based learning: application to symbolic regression. *Genetic Programming and Evolvable Machines* 16, 2 (2015), 133–150.
- [225] E. Yolcu and B. Poczos. 2019. Learning Local Search Heuristics for Boolean Satisfiability. In Advances in Neural Information Processing Systems. 7990–8001.
- [226] Si-Ho Yoo and Sung-Bae Cho. 2004. Partially evaluated genetic algorithm based on fuzzy c-means algorithm. In International Conference on Parallel Problem Solving from Nature. 440–449.
- [227] S. Yu, A. Aleti, J. C. Barca, and A. Song. 2018. Hyper-heuristic online learning for self-assembling swarm robots. In International Conference on Computational Science. 167–180.
- [228] Shiu Yin Yuen and Chi Kin Chow. 2009. A genetic algorithm that adaptively mutates and never revisits. *IEEE transactions on evolutionary computation* 13, 2 (2009), 454–472.
- [229] M. Zennaki and A. Ech-Cherif. 2010. A new machine learning based approach for tuning metaheuristics for the solution of hard combinatorial optimization problems. *Journal of Applied Sciences(Faisalabad)* 10, 18 (2010), 1991–2000.
- [230] Dawei Zhan, Yuansheng Cheng, and Jun Liu. 2017. Expected improvement matrix-based infill criteria for expensive multiobjective optimization. *IEEE Transactions on Evolutionary Computation* 21, 6 (2017), 956–975.
- 1452[231] H. Zhang and J. Lu. 2008. Adaptive evolutionary programming based on reinforcement learning. Information Sciences1453178, 4 (2008), 971–984.
- [232] J. Zhang, H. Chung, and W-L. Lo. 2007. Clustering-based adaptive crossover and mutation probabilities for genetic algorithms. *IEEE Transactions on Evolutionary Computation* 11, 3 (2007), 326–335.
- [233] Jianping Zhang, Yee-Sat Yim, and Junming Yang. 1997. Intelligent selection of instances for prediction functions in lazy learning algorithms. In *Lazy learning*. 175–191.
- [234] Jun Zhang, Zhi-hui Zhan, Ying Lin, Ni Chen, Yue-jiao Gong, Jing-hui Zhong, Henry SH Chung, Yun Li, and Yu-hui
 Shi. 2011. Evolutionary computation meets machine learning: A survey. *IEEE Computational Intelligence Magazine* 6, 4 (2011), 68–75.
- [235] Ke-Shi Zhang, Zhong-Hua Han, Zhong-Jian Gao, and Yuan Wang. 2019. Constraint aggregation for large number of constraints in wing surrogate-based optimization. *Structural and Multidisciplinary Optimization* 59, 2 (2019), 421–438.
- [236] Wei Zhang and Thomas G Dietterich. 1995. A reinforcement learning approach to job-shop scheduling. In *IJCAI*,
 Vol. 95. 1114–1120.
- [237] Zongzhao Zhou, Yew Ong, My Hanh Nguyen, and Dudy Lim. 2005. A study on polynomial regression and Gaussian
 Process global surrogate model in hierarchical surrogate-assisted evolutionary algorithm. 2005 IEEE Congress on Evolutionary Computation, IEEE CEC 2005. Proceedings 3, 2832 – 2839 Vol. 3.
- 1466
- 1467
- 1468
- 1469
- 1470