

University of Wollongong
Research Online

University of Wollongong Thesis Collection
1954-2016

University of Wollongong Thesis Collections

2004

Boundary element formulations for fracture mechanics problems

Wei-Liang Wu
University of Wollongong

Follow this and additional works at: <https://ro.uow.edu.au/theses>

University of Wollongong

Copyright Warning

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site.

You are reminded of the following: This work is copyright. Apart from any use permitted under the Copyright Act 1968, no part of this work may be reproduced by any process, nor may any other exclusive right be exercised, without the permission of the author. Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material.

Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

Unless otherwise indicated, the views expressed in this thesis are those of the author and do not necessarily represent the views of the University of Wollongong.

Recommended Citation

Wu, Wei-Liang, Boundary element formulations for fracture mechanics problems, PhD thesis, School of Mathematics and Applied Statistics, University of Wollongong, 2004. <http://ro.uow.edu.au/theses/253>

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

NOTE

This online version of the thesis may have different page formatting and pagination from the paper copy held in the University of Wollongong Library.

UNIVERSITY OF WOLLONGONG

COPYRIGHT WARNING

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site. You are reminded of the following:

Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material. Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

BOUNDARY ELEMENT FORMULATIONS FOR
FRACTURE MECHANICS PROBLEMS

By
Wei-Liang Wu

SUBMITTED IN PARTIAL FULFILLMENT OF THE
REQUIREMENTS FOR THE DEGREE OF
DOCTOR OF PHILOSOPHY
AT
UNIVERSITY OF WOLLONGONG
NORTHFIELDS AVENUE, WOLLONGONG NSW 2522
AUSTRALIA
NOVEMBER 2004

UNIVERSITY OF WOLLONGONG
SCHOOL OF
MATHEMATICS AND APPLIED STATICS

This thesis is submitted to the University of Wollongong, and has not been submitted for a higher degree to any other university or institution.

Wei-Liang Wu

November 2004

UNIVERSITY OF WOLLONGONG

Date: **November 2004**

Author: **Wei-Liang Wu**
Title: **Boundary Element Formulations for Fracture
Mechanics Problems**
School: **Mathematics and Applied Statics**
Degree: **Ph.D.**

Permission is herewith granted to University of Wollongong to circulate and to have copied for non-commercial purposes, at its discretion, the above title upon the request of individuals or institutions.

Signature of Author

THE AUTHOR RESERVES OTHER PUBLICATION RIGHTS, AND NEITHER THE THESIS NOR EXTENSIVE EXTRACTS FROM IT MAY BE PRINTED OR OTHERWISE REPRODUCED WITHOUT THE AUTHOR'S WRITTEN PERMISSION.

THE AUTHOR ATTESTS THAT PERMISSION HAS BEEN OBTAINED FOR THE USE OF ANY COPYRIGHTED MATERIAL APPEARING IN THIS THESIS (OTHER THAN BRIEF EXCERPTS REQUIRING ONLY PROPER ACKNOWLEDGEMENT IN SCHOLARLY WRITING) AND THAT ALL SUCH USE IS CLEARLY ACKNOWLEDGED.

To My Parents with Love and Gratitude.

Acknowledgements

I would like to acknowledge the many people who have helped me in my life and who helped bring this thesis to fruition.

In particular, I want to thank my supervisor, Dr. Xiaoping Lu who had constantly been a source of knowledge and expertise on mathematical techniques which have been utilised in this thesis. I thank her for her constant support, encouragement and her willingness to help at any time despite her hectic schedule.

Above all, I want to thank my teachers – both in Taiwan and Australia. To those who helped me learn in the classroom. To those who helped me learn in the world beyond the classroom.

I would also like to thank the colleagues of the University of Wollongong who devoted time and effort to provide me with critical feedback on earlier drafts, pointing inaccuracies, suggesting better examples, and gently noting things that needed smoothing. I would like to mention especially Dr. Ahmed A. El-Feki, Dr. Anna Maria Milan, Dr. Bin Liu and Frank Bierbrauer.

In addition, my deepest thanks are owed to my family who have always inspired me to greater things particularly my parents for their love, sacrifice and support.

Table of Contents

Acknowledgements	v
List of Tables	ix
List of Figures	x
1 Introduction	1
1.1 General Considerations	1
1.2 Modes of Crack Tip Deformation	4
1.3 Other Fracture Characterising Parameters	6
1.3.1 The J -integral	6
1.3.2 The Crack Tip Opening Displacement	7
1.4 Numerical Methods in Linear Elastic Fracture Mechanics	8
1.4.1 Finite Difference Method	8
1.4.2 Finite Element Method	8
1.4.3 Boundary Element Method	9
1.5 Advanced Formulations in Boundary Element Method	11
1.5.1 Dual Boundary Element Method	11
1.5.2 Subregion Boundary Element Method	12
1.5.3 Dual Reciprocity Boundary Element Method	13
2 Dual Boundary Integral Formulation for Two Dimensional Crack Problems	15
2.1 Introduction	16
2.2 The Dual Boundary Integral Formulation	18
2.3 Stress Intensity Factor Calculation	22
2.4 Numerical Examples	23
2.5 Conclusion	42

3	An Efficient Dual Boundary Element Method for Crack Problems with Anti-plane Shear Loading	43
3.1	Introduction	44
3.2	The Dual Boundary Integral Equation for Anti-plane Problems	46
3.3	Calculation of the Mode III Stress Intensity Factor	49
3.4	Numerical Examples	50
3.5	Conclusions	59
4	The Evaluation of Stress Intensity Factors	60
4.1	Introduction	60
4.2	The Numerical Evaluation of Stress Intensity Factors	63
4.2.1	J-integral	64
4.2.2	The Discontinuous Quarter Point Element Method	66
4.2.3	The Special Crack Tip Element Method	69
4.3	Numerical Examples	70
4.3.1	A Plate with a Central Slant Crack	71
4.3.2	Infinite Plate with Two Inclined Cracks	77
4.3.3	Infinite Plate with Two Parallel Cracks	82
4.4	Conclusion	86
5	A New Subregion Boundary Element Technique	87
5.1	Introduction	88
5.2	The Multi Region Technique of Boundary Element Method	91
5.3	Comparison of Subregion BEM Techniques	94
5.3.1	The Traditional Method	94
5.3.2	Kita & Kamiya's Method	94
5.3.3	The Proposed Method	96
5.4	Numerical Results	100
5.5	Conclusion	108
6	A Subregion DRBEM Formulation for the Dynamic Analysis of Two Dimensional Cracks	109
6.1	Introduction	110
6.2	Dual Reciprocity Boundary Element Method	113
6.3	Derivation of Particular Solutions	118
6.4	The Dynamic Stress Intensity Factors	119
6.5	Numerical Examples	120
6.5.1	A Rectangular Plate with a Central Crack	121

6.5.2	A Rectangular Plate with a Central Slant Crack	123
6.5.3	A Rectangular Plate with an Internal Kinked Crack	126
6.6	Conclusion	131
7	Conclusion	132
	Bibliography	135

List of Tables

2.1	Mode I SIF for an internal kinked crack in a rectangular plate	29
2.2	Mode II SIF for an internal kinked crack in a rectangular plate	29
2.3	Comparison of normalised stress intensity factors	35
3.1	Normalised mode III stress intensity factor for a straight central crack	52

List of Figures

1.1	The three modes of loading	4
1.2	Definition of the coordinate axis ahead of a crack tip	5
1.3	Stress normal to the crack plane in mode I	6
2.1	Rectangular plate with a central slant crack ($h/w = 2, \theta = 45^\circ$)	23
2.2	Normalised mode I SIF for the rectangular plate with a central slant crack: (a) the present method, (b) Reference [80], and (c) Reference [73]	24
2.3	Normalised mode II SIF for the rectangular plate with a central slant crack: (a) the present method, (b) Reference [80], and (c) Reference [73]	25
2.4	Normalised mode I SIF for the rectangular plate with a central slant crack ($a/w = 0.1$): (a) the present method, and (b) Reference [73]	26
2.5	Normalised mode II SIF for the rectangular plate with a central slant crack ($a/w = 0.1$): (a) the present method, and (b) Reference [73]	27
2.6	Rectangular plate with an internal kinked crack ($h/w = 2, a/w = 0.1$)	28
2.7	Normalised mode I SIF vs. crack ratio b/a at tip A . The angle of the kinked crack is (a) 30° , (b) 45° , (c) 60°	30
2.8	Normalised mode II SIF vs. crack ratio b/a at tip A . The angle of the kinked crack is (a) 30° , (b) 45° , (c) 60°	31
2.9	Normalised mode I SIF vs. crack ratio b/a at tip B . The angle of the kinked crack is (a) 30° , (b) 45° , (c) 60°	32
2.10	Normalised mode II SIF vs. crack ratio b/a at tip B . The angle of the kinked crack is (a) 30° , (b) 45° , (c) 60°	33
2.11	Rectangular plate with two inclined cracks ($h/w = 2, a/W = 0.25$) . .	34
2.12	Normalised mode I SIF vs. inclined angle θ : (a) Finite region (b) Infinite region at tip A , and (c) Finite region (d) Infinite region at tip B	36

2.13	Normalised mode II SIF vs. inclined angle θ : (a) Finite region (b) Infinite region at tip A , and (c) Finite region (d) Infinite region at tip B	37
2.14	Rectangular plate with two parallel cracks ($h/w = 2, a/w = 0.025$) . . .	38
2.15	Normalised mode I SIF for the rectangular plate with two parallel cracks: (a) the present method, and (b) Reference [93]	39
2.16	Normalised mode I SIF vs. s , with a/w given by (a) 0.025, (b) 0.05, (c) 0.1, (d) 0.2	40
2.17	Normalised mode II SIF vs. s , with a/w given by (a) 0.025, (b) 0.05, (c) 0.1, (d) 0.2	41
3.1	Rectangular plate with a central slant crack	51
3.2	Normalised mode III stress intensity factor (SIF) for the rectangular plate with a central slant crack (a) $\theta = 30^\circ$, (b) $\theta = 45^\circ$, and (c) $\theta = 60^\circ$	53
3.3	Normalised mode III SIF for the infinite plate with a central slant crack (a) the analytical solutions, and (b) the present method	54
3.4	A finite plate with two collinear cracks	55
3.5	Normalised mode III SIF for the rectangular plate with two identical collinear cracks at tip A : (a) the analytical results, (b) the present method and at tip B : (c) the analytical solutions, (d) the present method	56
3.6	A finite plate with two parallel cracks	57
3.7	Normalised mode III SIF for the rectangular plate with two parallel cracks (a) Reference [93] (b) the present method	58
4.1	Crack in an infinite plane	61
4.2	General continuous quadratic element	63
4.3	Coordinate reference system and contour path for J -integral	64
4.4	Singular quarter-point boundary elements	66
4.5	Modeling of the quarter point boundary element	68
4.6	Relative error of Mode I SIF for the infinite plate with a central slant crack from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	72
4.7	Relative error of Mode II SIF for the infinite plate with a central slant crack from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	73

4.8	Relative error of Mode <i>III</i> SIF for the infinite plate with a central slant crack from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	74
4.9	Mode <i>I</i> SIF of the finite plate with a central slant crack from the QPE with $\frac{a}{w} =$ (a) $\frac{2}{3}$, (b) $\frac{1}{2}$, (c) $\frac{1}{5}$ and the SCT with (d) $\frac{2}{3}$, (e) $\frac{1}{2}$, (f) $\frac{1}{5}$. . .	75
4.10	Mode <i>II</i> SIF of the finite plate with a central slant crack from the QPE with $\frac{a}{w} =$ (a) $\frac{2}{3}$, (b) $\frac{1}{2}$, (c) $\frac{1}{5}$ and the SCT with (d) $\frac{2}{3}$, (e) $\frac{1}{2}$, (f) $\frac{1}{5}$	76
4.11	Relative error of Mode <i>I</i> SIF for the infinite plate with two inclined cracks at tip <i>A</i> from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	78
4.12	Relative error of Mode <i>I</i> SIF for the infinite plate with two inclined cracks at tip <i>B</i> from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	79
4.13	Relative error of Mode <i>III</i> SIF for the infinite plate with two inclined cracks at tip <i>A</i> from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	80
4.14	Relative error of Mode <i>III</i> SIF for the infinite plate with two inclined cracks at tip <i>B</i> from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	81
4.15	Mode <i>I</i> SIF for the infinite plate with two parallel cracks from (a) the Reference [93], the QPE with (b) 6 elements, (c) 8 elements, (d) 10 elements and the SCT with (e) 6 elements, (f) 8 elements, and (g) 10 elements	83
4.16	Mode <i>II</i> SIF for the infinite plate with two parallel cracks from the QPE with (a) 6 elements, (b) 8 elements, (c) 10 elements and the SCT with (d) 6 elements, (e) 8 elements, and (f) 10 elements	84
4.17	Mode <i>III</i> SIF for the infinite plate with two parallel cracks from (a) the Reference [93], the QPE with (b) 6 elements, (c) 8 elements, (d) 10 elements and the SCT with (e) 6 elements, (f) 8 elements, and (g) 10 elements	85

5.1	A three subregion medium	92
5.2	A perfectly bonded dissimilar elastic semi-strip	101
5.3	Normalised normal stress distribution on the interface $(E_2/E_1, \nu_1, \nu_2) = (9.0, 0.5, 0.5)$: (a) Ref. [17], (b) the present method $(E_2/E_1, \nu_1, \nu_2) = (3.0, 0.5, 0.5)$: (c) Ref. [17], (d) the present method	102
5.4	A three-layer plate with a centre crack	103
5.5	Normalised mode I stress intensity factor (SIF) on the three-layer plate with a centre crack: (a) $l/h_2 = 0.1$, (b) $l/h_2 = 0.2$, (c) $l/h_2 = 0.3$, (d) $l/h_2 = 0.4$, (e) $l/h_2 = 0.5$	104
5.6	A three-layer plate with two identical co-linear cracks	105
5.7	Normalised mode I SIF at tip A on the three-layer plate with two co-linear cracks: (a) $l/h_2 = 0.1$, (b) $l/h_2 = 0.2$, (c) $l/h_2 = 0.3$, (d) $l/h_2 = 0.4$, (e) $l/h_2 = 0.5$	106
5.8	Normalised mode I SIF at tip B on the three-layer plate with two co-linear cracks: (a) $l/h_2 = 0.1$, (b) $l/h_2 = 0.2$, (c) $l/h_2 = 0.3$, (d) $l/h_2 = 0.4$, (e) $l/h_2 = 0.5$	107
6.1	Boundary and internal nodes	114
6.2	Crack on the body for subregion method	118
6.3	Rectangular plate with a central crack	121
6.4	Normalised mode I DSIF for the rectangular plate with a central crack (a) the present method, (b) the dual reciprocity method [6] and (c) the Laplace transform method [6]	122
6.5	Rectangular plate with a central slant crack	123
6.6	Normalised mode I DSIF for the rectangular plate with a central slant crack (a) the present method, (b) the dual reciprocity method [6] and (c) the Laplace transform method [6]	124
6.7	Normalised mode II DSIF for the rectangular plate with a central slant crack (a) the present method, (b) the dual reciprocity method [6] and (c) the Laplace transform method [6]	125
6.8	Rectangular plate with an internal kinked crack	126
6.9	Normalised mode I DSIF for the rectangular plate with an internal kinked crack at tip A (a) $b/a = 0.2$, (b) $b/a = 0.4$, and (c) $b/a = 0.6$	128
6.10	Normalised mode I DSIF for the rectangular plate with an internal kinked crack at tip B (a) $b/a = 0.2$, (b) $b/a = 0.4$, and (c) $b/a = 0.6$	129

6.11 Normalised mode II DSIF for the rectangular plate with an internal kinked crack at tip B (a) $b/a = 0.2$, (b) $b/a = 0.4$, and (c) $b/a = 0.6$. 130