

2010

Medical image retrieval with query-dependent feature fusion based on one-class SVM

Yonggang Huang
BeiHang University

Jun Zhang
University of Wollongong

Yongwang Zhao
BeiHang University

Dianfu Ma
BeiHang University

Follow this and additional works at: <https://ro.uow.edu.au/infopapers>



Part of the [Physical Sciences and Mathematics Commons](#)

Recommended Citation

Huang, Yonggang; Zhang, Jun; Zhao, Yongwang; and Ma, Dianfu: Medical image retrieval with query-dependent feature fusion based on one-class SVM 2010.
<https://ro.uow.edu.au/infopapers/3561>

Medical image retrieval with query-dependent feature fusion based on one-class SVM

Abstract

Due to the huge growth of the World Wide Web, medical images are now available in large numbers in online repositories, and there exists the need to retrieval the images through automatically extracting visual information of the medical images, which is commonly known as content-based image retrieval (CBIR). Since each feature extracted from images just characterizes certain aspect of image content, multiple features are necessarily employed to improve the retrieval performance. Meanwhile, experiments demonstrate that a special feature is not equally important for different image queries. Most of existed feature fusion methods for image retrieval only utilize query independent feature fusion or rely on explicit user weighting. In this paper, we present a novel query dependent feature fusion method for medical image retrieval based on one class support vector machine. Having considered that a special feature is not equally important for different image queries, the proposed query dependent feature fusion method can learn different feature fusion models for different image queries only based on multiply image samples provided by the user, and the learned feature fusion models can reflect the different importances of a special feature for different image queries. The experimental results on the IRMA medical image collection demonstrate that the proposed method can improve the retrieval performance effectively and can outperform existed feature fusion methods for image retrieval.

Disciplines

Physical Sciences and Mathematics

Publication Details

Huang, Y., Zhang, J., Zhao, Y. & Ma, D. (2010). Medical image retrieval with query-dependent feature fusion based on one-class SVM. 2010 13th IEEE International Conference on Computational Science and Engineering (pp. 176-183). IEEE.

Medical Image Retrieval with Query-Dependent Feature Fusion based on One-Class SVM

Yonggang Huang^{1,2}, Jun Zhang³, Yongwang Zhao^{1,2}, Dianfu Ma^{1,2}

¹Institute of Advanced Computing Technology, BeiHang University

²National Lab of Software Development Environment, BeiHang University

³School of Computer Science and Software Engineering, University of Wollongong
yonggang.h@gmail.com, zhaoyw@act.buaa.edu.cn

Abstract—Due to the huge growth of the World Wide Web, medical images are now available in large numbers in online repositories, and there exists the need to retrieval the images through automatically extracting visual information of the medical images, which is commonly known as content-based image retrieval (CBIR). Since each feature extracted from images just characterizes certain aspect of image content, multiple features are necessarily employed to improve the retrieval performance. Meanwhile, experiments demonstrate that a special feature is not equally important for different image queries. Most of existed feature fusion methods for image retrieval only utilize query independent feature fusion or rely on explicit user weighting. In this paper, we present a novel query dependent feature fusion method for medical image retrieval based on one class support vector machine. Having considered that a special feature is not equally important for different image queries, the proposed query dependent feature fusion method can learn different feature fusion models for different image queries only based on multiply image samples provided by the user, and the learned feature fusion models can reflect the different importances of a special feature for different image queries. The experimental results on the IRMA medical image collection demonstrate that the proposed method can improve the retrieval performance effectively and can outperform existed feature fusion methods for image retrieval.

I. INTRODUCTION

In the medical field, with the rapid advances in imaging technology, medical image are produced in ever-increasing quantities by hospitals, pharmaceutical companies, and academic medical research centre. These images of various modalities are playing an important role in detecting the anatomical and functional information about different body parts for the diagnosis, medical research, and education. Currently, many hospitals and radiology departments are equipped with Picture Archiving and Communications Systems (PACS) [1]. The images are commonly stored, retrieved and transmitted in the DICOM (Digital Imaging and Communication in Medicine) [2] format. The search for images is carried out according to the textual attributes of image headers (such as study, patient) and usually has many limitations.

Due to the huge growth of the World Wide Web, medical images are now available in large numbers in online repositories, atlases, and other health related resources [3]. In such a web-based environment, medical images are generally stored and accessed in common formats such as JPEG (Joint Photographic Experts Group), GIF (Graphics Interchange For-

mat), etc. These formats are used because they are easy to store and transmit compared to the large size of images in DICOM format [4], but also for anonymization purposes [3]. However, there is no header information attached to the images with these image formats other than DICOM format. In this case, the text-based approach is both expensive and ambiguous due to the fact that manually annotating these images are extremely time-consuming, highly subjective and requires domain-related knowledge. The content-based image retrieval (CBIR) [5] systems overcome these limitations since they are capable of carrying out a search for images based on the modality, anatomic region and different acquisition views [3] through automatically extracting visual information of the medical images. Currently, there exist some CBIR systems on medical image such as MedGIFT [3], COBRA [6], IRMA [1] and KmED [7].

The CBIR extract the low level visual features such as color, texture, or spatial location automatically and the images are retrieved based on the these low level visual features. Experiments [8] demonstrate that the image retrieval performance can be enhanced when employing multiple features, since each feature extracted from images just characterizes certain aspect of image content and multiple features can provide an adequate description of image content. Further experiments [9] [10] also show that a special feature is not equally important for different image queries since a special feature has different importances in reflecting the content of different images. Although some research efforts have been reported to enhance the image retrieval performance taking the feature fusion approaches, most of existed feature fusion methods for image retrieval only utilize query independent feature fusion which usually apply a single feature fusion model for all the image queries and do not consider that a special feature is not equally important for different image queries, the others usually require the users to tune appropriate parameters for the feature fusion models for different image queries.

Motivated by this observation, in this paper, with multiply image examples provided by the user, we propose a new query dependent feature fusion method for medical image retrieval based one-class support vector machines. The query dependent feature fusion problem was formulated as a one class classification problem in our work and we solved it

with one-class support vector machines because of its good generalization ability. Having considered that a special feature is not equally important for different image queries, the proposed query dependent feature fusion method for medical image retrieval can learn different feature fusion models for different image queries only based on multiply image samples provided by the user, and the learned feature fusion models can reflect the different importances of a special feature for different queries .

The remaining of the paper is organized as follows. Next section discusses some related work. In Section III , we give the formal definition of the query dependent feature fusion problem as one class classification problem. In Section IV, the one class support vector machine based query dependent feature fusion (*OSVM-QDFF*) approach is presented to solve the specific one class classification problem defined in Section III. Section IV discusses the low-level feature extraction processes for the medical image retrieval. The comparison experiments and the analysis of the results are presented in section V, and finally section VI provides our conclusion.

II. RELATED WORK

Since the image retrieval performance can be enhanced when employing multiple features, some research efforts have been reported to enhance the image retrieval performances taking the feature fusion approaches.

There are two main approaches to address the feature fusion problem for image retrieval [11]. One is called as *early fusion*, which perform the feature fusion by stacking the descriptor values as a single, large vector and the images is ranked by calculating the distances between these large vectors in a high dimensional feature space [12]. The *early fusion* approach usually suffers from the dimensionality arising [11]. The other is called as *late fusion*, which obtains image similarity through combining multiple feature similarities. Compared to the *early fusion* approach, the *late fusion* approach alleviates the dimensionality arising and different similarity measures can be used for different features [13]. Since these merits of the *late fusion* approach, the recently research works usually adopt *late fusion* approach for image retrieval.

In [14], the CombSumScore, CombMaxScore, CombSumRank, CombMaxRank fusion models are used to fuse the multiple similarities obtained with multi-feature multi-example queries, which treat different features equally for all the queries and can be called as average fusion models. Obviously, the average fusion models are not optimal as different features usually have different retrieval performances. In literate [15], the genetic algorithm is used to learn the best weights for different features, and then the learned feature fusion model is applied for all the image queries. In literate [16], different features are assigned with different weights according to the average retrieval precision of these features, and then the adjusted feature fusion model is applied for all the image queries. The feature fusion methods presented in [15] and [16] can enhance the retrieval performance to some extent as the different retrieval performances of different features are

considered. However, firstly, a certain amount of training data is needed in [15] and [16], secondly, the learned fusion models are not optimal for each image query as a special feature is not equally importance for different image queries. In summary, all these feature fusion methods for image retrieval apply a single feature fusion model for all the image queries and do not consider that a special feature is not equally important for different image queries.

In [17] and [18], the combined similarity between images is measured using one of the features selected by a feature fusion model expressed with logic operation based on Boolean model. To overcome the limitation of traditional Boolean model, [12] introduced a hierarchical decision fusion framework formulated based on fuzzy logic to extend AND and OR operations in Boolean logic. In [17] [18] [12], the feature fusion models for different image queries are presented with logic-based expressions and usually require the users to tune appropriate parameters for the fusion models, which could only be successful in specific field (for example, the art image [12]) since they require the user having a good understanding of the low level feature of the query images.

In literate [10], the author proposed a query dependent feature fusion method for image retrieval (which is called as local aggregation function in [10]) based on support vector machine (*LSVMC*). Regarding the multiply image examples provided by the user as positive examples and the randomly selected image examples from the image collection as negative examples, the author in [10] formulate the query dependent feature fusion problem as a strict two class classification problem and solved it by support vector machines, with equal treatments on both positive and negative examples. However, the strict two class classification based approach is not always reasonable since the negative examples randomly selected from the image collection can belong to any class and they usually do not cluster.

III. PROBLEM DEFINITION FOR THE QUERY-DEPENDENT FEATURE FUSION

In this section, we investigate the query dependent feature fusion problem for the query by example search paradigm when the user provides multiply example images as a query, and we formulate the query dependent feature fusion problem as a one class classification problem.

Let us consider an medical image collection $\Omega = \{I_1, \dots, I_i, \dots, I_N\}$ which contains N images that we are interested in retrieval. Suppose m low level feature descriptors are available $F = \{f_1, \dots, f_i, \dots, f_m\}$. The low level feature representation for image I with the feature descriptors set F can be denotes as

$$F^I = \{f_1^I, \dots, f_i^I, \dots, f_m^I\} \quad (1)$$

where f_i^I denotes the feature vector for image I using the feature descriptor f_i , and F^I denotes the feature vectors set for image I .

Let $D_i(.,.)$ denotes the distance metric for the i_{th} feature descriptor f_i , thus the distance between image I and image J

when using the i_{th} feature descriptor f_i can be represented as

$$d_i(I, J) = D_i(f_i^I, f_i^J) \quad (2)$$

Suppose the user provides multiply image examples as a query $Q = \{Q_1, \dots, Q_i, \dots, Q_q\}$. The combined image collection of the query and the image collection that we are interested in retrieval can be represented as

$$\Omega' = Q \cup \Omega \quad (3)$$

Given a image example Q_i in the query Q , the distances to each image in the image collection Ω' using the feature descriptor f_i can be represented as.

$$D_j(Q_i) = \{d_j(Q_i, Q_1), \dots, d_j(Q_i, Q_q), d_j(Q_i, I_1), \dots, d_j(Q_i, I_N)\} \quad (4)$$

where $D_j(Q_i)$ denotes the distances set for example image Q_i on image set Ω' with the feature descriptor f_j . In order to make the distances obtained with different feature descriptor be comparable, the distances with feature descriptor f_j are normalized as

$$\bar{d}_j = \frac{d_j - d_j^{min}}{d_j^{max} - d_j^{min}} \quad (5)$$

where d_j^{max} and d_j^{min} denotes the maximum and minimum distance in the distances set $D_j(Q_i)$. The normalized distances can be converted to the similarity as

$$s_j = 1 - \bar{d}_j \quad (6)$$

The similarities between the image example Q_i and the image I'_i in image collection Ω' with m different feature descriptors can be represent as a similarities vector

$$S(Q_i, I'_j) = (s_1(Q_i, I'_j), \dots, s_m(Q_i, I'_j)) \quad (7)$$

and the similarities between the example image Q_i and all the images in image collection Ω' can be represented as a similarity space $\varphi(Q_i)$ with the size of $(N+q) \times m$

$$\begin{bmatrix} s_1(Q_i, I'_1) & \dots & s_i(Q_i, I'_1) & \dots & s_m(Q_i, I'_1) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_i, I'_j) & \dots & s_i(Q_i, I'_j) & \dots & s_m(Q_i, I'_j) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_i, I'_{N+q}) & \dots & s_i(Q_i, I'_{N+q}) & \dots & s_m(Q_i, I'_{N+q}) \end{bmatrix} \quad (8)$$

By considering a linear fusion solution, the combined similarity between the image example Q_i and the image I'_j in Ω' can be represented as.

$$Sim(Q_i, I'_j) = S(Q_i, I'_j) \cdot \mathbf{w}^T \quad (9)$$

where $\mathbf{w} = (w_1, \dots, w_m)$ is feature weight vector and w_i denotes the weight assigned for feature f_i which reflect the feature importance for the query with the query set Q .

Suppose that the relevant image set for the query Q is Θ . Thus the optimal *Query-Dependent* feature fusion for the example image Q_i is to find appropriate feature weight vector $\mathbf{w} = (w_1, \dots, w_m)$ that can separate the relevant image set

Θ from the image collection Ω' in the similarity space $\varphi(Q_i)$ as

$$\begin{cases} Sim(Q_i, I'_j) = \mathbf{w} \cdot S(Q_i, I'_j) > \rho & \text{if } I'_j \in \Theta \\ Sim(Q_i, I'_j) = \mathbf{w} \cdot S(Q_i, I'_j) < \rho & \text{if } I'_j \notin \Theta \end{cases} \quad (10)$$

where ρ is the similarity threshold to separate the relevant image set Θ from the image collection Ω' .

Since each image example Q_i in query Q expresses the users' retrieval purpose equally and the feature fusion model for all the image examples Q_i in query Q should be the same (which is also the feature fusion model for the query Q). Therefore the optimal *Query-Dependent* feature fusion for the query Q is to find appropriate feature weight vector $\mathbf{w} = (w_1, \dots, w_m)$ that can separate the relevant image set Θ from the image collection Ω' in the similarity spaces $\varphi(Q_1), \dots, \varphi(Q_q)$ as

$$\begin{cases} Sim(Q_i, I'_j) = \mathbf{w} \cdot S(Q_i, I'_j) > \rho & \text{if } I'_j \in \Theta \quad i = 1, 2, \dots, q \\ Sim(Q_i, I'_j) = \mathbf{w} \cdot S(Q_i, I'_j) < \rho & \text{if } I'_j \notin \Theta \quad i = 1, 2, \dots, q \end{cases} \quad (11)$$

which is equally to find appropriate feature weight vector $\mathbf{w} = (w_1, \dots, w_m)$ that can separate the relevant image set Θ from the image collection Ω' in the combined similarity space φ as

$$\begin{bmatrix} s_1(Q_1, I'_1) & \dots & s_i(Q_1, I'_1) & \dots & s_m(Q_1, I'_1) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_1, I'_j) & \dots & s_i(Q_1, I'_j) & \dots & s_m(Q_1, I'_j) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_1, I'_{N+q}) & \dots & s_i(Q_1, I'_{N+q}) & \dots & s_m(Q_1, I'_{N+q}) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_q, I'_1) & \dots & s_i(Q_q, I'_1) & \dots & s_m(Q_q, I'_1) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_q, I'_j) & \dots & s_i(Q_q, I'_j) & \dots & s_m(Q_q, I'_j) \\ \dots & \dots & \dots & \dots & \dots \\ s_1(Q_q, I'_{N+q}) & \dots & s_i(Q_q, I'_{N+q}) & \dots & s_m(Q_q, I'_{N+q}) \end{bmatrix} \quad (12)$$

Notice that each image in image collection Ω' is represented with q similarities vectors, each of which represents the similarities to one example image in Q with m different feature descriptors. The combined similarity space φ can be obtained by simply combing the similarities spaces

$$\varphi = \varphi(Q_1) \cup \dots \cup \varphi(Q_q) \quad (13)$$

Consider that the size of Θ is much smaller compared to the size of the image collection Ω' as

$$|\Theta| \ll |\Omega'| \quad (14)$$

Thus the query dependent feature fusion problem for the query Q can be regards as a typical one class classification problem in the combined similarity space φ with the training

data as

$$\left\{ (Sim(Q_i, I'_j), L_{ij}) \mid 1 \leq j \leq (N+q), 1 \leq i \leq q \right\} \text{ and}$$

$$L_{ij} = \begin{cases} 1 & I'_j \in Q \\ 0 & I'_j \notin Q \end{cases} \quad (15)$$

where 1 indicates a positive sample and 0 indicates an unlabeled sample, since the example images in the query Q are relevant to the query Q .

Treating the example image in the query Q equally, the similarities between the image I'_i in Ω' and the query Q can be computed as

$$S(Q, I'_j) = \sum_{i=1}^q S(Q_i, I'_j) \quad (16)$$

and the combined similarities between the query Q and the images in Ω' can be obtained as

$$Sim(Q, \Omega') = \begin{bmatrix} Sim(Q, I'_1) \\ \dots \\ Sim(Q, I'_j) \\ \dots \\ Sim(Q, I'_{N+q}) \end{bmatrix} = \sum_{i=1}^q \varphi(Q_i) \cdot \mathbf{w}^T \quad (17)$$

In summary, the query dependent feature fusion problem for the query Q is to find appropriate feature weight vector $\mathbf{w} = (w_1, \dots, w_m)$ for formulation 17 through solving the one class classification problem defined in formulation 11 and 15.

IV. ONE CLASS SUPPORT VECTOR MACHINE BASED Query-Dependent FEATURE FUSION (OSVM-QDFF)

In section III, the query dependent feature fusion problem has been formulated as a one class classification problem in the combined similarity space φ . In this section, the One-class support vector machine (One-Class SVM) [19] is selected to solve the specific one class classification problem because of the good generalization ability. The algorithm is named One-class SVM since only positive examples are used in training and testing.

Considering a linear one classification problem in the combined similarity space φ with the positive examples φ^+

$$\varphi^+ = \{s_1, s_2, \dots, s_l\} \subset \varphi \quad (18)$$

where $l = p * p$ indicates the number of the positive examples in the combined similarity space. The goal of training of a linear One-Class SVM is to find a separating hyperplane in the combined similarity space

$$f(s) = \mathbf{w} \cdot s - \rho \quad (19)$$

where \mathbf{w} is the adaptive feature weight vector in this paper. The separating hyperplane stratifies that it is closer to the origin than all the examples in φ^+ as

$$f(s_i) > 0, \quad i = 1, 2, \dots, t \quad (20)$$




Fig. 1: The goal of training of a linear One-Class SVM is to find a separating hyperplane in the combined similarity space with the largest margin

and with the largest margin to the origin in such hyperplanes as Fig.1 presents.

$$\max \frac{\rho}{\|\mathbf{w}\|} \quad (21)$$

By properly chosen nonlinear function ϕ , the combined similarities space can be mapped to a high dimensional feature space F to get a potentially better representation of the data point and achieve a better classification as

$$\phi: \varphi \rightarrow F \quad (22)$$

and the output of the nonlinear One-Class SVM is a separating hyperplane in the high dimensional feature space F with the largest margin to the origin $\frac{\rho}{\|\mathbf{w}\|}$ and satisfy $f(s_i) > 0$ for all the positive examples s_i in φ^+ as

$$f(s) = \mathbf{w} \cdot \phi(s) - \rho \quad (23)$$

The linear One-Class SVM can be regarded as a typical nonlinear One-Class SVM with the mapping function

$$\phi(s) = s \quad (24)$$

With the training data $\phi(s_1), \phi(s_2), \dots, \phi(s_l)$, the optimal hyperplane \mathbf{w} can be found by solving the following quadratic programming problem [19]

$$\begin{cases} \min & \frac{1}{2} \|\mathbf{w}\|^2 - \rho \\ \text{s.t.} & \mathbf{w} \cdot \phi(s_i) \geq \rho \quad i = 1, 2, \dots, t \end{cases} \quad (25)$$

Considering that the sample points in F are not always linearly separable and it is too difficult to find a canonical hyperplane quickly in this case. There may be no hyperplane that separates φ^+ from φ in F . Therefore, the slack parameters, denoted by $\xi_i \geq 0$, is associated with each training samples. It allows for some training samples to be within the margin. The optimization is to find maximize margin and at the same time to minimize the average slack.

$$\begin{cases} \min & \frac{1}{2} \|\mathbf{w}\|^2 - \rho + \frac{1}{\nu l} \sum_{i=1}^l \xi_i \\ \text{s.t.} & \mathbf{w} \cdot s_i \geq \rho - \xi_i, \quad \xi_i \geq 0, \quad i = 1, 2, \dots, t \end{cases} \quad (26)$$

where ξ_i are slack variables, l is the number of training samples, and $\nu \in (0, 1]$ is a parameter that controls the

trade-off between maximizing the distance from the origin and separating most of the relevant samples. After introducing Lagrange multipliers α_i for each training samples, the dual problem of the optimization problem can be obtained as

$$\begin{cases} \max & \frac{1}{2} \sum_{i,j=1}^l \alpha_i \alpha_j \phi(s_i) \cdot \phi(s_j) \\ \text{s.t.} & 0 \leq \alpha_i \leq \frac{1}{\nu l} \\ & \sum_{i=1}^l \alpha_i = 1 \end{cases} \quad (27)$$

Solving the dual problem leads to

$$\mathbf{w} = \sum_{i=1}^l \alpha_i \phi(s_i), 0 \leq \alpha_i \leq \frac{1}{\nu l} \quad (28)$$

and the corresponding decision function becomes

$$f(s) = \sum_{i=1}^l \alpha_i \phi(s_i) \cdot \phi(s) - \rho \quad (29)$$

with the kernel function $K(s_i, s_j) = \phi(s_i) \cdot \phi(s_j)$ the decision function can be rewritten as

$$f(s) = \sum_{i=1}^l \alpha_i K(s_i, s) - \rho \quad (30)$$

Since the combined similarity between the image example Q_i and the image I'_j in Ω' is obtained as

$$\text{Sim}(Q_i, I'_j) = S(Q_i, I'_j) \cdot \mathbf{w}^T \quad (31)$$

Thus the combined similarity between the image example Q_i and the image I_j in Ω with the decision function in the combined similarity space φ can be represented as

$$\text{Sim}(Q_i, I_j) = f(S(Q_i, I_j)) + \rho \quad (32)$$

In order to obtain the combined similarity between the query Q and the image I_j in Ω , the gauss normalization is firstly used to make the similarities obtained with with different example image Q_i be comparable as

$$\text{Sim}'(Q_i, I_j) = \frac{\text{Sim}(Q_i, I_j) - \mu}{3\sigma + 1} \quad (33)$$

where μ and σ are the average value and the standard deviation of the similarities obtained with example image Q_i as

$$\mu = \frac{\sum_{j=1}^N \text{Sim}(Q_i, I_j)}{N} \quad (34)$$

$$\sigma = \sqrt{\frac{\sum_{j=1}^N (\text{Sim}(Q_i, I_j) - \mu)^2}{N - 1}} \quad (35)$$

The final similarity between the query Q and the image I_j in Ω is obtained as the sum of the normalized similarities with convert using the exponential function

$$\text{Sim}'(Q, I_j) = \sum_{i=1}^q \exp(\text{Sim}'(Q_i, I_j)) \quad (36)$$

V. LOW-LEVEL MEDICAL IMAGE FEATURE REPRESENTATION

In order to efficiently retrieve images relevant to a query, a CBIR system usually extracts low-level image features to represent an image in an off-line preprocessing stage. Image features can be categorized into color, shape, texture and spatial relationships. In this paper, we extract the low-level feature representation for medical image retrieval as follows:

Color Feature: we utilize the Color Layout Descriptor (CLD) [20] to represent spatial color distribution within the medical image. Although CLD is created for color images, it is equally suitable for gray-level images with proper choice of coefficients [4]. It is obtained by applying the discrete cosine transformation (DCT) on the 2-D array of local representative colors in the $YCbCr$ color space where Y is the luma component and Cb and Cr are the blue and red chroma components. Each channel is represented by 8 bits and each of the 3 channels is averaged separately for the 8×8 image blocks. In our work, a CLD with 64 Y , 3 Cb , and 3 Cr , is extracted to form 70-dimensional feature vector. The distance between two CLD vectors is calculated as :

$$D_{\text{clD}}(Q, I) = \sqrt{\sum_i (Y_{Q_i} - Y_{I_i})^2} + \sqrt{\sum_i (Cb_{Q_i} - Cb_{I_i})^2} + \sqrt{\sum_i (Cr_{Q_i} - Cr_{I_i})^2} \quad (37)$$

Texture Feature: In [21], Tamura propose six texture features corresponding to human visual perception: *coarseness, contrast, directionality, line-likeness, regularity, and roughness*. The first three features are very important from experiments testing, thus in this paper 1 *coarseness*, 1 *contrast* and 16 *directionality* from 16 directions is extracted to form 18-dimensional feature vector in order to represent the texture feature of medical images. The distance between two Tamura feature vector is calculated as:

$$D_{\text{tamura}}(Q, I) = \sqrt{\sum_i (T_{Q_i} - T_{I_i})^2} \quad (38)$$

Edge Feature: The Edge Histogram Descriptor (EHD) [20] is used to represent the global edge feature in this paper. The EHD represents local edge distribution in an image by dividing the image into 4×4 sub-images and generating a histogram from the edges present in each of these sub-images. Edges in the image are categorized into five types, namely vertical, horizontal, 45° diagonal, 135° diagonal and non-directional edges. Finally, a histogram with $16 \times 5 = 80$ bins is obtained, corresponding to a 80-dimensional feature vector. The distance between two EHD vectors is calculated as shown below:

$$D_{\text{ehd}} = \sum_i |H_{Q_i} - H_{I_i}| \quad (39)$$

VI. EXPERIMENTS AND RESULT

To evaluate the effectiveness of the proposed One-Class SVM based query dependent feature fusion method for medical image retrieval, exhaustive experiments were performed

Examples	CombSum Score	CombMax Score	CombSum Rank	CombMax Rank	Linear L SVMC	Polynomial L SVMC	Sigmoid L SVMC	Linear OSVM-QDFF	Polynomial OSVM-QDFF	Sigmoid OSVM-QDFF
4 Examples	0.4128	0.2279	0.2806	0.3518	0.4298	0.4448	0.4296	0.4619	0.4662	0.4688
6 Examples	0.4244	0.263	0.2857	0.4048	0.4509	0.4763	0.4507	0.5199	0.5342	0.5254
8 Examples	0.4351	0.2868	0.2969	0.4291	0.4721	0.5024	0.4719	0.564	0.5801	0.5685

TABLE III: Mean average precision of different feature fusion methods

Examples	Linear OSVM-QDFF	Linear OSVM-QDFF	Polynomial OSVM-QDFF	Polynomial OSVM-QDFF	Sigmoid OSVM-QDFF	Sigmoid OSVM-QDFF
	vs	vs	vs	vs	vs	vs
	Best Average Fusion Model	Best L SVMC	Best Average Fusion Model	Best L SVMC	Best Average Fusion Model	Best L SVMC
4 Examples	11.8944	3.8444	12.936	4.8112	13.5659	5.3957
6 Examples	22.5024	9.1539	25.8718	12.1562	23.7983	10.3086
8 Examples	25.4169	12.2611	28.9971	15.4658	26.4176	13.1568

TABLE IV: Relative Improvement [%] of OSVM-QDFF to Best Average Fusion Model and Best L SVMC

Kernel	C	γ	r	d
Linear	1	-	-	-
Polynomial	256	0.0625	0	3
Sigmoid	32	0.0313	0	-

TABLE I: Final parameter set for SVMs

Kernel	ν	γ	r	d
Linear	0.05	-	-	-
Polynomial	0.0625	2	0	3
Sigmoid	0.5	0.0313	0	-

TABLE II: Final parameter set for One-Class SVMs

on the IRMA medical image collection. The IRMA medical image collection contains 9000 radio graphs taken randomly from medical routine at the RWTH Aachen University Hospital which are subdivided into 57 classes [22]. The images in the collection are in grey level and in PNG (Portable Network Graphics) format. All the images are classified manually by reference coding with respect to a mono-hierarchical coding scheme [22] which describe the imaging modality, the body orientation, the body region examined and the biological system examined. The images have a high intra-class variability and inter-class similarity, which make the retrieval task much difficult [4]. To evaluate the content based medical image retrieval, the query which contains a small number of example images was randomly selected from each class and the remained images in that class are regarded as the corresponding ground truth set for the query. In this paper, the precision P , the recall R , the average precision AP and the mean average precision MAP proposed in [23] are used to measured the retrieval performance for medical image retrieval.

1) *Retrieval experiments:* To evaluate the performance of the proposed One-Class SVM based query dependent feature fusion method, the query independent feature fusion methods—the average fusion models (including CombSumScore, CombMaxScore, CombSumRank, CombMaxRank) presented in literature [14] and the query dependent feature fusion method—the local aggregation function based on support vector machines

presented in literature [10] are implemented as references. Three sets of experiments are performed with the number of examples image in the query varying from 4, 6, 8. For each set of experiments, 4 queries with the corresponding number of example images were generated randomly for each class, which resulting $57 * 4 = 228$ queries and their corresponding ground truth sets.

Since One-Class SVM and SVM have a lot of parameters to be set such as regularization parameter, kernel parameters. In order to produce robust retrieval results, it is very important to set these parameters. In this paper, we conducted the experiments with three different kernels such as linear, polynomial, sigmoid for both One Class SVM and SVM as follows:

-the linear machines with kernel function

$$K(s_i, s_j) = s_i^T s_j \quad (40)$$

-the polynomial machines with kernel function

$$K(s_i, s_j) = (\gamma s_i^T s_j + r)^d, \gamma > 0 \quad (41)$$

where d is the degree of the polynomial kernel

-the sigmoid machines with kernel function

$$K(s_i, s_j) = \tan(\gamma s_i^T s_j + r) \quad (42)$$

For the linear kernel machines, there are no parameters to set. For the nonlinear machines including the polynomial and the sigmoid, there are additional parameters such as γ , r and d should be set appropriately. For the kernel parameters r and d of both polynomial and sigmoid, we used the standard values. In order to effectively to decide the regularization parameter and the kernel parameter γ for the polynomial and sigmoid, we apply grid search for optimal parameter set that produces the best retrieval performance. The retrieval performance is measured by the mean average precision of 57 queries, with 1 query of 6 example images were generated randomly for each class. Table I provides the results of final parameters for SVMs with different three kernels. Table II provides the results of final parameters for one-class SVMs with different three kernels.

Additionally, the SVM and One-Class SVM with radial basis kernel function are also experimented in our work,




Fig. 2: Retrieval Performance of various feature fusion methods for image retrieval

and their retrieval performances are disappointed on our test dataset.

2) *Experimental results and analysis:* The plots in Figure 2 depict the average precision-recall graphs over all the 228 queries with different example images for the three comparison feature fusion methods: the *Average Fusion Models* [14], the local aggregation function based on SVM (*LSVMC*) [10] and the One-Class SVM based query dependent feature fusion method (*OSVM-QDFF*) proposed in this paper. Table III present the mean average precision over the 228 queries for the three comparison feature fusion methods with different example images. Table IV presents the relative improvement of *OSVM-QDFF* to the best *Average Fusion Model* and the

best *LSVMC*. The figure show that the proposed *OSVM-QDFF* always performances better than average fusion models and *LSVMC*. For the case of four query images, *OSVM-QDFF* improves the retrieval performance over the best average fusion model about %14 and about %5 over the the best *LSVMC*. For the case of six query images, *OSVM-QDFF* improves the retrieval performance over the best average fusion model about %26 and about %12 over the the best *LSVMC*. For the case of eight query images, *OSVM-QDFF* improves the retrieval performance over the best average fusion model about %29 and about %15 over the the best *LSVMC*.

For the *Average Fusion Model*, different features are configured of equal weighting for different queries which does

not consider the special feature is not equally important for different queries, thus *Average Fusion Model* do the worst retrieval performance. For the *LSVMC*, the *Query-Independent* feature fusion problem has been regarded as a strict two class classification problem, which is not always reasonable since the negative examples randomly selected from the image collection can belong to any class and they usually do not cluster.

VII. CONCLUSION

Due to the huge growth of the World Wide Web, medical images are now available in large numbers in online repositories, and there exists the need to retrieval the images based on the modality, anatomic region and different acquisition views through automatically extracting visual information of the medical images, which is commonly known as content-based image retrieval (CBIR). Since each feature extracted from images just characterizes certain aspect of image content, multiple features are necessarily employed to improve the retrieval performance. Meanwhile, a special feature is not equally important for different image queries since a special feature has different importances in reflecting the content of different images. Although some research efforts have been reported to enhance the image retrieval performance taking the feature fusion approaches, most of existed feature fusion methods for image retrieval only utilize query independent feature fusion which usually apply a single feature fusion model for all the image queries and do not consider that a special feature is not equally important for different image queries, the others usually require the users to tune appropriate parameters for the feature fusion models for different image queries. In this paper, with multiply query samples, we formulate the feature fusion problem as a one class classification problem in the combined similarities space and present a query dependent feature fusion method for medical image retrieval based on One-Class support vector machine. The proposed query dependent feature fusion method can learn appropriate feature fusion models for different query based on multiply query samples, and the learned feature fusion models can reflect the different importances of a special feature for different image queries. The experimental results on the IRMA medical image collection demonstrate that the proposed method can improve the retrieval performance effectively and can outperform existed feature fusion methods for image retrieval.

ACKNOWLEDGMENT

This research work was supported by grants from the Chinese Special Project of Science and Technology: Core electronic devices, high-end general chips and infrastructural software (2010ZX01042-002-001) and National Natural Science Foundation of China (NSFC) under Grant No.61003017.

REFERENCES

- [1] T. M. Lehmann, M. O. Güld, C. Thies, B. Fischer, D. Keysers, M. Kohnen, H. Schubert, and B. B. Wein, "Content-based image retrieval in medical applications for picture archiving and communication systems," in *Proceedings SPIE*, vol. 5033, 2003, pp. 109–117.
- [2] P. Mildenerger, M. Eichelberg, and E. Martin, "Introduction to the DICOM standard," *European radiology*, vol. 12, no. 4, p. 920, 2002.
- [3] F. Florea, H. Müller, A. Rogozan, A. Geissbühler, and S. Darmoni, "Medical image categorization with MedIC and MedGIFT," *Medical Informatics Europe (MIE 2006)*, 2006.
- [4] M. Rahman *et al.*, "Medical image retrieval with probabilistic multi-class support vector machine classifiers and adaptive similarity fusion," *Computerized Medical Imaging and Graphics*, vol. 32, no. 2, pp. 95–108, 2008.
- [5] A. W. Smeulders, M. Worring, S. Santini, A. Gupta, and R. Jain, "Content-based image retrieval at the end of the early years," *IEEE Transactions on pattern analysis and machine intelligence*, pp. 1349–1380, 2000.
- [6] E. A. El-Kwae, H. Xu, and M. R. Kabuka, "Content-based retrieval in picture archiving and communication systems," *Journal of Digital Imaging*, vol. 13, no. 2, pp. 70–81, 2000.
- [7] W. W. Chu, C. C. Hsu, A. F. Cardenas, and R. K. Taira, "Knowledge-based image retrieval with spatial and temporal constructs," *IEEE Transactions on Knowledge and Data Engineering*, vol. 10, no. 6, pp. 872–888, 1998.
- [8] T. Deselaers, D. Keysers, and H. Ney, "Features for image retrieval: An experimental comparison," *Information Retrieval*, vol. 11, no. 2, pp. 77–107, 2008.
- [9] A. Frome, Y. Singer, and J. Malik, "Image retrieval and classification using local distance functions," *Advances in Neural Information Processing Systems*, vol. 19, p. 417, 2007.
- [10] J. Zhang and L. Ye, "Local aggregation function learning based on support vector machines," *Signal Processing*, vol. 89, no. 11, pp. 2291–2295, 2009.
- [11] C. G. Snoek, M. Worring, and A. W. Smeulders, "Early versus late fusion in semantic video analysis," in *Proceedings of the 13th annual ACM International Conference on Multimedia*, 2005, p. 402.
- [12] A. Kushki, P. Androustos, K. N. Plataniotis, and A. N. Venetsanopoulos, "Retrieval of images from artistic repositories using a decision fusion framework," *IEEE Transactions on Image Processing*, vol. 13, no. 3, p. 277, 2004.
- [13] J. Zhang and L. Ye, "Properties of series feature aggregation schemes," *World Review of Science, Technology and Sustainable Development*, vol. 7, no. 1, pp. 100–115, 2010.
- [14] K. Donald and A. Smeaton, "A comparison of score, rank and probability-based fusion methods for video shot retrieval," *Image and Video Retrieval*, pp. 61–70, 2005.
- [15] H. Shao, J. W. Zhang, W. C. Cui, and H. Zhao, "Automatic feature weight assignment based on genetic algorithm for image retrieval," in *2003 IEEE International Conference on Robotics, Intelligent Systems and Signal Processing, 2003. Proceedings*, 2003, pp. 731–735.
- [16] R. Liyun, M. Shaoping, and L. Jing, "Feature fusion based on the average precision in image retrieval," *Journal of Computer Research and Development*, vol. 9, 2005.
- [17] M. Ortega, Y. Rui, K. Chakrabarti, K. Porkaew, S. Mehrotra, and T. S. Huang, "Supporting ranked boolean similarity queries in MARS," *IEEE Transactions on Knowledge and Data Engineering*, vol. 10, no. 6, pp. 905–925, 1998.
- [18] C. Carson, S. Belongie, H. Greenspan, and J. Malik, "Blobworld: Image segmentation using expectation-maximization and its application to image querying," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 24, no. 8, pp. 1026–1038, 2002.
- [19] B. Schölkopf, J. C. Platt, J. Shawe-Taylor, A. J. Smola, and R. C. Williamson, "Estimating the support of a high-dimensional distribution," *Neural computation*, vol. 13, no. 7, pp. 1443–1471, 2001.
- [20] S. F. Chang, T. Sikora, and A. Purl, "Overview of the MPEG-7 standard," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 11, no. 6, pp. 688–695, 2001.
- [21] H. Tamura, S. Mori, and T. Yamawaki, "Textural features corresponding to visual perception," *IEEE Transactions on Systems, Man and Cybernetics*, vol. 8, no. 6, pp. 460–473, 1978.
- [22] T. M. Lehmann, B. B. Wein, J. Dahmen, J. Bredno, F. Vogelsang, and M. Kohnen, "Content-based image retrieval in medical applications: a novel multistep approach," vol. 3972, Dec. 1999, pp. 312–320.
- [23] H. Müller, W. Müller, D. M. Squire, S. Marchand-Maillet, and T. Pun, "Performance evaluation in content-based image retrieval: Overview and proposals," *Pattern Recognition Letters*, vol. 22, no. 5, pp. 593–601, 2001.

IEEE

CSE'10

13th IEEE International Conference on
Computational Science and Engineering

11-13 December 2010 • Hong Kong, China

CONFERENCE INFORMATION

PAPERS BY SESSION

PAPERS BY AUTHOR

GETTING STARTED

TRADEMARKS

SEARCH



IEEE computer society



ST. FRANCIS XAVIER
UNIVERSITY



THE HONG KONG
POLYTECHNIC UNIVERSITY
香港理工大學

Published by



Proceedings

2010 13th IEEE International Conference
on Computational Science and Engineering
CSE 2010

11-13 December 2010
Hong Kong, China

Proceedings

2010 13th IEEE International Conference
on Computational Science and Engineering
CSE 2010

11-13 December 2010
Hong Kong, China



Los Alamitos, California
Washington • Tokyo



Copyright © 2010 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved.

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries may photocopy beyond the limits of US copyright law, for private use of patrons, those articles in this volume that carry a code at the bottom of the first page, provided that the per-copy fee indicated in the code is paid through the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

Other copying, reprint, or republication requests should be addressed to: IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, P.O. Box 133, Piscataway, NJ 08855-1331.

The papers in this book comprise the proceedings of the meeting mentioned on the cover and title page. They reflect the authors' opinions and, in the interests of timely dissemination, are published as presented and without change. Their inclusion in this publication does not necessarily constitute endorsement by the editors, the IEEE Computer Society, or the Institute of Electrical and Electronics Engineers, Inc.

IEEE Computer Society Order Number E4323
ISBN-13: 978-0-7695-4323-9
BMS Part # CFP10CSN-CDR

Additional copies may be ordered from:

IEEE Computer Society
Customer Service Center
10662 Los Vaqueros Circle
P.O. Box 3014
Los Alamitos, CA 90720-1314
Tel: + 1 800 272 6657
Fax: + 1 714 821 4641
<http://computer.org/cspress>
csbooks@computer.org

IEEE Service Center
445 Hoes Lane
P.O. Box 1331
Piscataway, NJ 08855-1331
Tel: + 1 732 981 0060
Fax: + 1 732 981 9667
[http://shop.ieee.org/store/
customer-service@ieee.org](http://shop.ieee.org/store/customer-service@ieee.org)

IEEE Computer Society
Asia/Pacific Office
Watanabe Bldg., 1-4-2
Minami-Aoyama
Minato-ku, Tokyo 107-0062
JAPAN
Tel: + 81 3 3408 3118
Fax: + 81 3 3408 3553
tokyo.ofc@computer.org

Individual paper REPRINTS may be ordered at: <reprints@computer.org>

Editorial production by Patrick Kellenberger
Cover art production by Mark Bartosik



**IEEE Computer Society
Conference Publishing Services (CPS)**

<http://www.computer.org/cps>

2010 13th IEEE International Conference on Computational Science and Engineering

CSE 2010

Table of Contents

Message from the General Chairs	xii
Message from the Program Chairs	xiv
Message from the Steering Committee	xv
Organizing Committee	xvi
Program Committee	xviii
Additional Reviewers	xxiii
SEC 2010 Message from the Symposium Chairs	xxiv
WMSC 2010 Message from the Workshop Chairs	xxv
WMSC 2010 Organizing and Program Committees	xxvi
Keynote	xxviii

CSE 2010: The 13th IEEE International Conference on Computational Science and Engineering

Mobile Computing and Wireless Communications I

Adaptive Data Compression in Wireless Body Sensor Networks	1
<i>Kun Hua, Honggang Wang, Wei Wang, and Shaoen Wu</i>	
Modeling and Prolonging Techniques on Operational Lifetime of Wireless Sensor Networks	6
<i>Fuu-Cheng Jiang, Chao-Tung Yang, Shih-Meng Teng, Hsiang-Wei Wu, and Yi-Ju Chiang</i>	
Performance Evaluation of an Adaptive Congestion Avoidance Algorithm for IEEE 802.15.4	14
<i>Ki-Chul Noh, Seung-Yeon Lee, Youn-Soon Shin, Kang-Woo Lee, and Jong-Suk Ahn</i>	
Augmented Reality System Design and Scenario Study for Location-Based Adaptive Mobile Learning	20
<i>William Chang and Qing Tan</i>	

Mobile Computing and Wireless Communications II

AIM: An Auction Incentive Mechanism in Wireless Networks with Opportunistic Routing	28
<i>Kun Zhang, Rui Wang, and Depei Qian</i>	
Service Price Discrimination in Wireless Network	34
<i>Zhide Chen and Li Xu</i>	
A Novel Martingale Approach to QoS-Aware Wireless Sensor Networks	42
<i>Deborah Duran-Herrmann, Shichuan Ma, Yaoqing (Lamar) Yang, and Yi Qian</i>	

Database and Data Mining

Time-Series Classification Based on Individualised Error Prediction	48
<i>Krisztian Buza, Alexandros Nanopoulos, and Lars Schmidt-Thieme</i>	
Research on Stage Classification of Flight Parameter Based on PTSVM	55
<i>Hui Lu and Kefei Mao</i>	
CORER: A New Rule Generator Classifier	64
<i>Javad Basiri, Fattaneh Taghiyareh, and Sahar Gazani</i>	

Cluster, Grid and Cloud Computing

ColorCom2: A Transparent Co-located Virtual Machine Communication Mechanism	72
<i>Liang Zhang, Yuebin Bai, Ming Liu, and Hanwen Xu</i>	
QAFT: A QoS-Aware Fault-Tolerant Scheduling Algorithm for Real-Time Tasks in Heterogeneous Systems	80
<i>Xiaomin Zhu, Jianghan Zhu, Manhao Ma, and Dishan Qiu</i>	
A Semi-structured Overlay for Multi-attribute Range Queries in Cloud Computing	88
<i>You-Fu Yu and Kuan-Chou Lai</i>	
DCMTs: Supporting Dynamically Created Migratory Threads	96
<i>Yueting Zhu, Wu Zhang, Hai Jiang, Yu Lei, and Junjie Peng</i>	

Embedded and Ubiquitous Computing

An Approximate Timing Analysis Framework for Complex Real-Time Embedded Systems	102
<i>Yue Lu, Thomas Nolte, and Johan Kraft</i>	
Fast Fuzzy C-Means Clustering Based on Low-Cost High-Performance VLSI Architecture in Reconfigurable Hardware	112
<i>Yao-Jung Yeh, Hui-Ya Li, Cheng-Yen Yang, and Wen-Jyi Hwang</i>	
Partitioning Granularity, Communication Overhead, and Adaptation in OS Services for Distributed Reconfigurable Systems on Chip	119
<i>Sufyan Samara</i>	

Design of Dynamically Reconfigurable Processor for the H.264/AVC Image Prediction and De-blocking Filter	127
<i>Y. Hayakawa and A. Kanasugi</i>	

CSE Applications I

Revealing Feasibility of FMM on ASIC: Efficient Implementation of N-Body Problem on FPGA	132
<i>Zhe Zheng, Yongxin Zhu, Xu Wang, Zhiqiang Que, Tian Huang, Xiaojing Yin, Hui Wang, Guoguang Rong, and Meikang Qiu</i>	
A Hybrid Harmony Search Method Based on OBL	140
<i>X. Z. Gao, X. Wang, and S. J. Ovaska</i>	
Gateway to Quality Living for the Elderly: Charting an Innovative Approach to Evidence-Based E-Health Technologies for Serving the Chronically Ill	146
<i>Joseph Tan, Patrick C. K. Hung, Michael Dohan, Thomas Trojer, Matthias Farwick, and Jayshiro Toshiro</i>	

CSE Applications II

Minimizing Thermal Disparities during Placement in 3D ICs	160
<i>Prasun Ghosal, Hafizur Rahaman, and Parthasarathi Dasgupta</i>	
GPU-RMAP: Accelerating Short-Read Mapping on Graphics Processors	168
<i>Ashwin M. Aji, Liqing Zhang, and Wu-chun Feng</i>	
Medical Image Retrieval with Query-Dependent Feature Fusion Based on One-Class SVM	176
<i>Yonggang Huang, Jun Zhang, Yongwang Zhao, and Dianfu Ma</i>	
Intelligent Mode Decision Procedure for MVC Inter-view Frame	184
<i>Xingang Liu, Kwanghoon Sohn, Laurence T. Yang, and Wei Zhu</i>	

Intelligent and Bio-inspired Computing

Parametric Control in a Region-Based Coupled MRF Model with Phase Dynamics for Coarse Image Region Segmentation	190
<i>Haichao Liang, Kazuki Nakada, Kenji Matsuzaka, Takashi Morie, and Masato Okada</i>	
Discrete Particle Swarm Optimization for Materials Budget Allocation in Academic Libraries	196
<i>Tsu-Feng Ho, Shyong Jian Shyu, Yi-Ling Wu, and Bertrand M. T. Lin</i>	
Uncalibrated Camera Vision Pointing Recognition for HCI	204
<i>Ye-Peng Guan</i>	

Advanced Networking and its Security, Privacy and Trust

Fractional Exponent Coupling of RIO	208
<i>Wen-Ping Lai and Zhen-Hua Liu</i>	
An Effective Method to Improve the Resistance to Frangibility in Scale-Free Networks	214
<i>Kaihua Xu, Yongwei Meng, Yuhua Liu, Naixue Xiong, Laurence T. Yang, and Meirong Zheng</i>	
Vulnerability Analysis and Protection Schemes of Universal Plug and Play Protocol	222
<i>Abdullah Al Hasib and M. A. Mottalib</i>	

Distributed and Parallel Computing I

Availability-Aware Cache Management with Improved RAID Reconstruction Performance	229
<i>Suzhen Wu, Bo Mao, Dan Feng, and Jianxi Chen</i>	
Input-Driven Reconfiguration for Area and Performance Adaption of Reconfigurable Accelerators	237
<i>Like Yan, Yuan Wen, and Tianzhou Chen</i>	
A Novel Generalized-Comparison-Based Self-Diagnosis Algorithm for Multiprocessor and Multicomputer Systems Using a Multilayered Neural Network	245
<i>Mourad Elhadef and Amiya Nayak</i>	

Distributed and Parallel Computing II

Implementing Parallel LU Factorization with Pipelining on a MultiCore Using OpenMP	253
<i>Panagiotis D. Michailidis and Konstantinos G. Margaritis</i>	
A Locality-Aware Publish/Subscribe Scheme for High Level Architecture on Structured Peer-to-Peer Networks	261
<i>Wei-Chao Chang, Shih-Hsiang Lo, Kuan-Chou Lai, Kuan-Ching Li, and Yeh-Ching Chung</i>	
LogGPH: A Parallel Computational Model with Hierarchical Communication Awareness	268
<i>Liang Yuan, Yunquan Zhang, Yuxin Tang, Li Rao, and Xiangzheng Sun</i>	

SEC 2010: The 2010 International Symposium on Scientific and Engineering Computing

Mobile Computing and Wireless Communications

Antenna Selection Scheme for Application in MIMO Systems with Non-constant Envelope Mapping	275
<i>Shu-yun Jia, Jian Wang, Jin-tao Wang, and Bo Ai</i>	
Approaches and Issues in Location-Aware Continuous Authentication	279
<i>Stan Kurkovsky and Ewa Syta</i>	
Enhancing LOCATION Information Using Semantic Composition	284
<i>Hakki C. Cankaya, Eduardo Blanco, and Dan Moldovan</i>	

Data Management with Applications

Optimizing Academic Conference Classification Using Social Tags	289
<i>Jing Xia, Kunmei Wen, Ruixuan Li, and Xiwu Gu</i>	
Emotion Sensing for Internet Chatting: A Web Mining Approach for Affective Categorization of Events	295
<i>Cheng-Yu Lu, William W. Y. Hsu, Hsing-Tsung Peng, Jen-Ming Chung, and Jan-Ming Ho</i>	
Research on Mining Rules from Multi-criterion Group Decision Making Based on Genetic Algorithms	302
<i>Xinqiao Yu, Naixue Xiong, and Wei Zhang</i>	

Cluster, Grid and Cloud Computing

An Adaptively Hierarchical Framework for Remote Paging on Grids	308
<i>Tyng-Yeu Liang and Hung-Fu Li</i>	
Characterization of Scientific and Transactional Applications under Multi-core Architectures on Cloud Computing Environment	314
<i>Denis R. Ogura and Edson T. Midorikawa</i>	
Implementation of a Medical Image File Accessing System on Cloud Computing	321
<i>Chao-Tung Yang, Lung-Teng Chen, Wei-Li Chou, and Kuan-Chieh Wang</i>	

Intelligent and Bio-inspired Computing

A Knowledge-Based Artificial Fish-Swarm Algorithm	327
<i>X. Z. Gao, Ying Wu, Kai Zenger, and Xianlin Huang</i>	
A Harmony Search-Based Differential Evolution Method	333
<i>X. Z. Gao, X. Wang, and S. J. Ovaska</i>	
Hardware Implementation of k -Winner-Take-All Neural Network with On-chip Learning	340
<i>Hui-Ya Li, Chien-Min Ou, Yi-Tsan Hung, Wen-Jyi Hwang, and Chia-Lung Hung</i>	

Security, Privacy and Trust

- An Image Interpolation Based Reversible Data Hiding Method Using R-Weighted Coding346
Yildiray Yalman, Feyzi Akar, and Ismail Erturk
- A Novel Image Based CAPTCHA Using Jigsaw Puzzle351
Haichang Gao, Dan Yao, Honggang Liu, Xiyang Liu, and Liming Wang

WMSC 2010: The Second International Workshop on Workflow Management in Service and Cloud Computing

Service Delivery and Composition

- A Comprehensive Evaluation Method for Cross-Organizational Service Selection357
Rutao Yang, Lianyong Qi, Wenmin Lin, Wanchun Dou, and Jinjun Chen
- Runtime Configurable Service Process Model363
Liang Zhou and Jian Cao
- A QoS-Optimal Automatic Service Composition Method Based on Backtracting Theory369
Wenmin Lin, Rutao Yang, Xiaojie Si, Lianyong Qi, and Wanchun Dou
- Process Semantic-Enabled Customisation for Active Service Provisioning375
Bin Wen, Keqing He, Peng Liang, and Lai Xu

Quality of Services for Workflow Execution

- A DMC Based Dynamically Self-Configuration Service Process Engine382
Xuezhi Chai and Jian Cao
- Research on the Mechanism of Tourism Information Change Management Based on ECA Rules388
Tao Hu and BaoHong Li
- An Algorithm on the Mining of Batch Processing Process393
Yiping Wen, Jianxun Liu, and Zhigang Chen

Scientific Computing in the Cloud

- A Taxonomy for the Analysis of Scientific Workflow Faults398
Marco Lackovic, Domenico Talia, Rafael Tolosana-Calasanz, José A. Bañares, and Omer F. Rana
- Persistent Locality Management of Scientific Application Workflows404
Lamine Aouad, Tahar Kechadi, and Serge Petiton
- Discovering Batch Processing Area from Workflow Logs410
Yiping Wen, Jianxun Liu, and Zhigang Chen

A Dynamic Self-Adaptive Trust Model for P2P E-Commerce System	415
<i>Jie Wang, Miaomiao Li, Yang Yu, and Zhenguang Huang</i>	

Cloud Workflow Applications

A Framework: Workflow-Based Social Network Discovery and Analysis	421
<i>Jihye Song, Minjoon Kim, Haksung Kim, and Kwanghoon Kim</i>	

Cost-Aware Virtual USB Drive: Providing Cost-Effective Block I/O Management Commercial Cloud Storage for Mobile Devices	427
<i>Young Jin Nam, Young Kyun Park, Jong Tae Lee, and Fredrick Ishengoma</i>	

Bridging to the Cloud: Solution Design Trends Helping "Legacy" Systems Leverage Cloud Computing	433
<i>Brian D. Goodman and Ran SH. Zhou</i>	

Author Index	439
---------------------------	-----

Message from the General Chairs

CSE 2010

Welcome to the IEEE 13th International Conference on Computational Science and Engineering (CSE-2010) sponsored by IEEE Computer Society Technical Committee of Scalable Computing (TCSC), organized by Hong Kong Polytechnic University, China. It is our great pleasure to hold CSE-2010 in Hong Kong, China, December 11-13, 2010. On behalf of the organizing committee of CSE-2010, we would like to express to all participants our cordial welcome and high respect.

The field of Computational Science and Engineering area has earned prominence through advances in electronic and integrated technologies beginning in the 1940s. Current times are very exciting and the years to come will witness a proliferation in the use of various advanced computing systems. This emerging and promising discipline is increasingly shaping future research and development activities in academia and industry, ranging from engineering, science, finance, economics, to arts and human science, especially when the large and complex problems must be solved within a tight schedule. This conference will bring together computer scientists, applied mathematicians, engineers in different disciplines and researchers to present, discuss, and exchange ideas, results, and experiences in the area of advanced computing for problems in science and engineering applications and interdisciplinary applications.

CSE-2010 is the next event in a series of highly successful International Conferences on Computational Science and Engineering, held mainly as the International Workshop on High Performance Scientific and Engineering Computing for 10 editions, mostly in conjunction with International Conference on Parallel Processing (ICPP), as COATA-98 (Orlando, USA, July 1998), HPSEC-99 (Fukushima, Japan, September 1999), HPSEC-00 (Toronto, Canada, August 2000), HPSEC-01 (Valencia, Spain, September 2001), HPSEC-02 (Vancouver, Canada, August 2002), HPSEC-03 (Kaohsiung, Taiwan, October 2003), HPSEC-04 (Montreal, Canada, August 2004), HPCSE-04 with WCC-04 (Toulouse, France, August 2004), HPSEC-05 (Oslo, Norway, June 2005), and HPSEC-06 (Columbus, USA, August 2006). The previous CSE-08 and CSE-09 were held in São Paulo, Brazil, July 16-18, 2008 and Vancouver, Canada, August 29-31, 2009.

CSE-2010 consists of the main conference, one symposium SEC-2010 and one workshop WMSC-2010. Through CSE-2010, SEC-2010 and WMSC-2010, about 65 paper presentations from more than 24 countries or regions, and keynote sessions by distinguished guest speakers are presented during these three days. CSE-2010 is supported by many people and organizations as well as the general chairs whose main responsibility is to coordinate the various tasks carried out with willing and talented volunteers. First, we want to thank Professor Laurence T. Yang, the Steering Chair of CSE-2010, for giving us the opportunity to hold this conference and for his guidance on organizing the conference. We also greatly appreciate Program Chairs, Hai Jiang, Arkansas State University, USA, Luc Giraud, INRIA, France and Yunquan Zhang, Chinese Academy of Sciences, China, and 13 Program Vice Chairs for their hard and excellent work on organizing a very strong Program Committee, outstanding reviewing process to select high-quality papers from a large number of submissions (230), and producing an excellent conference program. We are grateful to all workshop/symposia chairs for their professional and excellent expertise in organizing the attractive workshops/symposia, and other committee chairs, steering and advisory members, and program committee members for their great supports. We are grateful to all authors who submitted their high-quality papers to CSE-2010 main conference and workshops/symposia.

Last but not least, we also would like to express our appreciation for Wilfred Lin, Alice Lam, Carmen Au, and Yao Yu from Hong Kong Polytechnic University, China for their hard work, excellent service, and superb local arrangements.

We thank all of you for participating in CSE-2010, and we hope you find the conference stimulating and constructive and at the same time enjoy the beautiful Hong Kong, China!

Jiannong Cao, Hong Kong Polytechnic University, China
Eric de Sturler, Virginia Tech, USA
Sotirios G. Ziavras, New Jersey Institute of Technology, USA
General Chairs of CSE-2010

Message from the Program Chairs

CSE 2010

It is our great pleasure to welcome you to the 13th IEEE International Conference on Computational Science and Engineering (CSE-2010) in Hong Kong, China, December 11-13. The CSE conference, sponsored by the IEEE Technical Committee on Scalable Computing (TCSC), is well established and is in its 13th edition with wide acceptance and reputation in the field.

This 2010 edition of CSE consists of 37 papers selected from 230 submissions, giving an acceptance rate of 16%. We wish to acknowledge the authors for choosing CSE-2010 as the venue to present their research. The final decision has been taken after a high quality review process that produced at least three reviews per paper (four or five reviews in most cases), involving more than 200 program committee members. Fortunately, we were well assisted by 13 Program Vice-Chairs, reputed experts in their fields: Nik Bourbakis (Intelligent and Bio-inspired Computing), Chao-Tung Yang (Distributed and Parallel Computing), Alfredo Cuzzocrea (Database and Data Mining), Daniel Grosu (Cluster, Grid, Cloud and P2P Computing), Jian Wu (Web Services and Internet Computing), Tao Jiang (Mobile Computing and Wireless Communications), Hsi-Ya Chang (CSE Applications), Nectarios Koziris (Scientific and Engineering Computing), Wen-Jyi Hwang (Embedded and Ubiquitous Computing), Honggang Wang (Advanced Networking and Applications), Chin-Feng lee (Security, Privacy and Trust), Vincenzo De Florio (Dependable, Reliable and Autonomic Computing), and Qing Tan (CSE Education). We gratefully thank them for assembling the program committee for their track guiding the reviewing process. Thanks are extended to the program committee members and the additional reviewers who dedicated their valuable time and expertise to provide professional reviews working under a very tight schedule.

The coordination with the Steering Chair (Laurence T. Yang) and the General Chairs (Jiannong Cao, Eric de Sturler and Sotirios G. Ziavras), the Steering Committee members (Hai-xiang Lin, Kuan-Ching Li and Rodrigo F. de Mello) were essential for the success of the final program. We sincerely appreciate their constant support and guidance. It was a great pleasure to work with such an excellent team. Also, we would like to express our gratitude to Andy Yongwen Pan for managing the conference website, and for his efficient assistance in managing the web-based submission and reviewing system.

Finally, we expect the conference favors a useful interaction between researchers, and provides a stimulating forum for exchanging and developing new research ideas in the exciting and rapidly changing field of computational science and engineering.

Hai Jiang, Arkansas State University, USA
Luc Giraud, INRIA, France
Yunquan Zhang, Chinese Academy of Sciences, China
Program Chairs of CSE-2010

Message from the Steering Committee

CSE 2010

Welcome to the 13th IEEE International Conference on Computational Science and Engineering (CSE-2010). It is our great pleasure and honor to hold CSE-2010 at Hong Kong, China, December 11-13, 2010. On behalf of the CSE-2010 steering committee and organizing committee, we would like to express to all the participants from across the world our cordial welcome and high respect.

Computational Science and Engineering is increasingly emerging as a promising discipline in shaping future research and development activities in academia and industry, ranging from engineering, science, finance, economics, arts and humanitarian fields, especially when the solution of large and complex problems must cope with tight timing schedules. CSE-2010 is the next event, in a series of highly successful International Conferences on Computational Science and Engineering (CSE), held mainly as the International Workshop on High Performance Scientific and Engineering Computing for 10 editions, mostly in conjunction with International Conference on Parallel Processing (ICPP), as COATA-98 (Orlando, USA, July 1998), HPSEC-99 (Fukushima, Japan, September 1999), HPSEC-00 (Toronto, Canada, August 2000), HPSEC-01 (Valencia, Spain, September 2001), HPSEC-02 (Vancouver, Canada, August 2002), HPSEC-03 (Kaohsiung, Taiwan, October 2003), HPSEC-04 (Montreal, Canada, August 2004), HPCSE-04 with WCC-04 (Toulouse, France, August 2004), HPSEC-05 (Oslo, Norway, June 2005), and HPSEC-06 (Columbus, USA, August 2006). The previous CSE-08 and CSE-09 were held in São Paulo, Brazil, July 16-18, 2008 and Vancouver, Canada, August 29-31, 2009.

An international conference can only be organized by supports and great voluntary efforts of many people and organizations and our main responsibility is to coordinate the various tasks carried out with other willing and talented volunteers. We would like to thank the General Chairs: Jiannong Cao, Hong Kong Polytechnic University, China, Eric de Sturler, Virginia Tech, USA, and Sotirios G. Ziavras, New Jersey Institute of Technology, USA, for very successful organization of CSE-2010. We would like to express our special thanks to Hai Jiang, Arkansas State University, USA, Luc Giraud, INRIA, France and Yunquan Zhang, Chinese Academy of Sciences, China, for making excellent technical program as the Program Chairs. We would like to greatly appreciate, Ligang He, University of Warwick, UK, and Kuan-Chou Lai, National Taichung University, Taiwan, for organizing CSE-2010 workshops/symposia. We also thank all chairs and committee members of the CSE-2010 workshops/symposia. Without workshops/symposia, we could not successfully organize CSE-2010. We also would like to express our appreciation for Wilfred Lin, Alice Lam, Carmen Au, and Yao Yu from Hong Kong Polytechnic University, China for their hard work, excellent service, and superb local arrangements.

Finally, we also would like to take opportunity to thank all the members of the organizing committee, the program vice-chairs and technical program committee as well as all of the authors who submitted papers and reviewers who reviewed huge number of papers.

Laurence T. Yang (Chair), St Francis Xavier University, Canada
Hai-xiang Lin, Delft University of Technology, Netherlands
Kuan-Ching Li, Providence University, Taiwan
Rodrigo F. de Mello, University of São Paulo, Brazil
Steering Committee of CSE-2010

Organizing Committee

CSE 2010

Honorary Chairs

Jon C. Muzio, University of Victoria, Canada
Richard P. Brent, Australian National University, Australia

General Chairs

Jiannong Cao, Hong Kong Polytechnic University, China
Eric de Sturler, Virginia Tech, USA
Sotirios G. Ziavras, New Jersey Institute of Technology, USA

Program Chairs

Hai Jiang, Arkansas State University, USA
Luc Giraud, INRIA, France
Yunquan Zhang, Chinese Academy of Sciences, China

Program Vice-Chairs

Intelligent and Bio-inspired Computing
Nik Bourbakis, Wright State University, USA

Distributed and Parallel Computing
Chao-Tung Yang, Tunghai University, Taiwan

Database and Data Mining
Alfredo Cuzzocrea, ICAR and University of Calabria, Italy

Cluster, Grid, Cloud and P2P Computing
Daniel Grosu, Wayne State University, USA

Web Services and Internet Computing
Jian Wu, Zhejiang University, China

Mobile Computing and Wireless Communications
Tao Jiang, Huazhong University of Science & Technology, China

CSE Applications

Hsi-Ya Chang, National Center for HPC, Taiwan

Scientific and Engineering Computing
Nectarios Koziris, National Technical University of Athens, Greece

Embedded and Ubiquitous Computing

Wen-Jyi Hwang, National Taiwan Normal University, Taiwan

Advanced Networking and Applications

Honggang Wang, University of Massachusetts Dartmouth, USA

Security, Privacy and Trust

Chin-Feng Lee, Chaoyang University of Technology, Taiwan

Dependable, Reliable and Autonomic Computing

Vincenzo De Florio, University of Antwerp, Belgium

CSE Education

Qing Tan, Athabasca University, Canada

Steering Committee

Laurence T. Yang (Chair), St. Francis Xavier University, Canada

Hai-xiang Lin, Delft University of Technology, Netherlands

Kuan-Ching Li, Providence University, Taiwan

Rodrigo F. de Mello, University of São Paulo, Brazil

Workshop Chairs

Ligang He, University of Warwick, UK

Kuan-Chou Lai, National Taichung University, Taiwan

Panel Chair

Yeh-Ching Chung, National Tsing Hua University, Taiwan

Local Chair

Alvin Chan, Hong Kong Polytechnic University, China

Web and Submission Chairs

Andy Yongwen Pan, St. Francis Xavier University, Canada

Program Committee

CSE 2010

Intelligent and Bio-inspired Computing

Soon Chung, Wright State University, USA
Dakopoulos Dimitrios, Wright State University, USA
Praveen Kakumanu, Meridian Group, Inc., USA
Raghudeep Kannavara, Intel Corporation, USA
Alexandros Karargyris, National Institutes of Health (NIH), USA
Alexandros Pantelopoulos, Wright State University, USA
Athanasios Tsitsoulis, Wright State University, USA
Xiaojie Wang, Beijing University of Posts and Telecommunications, China
Ming Yang, Marquette University, USA

Distributed and Parallel Computing

Erik Elmroth, Umea University, Sweden
Jing He, Georgia State University, USA
Michael Hobbs, Deakin University, Australia
Thilo Kielmann, Vrije University Amsterdam, Netherlands
Kuan-Chou Lai, National Taichung University, Taiwan
Mitsuhisa Sato, University of Tsukuba, Japan
Wen-Chung Shih, Asia University, Taiwan
Lei Shu, Osaka University, Japan
Lizhe Wang, Indiana University, USA
Chao-Chin Wu, National Changhua University of Education, Taiwan
Feng Xia, Dalian University of Technology, China
Mehmet Yildiz, IBM, Australia

Database and Data Mining

Alberto Abello, Polytechnical University of Catalunya, Spain
Ajith Abraham, Norwegian University of Science and Technology, Norway
Luca Becchetti, University La Sapienza of Rome, Italy
Ladjet Bellatreche, LISI-ENSA and University of Poitiers, France
Bettina Berendt, Catholic University of Leuven, Belgium
Christos Bouras, University of Patras, Greece
Elena Camossi, Joint Research Centre ISPRA, Italy
Barbara Catania, University of Genova, Italy
Jerome Darmont, University of Lyon 2, France
Antonios Deligiannakis, Technical University of Crete, Greece
Curtis Dyreson, Utah State University, USA
Eric Gregoire, CRIL-CNRS and University of Artois, France
Ching-Hsien Hsu, Chung Hua University, Taiwan
Carson K. Leung, University of Manitoba, Canada

Bo Ning, Dalian Maritime University, China
Eric Pardede, La Trobe University, Australia
Andrea Pugliese, University of Calabria, Italy
Dominik Slezak, Infobright and University of Warsaw, Poland
Alberto Marchetti Spaccamela, University La Sapienza of Rome, Italy
Eiko Yoneki, University of Cambridge, UK
Bin Zhou, Simon Fraser University, Canada

Cluster, Grid, Cloud and P2P Computing

Sherif Abdelwahed, Mississippi State University, USA
Mark Baker, University of Reading, UK
Ivona Brandic, Vienna University of Technology, Austria
Anthony Chronopoulos, University of Texas at San Antonio, USA
Emmanuel Jeannot, INRIA, France
Zaki Malik, Wayne State University, USA
Gaurang Mehta, University of Southern California, USA
Dirk Neumann, University Freiburg, Germany
Manish Parashar, Rutgers University and NSF, USA
Maria Perez, Universidad Politecnica de Madrid, Spain
Radu Prodan, University of Innsbruck, Austria
Ioan Raicu, Illinois Institute of Technology, USA
Ramin Yahyapour, Dortmund University, Germany
Albert Zomaya, University of Sydney, Australia

Web Services and Internet Computing

Jian Cao, Shanghai Jiao Tong University, China
Deren Chen, Zhejiang University, China
Shuiguang Deng, Zhejiang University, China
Meina Song, Beijing University of Posts and Telecommunications, China
Yang Tao, University of California at Santa Barbara, USA
Zhongjie Wang, Harbin Institute of Technology, China
Xifeng Yan, University of California at Santa Barbara, USA
Wenbo Zhang, Chinese Academy of Sciences, China
Xiaolin Zheng, Zhejiang University, China
Hua Zhong, Institute of Software, Chinese Academy of Sciences, China

Mobile Computing and Wireless Communications

Ai Bo, Beijing Jiaotong University, China
Jiming Chen, Zhejiang University, China
Wen Chen, Shanghai Jiaotong University, China
Peng Gao, China Mobile Group Design Institute Co., China
Yejun He, Shenzhen University, China
Hai Jiang, University of Alberta, Canada
Jinhua Jiang, Stanford University, USA
Yixin Jiang, Tsinghua University, China
Xiangming Li, Beijing Institute of Technology, China

Daiming Qu, Huazhong University of Science and Technology, China
Bo Rong, Communications Research Centre, Canada
Linyang Song, Peking University, China
Chonggang Wang, InterDigital, USA
Jintao Wang, Tshinghua University, China
Xinbing Wang, Shanghai Jiaotong University, China
Yulei Wu, University of Bradford, UK
Changchuang Yin, Beijing University of Posts and Telecommunications, China
Weiyi Zhang, North Dakota State University, USA

CSE Applications

David E. Bernholdt, Oak Ridge National Lab, USA
Jee-Gong Chang, National Center for HPC, Taiwan
Wenguang Chen, Tsinghua University, China
Kuo Ning Chiang, National Center for HPC, Taiwan
Jung Hong Chuang, National Chiao Tung University, Taiwan
Jose Alfredo F. Costa, Universidade Federal do Rio Grande do Norte, Brazil
Georgios Goumas, National Technical University of Athens, Greece
Kuo-Chan Huang, National Taichung University, Taiwan
Hai Jin, Huazhong University of Science & Technology, China
Boo Cheong Khoo, National University of Singapore, Singapore
Ming-Hsien Lee, Tamkang University, Taiwan
Xingang Liu, Yonsei University, Korea
Kengo Nakajima, University of Tokyo, Japan
Thomas Rauber, University Bayreuth, Germany
Sheng-De Wang, National Taiwan University, Taiwan
I-Chen Wu, National Chiao-Tung University, Taiwan
Shi-Jim Yen, National Dong Hwa University, Taiwan

Scientific and Engineering Computing

Martin Buecker, RWTH Aachen University, Germany
Zizhong Chen, Colorado School of Mines, USA
Robert van Engelen, Florida State University, USA
Jose-Ramon Herrero, Universitat Politecnica de Catalunya (UPC), Spain
Kornilios Kourtis, National Technical University of Athens, Greece
Heshan Lin, Virginia Polytechnic Institute and State University, USA
Dimitrios Nikolopoulos, FORTH-ICS & University of Crete, Greece
Thomas Rauber, University of Bayreuth, Germany
Gudula Ruenger, Chemnitz University of Technology, Germany
Chau-Wen Tseng, University of Maryland at College Park, USA
Xuemin Tu, University of California at Berkeley, USA

Embedded and Ubiquitous Computing

Joseph Arul, Fu Jen Catholic University, Taiwan
Sung Woo Chung, Korea University, Korea
Jiman Hong, Soongsil University, Korea

Wei-Lien Hsu, AMD Inc., USA
Chia-Tien Dan Lo, Southern Polytechnic State University, USA
Thomas Nolte, Malardalen University, Sweden
Chien-Min Ou, Chin Yun University, Taiwan
Hiren D. Patel, University of Waterloo, Canada
Shanq-Jang Ruan, National Taiwan University of Science and Technology, Taiwan
Feilong Tang, Shanghai Jiao Tong University, China
Russell Tessier, University of Massachusetts at Amherst, USA
Hiroyuki Tomiyama, Ritsumeikan University, Japan
Qixin Wang, Hong Kong Polytechnic University, Hong Kong
Yi-Chong Zeng, Academia Sinica, Taiwan
Wei Zhang, Nanyang Technological University, Singapore

Advanced Networking and Applications

Jimin Chen, Zhejiang University, China
Hua Fang, University of Massachusetts Medical School, USA
Wen-Chen Hu, University of North Dakota, USA
Kun Hua, Lawrence Technological University, USA
Gang Kou, University of Electronic Science and Technology of China, China
Haiyan Luo, University of Nebraska-Lincoln, USA
Lei Shu, Osaka University, Japan
Wei Wang, South Dakota State University, USA
Dalei Wu, University of Nebraska-Lincoln, USA
Shaoen Wu, University of Southern Mississippi, USA
Liudong Xing, University of Massachusetts at Dartmouth, USA
Yaoqing Yang, University of Nebraska-Lincoln, USA
Liang Zhou, ENSTA Paris Techniques, France

Security, Privacy and Trust

Jin Wook Byun, Pyeongtaek University, Korea
Jordi Forne, Universitat Politècnica de Catalunya, Spain
Swee-Huay Heng, Multimedia University, Malaysia
Kwangjo Kim, Korea Advanced Institute of Science and Technology, Korea
Lenny Koh, The University of Sheffield, UK
Manoj Kumar, R. K. College Shamli, India
Minoru Kuribayashi, Kobe University, Japan
Marc Lacoste, Orange Labs, France
Tieyan Li, Institute for InfoComm Research (I2R), Singapore
Chia-Chen Lin, Providence University, Taiwan
Pedro Peris Lopez, Delft University of Technology, Netherlands
David Naccache, Ecole Normale Supérieure, France
Victor Pomponiu, Università degli Studi di Torino, Italy
Ali Shahrabi, Glasgow Caledonian University, UK
Mei-Ling Shyu, University of Miami, USA
Willy Susilo, University of Wollongong, Australia
Hiroki Takakura, Nagoya University, Japan

Joseph Tan, McMaster University, Canada
Hao-Kuan Tso, Republic of China Army, Taiwan
Kok Sheik Wong, University of Malaya, Malaysia
Yildiray Yalman, Kocaeli University, Turkey
Cheng-Hsing Yang, National Pingtung University of Education, Taiwan
Muhammad Younas, Oxford Brookes University, UK

Dependable, Reliable and Autonomic Computing

Marcello Cinque, University of Naples, Italy
Luca Foschini, Universita' di Bologna, Italy
Stephane Frenot, Institut National de Recherche en Informatique
et Automatique (INRIA), France
Lorenz Frohofer, Vienna University of Technology, Austria
Geir Horn, Stiftelsen for Industriell og Teknisk Forskning (SINTEF), Norway
Mohamed Ba Khouya, University of Technology Belfort Montbeliard, France
Leo G Marcus, The Aerospace Corporation, USA
Gianluca Mazzini, University of Ferrara, Italy
Eric Pardede, La Trobe University, Australia
Luca Simoncini, University of Pisa, Italy

CSE Education

Hui-Chun Chu, Soochow University, Taiwan
Ashraf Darwish, Helwan University, Egypt
Ibrahiem Emary, King Abdulaziz University, Saudi Arabia
Dragan Gasevic, Athabasca University, Canada
Tsukasa Hirashima, Hiroshima University, Japan
Yueh-Min Hunag, National Cheng Kung University, Taiwan
Gwo-Jen Hwang, National Taiwan University of Science and Technology, Taiwan
Hassan Karimi, University of Pittsburgh, USA
Yen-Hung Kuo, Institute for Information Industry, Taiwan
Athina Lazakidou, University of Peloponnese, Greece
Nashwa Mamdouh, Arab Academy for Science Technology and Maritime Transport, Egypt
Griff Richards, Simon Fraser University, Canada
Joel Rodrigues, University of Beira Interior, Portugal
Demetrios Sampson, University of Piraeus, Greece
Vincent Tam, Hong Kong University, China
Radu Vasiu, University of Timisoara, Romania
Ke Wang, Jilin University, China
Xiaokun Zhang, Athabasca University, Canada

Additional Reviewers

CSE 2010

Heithem Abbes
David Allenor
Yanmeng Ba
Anupam Bhattacharjee
Toon Calders
Che-Wei Chang
Dongsheng Che
Jianwen Chen
Rick Chen
Rui Chen
Jaeyoung Choi
Thilan Costa
Jörg Dümmler
Robert Dew
Rubing Duan
Nandan Garg
Jiaqi Ge
Guan Haibing
Ralf Hoffmann
Yueh-Min Huang
Kitae Jeong
Girish Jha
Samia Kouki
Kevin Kreiser
Raphael Kunis
Mohsen Laabidi
Fenglien Lee
Mun-Kyu Lee

Rong-Jhang Liao
Yu-Chia Lin
Luis David Lopez
Hao Luan
Glenn Luecke
Richard Mcclatchey
Jose Maria Monteiro
Chandima Nadungodage
Mariusz Pajer
Heng Qi
Bahaa Saify
Chris Sung
Andy Tyrrell
Bo Wang
Tongyuan Wang
Wenhua Wang
Hiroshi Watanabe
Eriko Werbet
Jufeng Xu
Bo Yang
Chuan-Yue Yang
Yanli Yu
Sharrukh Zaman
Lianyu Zhao
Zhipeng Zhao
Cheng Zhu
Zongliang Zhuansun

Message from the Symposium Chairs

SEC 2010

We are happy to welcome you at the 2010 International Symposium on Scientific and Engineering Computing (SEC-2010). The symposium was held in conjunction with the 13th IEEE International Conference on Computational Science and Engineering (CSE-2010), Hong Kong, China, December 11-13, 2010.

SEC-2010 contains 14 invited papers selected from the ones submitted to the CSE-2010 main conference, and thus all the papers were peer reviewed by at least 3 or 4 members of the CSE-2010 program committee. The goal of SEC-2010 is to provide an additional forum within CSE-2010 to cover novel theories, methodologies, algorithm design, computing techniques for problems in science and engineering applications and inter-disciplinary applications. Papers of high quality in the following areas were invited: Intelligent, Bio-inspired and Autonomic Computing, Distributed and Parallel Computing, Distributed Database and Data Mining, Grid, P2P, Web Services and Internet Computing, Mobile Computing and Wireless Communications, HPC Applications, Embedded and Ubiquitous Computing, Advanced Networking and Applications, Security, Privacy and Trust Education in Computational Scientific and Engineering and various scientific and engineering applications. We thank the authors for submitting their excellent works and the members of CSE-2010 program committee for managing the reviews of the symposium papers in a short time.

We believe this symposium complements perfectly the focus of CSE-2010 and provides additional breadth and depth to the main conference. Finally, we sincerely hope that you will enjoy the symposium and have a fruitful meeting in Hong Kong, China, December 11-13, 2010.

General Chairs

Kuan-Ching Li, Providence University, Taiwan

Rodrigo F. de Mello, University of Sao Paulo, Brazil

Program Chairs

Kuan-Chou Lai, National Taichung University, Taiwan

Ligang He, University of Warwick, UK

Message from the Workshop Chairs

WMSC 2010

Welcome to the 2010 IEEE International Workshop on Workflow Management in Service and Cloud Computing (WMSC-2010). This workshop has been co-located with the 13th IEEE International Conference on Computational Science and Engineering (CSE-2010) held on December 11-13, 2010, in Hong Kong, China.

CSE-2010 is the next event in a series of highly successful International Conferences on Computational Science and Engineering, held mainly as the International Workshop on High Performance Scientific and Engineering Computing for 10 editions, mostly in conjunction with International Conference on Parallel Processing (ICPP), as COATA-98 (Orlando, USA, July 1998), HPSEC-99 (Fukushima, Japan, September 1999), HPSEC-00 (Toronto, Canada, August 2000), HPSEC-01 (Valencia, Spain, September 2001), HPSEC-02 (Vancouver, Canada, August 2002), HPSEC-03 (Kaohsiung, Taiwan, October 2003), HPSEC-04 (Montreal, Canada, August 2004), HPCSE-04 with WCC-04 (Toulouse, France, August 2004), HPSEC-05 (Oslo, Norway, June 2005), and HPSEC-06 (Columbus, USA, August 2006). The previous CSE-08 and CSE-09 were held in São Paulo, Brazil, July 16-18, 2008 and Vancouver, Canada, August 29-31, 2009.

Workshops play a key role in the success of a conference and the WMSC-2010 focuses upon a cornerstone of workflow in service and cloud computing environments. The workshop had 26 papers submitted from a truly international set of authors. Of these 26 papers a final group of 14 papers were selected for oral presentation. Each of these had 2 reviews that were undertaken by an internationally recognized collection of workflow and service computing experts. We gratefully acknowledge their timely reviews of the papers and thank them for the professionalism shown in undertaking this task.

Any international conference or workshop cannot take place without the support and efforts of many people and organizations. We gratefully acknowledge the support of the CSE-2010 conference organizers. In particular we would like to express special thanks to Jiannong Cao, Laurence T. Yang, Hai Jiang, and Kuan-Ching Li for the excellent steering and organization of CSE-2010 and allowing the co-location of WMSC-2010.

We also would like to take opportunity to thank all the members of the organizing committee, the program vice-chairs and technical program committee as well as all of the authors who submitted papers and reviewers who reviewed huge number of papers.

We thank all of you for participating in WMSC-2010 and CSE-2010, and we hope you find the conference stimulating and constructive and at the same time enjoy the beautiful Hong Kong, China!

General Chair

Rajkumar Buyya, University of Melbourne, Australia

Program Chairs

Jianxun Liu, Hunan University of Science and Technology, China

Jinjun Chen, Swinburne University of Technology, Australia