



Open Archive Toulouse Archive Ouverte (OATAO)

OATAO is an open access repository that collects the work of some Toulouse researchers and makes it freely available over the web where possible.

This is an author's version published in: <https://oatao.univ-toulouse.fr/26972>

Official URL:

To cite this version :

Rolandi, Laura Victoria and Jardin, Thierry and Fontane, Jérôme and Gressier, Jérémie and Joly, Laurent Stability analysis of the compressible flow past a NACA0012 airfoil at low Reynolds numbers. (2020) In: 73rd Annual Meeting of the American Physical Society's Division of Fluid Dynamics (DFD), 22 November 2020 - 24 November 2020 (Chicago, United States). (Unpublished)

Any correspondence concerning this service should be sent to the repository administrator:

tech-oatao@listes-diff.inp-toulouse.fr

Abstract Submitted
for the DFD20 Meeting of
The American Physical Society

Stability analysis of the compressible flow past a NACA0012 airfoil at low Reynolds numbers LAURA VICTORIA ROLANDI, THIERRY JARDIN, JEROME FONTANE, JEREMIE GRESSIER, LAURENT JOLY, ISAE-SUPAERO, Universite de Toulouse, France — Compressible flows at low Reynolds number are characterized by very low density and/or pressure and, nowadays, they are of very interest since these conditions can be found in many innovative applications such as the Hyperloop train, the stratospheric flight and the martian exploration. In the view of stratospheric flight, our work aims to investigate how compressibility affects the wake dynamics of a NACA0012 profile. We first characterize the unsteady flow past the airfoil at $Re = 1000$ using DNS for various angles of attack $\alpha \in [0^\circ; 20^\circ]$ and Mach numbers up to $M = 0.5$. Compressibility is found to attenuate the double harmonic oscillations of the wake, which is directly observable in the aerodynamic coefficients. Then, a steady flow is obtained using the filtering technique of Åkervik *et al.* (2006). These flow fields are used as base flows for a global stability analysis. At these angles of attack the neutral curves are determined in the (M, Re) plane. For a given Reynolds number, we observe a stabilizing or a destabilizing effect of compressibility depending on the angle of attack, while the increase of the Mach number always results in a decrease of the critical Reynolds number for all α .

Laura Victoria Rolandi
ISAE-SUPAERO, Universite de Toulouse, France

Date submitted: 28 Jul 2020

Electronic form version 1.4