

Conference Paper

Machine Learning-assisted Antenna Design optimization: A Review and the State-of-the-art

Akinsolu, M. O., Mistry, K. K., Liu, B., Lazaridis, P. I., and Excell, P.

This is a paper presented at the 14th European Conference on Antennas and Propagation (EuCAP), Copenhagen, Denmark. The published version is available at:

<https://ieeexplore.ieee.org/document/9135936>

Copyright of the author(s). Reproduced here with their permission and the permission of the conference organisers.

Recommended citation:

Akinsolu, M. O., Mistry, K. K., Liu, B., Lazaridis, P. I., and Excell, P. (2020), 'Machine Learning-assisted Antenna Design optimization: A Review and the State-of-the-art', Presented at 14th European Conference on Antennas and Propagation (EuCAP), Copenhagen, Denmark, 15-20 March 2020. doi: [10.23919/EuCAP48036.2020.9135936](https://doi.org/10.23919/EuCAP48036.2020.9135936)

Machine Learning-assisted Antenna Design Optimization: A Review and the State-of-the-art

Mobayode O. Akinsolu*, Keyur K. Mistry†, Bo Liu*, Pavlos I. Lazaridis†, Peter Excell *

*Faculty of Arts, Science and Technology, Wrexham Glyndŵr University, Wrexham LL11 2AW, UK.

†School of Computing and Engineering, University of Huddersfield, Huddersfield HD1 3DH, UK.

*mobayode.akinsolu@glyndwr.ac.uk, b.liu@glyndwr.ac.uk and p.excell@glyndwr.ac.uk

†keyur.mistry@hud.ac.uk and p.lazaridis@hud.ac.uk

Abstract—Antenna design optimization continues to attract a lot of interest. This is mainly because traditional antenna design methodologies are exhaustive and have no guarantee of yielding successful outcomes due to the complexity of contemporary antennas in terms of topology and performance requirements. Though design automation via optimization complements conventional antenna design approaches, antenna design optimization still presents a number of challenges. The major challenges in antenna design optimization include the efficiency and optimization capability of available methods to address a broad scope of antenna design problems considering the growing stringent specifications of modern antennas. This paper presents a review of the most recent progress in antenna design optimization with a focus on methods which address the challenges of efficiency and optimization capability via machine learning techniques. The methods highlighted in this paper will likely have an impact on the future development of antennas for a multiplicity of applications.

Index Terms—antenna optimization, machine learning, surrogate model-based optimization.

I. INTRODUCTION

Over the last few decades, antennas and their associated systems have evolved rapidly due to unprecedented changes in their geometric and material profiles to meet modern applications such as body-centric communications [1] and multi-band operations for 2G/3G/4G/5G [2]. Generally, antennas can be designed by following rules of thumb which often premise on design experience [3]. Due to increasingly stringent specifications and the realization of additional performance requirements, present-day antenna structures are usually topologically and electromagnetically complex with a large number of sensitive design parameters [2]. Even though experience-based rules of thumb can provide a practical guide to antenna designers, they are mostly suitable for simple antenna structures and applying them correctly often yield sub-optimal designs (even for simple antenna structures [4]). Consequently, finding the best designs, which fulfil the desired performance for contemporary antennas, could be very challenging.

To address the above bottleneck, it is a common practice to fine-tune the geometric and/or material parameters of antenna structures for performance improvement. The most popular approaches still revolve around experience-based parameter sweeping of a few parameters at a time [1]. For modern antennas with many sensitive parameters, this process could

be time-consuming without any guarantee of successful outcomes - it is often a process of trial and error. Thus, the need for design automation via optimization. To improve the performance of antennas via optimization, local and/or global numerical optimization methods are chiefly employed [4]. Even though numerical optimization is evidently more superior than experience-driven parameter sweeping, there are still some challenges.

Local optimization methods often require a good initial design or starting point (which is typically not available in practice for modern antenna structures) to obtain good results [4]. Global optimization methods on the other hand are more attractive because of their robustness and non-requirement of an initial design, but they often require a very large (sometimes unaffordable) number of electromagnetic (EM) simulations to obtain near-optimum designs [4]. For a thorough characterization of antennas, numerical technique-based full-wave EM simulations are inevitable. Full-wave EM simulations are inherently computationally expensive. A one-time design characterization via an EM simulation does not constitute a problem, but the massive amounts of such EM simulations required by global optimization methods constitutes an unaffordable computational overhead.

To lower the computational overhead of antenna synthesis, machine learning methods are often used to aid numerical optimization methods by integrating them in the optimization kernel a priori and/or a posteriori [5], [6]. Surrogate modelling tends to be the most popular machine learning method used to aid numerical optimization methods for antenna synthesis [6]. In the optimization process, surrogate modelling mainly works by replacing computationally exact function evaluations (i.e., computationally expensive EM simulations) with computationally cheap approximation models. These approximation models are called surrogate models and they are usually constructed using statistical learning techniques [7]. Though a number of surrogate modelling techniques have been shown to be very successful for the machine learning-assisted optimization of EM designs [8], Gaussian process (GP) or kriging [9] tends to be popular in the antenna design domain [10]–[12]. The conjunctive use of surrogate modelling techniques and numerical optimization methods in a single optimization framework is referred to as surrogate-based optimization (SBO) [5], [6].

Several SBO methods employing local optimization methods and/or global optimization methods as their search engines have been proposed for the single-objective, multi-fidelity, multi-objective and process variation-aware or yield optimization of antennas [11], [13]–[16]. As a result, there is a variety of SBO paradigms for the machine learning-assisted optimization of antennas. In this review, state-of-the-art SBO methods for the machine learning-assisted optimization of antennas are discussed in an attempt to establish their use cases. Particularly, these methods are evaluated in terms of generality, efficiency, optimization capability and ease-of-use according to existing literature.

II. OPTIMIZATION OF ANTENNAS

A. Single-objective optimization

Very often antenna optimization problems are modeled as single-objective optimization problems. A typical example is the maximization of the isotropic gain [4]. Typically, a single-objective optimization can be mathematically described as shown in (1)

$$\begin{aligned} & \text{minimize} && f(x) \\ & \text{s.t.} && g_i(x) \leq 0, i = 1, 2, \dots, k. \\ & && x \in [a, b]^d. \end{aligned} \quad (1)$$

where x the decision variable (typically, a set of parametric values which describe an antenna design), d is the dimension of x and $[a, b]^d$ are the search ranges of the decision variable, $f(x)$ is the objective function such as the in-band maximum reflection coefficient to be minimized, $g_i(x)$ are the constraints such as the specifications on the gain, and k is the number of constraints. Considering a minimization problem, the optimal solution for (1) will be the value of the value of $x_o \in [a, b]^d$ where there is no other point $x_i \in [a, b]^d$ with $f(x_i) < f(x_o)$.

Typically, antenna optimization problems are constrained optimization problems. This is because antennas specifications are often two or more as described mathematically in (1). For most constrained optimization problems, a weighted sum of the constraints and the objective is used to derive a penalty function which then becomes the single objective function value for the optimization. This approach is called the penalty method [17] and it is the method mostly employed for the aggregation of the multiple requirements of antenna problems.

In recent times, several SBO methods have been proposed for the single-objective and/or constrained optimization of antennas [15], [18], [19]. In general, a critical trade-off between the surrogate model quality and the efficiency (premised on the essential number of EM simulations) exists in these SBO methods. This stems from the requirement of more training data points (which can only be obtained by expensive EM simulations) for the construction of high quality surrogate models. As a result, many SBO methods focus on efficiency improvement and the method to find an appropriate trade-off (i.e., a good balance between the quality of the surrogate modelling and the efficiency of the optimization) is called surrogate model management. Some of the recent approaches

proposed to address this challenge amongst others in SBO methods are discussed as follows.

To address the well-known wrong convergence issue in standard space-mapping optimization of antennas [20], a local search mechanism (the trust region (TR) approach) where a surrogate model is optimized in a restricted neighbourhood (i.e., a local region) is employed in [21]. For most practical cases, the Jacobian matrix which characterizes the linear model of the TR gradient search is evaluated through finite differentiation at the cost of additional EM simulations per algorithmic iteration [22]. The number of the additional EM simulations corresponds to the dimensionality of the design space; consequently, the Jacobian updates primarily decide the computational overhead of the optimization process. To reduce the computational cost of the TR gradient search in [21], a method which uses an adaptive scheme for sparse Jacobian updates is proposed in [15]. In [15], the Jacobian matrix is only updated in part by considering the relationship between the subsequent design vectors and TR region size.

To enhance the convergence speed, reduce the dimensionality of the search space and improve the starting point of the local search mechanism (TR gradient search in [21]), a multi-stage optimization method using large scale sensitivity analysis and local optimization routines is proposed in [19]. The method in [19] iteratively locates a feasible region in the antenna's multi-dimensional parameter space through a sequence of constrained optimization runs (considering a goal at a time). The optimization procedure is then initialized by focusing on the subspace of the most influential parameters (selected via a large scale sensitivity analysis) first to improve the starting point of the TR gradient search.

To circumvent the requirement of a starting point or an initial design, while ensuring high efficiency and good convergence speed, a class of SBO methods which offer a good balance between the quality of the surrogate modelling and the efficiency of the optimization have been proposed in [11], [12], [23]. This class of SBO methods employing global search and online surrogate models (i.e., surrogate models which are updated continuously throughout the optimization process) is called the surrogate model-assisted differential evolution for antenna optimization (SADEA) family of algorithms. SADEA family of algorithms use the state-of-the-art surrogate model-aware evolutionary search framework [24] for their surrogate model management and they offer three to 20 times speed improvement compared to standard global optimization methods [4]. They are robust and very generic because they have no limitations on the dimension space and no ad-hoc processes are required in their modus operandi.

B. Multi-fidelity optimization

Multi-fidelity optimization of antennas can easily be categorized as a class of antenna optimization efficiency improvement method on its own. Basically, the general idea of multi-fidelity optimization of antennas is to use cheaper and less accurate low-fidelity models to filter out non-promising solutions, and to use expensive but accurate high-fidelity models to

perform a search around "promising" solutions obtained by the low-fidelity model. Depending on the optimization framework, these models could be surrogate and/or EM models [25], [26]. To achieve this co-working, very often data-driven surrogate models and EM (i.e., antenna) models of varying accuracies or fidelities are integrated into a single optimization framework to lower the overall computational cost of optimization [27].

The primary challenge with machine learning-assisted multi-fidelity antenna optimization methods has always been how to efficiently ensure the uniqueness of the parameter extraction from the low-fidelity design space to the high-fidelity design space [26]–[28]. In recent times, a number of methods have been proposed to adequately overcome this bottleneck for various use cases [26], [27], [29]. Some of the latest methods are discussed as follows based on their innovations.

To lower the computational overhead of the multi-fidelity optimization of antennas, a conjunctive use of varying-fidelity antenna models with data-driven surrogate models is proposed in [29]. In [29], a surrogate model realized in a constrained domain through a space reduction technique is used. The space reduction technique works by employing the simplex formed by designs from the low-fidelity EM model design space to determine (by way of estimation) the lateral spread of the solution domain. The designs obtained from the low-fidelity design space are then verified/validated using a few high-fidelity EM simulations. Typically, only one of the final designs is required and used.

To improve the convergence speed of the multi-fidelity optimization of antennas, the method proposed in [26] exploits a number of multi-fidelity coarse models with increasing discretization levels (with the discretization level of the last one closest to the fine model) for the iterative construction of a series of local surrogate models by means of polynomial interpolation. In [26], a judgement factor based on the overall degree of similarity between the current surrogate model and the corresponding model is used to provide information for the update of the local region size. The optimized design of the final local surrogate model is assumed to be a good estimation of the optimal design of the high-fidelity model and its accuracy is improved by means of input space mapping performed in its local region.

To reliably handle model discrepancies in the multi-fidelity optimization of antennas, while ensuring high efficiency and good convergence speed, a multi-stage SBO method which features data mining and a local search mechanism is proposed in [27] stemming from the algorithmic framework in [30]. In [27], a one-off coarse model is used to carry out an SADEA-based optimization to generate a pool of data designs at the first stage. The pool of data designs from the first stage are then clustered using an iterative clustering algorithm to form an initial database for the final stage. At the final stage, a one-off fine model is used to carry out an SADEA-based optimization aided by a surrogate-model-assisted local search starting from the initial database from the previous stage. The method proposed in [27] is very generic because there are no

limitations on the dimension space and no ad-hoc processes are required for the update of the coarse and/or fine EM models (both are one-off in the entire optimization process).

C. Multi-objective optimization

Mathematically, a typical multi-objective optimization problem can be described according to (2). A typical case of an antenna design problem handled as a multi-objective optimization problem is the minimization of the reflection coefficient values within multiple bands and the minimization of the antenna structure for a planar antenna [31].

$$\begin{aligned} &\text{minimize} \quad \{f_1(x), f_2(x), \dots, f_m(x)\} \\ &x \in [a, b]^d. \end{aligned} \quad (2)$$

where $\{f_1(x), f_2(x), \dots, f_m(x)\}$ are the optimization objectives and m is the total number of objectives.

Multi-objective optimization techniques can be broadly classified into a priori and a posteriori methods according to the decision-making processes [32]. In contrast to a priori methods, a posteriori methods do not require prior preference information from the decision maker [32]. Instead, they produce a number of well representative optimal trade-off candidate solutions for a decision maker to check on a Pareto front (PF) - an image of Pareto optimal solutions (called the Pareto set) in the objective space [32]. A Pareto optimal solution is a candidate solution that obtains the best trade-off.

The primary challenge associated with the design and optimization of antennas using conventional multi-objective optimization methods is the overly large (often impractical) amount of expensive EM simulations required for the completion of the optimization process [33]. Additionally, after a successful run, the set of alternative design solutions generated by the Pareto front is often redundant when the designer preferences are vivid and only one final design solution is selected and used [34]. To overcome this challenge, several machine learning-assisted multi-objective optimization methods have been proposed in recent times for the synthesis of antennas [31], [34]–[36]. Some of these methods are discussed as follows based on their innovations.

To lower the computational overhead of the multi-objective optimization of antennas via off-line surrogate modelling (i.e., a one-off surrogate model construction in the optimization process), a sparsely connected backward propagation neural network is employed in [31]. The surrogate model in [31] is constructed only after the network parameters are adaptively tuned using hybrid real-binary particle swarm optimization algorithm [37] to promote global optimization capability, and a time-varying transfer function is set to lower the tendency of easily getting trapped into a local optimum and to improve convergence speed. It is then used to replace computationally expensive full-wave EM simulations in a standard multi-objective optimization framework using multi-objective evolutionary algorithms (MOEAs) to generate the PF.

To improve the convergence speed and to promote a better spread of design solutions for the multi-objective optimization of antennas via local search mechanisms, a non-dominated

and local search-assisted multi-objective optimization method is proposed in [35]. The method in [35] differs from the conventional multi-objective optimization methods via the adoption of a local search method to generate an improved population in the optimization process. To obtain the population for consecutive iterations, the traditional non-dominated sorting method [38] and the farthest-candidate method [38] are used. The population is updated by the local search for improved convergence speed by replacing current solutions with neighbouring solutions using the replacement strategy in [38]. As a result, boundary solutions (i.e., solutions with minimum and maximum fitness values) are prioritized for selection to ensure an even distribution of the Pareto-optimal solutions on the PF.

To lower the computational overhead and improve the convergence speed of the multi-objective optimization of antennas via surrogate modelling and variable-fidelity EM models, a robust methodology is presented in [34], [36]. The essential component of this method is the sequential domain patching of the design space. This is carried out by firstly generating extreme Pareto-optimal designs (two designs) realized by using an auxiliary low-fidelity model of the antenna conjunctively with a GP interpolation model in a standard multi-objective optimization framework using MOEA [39]. The patching process is then implemented as a stencil-based search targeted at linking the extreme Pareto-optimal designs through an iterative generation of subregions within the design space to have an initial approximation of the Pareto set. Since the initial Pareto set is realized at the level of a low-fidelity model, the final Pareto set is generated by refining the selected coarse designs using the output space mapping (OSM) procedure [40]. The OSM correction mainly ensures that at the beginning of each iteration the fitness of the refined models correspond to the fitness of the second-order polynomial approximation of the low-fidelity models [41].

D. Process variation-aware or yield-driven optimization

A majority of optimization-driven antenna design methods do not account for the likely discrepancies that may exist between the nominal antenna structure (often the optimal design obtained after optimization) and the actual (fabricated) antenna structure. For a robust design of antennas and to ensure a full design closure, statistical analysis is required for the quantification of the fabricated antenna deviations from its nominal design values. This procedure is referred to as process variation-aware or yield-driven design and it is aimed at maximizing the probability that a fabricated prototype will meet the performance specifications within the range of assumed statistical deviations from its nominal design [16], [42].

To carry out statistical modelling for yield evaluation, the traditional Monte Carlo (MC) method is the most common and generic method [42]. However, the number of trials required to have an accurate MC yield estimate is often large [42] leading to a slow convergence speed. Due to the slow convergence speed of MC and the dimensionality of

contemporary antennas, a very large number of samples (i.e., many hundreds to thousands of computationally expensive full-wave EM simulations and their responses) will be required for the yield analysis of antenna design problems [16]. This is computationally prohibitive; consequently, conventional statistical methods such as MC are not very popular for antenna design.

Though a number of techniques have been proposed for the expedited statistical analysis of EM models and microwave structures, these techniques have mostly been applied to the design of integrated circuits, multiconductors, microstrip and filters [43], [44]. With a focus on yield-driven design of antennas, a low-cost statistical analysis and yield optimization of antennas using auxiliary response surface approximation is proposed in [16]. In [16], a fast GP surrogate model is constructed within the vicinity of the nominal design (i.e., the optimal design obtained after an optimization run) and a low-cost MC analysis is carried out using the fast surrogate model. The yield estimate (i.e., the likelihood that the performance specifications stipulated for the antenna are satisfied within the range of assumed statistical deviations with respect to the fabrication and/or material tolerances) is then maximized using sequential approximate optimization by employing the local interpolation surrogate (statistically optimized) and rebuilt in a new domain.

As a way of lowering the computational overhead of yield-driven design of antennas, a performance-based nested surrogate modelling method using a two-level kriging is proposed in [45]. In [45], two varying surrogate models are considered - a first-level surrogate model which is used to identify the "promising region" of the parameter space by mapping the objective space into the geometry parameter space of the antenna to have the surrogate domain and the final (second level) surrogate model is built over the domain to connote the antenna responses. Since the dimension of design space is not very high, the mapping or surjective transformation adopted for parameter extraction makes the allocation of uniform training data points very straightforward in [45]. The same mapping subsequently allows for a suitable optimization of the surrogate which can then be directly used in a yield-driven optimization framework.

III. CONCLUSION

In this paper, present-day machine learning-assisted antenna optimization methods are reviewed. These methods have been discussed under the general forms or approaches to antenna optimization. Methods which are suitable for high-dimensional parameter spaces and multiple specifications without the requirement of initial designs and/or ad-hoc processes are recommended for use due to their generality, robustness and optimization capability to handle a variety of modern antenna design problem cases.

REFERENCES

- [1] C. Mendes and C. Peixeiro, "A dual-mode single-band wearable microstrip antenna for body area networks," *IEEE Antennas and Wireless Propagation Letters*, vol. 16, pp. 3055–3058, 2017.

- [2] A. Alieldin *et al.*, "A triple-band dual-polarized indoor base station antenna for 2G, 3G, 4G and sub-6 ghz 5G applications," *IEEE Access*, vol. 6, pp. 49 209–49 216, 2018.
- [3] T. Weiland, M. Timm, and I. Munteanu, "A practical guide to 3-d simulation," *IEEE Microwave Magazine*, vol. 9, no. 6, pp. 62–75, 2008.
- [4] V. Grout *et al.*, "Software solutions for antenna design exploration: A comparison of packages, tools, techniques, and algorithms for various design challenges," *IEEE Antennas and Propagation Magazine*, vol. 61, no. 3, pp. 48–59, 2019.
- [5] S. Koziel and L. Leifsson, *Surrogate-based modeling and optimization*. Springer, 2013.
- [6] S. Koziel and S. Ogurtsov, "Surrogate-based optimization," in *Antenna Design by Simulation-Driven Optimization*. Springer, 2014, pp. 13–24.
- [7] A. I. Forrester and A. J. Keane, "Recent advances in surrogate-based optimization," *Progress in Aerospace Sciences*, vol. 45, no. 1-3, pp. 50–79, 2009.
- [8] I. Couckuyt *et al.*, "Surrogate-based infill optimization applied to electromagnetic problems," *International Journal of RF and Microwave Computer-Aided Engineering*, vol. 20, no. 5, pp. 492–501, 2010.
- [9] T. J. Santner, B. J. Williams, W. Notz, and B. J. Williams, *The design and analysis of computer experiments*. Springer, 2003, vol. 1.
- [10] S. Koziel, S. Ogurtsov, I. Couckuyt, and T. Dhaene, "Variable-fidelity electromagnetic simulations and co-kriging for accurate modeling of antennas," *IEEE Transactions on Antennas and Propagation*, vol. 61, no. 3, pp. 1301–1308, 2012.
- [11] B. Liu, H. Aliakbarian, Z. Ma, G. A. Vandenbosch, G. Gielen, and P. Excell, "An efficient method for antenna design optimization based on evolutionary computation and machine learning techniques," *IEEE transactions on antennas and propagation*, vol. 62, no. 1, pp. 7–18, 2013.
- [12] B. Liu, M. O. Akinsolu, N. Ali, and R. Abd-Alhameed, "Efficient global optimisation of microwave antennas based on a parallel surrogate model-assisted evolutionary algorithm," *IET Microwaves, Antennas & Propagation*, vol. 13, no. 2, pp. 149–155, 2018.
- [13] S. Koziel and A. Bekasiewicz, "Fast em-driven size reduction of antenna structures by means of adjoint sensitivities and trust regions," *IEEE Antennas and Wireless Propagation Letters*, vol. 14, pp. 1681–1684, 2015.
- [14] A.-K. S. Hassan, A. S. Etman, and E. A. Soliman, "Optimization of a novel nano antenna with two radiation modes using kriging surrogate models," *IEEE Photonics Journal*, vol. 10, no. 4, pp. 1–17, 2018.
- [15] S. Koziel and A. Pietrenko-Dabrowska, "Reduced-cost electromagnetic-driven optimisation of antenna structures by means of trust-region gradient-search with sparse jacobian updates," *IET Microwaves, Antennas & Propagation*, vol. 13, no. 10, pp. 1646–1652, 2019.
- [16] S. Koziel and A. Bekasiewicz, "Sequential approximate optimisation for statistical analysis and yield optimisation of circularly polarised antennas," *IET Microwaves, Antennas & Propagation*, vol. 12, no. 13, pp. 2060–2064, 2018.
- [17] A. E. Smith, D. W. Coit, T. Baeck, D. Fogel, and Z. Michalewicz, "Penalty functions," *Evolutionary computation*, vol. 2, pp. 41–48, 2000.
- [18] S. Koziel and A. Bekasiewicz, "Fast surrogate-assisted frequency scaling of planar antennas with circular polarisation," *IET Microwaves, Antennas & Propagation*, vol. 13, no. 5, pp. 602–607, 2019.
- [19] A. Bekasiewicz and S. Koziel, "Reliable multi-stage optimization of antennas for multiple performance figures in highly-dimensional parameter spaces," *IEEE Antennas and Wireless Propagation Letters*, vol. 18, no. 17, pp. 1522–1526, 2019.
- [20] S. Koziel, F. Mosler, S. Reitzinger, and P. Thoma, "Robust microwave design optimization using adjoint sensitivity and trust regions," *International Journal of RF and Microwave Computer-Aided Engineering*, vol. 22, no. 1, pp. 10–19, 2012.
- [21] S. Koziel, J. W. Bandler, and Q. S. Cheng, "Robust trust-region space-mapping algorithms for microwave design optimization," *IEEE Transactions on Microwave Theory and Techniques*, vol. 58, no. 8, pp. 2166–2174, 2010.
- [22] S. Koziel and A. Pietrenko-Dabrowska, "An efficient trust-region algorithm for wideband antenna optimization," in *2019 13th European Conference on Antennas and Propagation (EuCAP)*. IEEE, 2019, pp. 1–5.
- [23] M. O. Akinsolu *et al.*, "A parallel surrogate model assisted evolutionary algorithm for electromagnetic design optimization," *IEEE Transactions on Emerging Topics in Computational Intelligence*, vol. 3, no. 2, pp. 93–105, 2019.
- [24] B. Liu *et al.*, "Behavioral study of the surrogate model-aware evolutionary search framework," in *2014 IEEE Congress on Evolutionary Computation (CEC)*. IEEE, 2014, pp. 715–722.
- [25] S. Koziel and A. Bekasiewicz, "Fast em-driven optimization using variable-fidelity em models and adjoint sensitivities," *IEEE Microwave and Wireless Components Letters*, vol. 26, no. 2, pp. 80–82, 2016.
- [26] Y. Song, Q. S. Cheng, and S. Koziel, "Multi-fidelity local surrogate model for computationally efficient microwave component design optimization," *Sensors*, vol. 19, no. 13, p. 3023, 2019.
- [27] B. Liu, S. Koziel, and N. Ali, "Sadea-II: A generalized method for efficient global optimization of antenna design," *Journal of Computational Design and Engineering*, vol. 4, no. 2, pp. 86–97, 2017.
- [28] S. Koziel and J. W. Bandler, "Reliable microwave modeling by means of variable-fidelity response features," *IEEE Transactions on Microwave Theory and Techniques*, vol. 63, no. 12, pp. 4247–4254, 2015.
- [29] S. Koziel and A. T. Sigurðsson, "Multi-fidelity em simulations and constrained surrogate modelling for low-cost multi-objective design optimisation of antennas," *IET Microwaves, Antennas & Propagation*, vol. 12, no. 13, pp. 2025–2029, 2018.
- [30] B. Liu, S. Koziel, and Q. Zhang, "A multi-fidelity surrogate-model-assisted evolutionary algorithm for computationally expensive optimization problems," *Journal of Computational Science*, vol. 12, pp. 28–37, 2016.
- [31] J. Dong, W. Qin, and M. Wang, "Fast multi-objective optimization of multi-parameter antenna structures based on improved bpnn surrogate model," *IEEE Access*, vol. 7, pp. 77 692–77 701, 2019.
- [32] G. Chiandussi, M. Codegone, S. Ferrero, and F. E. Varesio, "Comparison of multi-objective optimization methodologies for engineering applications," *Computers & Mathematics with Applications*, vol. 63, no. 5, pp. 912–942, 2012.
- [33] K. Slawomir and B. Adrian, *Multi-objective design of antennas using surrogate models*. World Scientific, 2016.
- [34] S. Koziel and A. Bekasiewicz, "Comprehensive comparison of compact uwb antenna performance by means of multiobjective optimization," *IEEE Transactions on Antennas and Propagation*, vol. 65, no. 7, pp. 3427–3436, 2017.
- [35] C. Zhang *et al.*, "New multi-objective optimisation algorithm for uniformly excited aperiodic array synthesis," *IET Microwaves, Antennas & Propagation*, vol. 13, no. 2, pp. 171–177, 2018.
- [36] S. Koziel and A. Bekasiewicz, "Multiobjective antenna design by means of sequential domain patching," *IEEE Antennas and Wireless Propagation Letters*, vol. 15, pp. 1089–1092, 2015.
- [37] N. Jin and Y. Rahmat-Samii, "Hybrid real-binary particle swarm optimization (HPSO) in engineering electromagnetics," *IEEE Transactions on Antennas and Propagation*, vol. 58, no. 12, pp. 3786–3794, 2010.
- [38] B. Chen, W. Zeng, Y. Lin, and D. Zhang, "A new local search-based multiobjective optimization algorithm," *IEEE Transactions on Evolutionary Computation*, vol. 19, no. 1, pp. 50–73, 2014.
- [39] S. Koziel, A. Bekasiewicz, and W. Zieniutycz, "Expedited em-driven multiobjective antenna design in highly dimensional parameter spaces," *IEEE Antennas and Wireless Propagation Letters*, vol. 13, pp. 631–634, 2014.
- [40] S. Koziel and S. Ogurtsov, "Multi-objective design of antennas using variable-fidelity simulations and surrogate models," *IEEE Transactions on Antennas and Propagation*, vol. 61, no. 12, pp. 5931–5939, 2013.
- [41] S. Koziel, "Computationally efficient multi-fidelity multi-grid design optimization of microwave structures," *Applied Computational Electromagnetics Society Journal*, vol. 25, no. 7, pp. 578–586, 2010.
- [42] J. F. Swidzinski and K. Chang, "Nonlinear statistical modeling and yield estimation technique for use in monte carlo simulations [microwave devices and ics]," *IEEE Transactions on Microwave Theory and Techniques*, vol. 48, no. 12, pp. 2316–2324, 2000.
- [43] I. S. Stievano, P. Manfredi, and F. G. Canavero, "Parameters variability effects on multiconductor interconnects via hermite polynomial chaos," *IEEE Transactions on Components, Packaging and Manufacturing Technology*, vol. 1, no. 8, pp. 1234–1239, 2011.
- [44] J. S. Ochoa and A. C. Cangellaris, "Random-space dimensionality reduction for expedient yield estimation of passive microwave structures," *IEEE Transactions on Microwave Theory and Techniques*, vol. 61, no. 12, pp. 4313–4321, 2013.
- [45] S. Koziel and A. Pietrenko-Dabrowska, "Performance-based nested surrogate modeling of antenna input characteristics," *IEEE Transactions on Antennas and Propagation*, vol. 67, no. 5, pp. 2904–2912, 2019.