

1 A review of BIM integration with building performance analysis in the project life-cycle

2 Ruoyu Jin^a, Botao Zhong^b, Ling Ma^{c,*}, Arman Hashemi^a, Lieyun Ding^b

3 ^aSchool of Environment and Technology, Univ. of Brighton, Brighton BN2 4GJ, U.K.

4 ^bSchool of Civil Engineering and Mechanics, Huazhong University of Science &
5 Technology, Wuhan, 430074, China

6 ^cThe Bartlett School of Construction and Project Management, University College London,
7 London WC1E 6BT, U.K.

8 Abstract

9 Adopting Building Information Modelling (BIM) in Building Performance Analysis (BPA)
10 is becoming an emerging research area in the application of information technology in the
11 Architecture, Engineering, and Construction (AEC) industry. To investigate the current state of
12 research in the adoption of BIM in BPA, this study performed a holistic review consisting of a
13 bibliometric analysis of existing literature, content analysis of selected studies, as well as
14 follow-up qualitative discussion in BIM integration with BPA. The bibliometric analysis
15 identified 60 relevant studies; the content analysis of these studies revealed the research
16 focuses of BIM-enabled BPA, including interoperability, semantics, and sustainability rating
17 systems; the qualitative discussion further highlighted the learning process throughout project
18 delivery stages and addressed the potential gap between ‘as-designed’ building performance
19 and ‘as-built’ performance. Overall, this study contributes to existing research by identifying
20 key input attributes and workflow in BPA, reviewing the state-of-the-art research on BIM
21 integration with BPA, and investigating the major research areas, namely, interoperability
22 issues in BIM-enabled BPA within the context of life-cycle BPA.

23 **Keywords:** Building information modelling; Building performance analysis;
24 Interoperability; Level of details; Energy performance.

25 1 Introduction

26 The building sector accounts for 20% to 40% of the overall energy consumption [74,79,97]
27 and one-third of the greenhouse gas emission worldwide[76]. It is vital to evaluate the energy
28 performance of a building in the design stage to ensure minimum building energy consumption
29 and maximum building performance before it is built because any changes to be made later are
30 subject to excessive cost and resource waste. The building performance analysis (BPA)
31 provides feedback on building design and facilitates the design optimisation. BPA in existing
32 studies has been primarily focused on building energy assessment[19,62,88]. However,
33 researchers in this study believe that BPA should cover a more comprehensive list of building
34 performance indicators besides energy performance, such as daylighting [24], carbon footprint
35 [9],and overall sustainability performance [7].

36 Traditionally, engineers who build the building energy models act as assistants to
37 architects and use professional tools in their domain. Recently, the integration of design tools
38 and building energy modelling tools have changed the way the two types of professional work
39 together. The emerging Building Information Modelling (BIM) technology is becoming part of

40 the design practice. BIM provides more accurate and interoperability capabilities than
41 traditional computer-aided design[65]. Traditionally, the indoor work of information input in
42 translating a geometric model to the simulation model is accomplished by an energy modeller.
43 This progress is complicated and time-consuming. Also, manual input work may lead to low
44 efficiency and limitation of data integration. BIM integrated multidisciplinary information in a
45 model which facilitates the BPA in preliminary design phases. BIM authoring tools not only
46 create geometric models but also can store non-graphical information such as material
47 properties. It could be used as a repository of the information for a building energy analysis,
48 such as the identity, geometry, material and other alphanumeric data of building components
49 [36].

50 Although BIM-enabled BPA has become an interactive and intuitive process such that a
51 designer without any simulation skill can perform the calculation which leads to analysis
52 reports including charts and diagrams, the reliability of the calculation depends on the richness
53 and accuracy of the information defined in the model. Multiple studies [16,67,75,100] have
54 emphasised that integration of BIM and BPA can optimise the building performance in early
55 design stages. It is also imperative that the designer establishes the knowledge base of the types
56 of BPAs required corresponding to different design stages with different Levels of
57 Development (LoDs). However, it remains a challenge of how to couple building information
58 and building performance models in the design lifecycle [67].It should be noticed that the
59 building information herein does not only include geometric models, but also non-geometric or
60 semantic information as demonstrated in existing studies focusing on transporting information
61 from BIM to BPA.

62 Although there have been a few studies [42,80,85] providing a review of studies on
63 integration of BIM and BPA, these existing studies were either limited to the review of
64 technological development (e.g., laser scanning) or data acquisition and analytics. For example,
65 the study of Gerrish et al. [32] demonstrated a method to link the data from BIM to building
66 operation through a case study of building design and operation. The feedback on user based
67 issues implementing BIM as a performance management tool [32] was collected through
68 follow-up interviews to stakeholders. So far limited review work has been done to consider
69 different project stages and their significance when applying BIM for BPA. This study aims to
70 investigate the contemporary research focuses and issues in BIM-enabled BPA based on a
71 thorough literature review. Section 2 provides the background of project design stages by
72 illustrating design details related to different building design stages; Section 3 describes the
73 literature review methodology; Section 4 illustrates the details of review-based analysis and
74 findings related to BIM integration with BPA; Section 5 summarises the content analysis of
75 BIM integration with BPA; Section 6 investigates the major research area (i.e., interoperability)
76 identified in the content analysis of the literature; Section 7 provides a further qualitative
77 discussion by incorporating project life cycle into the integrated BIM&BPA; and finally
78 Section 8 concludes the review-based study.


79 **2 Background**

80 The Royal Institute of British Architects (RIBA) divided a project lifecycle into eight
81 stages which serve as milestones for determining the activities of the project stakeholders and

82 agreeing on information deliverables[45]. Based on RIBA’s definitions, the activities of the
 83 conceptual design, preliminary design, and the detailed design stages are summarised herein.
 84 The deliverables at each stage include BPA at different LoDs, i.e., LoD100, LoD200, and
 85 LoD300. These are shown in Figure 1, Figure 2, and Figure 3.

86 2.1 Conceptual design (LoD100)

87 In the conceptual design stage, descriptions of internal environmental conditions and
 88 seasonal control strategies and systems should be prepared. At this stage, BPA requires the
 89 identification of design objectives, desired rooms or spaces, room sizes, relationships between
 90 spaces and relationships to the site. The content of BPA and information required in the
 91 conceptual design stage are shown in Figure 1.



92

93

Figure 1 BPA at the conceptual design stage – LoD100

94 BPA at the conceptual design stage includes:

- 95 • Sun and shadows analysis, which is to simulate the sun moves through the sky and analyse
 96 the shade on site;
- 97 • Energy loads analysis, which is to identify the area requires heating and cooling;
- 98 • Solar radiation analysis, which is to quantify the amount of the solar energy that can be
 99 used for energy generation on site;
- 100 • Daylighting analysis of conceptual design, which is to quantify the sunlight in the project
 101 that can be used to reduce light loads and cooling loads.

102 Generally, the energy consumption of a building can be affected by several factors, such as
 103 daylight harvesting, natural ventilation and thermal mass. There are some significant factors
 104 which are essential to energy consumption optimisation, such as the shape and size of a
 105 building [12], building orientation [1] and building topology [48].A BIM model that includes
 106 all the information is referred as LoD100.

107 2.2 Preliminary design (LoD200)

108 The preliminary design starts with sketches, floor plan studies, and 3D or physical models.
 109 The BPA at this stage requires floor plans, elevations, sections, area analysis, rendering and
 110 preliminary cost (Figure 2). A BIM model that includes all the information is referred as
 111 LoD200.




Figure 2. BPA at the preliminary design stage – LoD200

According to Figure 2, Building elements should be defined as general geometric primitives with approximate dimensions, shapes, location, and orientation. BPA at the preliminary design stage includes:

- Lighting and daylighting analysis, which is to test interior visual comfort with the help of computer simulation and lighting consultants;
- HVAC analysis, which is to adjust building systems, and compare results to determine the optimal configuration;
- Airflow analysis, which is to improve the air quality and natural ventilation;
- Energy use analysis, which is to calculate normal energy use (i.e., fuel and electricity) based on the building's geometry, climate, building type, envelope properties, and active systems (HVAC & Lighting).

Building design at this stage should be associated with a more accurate BPA. It is essential to take into account a comprehensive list of building information to assess building performance at the preliminary stage, including geometric, semantic and topological information [82]. Factors influencing building energy consumption would include building orientation, building layout and form, geometry, building fabrics, building envelope and passive strategies such as solar gain and shading strategies and natural ventilation strategies. Design optimisation could be assisted by building performance simulation through understanding and weighing the critical influence factors (e.g., building fabrics). Decision making during preliminary design stages would have an enormous effect on building energy performance.

2.3 Detailed design (LoD300)

The detailed design phase includes finalising the size of the rooms and spaces, refining the appearance, selecting materials, determining the systems, and deciding on the door and window types and locations. A full formal sustainability assessment should be carried out. A design stage carbon/energy declaration need to be undertaken.

At the end of the design development phase, the documents from the preliminary design phase need to be updated in further detail to support BPA. It is common to also have documents including specification outline, key details, interior schedules, and revised cost estimate, as shown in Figure 3. A BIM model that includes all the information is referred as LoD300.




Figure 3 BIM-enabled BPA at the detailed design stage – LoD300

The information specified at this stage should be able to support the generation of construction documents and shop drawings. The geometry of the building elements should be defined using more accurate quantity, size, shape, location, and orientation. Physical characteristics of the building elements should be defined as alphanumeric properties.

Building energy analysis in the detailed design stage includes:


- Detailed building energy use analysis of the final design and other performance-based analysis in support of detailed information, such as lighting and daylighting analysis, sun and shadow analysis, airflow and ventilation analysis;
- Greenhouse gas emission and carbon footprint analysis;
- Living comfort analysis;
- Cost analysis

3 The literature review method

The literature review of BIM-enabled BPA followed three steps:

- A bibliometric search and review of *Scopus*-indexed journal articles followed by categorising keywords focusing on BPA integrated with BIM;
- content analysis of existing studies linking BIM to BPA;
- qualitative discussion for applying LoDs into BIM-assisted BPA following the study of GhaffarianHoseini et al [35].

These research methods used in this paper are illustrated in Figure 4.



166
167

168 *Figure 4 Description of the study sections and corresponding research methods*

169 3.1 Initial review of BIM integration with BPA

170 The bibliometric analysis of the literature was carried out using VOSViewer [93].
171 VOSViewer supports the analysis of clustering solutions with visualisations[92]. Scopus was
172 chosen as the source to search the key published literature on BIM-enabled BPA, as it was
173 identified by Aghaei Chadegani et al. [14] that Scopus has broader coverage of journals in the
174 area of construction IT than other search engines including Web of Science with more recent
175 publications. The following query was used to retrieve recent publications on BIM-enabled
176 BPA.

177 TITLE-ABS-KEY ("BIM" OR "building information modelling" OR "building
178 information modelling") AND TITLE-ABS-KEY ("building performance" OR "energy
179 analysis" OR "energy performance")

180 The query limited the years of publication to recent ten years (from 2009 to 2018), only
181 Articles or Article in Press in Journals were included, and finally it restricted the language to be
182 English.

183 3.2 Content analysis of key studies linking BIM to BPA

184 Following the bibliometric review assisted by VOSViewer, content analysis, which is the
185 research method that has been adopted in multiple studies [28,91] in the field of engineering
186 and management, was adopted to summarise the research contents within the selected sample
187 of journal articles. Content analysis is a tool to examine trends and patterns in documents, and
188 it allows researchers to sift through a large amount of data with relative ease in a systematic
189 approach. The detailed steps of performing content analysis can be found in several existing
190 studies such as Bogus et al. [10].


191 3.3 Incorporating different project stages into the integrated BIM&BPA

192 Based on the design stage descriptions illustrated in Figures 1-3, bibliometric review,
193 content analysis, as well as existing studies stressing LoD and project life cycle[2], a follow-up
194 discussion targeting on the integrated BIM and BPA in the context of project stages was
195 initiated and discussed in a qualitative approach. The workflow was demonstrated,
196 highlighting the input of building parameters and outputs within different LoDs.

197 **4 The bibliometric analysis**

198 Following the bibliometric search in Scopus, manual searching and screening was also
199 conducted to weed out studies that did not fall into the scope of BIM-enabled BPA. For

200 example, the study of Jalaei et al. [46], although adopting BIM in the building conceptual
 201 design for decision making of material selection, did not focus on integrating BIM and BPA.
 202 Finally, 546 research papers in total were selected from Scopus. These papers have 6,264
 203 keywords; 299 of them, including both Author and Index keywords, were used in at least five
 204 papers. Some of the irrelevant or apparent keywords (e.g., BIM or building) were manually
 205 removed from the list. Then, some keywords with semantically similar meanings were
 206 categorised into the same terminology. For example, *air conditioning, heating, and ventilation*
 207 were categorised as *HVAC*; *Bayesian networks, decision trees, and artificial neural network*
 208 were all categorised as *Machine learning based methods*. After removing the irrelevant
 209 keywords and categorizing the remaining keywords with semantic similarities, 57 keywords
 210 are selected, as shown in Figure 5. These keywords were categorized and visualised to
 211 highlight the research focuses in recent years.



212
 213 *Figure 5 The identified 57 major keywords (not all the 57 keywords are visible)*


214 The font size of keywords indicates the frequency of them in the sample journal articles.
 215 The distance between two keywords could infer their closeness. For example, the *architectural,*
 216 *structural or building services design* is highly relevant to decision making and life-cycle
 217 assessment. It can be found that *architectural, structural or building services design, energy*
 218 *performance, and building performance assessment* are the most frequently studied as the
 219 research focuses. These frequently keywords can be found closely connected to the rest
 220 keywords (e.g., data acquisition, handling, and processing). The relationships among these
 221 keywords can be summarized as below:

- 222 • Energy performance of building is one of the widely studied building performance assisted
223 by BPA software, especially in the early design stages [56]. Other building performance
224 studied included, but were not limited to daylighting [24], and thermal comfort;
- 225 • Sustainability rating systems (e.g., LEED or Leadership in Energy and Environmental
226 Design) have been embedded in BIM-driven green building design [68];
- 227 • Influence factors to BPA that should be considered, for example, the real behaviour of
228 building users [26];
- 229 • The linkage between BIM and BPA could be achieved or showcased with certain hardware
230 and software, such as wireless sensor network to monitor thermal conditions in built
231 environment [64]
- 232 • Data shared between BIM and BPA need the further handling, processing, and analytics,
233 such as sensitivity analysis as showcased in Ahn et al. [3]. Multiple data analytics
234 approaches have been adopted in the assisting BIM-driven BPA, such as algorithms [37]
235 and programming [48]. These approaches have been applied in achieving optimization
236 [52]in building performance design;
- 237 • Interoperability-related data format (e.g., IFC or *Industry Foundation Class*) would be
238 needed to allow information exchange between BIM and BPA. The information would
239 include both geometric information [44]and semantic data [59].
- 240 • Other research focuses, such as utilising integrated BIM and BPA for engineering
241 education purpose [39], have not been widely studied.

242 These 57 keywords were categorised into six clusters which could be defined as:

- 243 • BPA measurements (e.g., *energy performance*);
- 244 • Design-related (e.g., *ecodesign*);
- 245 • Influence factors to BPA ;
- 246 • Equipment or hardware needed in BIM or BPA (e.g., *laser application*);
- 247 • Methodologies adopted (e.g., *machine learning-based methods*);
- 248 • Interoperability-related (e.g., *IFC*).

249 Not all the initially identified 57 keywords were all related to BIM-enabled BPA,
250 especially discussing the input (e.g., building envelope) and output variables (e.g., energy use)
251 in BPA. Therefore, these 57 keywords were further reduced to 15 according to their relevance
252 to this research. A total of 60 out of the 546 papers which used these 15 keywords were
253 identified for further content analysis. Figure 6 illustrates these 15 main keywords.



254
255 *Figure 6 Categorized keywords related to BIM integration with BPA*

256 According to Figure 6, BPA can be divided into these few major categories:

- 257
- Building energy performance (e.g., energy conservation)
 - 258 • Environmental sustainability
 - 259 • Indoor comfort including illumination and daylighting
 - 260 • Resources (e.g., water and carbon footprint)

261 Several main input factors in building design that would affect BPA include:

- 262
- Thermal characteristics of building elements (insulation, roofs, windows);
 - 263 • Building envelope including position and orientation information;
 - 264 • Heating, ventilation and air conditioning (HVAC) system


265 Besides these BPA categories, Figure 6 also indicates that sustainability assessment (e.g.,
266 LEED rating system[86]) is one of the key research areas[51]. It was suggested by Chong et al.
267 [22] that new BIM standards and guidelines should include requirements on BIM tools’
268 compliance with specific sustainability assessment. Interoperability is a crucial issue when
269 linking BIM into BPA. BIM offers interoperability opportunities and integration among
270 different players. Although BIM can provide accurate material quantities and building
271 components [34], insufficient interoperability between BIM and BPA raises barriers to reliable
272 BIM-based BPA such as energy assessment [21].

273 **5 Content analysis of the literature**

274 Content analysis was conducted to summarize the 60 papers selected in the previous
275 section. BIM-enabled BPA is achieved through BIM authoring tools and BPA analysis tools.
276 Some BIM authoring tools have integrated BPA to deliver lifecycle building performance
277 simulations, including expected energy demand, the projected financial running costs of the
278 energy demand and CO₂ emissions. BIM-enabled BPA allows a fast, accurate, and iterative
279 workflow as the ability to import the building geometry and thermal data from BIM has
280 significant potential to reduce the time and uncertainty in BPA [43]. The potential

281 interoperability between BIM and BPA was tested by Calquin et al. [11] to showcase how the
 282 existing BIM authoring tools (e.g., Autodesk Revit) could support BPA.

283 More statistical details of the totally 60 similar studies listed in Table 1 are summarised in
 284 Figure 7.



285
 286 *Figure 7 Frequency of research keywords in totally 60 research papers linking BIM to*
 287 *BPA*

288 As the showcases for demonstration purpose, Table 1 lists some typical examples of
 289 studies in linking BIM authoring tools to BPA tools.

290 *Table 1 Studies in linking BIM authoring tool to BPA tool*

Case study	BIM authoring	BPA tools	Data exchange and format	Information shared from BIM to BPA	Contribution
Eight-floor residential apartment building in Canada[51]	Autodesk Revit incorporating early stage design (i.e., conceptual design) information	Ecotect and IES-VE for energy analysis and lighting simulation	IFC and gbXML in Ecotect, and gbXML in IES-VE	Building's 3D geometric information, building components, services, Place and location	Plug-ins were created to enhance interoperability; The workflow developed in linking BIM to BPA enabled users to compare the select different materials and components for design and performance analysis.
A five-story	ArchiCAD	Energy-	IFC providing	Geometry and	Both the pros and cons of

library building in Korea [3]		Plus	information delivery manual (IDM) and model view definition (MVD)	space boundary information	full and semi-automation from BIM to energy simulation were discussed.
A high-rise residential building in the U.S.[75]	Autodesk Revit	Dynamo; Autodesk Green Building Studio	gbXML open schema	Project location, building type, moreover, building operating schedule, construction and material properties	A BIM-based framework was proposed and tested for building performance optimisation in the design stage
Five test cases in Modelica-BIM Structure Example package[57]	Autodesk Revit	Modelica-BIM Structure Example package	Revit2Modelica consisting of Revit Application Programming Interface (API)	Geometry, materials properties, and location information	BIM-based energy simulation using an Object-Oriented Physical Modelling approach using ModelicaBIM library was developed and validated.
A residential building and an instructional facility in the U.S.[43]	Autodesk Revit	The BPA tool not specified	gbXML	Thermal properties, but the limited geometric information could be transported from BIM to BPA	As-is building thermal properties were tested and updated in gbXML-based BIM for energy analysis.
An office building and a university library building in Korea[21]	Autodesk Revit and ArchiCAD	Energy-Plus	IFC converted to Input Data Format (IDF)	Building materials with thermal properties, geometry, space type	The BIM-enabled energy performance assessment process, a materials library, and a decision-support the system was initiated to address the low interoperability issue between BIM and BPA.

292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333

These few examples of previous studies are shown in Table 1 to demonstrate the existing research in addressing the gap of interoperability between BIM authoring tools and BPA tools through certain data format (e.g., IFC and gbXML). Although IFC and gbXML are the two major data formats studies on BIM-enabled BPA, researchers have also proposed alternative technical or managerial approaches, such as combination of design tools and visual programming language suggested by Negendahl [67] and Revit2Modelica consisting of Revit Application Programming Interface (API) developed by Kim et al. [57].


The research keywords in these 60 selected studies were divided into seven categories, namely project stages, BIM authoring tools, BPA tools adopted, input information in BIM, outputs in BPA, the data format, and key contributions & issues raised in the studies. Major findings are listed below:

- Interoperability[31,41,43,48,60,72] is one of the most frequently stressed issues in the integration of BIM and BPA. Multiple approaches have been proposed to address the interoperability issue, including algorithms [15,33,48], programming[9,25,55], and plug-ins [23,70,87]. Ontology and semantics[8,15,78]were addressed in some of these selected studies. These key terms, including framework [5,68,83], interface [58,69,77],prototype [13,18,40], and platform [21,27,46],have been frequently highlighted in these studies.
- Building energy performance is the most frequently studied BPA output, followed by carbon footprint, daylighting, thermal comfort, and indoor environmental quality.
- Various BIM authoring tools and BPA tools were adopted in these case studies. Compared to the BIM tools in which Autodesk Revit is the dominating software package, the use of BPA tools tended to vary widely.
- Most studies targeted at the building design stage, especially the early design stage as the phase where BIM can be coordinated with BPA. However, there has still been insufficient studies incorporating LoDs into the design stages. Gourlis and Kovacic [38] stressed the importance of incorporating LoDs in bridging BIM to building energy modelling (BEM) in order the reduce the uncertainties in integrated BIM and BEM, which are not solely an issue of software interoperability but also the redefinition of the design process.

The interoperability issue has been emphasised in the research of BIM integration to BPA. BPA for performance-based design is an area allowing the architects to create and explore different design alternatives [6]. There is a consensus on the need to achieve performance-based design via integrated use of BIM. Lack of integration and low levels of BIM use prevents applying BIM in the early design decisions to improve building energy performance. The issue of interoperability is widely present in many areas if collaboration and data exchange are needed [6]. An open data readable by any software package is considered vital to enhance the multi-party collaboration. Therefore, it is imperative to use an open standard that facilitates the collaborative work allowing any stakeholder to exchange data no matter what software where the data is created. The ISO-registered IFCdata standard can facilitate BIM interoperability by allowing information flow within the AEC industry [96]. IFC is a scheme widely accepted by the AEC industry to exchange BIM-based models [6]. It uses

334 four layers (i.e., resources, core, interoperability and domain) to describe the geometric
 335 information, semantic information, and ontology in a BIM-based model. Besides IFC, gbXML
 336 is another widely adopted scheme that facilitates the exchange of data between BIM and BPA
 337 tools. Previous studies [90,95,98] summarized in Figure6 shared the similar methodology by
 338 developing a framework, interface or platform with specific data schema (e.g., IFC or gbXML),
 339 defining the scope of input information in BIM (e.g., geometric zones) and BPA output (e.g.,
 340 energy performance), adopting a building case study for validation, and proposing
 341 recommendation for further improvements. In the web service based framework linking BIM
 342 to building energy simulation, Cheng and Das [20] highlighted code checking for automating
 343 the building design evaluation process. Unfortunately, the full potential of BPA has not been
 344 achieved due to lack of integration that prevents collaboration relationships throughout the
 345 project life cycle. It could also be indicated from existing studies of linking BIM to BPA that
 346 there is a further need of studying the interoperability between BIM and BPA tools when
 347 building components are in a higher LoD or when the building is more complex.

348 The content analysis results showed two major research problems in BIM integration with
 349 BPA: interoperability issues and BPA across the project life-cycle. To further address the
 350 interoperability issues in BIM integration with BPA, a total of 129 journal articles from the
 351 refined literature sample focusing on interoperability issues in BIM-enabled BPA were
 352 reviewed. Figure 8 illustrates these keywords within of the 129 BIM-interoperability related
 353 articles.



354
 355 *Figure 8 Keywords within interoperability-related issues in BIM*

356 It can be found that the design stages, including architectural and structural of buildings,
 357 are the keywords most frequently studied in the research. The connection lines convey the
 358 information summarised and evaluated below:

- 359 • The interoperability issues encountered in BIM, highlighted in multiple studies
 360 [4,71,83], have been more frequently studied in the area of energy performance

361 compared to other areas such as life cycle or GIS (i.e., Geographic Information System).
362 Currently, the interoperability in BIM is still low and limited to 3D coordination, and
363 there have been limited standards guiding performance-based design in BIM [6]. An
364 established standard to allow BIM in a multi-dimensional information transfer would be
365 needed for enhanced multi-stakeholder information interaction. The information
366 interaction should not be limited to design stages when utilizing BIM for BPA, but also
367 construction stages and follow-up phases in the project life cycle. Currently the BPA in
368 existing studies of BIM interoperability has been largely focusing on energy
369 performance. It is expected that a comprehensive coverage of building sustainability be
370 incorporated in an indicator system. This sustainability indicator system assisted by
371 integrated BIM and BPA should not be limited to energy performance, thermal comfort,
372 daylighting, but also resident health and wellbeing indoor;

- 373 • Data handling, storage, sharing, exchange in BIM interoperability is the key technical
374 issue, with specific mainstream information flow formats, such as IFC. Interoperability,
375 mainly related to IFC capacity to support information exchange among multiple BIM
376 tools for different applications (e.g., energy simulation) is one of the main BIM-related
377 research focuses according to Santos et al. [81]. Ugglá and Horemuz [89] tested the
378 geographic capabilities of IFC and found that the open BIM standard IFC could be
379 improved by adding a separate scale factor for the horizontal plane and support for
380 object-specific map projections. Venugopal et al. [94] found the ambiguous nature of
381 the current IFC definitions and suggested a semantically robust reform in order to
382 extend IFC and to define subsets as model view definitions (MVD). Other work
383 performed to improve the IFC schema can be found in various studies. For example, Sun
384 et al. [29] applied a content-based compression algorithm to reduce the redundant
385 information carried in the existing IFC files for information optimization. It could be
386 envisaged that enhanced IFC scheme or other open data platform will be implemented in
387 the future for seamless information flow in AEC projects;
- 388 • Non-graphic information defined by semantics and ontology is one of the researches
389 focuses. The interoperability issue within BIM-BPA integration should include both
390 graphics and semantic aspects. Semantic performance could enhance IFC
391 interoperability to BPA [73] and improve the interoperability between BIM and its
392 synergies [53]. Extending the BIM interoperability at the semantic level is important to
393 link BIM with other geospatial data crossing construction project stages [54]. Karan and
394 Irizarry [54] proposed a methodology to integrate BIM and GIS and applied the
395 semantic web technology for construction site planning, and stated that future work was
396 needed to develop an interoperable framework for linked data;
- 397 • Both technological aspects (e.g., data interoperability[47,78]) and managerial (e.g.,
398 collaboration among project parties [49,50] and data management [31]) have been
399 studied for the successful integration between BIM and BPA. The interface and
400 BIM-based “green” building platform to enable the information sharing among AEC
401 professionals, end-users and policymakers have been studied by El-Diraby et al. [27] to
402 emphasise both technical and managerial aspects of BIM. Interoperability issues in BIM

403 has not been the widely studied for AEC education and construction project
404 management (e.g., interdisciplinary communication). More studies could be performed
405 to verify how the improved interoperability would affect the AEC project performance,
406 e.g., productivity, cost, and scheduling, etc. From the managerial perspective, case
407 studies could be conducted to verify the effects of enhanced interoperability on project
408 performance.

409 **6 Qualitative Discussion**

410 This paper finally discusses the integration of BIM and BPA to facilitate a more precise
411 communication between architect/engineer and energy modeller/building performance analyst
412 at different stages of a building project.

413 At the design stages, the BIM model is enriched continuously. Section 2 has illustrated the
414 capabilities of BIM-enabled BPA with different model LoDs. The LoDs were defined (as
415 shown in Figure 1, Figure 2, and Figure 3) based on the LoD matrix proposed by
416 Abou-Ibrahim1 and Hamzeh[2]. Some research has taken into account the LoDs in
417 BIM-enabled BPA[30].

418 BPA can be conducted across the project life cycle. As the project progresses, the
419 building performance may not meet the original design requirement. As a result, building
420 performance monitoring measures should be taken to identify the gap between the designed
421 building performance and the actual performance, and potential causes of the gaps (e.g.,
422 human behaviour related factors studied by Chen et al. [17], Li et al. [99], and Magalhães et
423 al. [63]). The performance gap analysis strengthens the design review and knowledge base
424 proposed in the BIM-IKBMS framework by Ghaffarian et al. [35]. The comparison of
425 building performance and design review form the loop in the framework, which enables the
426 learning process in building design stages to address the gap between actual and designed
427 building performance. The building performance simulation would then be updated adopting
428 the developed deterministic or stochastic models by addressing the causes of performance
429 gaps. One example of the prediction model for building performance is data mining approach
430 studied by Singaravel et al.[84].

431 The proposed BIM-enabled BPA serve as the case by contributing to the knowledge base
432 – a digital asset. The knowledge base would provide a collection of previous experience,
433 history and operations for building components so that the building maintenance teams could
434 adopt efficient implements in certain similar cases according to Motawa and Almarshad [66].
435 As indicated by Singaravel et al. [84], deep-learning neural network approach could be one
436 method to allow reliable prediction of BPA using the established cases from the knowledge
437 base. The database could be further developed to apply Big Data for BPA by incorporating
438 more input parameters, such as user profile and building sector, etc.

439 More future research directions can be proposed following the discussion of
440 BIM-enabled BPA in the context of green buildings. For example, the performance analysis
441 of green buildings adopting integrated photovoltaics in the research of Kuo et al. [61] can be
442 extended by studying BIM-enabled BPA for buildings using renewable energy sources.
443 BIM-enabled BPA for green buildings can also be extended from low energy-based design to

444 other aspects of sustainability, such as low carbon, indoor comfort, and resource
445 consumption.

446 **7 Conclusions**

447 This study adopted multiple research methods in identifying the major research topics in
448 the area of BIM integration with BPA across the project life-cycle. A bibliometric review was
449 conducted to identify most frequent keywords within BIM integration with BPA. Major
450 categories within BPA (e.g., building energy performance) and corresponding influence
451 factors (e.g., building envelope) were identified through literature review.

452 The raising issue of interoperability between BIM and BPA was highlighted as one of the
453 main research areas. Through a further bibliometric analysis to narrow the scope of search
454 focusing on interoperability within BIM, it was indicated that 1) most interoperability issues
455 were related to application of BIM in building energy performance analysis; 2) both
456 geographic and semantic information was involved in studying BIM interoperability issues; 3)
457 both technical (e.g., data scheme) and managerial aspects should be considered critical in
458 integrating BIM to BPA. The interoperability issue was further studied using content analysis to
459 summarise 60 existing studies attempting linking BIM to BPA. Approaches to enhancing the
460 interoperability issue between BIM and BPA could be found in these terminologies, including
461 framework, interface, prototype, and platform, with critical methods proposed (e.g., algorithms,
462 programming, and plug-ins). Ontology and semantics have become the research focuses. This
463 research proposed the research directions to incorporate BIM to BPA crossing the building
464 project delivery stages.

465 Both bibliometric analysis and content analysis also revealed the importance of integrating
466 BIM and BPA in the project life-cycle. The LoDs at different project stages were highlighted
467 which involve essential building information and building performance outcomes. The
468 definition of LoDs enables information exchange and data sharing between BIM and BPA in
469 different design stages. This paper proposed the research direction which allows a more precise
470 communication between architect/engineer and energy modeller/building performance analyst
471 at different stages of a building project. The performance gap analysis, development of
472 knowledge base, and design review in the further discussion drive the ongoing learning process
473 in transporting information in the building design model to the building performance model.
474 Future case studies could be conducted to investigate the information exchange between BIM
475 and BPA crossing different stages in the project life cycle. Future research can also extend the
476 BIM-enabled BPA in a wider scope of green buildings by considering more sustainability
477 measurements or scenarios, such as the adoption of renewable energy sources, indoor comfort,
478 and resource consumptions, etc.

479 **Reference**

- 480 [1] F.H. Abanda, L. Byers, An investigation of the impact of building orientation on energy consumption in
481 a domestic building using emerging BIM (Building Information Modelling), *Energy* 97 (2016) 517-527.
- 482 [2] H. Abou-Ibrahim, F. Hamzeh, Enabling lean design management: An LOD based framework, *Lean*
483 *Construction Journal* 2016 (2016) 12-24.

-
- 484 [3] K.-U. Ahn, Y.-J. Kim, C.-S. Park, I. Kim, K. Lee, BIM interface for full vs. semi-automated building energy
485 simulation, *Energy and Buildings* 68 (PART B) (2014) 671-678.
- 486 [4] O.O. Akinade, L.O. Oyedele, K. Omoteso, S.O. Ajayi, M. Bilal, H.A. Owolabi, H.A. Alaka, L. Ayris, J.
487 Henry Looney, BIM-based deconstruction tool: Towards essential functionalities, *International Journal*
488 *of Sustainable Built Environment* 6 (1) (2017) 260-271.
- 489 [5] Z. Alwan, J.M. E.D. Love, P. Steve, B.J. Gledson, Towards green building performance evaluation using
490 asset information modelling, *Built Environment Project and Asset Management* 5 (3) (2015) 290-303.
- 491 [6] Y. Arayici, T. Fernando, V. Munoz, M. Bassanino, Interoperability specification development for
492 integrated BIM use in performance based design, *Automation in Construction* 85 (2018) 167-181.
- 493 [7] S. Azhar, W.A. Carlton, D. Olsen, I. Ahmad, Building information modeling for sustainable design and
494 LEED® rating analysis, *Automation in Construction* 20 (2) (2011) 217-224.
- 495 [8] C.A. Balaras, S. Kontoyiannidis, E.G. Dascalaki, K.G. Droutsa, Intelligent services for Building
496 Information Modeling - Assessing variable input weather data for building simulations, *Open*
497 *Construction and Building Technology Journal* 7 (2013) 138-145.
- 498 [9] L.C. Bank, B.P. Thompson, M. McCarthy, Decision-making tools for evaluating the impact of materials
499 selection on the carbon footprint of buildings, *Carbon Management* 2 (4) (2014) 431-441.
- 500 [10] S.M. Bogus, G.C. Migliaccio, R. Jin, Study of the relationship between procurement duration and
501 project performance in design-build projects: Comparison between water/wastewater and
502 transportation sectors, *Journal of Management in Engineering* 29 (4) (2013) 382-391.
- 503 [11] D.A.L. Calquin, G. Wandersleben, L.S. Castillo, Interoperability map between BIM and BPS software, in:
504 R.R. Issa, I. Flood (Eds.), 2014 International Conference on Computing in Civil and Building Engineering,
505 American Society of Civil Engineers (ASCE), 2014, pp. 601-608.
- 506 [12] T. Catalina, J. Virgone, V. Iordache, Study on the impact of the building form on the energy
507 consumption, 12th Conference of International Building Performance Simulation Association
508 Building Simulation 2011, BS 2011, Sydney, NSW, 2011, pp. 1726-1729.
- 509 [13] A. Cemesova, C.J. Hopfe, R.S. McLeod, PassivBIM: Enhancing interoperability between BIM and low
510 energy design software, *Automation in Construction* 57 (2015) 17-32.
- 511 [14] A.A. Chadegani, H. Salehi, M.M. Yunus, H. Farhadi, M. Fooladi, M. Farhadi, N.A. Ebrahim, A
512 Comparison between Two Main Academic Literature Collections: Web of Science and Scopus
513 Databases, *Asian Social Science* 9 (5) (2013) 18-26.
- 514 [15] S. Chardon, B. Brangeon, E. Bozonnet, C. Inard, Construction cost and energy performance of single
515 family houses: From integrated design to automated optimization, *Automation in Construction* 70
516 (2016) 1-13.
- 517 [16] C.-J. Chen, S.-y. Chen, S.-h. Li, H.-t. Chiu, Green BIM-based building energy performance analysis,
518 *Computer-Aided Design and Applications* 14 (5) (2017) 650-660.
- 519 [17] C. Chen, D.J. Cook, A.S. Crandall, The user side of sustainability: Modeling behavior and energy usage
520 in the home, *Pervasive and Mobile Computing* 9 (1) (2013) 161-175.
- 521 [18] L. Chen, W. Pan, A BIM-integrated Fuzzy Multi-criteria Decision Making Model for Selecting
522 Low-Carbon Building Measures, *Procedia Engineering* 118 (2015) 606-613.
- 523 [19] S.Y. Chen, A green building information modelling approach: Building energy performance analysis
524 and design optimization, *MATEC Web of Conferences*, Vol. 169, 2018.

-
- 525 [20] J.C.P. Cheng, M. Das, A bim-based web service framework for green building energy simulation and
526 code checking, *Journal of Information Technology in Construction* 19 (2014) 150-168.
- 527 [21] J. Choi, J. Shin, M. Kim, I. Kim, Development of openBIM-based energy analysis software to improve
528 the interoperability of energy performance assessment, *Automation in Construction* 72 (2016) 52-64.
- 529 [22] H.-Y. Chong, C.-Y. Lee, X. Wang, A mixed review of the adoption of Building Information Modelling
530 (BIM) for sustainability, *Journal of Cleaner Production* 142 (Part 4) (2017) 4114-4126.
- 531 [23] C.-C. Chou, C.-T. Chiang, P.-Y. Wu, C.-P. Chu, C.-Y. Lin, Spatiotemporal analysis and visualization of
532 power consumption data integrated with building information models for energy savings, *Resources,
533 Conservation and Recycling* 123 (2017) 219-229.
- 534 [24] L. Díaz-Vilariño, S. Lagüela, J. Armesto, P. Arias, Indoor daylight simulation performed on
535 automatically generated as-built 3D models, *Energy and Buildings* 68 (PART A) (2014) 54-62.
- 536 [25] B. Dong, Z. O'Neill, Z. Li, A BIM-enabled information infrastructure for building energy Fault Detection
537 and Diagnostics, *Automation in Construction* 44 (2014) 197-211.
- 538 [26] M. Eguaras-Martínez, M. Vidaurre-Arbizu, C. Martín-Gómez, Simulation and evaluation of building
539 information modeling in a real pilot site, *Applied Energy* 114 (2014) 475-484.
- 540 [27] T. El-Diraby, T. Krijnen, M. Papagelis, BIM-based collaborative design and socio-technical analytics of
541 green buildings, *Automation in Construction* 82 (2017) 59-74.
- 542 [28] J. Esther Paik, V. Miller, S. Mollaoglu, W. Aaron Sun, Interorganizational Projects: Reexamining
543 Innovation Implementation via IPD Cases, *Journal of Management in Engineering* 33 (5) (2017).
- 544 [29] G. Gao, Y.-S. Liu, M. Wang, M. Gu, J.-H. Yong, A query expansion method for retrieving online BIM
545 resources based on Industry Foundation Classes, *Automation in Construction* 56 (2015) 14-25.
- 546 [30] T. Gerrish, K. Ruikar, M. Cook, M. Johnson, M. Phillip, Using BIM capabilities to improve existing
547 building energy modelling practices, *Engineering, Construction and Architectural Management* 24 (2)
548 (2017) 190-208.
- 549 [31] T. Gerrish, K. Ruikar, M. Cook, M. Johnson, M. Phillip, C. Lowry, BIM application to building energy
550 performance visualisation and management: Challenges and potential, *Energy and Buildings* 144
551 (2017) 218-228.
- 552 [32] T. Gerrish, K. Ruikar, M. Cook, M. Johnson, M. Phillip, C. Lowry, BIM application to building energy
553 performance visualisation and managementChallenges and potential, *Energy and Buildings* 144 (2017)
554 218-228.
- 555 [33] P. Geyer, Systems modelling for sustainable building design, *Advanced Engineering Informatics* 26 (4)
556 (2012) 656-668.
- 557 [34] A. GhaffarianHoseini, D. Tien Doan, N. Naismith, J. Tookey, A. GhaffarianHoseini, Amplifying the
558 practicality of contemporary building information modelling (BIM) implementations for New Zealand
559 green building certification (Green Star), *Engineering, Construction and Architectural Management* 24
560 (4) (2017) 696-714.
- 561 [35] A. GhaffarianHoseini, T. Zhang, O. Nwadigo, A. GhaffarianHoseini, N. Naismith, J. Tookey, K.
562 Raahemifar, Application of nD BIM Integrated Knowledge-based Building Management System
563 (BIM-IKBMS) for inspecting post-construction energy efficiency, *Renewable and Sustainable Energy
564 Reviews* 72 (2017) 935-949.
- 565 [36] N. Ghiassi, F. Tahmasebi, A. Mahdavi, Harnessing buildings' operational diversity in a computational
566 framework for high-resolution urban energy modeling, *Building Simulation* 10 (6) (2017) 1005-1021.

-
- 567 [37] G.I. Giannakis, G.N. Lilis, M.A. Garcia, G.D. Kontes, C. Valmaseda, D.V. Rovas, A methodology to
568 automatically generate geometry inputs for energy performance simulation from ifc bim models,
569 14th Conference of International Building Performance Simulation Association, International Building
570 Performance Simulation Association, Hyderabad, India, 2015, pp. 504-511.
- 571 [38] G. Gourelis, I. Kovacic, Building Information Modelling for analysis of energy efficient industrial
572 buildings – A case study, *Renewable and Sustainable Energy Reviews* 68 (2017) 953-963.
- 573 [39] S.J. Guo, T. Wei, Cost-effective energy saving measures based on BIM technology: Case study at
574 National Taiwan University, *Energy and Buildings* 127 (2016) 433-441.
- 575 [40] A. Gupta, A. Cemesova, C.J. Hopfe, Y. Rezgui, T. Sweet, A conceptual framework to support solar PV
576 simulation using an open-BIM data exchange standard, *Automation in Construction* 37 (2014)
577 166-181.
- 578 [41] E. Guzmán Garcia, Z. Zhu, Interoperability from building design to building energy modeling, *Journal*
579 *of Building Engineering* 1 (2015) 33-41.
- 580 [42] S. Habibi, The promise of BIM for improving building performance, *Energy and Buildings* 153 (2017)
581 525-548.
- 582 [43] Y. Ham, M. Golparvar-Fard, Mapping actual thermal properties to building elements in gbXML-based
583 BIM for reliable building energy performance modeling, *Automation in Construction* 49 (2015)
584 214-224.
- 585 [44] N. Harmathy, Z. Magyar, R. Folić, Multi-criterion optimization of building envelope in the function of
586 indoor illumination quality towards overall energy performance improvement, *Energy* 114 (2016)
587 302-317.
- 588 [45] W.P. Hughes, A comparison of two editions of the RIBA Plan of Work, *Engineering, Construction and*
589 *Architectural Management* 10 (5) (2003) 302-311.
- 590 [46] F. Jalaei, A. Jrade, M. Nassiri, Integrating decision support system (DSS) and building information
591 modeling (BIM) to optimize the selection of sustainable building components, *Journal of Information*
592 *Technology in Construction* 20 (2015) 399-420.
- 593 [47] W. Jeong, K. Kim, A Performance Evaluation of the BIM-Based Object-Oriented Physical Modeling
594 Technique for Building Thermal Simulations: A Comparative Case Study, *Sustainability* 8 (7) (2016)
595 1-27.
- 596 [48] W. Jeong, J. Son, An Algorithm to Translate Building Topology in Building Information Modeling into
597 Object-Oriented Physical Modeling-Based Building Energy Modeling, *Energies* 9 (1) (2016).
- 598 [49] R. Jin, C. Hancock, L. Tang, C. Chen, D. Wanatowski, L. Yang, Empirical Study of BIM
599 Implementation–Based Perceptions among Chinese Practitioners, *Journal of Management in*
600 *Engineering* 33 (5) (2017).
- 601 [50] R. Jin, C.M. Hancock, L. Tang, D. Wanatowski, BIM Investment, Returns, and Risks in China’s AEC
602 Industries, *Journal of Construction Engineering and Management* 143 (12) (2017).
- 603 [51] A. Jrade, F. Jalaei, Integrating building information modelling with sustainability to design building
604 projects at the conceptual stage, *Building Simulation* 6 (4) (2013) 429-444.
- 605 [52] D. Jung, D. Lee, J. Shin, B. Song, S. Park, Optimization of energy consumption using BIM-based building
606 energy performance analysis, *Applied Mechanics and Materials* 281 (2013) 649-652.
- 607 [53] E.P. Karan, J. Irizarry, Extending BIM interoperability to preconstruction operations using geospatial
608 analyses and semantic web services, *Automation in Construction* 53 (Supplement C) (2015) 1-12.

-
- 609 [54] E.P. Karan, J. Irizarry, Extending BIM interoperability to preconstruction operations using geospatial
610 analyses and semantic web services, *Automation in Construction* 53 (2015) 1-12.
- 611 [55] H. Kim, K. Anderson, Energy Modeling System Using Building Information Modeling Open Standards,
612 *Journal of Computing in Civil Engineering* 27 (3) (2013) 203-211.
- 613 [56] I. Kim, J. Kim, J. Seo, Development of an IFC-based IDF converter for supporting energy performance
614 assessment in the early design phase, *Journal of Asian Architecture and Building Engineering* 11 (2)
615 (2012) 313-320.
- 616 [57] J.B. Kim, W. Jeong, M.J. Clayton, J.S. Haberl, W. Yan, Developing a physical BIM library for building
617 thermal energy simulation, *Automation in Construction* 50 (C) (2015) 16-28.
- 618 [58] J.B. Kim, W. Jeong, M.J. Clayton, J.S. Haberl, W. Yan, Developing a physical BIM library for building
619 thermal energy simulation, *Automation in Construction* 50 (2015) 16-28.
- 620 [59] K. Kim, G. Kim, D. Yoo, J. Yu, Semantic material name matching system for building energy analysis,
621 *Automation in Construction* 30 (2013) 242-255.
- 622 [60] S. Kota, J.S. Haberl, M.J. Clayton, W. Yan, Building Information Modeling (BIM)-based daylighting
623 simulation and analysis, *Energy and Buildings* 81 (2014) 391-403.
- 624 [61] H.J. Kuo, S.H. Hsieh, R.C. Guo, C.C. Chan, A verification study for energy analysis of BIPV buildings with
625 BIM, *Energy and Buildings* 130 (2016) 676-691.
- 626 [62] Z. Li, B. Dong, Short term predictions of occupancy in commercial buildings—Performance analysis for
627 stochastic models and machine learning approaches, *Energy and Buildings* 158 (2018) 268-281.
- 628 [63] S.M.C. Magalhães, V.M.S. Leal, I.M. Horta, Modelling the relationship between heating energy use
629 and indoor temperatures in residential buildings through Artificial Neural Networks considering
630 occupant behavior, *Energy and Buildings* 151 (2017) 332-343.
- 631 [64] M. Marzouk, A. Abdelaty, Monitoring thermal comfort in subways using building information
632 modeling, *Energy and Buildings* 84 (2014) 252-257.
- 633 [65] R. Miettinen, S. Paavola, Beyond the BIM utopia: Approaches to the development and
634 implementation of building information modeling, *Automation in Construction* 43 (Supplement C)
635 (2014) 84-91.
- 636 [66] I. Motawa, A. Almarshad, A knowledge-based BIM system for building maintenance, *Automation in
637 Construction* 29 (2013) 173-182.
- 638 [67] K. Negendahl, Building performance simulation in the early design stage: An introduction to
639 integrated dynamic models, *Automation in Construction* 54 (2015) 39-53.
- 640 [68] T.H. Nguyen, S.H. Toroghi, F. Jacobs, Automated Green Building Rating System for Building Designs,
641 *Journal of Architectural Engineering* 22 (4) (2016).
- 642 [69] M. Niknam, S. Karshenas, Sustainable Design of Buildings using Semantic BIM and Semantic Web
643 Services, *Procedia Engineering* 118 (2015) 909-917.
- 644 [70] S. Niu, W. Pan, Y. Zhao, A BIM-GIS Integrated Web-based Visualization System for Low Energy Building
645 Design, *Procedia Engineering* 121 (2015) 2184-2192.
- 646 [71] O. Oduyemi, M.I. Okoroh, O.S. Fajana, The application and barriers of BIM in sustainable building
647 design, *Journal of Facilities Management* 15 (1) (2017) 15-34.
- 648 [72] W. Pan, H. Qin, Y. Zhao, Challenges for energy and carbon modeling of high-rise buildings: The case of
649 public housing in Hong Kong, *Resources, Conservation and Recycling* 123 (2017) 208-218.

-
- 650 [73] P. Pauwels, D. Van Deursen, R. Verstraeten, J. De Roo, R. De Meyer, R. Van de Walle, J. Van
651 Campenhout, A semantic rule checking environment for building performance checking, *Automation
652 in Construction* 20 (5) (2011) 506-518.
- 653 [74] L. Pérez-Lombard, J. Ortiz, C. Pout, A review on buildings energy consumption information, *Energy
654 and Buildings* 40 (3) (2008) 394-398.
- 655 [75] M. Rahmani Asl, S. Zarrinmehr, M. Bergin, W. Yan, BPOpt: A framework for BIM-based performance
656 optimization, *Energy and Buildings* 108 (2015) 401-412.
- 657 [76] A. Robert, M. Kummert, Designing net-zero energy buildings for the future climate, not for the past,
658 *Building and Environment* 55 (2012) 150-158.
- 659 [77] H.-S. Ryu, K.-S. Park, A Study on the LEED Energy Simulation Process Using BIM, *Sustainability* 8 (2)
660 (2016) 13.
- 661 [78] R. Sacks, L. Ma, R. Yosef, A. Borrmann, S. Daum, U. Kattel, Semantic Enrichment for Building
662 Information Modeling: Procedure for Compiling Inference Rules and Operators for Complex Geometry,
663 *Journal of Computing in Civil Engineering* 31 (6) (2017).
- 664 [79] R. Saidur, Energy consumption, energy savings, and emission analysis in Malaysian office buildings,
665 *Energy Policy* 37 (10) (2009) 4104-4113.
- 666 [80] L. Sanhudo, N.M.M. Ramos, J. Poças Martins, R.M.S.F. Almeida, E. Barreira, M.L. Simões, V. Cardoso,
667 Building information modeling for energy retrofitting – A review, *Renewable and Sustainable Energy
668 Reviews* 89 (2018) 249-260.
- 669 [81] R. Santos, A.A. Costa, A. Grilo, Bibliometric analysis and review of Building Information Modelling
670 literature published between 2005 and 2015, *Automation in Construction* 80 (Supplement C) (2017)
671 118-136.
- 672 [82] A. Schlueter, F. Thesseling, Building information model based energy/exergy performance assessment
673 in early design stages, *Automation in Construction* 18 (2) (2009) 153-163.
- 674 [83] F. Shadram, T.D. Johansson, W. Lu, J. Schade, T. Olofsson, An integrated BIM-based framework for
675 minimizing embodied energy during building design, *Energy and Buildings* 128 (2016) 592-604.
- 676 [84] S. Singaravel, J. Suykens, P. Geyer, Deep-learning neural-network architectures and methods: Using
677 component-based models in building-design energy prediction, *Advanced Engineering Informatics* 38
678 (2018) 81-90.
- 679 [85] B. Soust-Verdaguer, C. Llatas, A. García-Martínez, Critical review of bim-based LCA method to
680 buildings, *Energy and Buildings* 136 (2017) 110-120.
- 681 [86] O. Suzer, Analyzing the compliance and correlation of LEED and BREEAM by conducting a
682 criteria-based comparative analysis and evaluating dual-certified projects, *Building and Environment*
683 147 (2019) 158-170.
- 684 [87] M.M. Tahmasebi, S. Banihashemi, M.S. Hassanabadi, Assessment of the Variation Impacts of Window
685 on Energy Consumption and Carbon Footprint, *Procedia Engineering* 21 (2011) 820-828.
- 686 [88] W. Tian, Y. Heo, P. de Wilde, Z. Li, D. Yan, C.S. Park, X. Feng, G. Augenbroe, A review of uncertainty
687 analysis in building energy assessment, *Renewable and Sustainable Energy Reviews* 93 (2018)
688 285-301.
- 689 [89] G. Ugglá, M. Horemuz, Geographic capabilities and limitations of Industry Foundation Classes,
690 *Automation in Construction* 96 (2018) 554-566.

-
- 691 [90] F.M. Ugliotti, M. Dellosta, A. Osello, BIM-based Energy Analysis Using Edilclima EC770 Plug-in, Case
692 Study Archimede Library EEB Project, *Procedia Engineering* 161 (2016) 3-8.
- 693 [91] W.P. Utama, A.P.C. Chan, R. Gao, H. Zahoor, Making international expansion decision for construction
694 enterprises with multiple criteria: a literature review approach, *International Journal of Construction*
695 *Management* 18 (3) (2017) 221-231.
- 696 [92] N.J. van Eck, L. Waltman, Citation-based clustering of publications using CitNetExplorer and
697 VOSviewer, *Scientometrics* 111 (2) (2017) 1053-1070.
- 698 [93] N.J. van Eck, L. Waltman, Software survey: VOSviewer, a computer program for bibliometric mapping,
699 *Scientometrics* 84 (2) (2010) 523-538.
- 700 [94] M. Venugopal, C.M. Eastman, J. Teizer, An ontology-based analysis of the industry foundation class
701 schema for building information model exchanges, *Advanced Engineering Informatics* 29 (4) (2015)
702 940-957.
- 703 [95] J. Wang, X. Wang, W. Shou, H.-Y. Chong, J. Guo, Building information modeling-based integration of
704 MEP layout designs and constructability, *Automation in Construction* 61 (2016) 134-146.
- 705 [96] J. Wu, J. Zhang, Automated BIM Object Classification to Support BIM Interoperability, in: Y. Lee, R.
706 Harris, C. Wang, C. Harper, C. Berryman (Eds.), *Construction Research Congress 2018: Sustainable*
707 *Design and Construction and Education*, CRC 2018, Vol. 2018-April, American Society of Civil Engineers
708 (ASCE), 2018, pp. 706-715.
- 709 [97] Y. Xing, N. Hewitt, P. Griffiths, Zero carbon buildings refurbishment—A Hierarchical pathway,
710 *Renewable and Sustainable Energy Reviews* 15 (6) (2011) 3229-3236.
- 711 [98] Z. Yang, A. Ghahramani, B. Becerik-Gerber, Building occupancy diversity and HVAC (heating,
712 ventilation, and air conditioning) system energy efficiency, *Energy* 109 (2016) 641-649.
- 713 [99] L. Yu, Q. Lu, Y. Liu, Influencing factors and prediction model of urban residential building energy
714 consumption based on BIM technology, *Boletin Tecnico/Technical Bulletin* 55 (6) (2017) 67-73.
- 715 [100] M.A. Zanni, R. Soetanto, K. Ruikar, Towards a BIM-enabled sustainable building design process: roles,
716 responsibilities, and requirements, *Architectural Engineering and Design Management* 13 (2) (2016)
717 101-129.
- 718