

# 1 A simplified method for predicting the settlement of circular footings on multi- 2 layered geocell-reinforced non-cohesive soils

3 S.N. Moghaddas Tafreshi<sup>1</sup>, T. Shaghaghi<sup>2</sup>, Gh. Tavakoli Mehrjardi<sup>3</sup>, A.R. Dawson<sup>4</sup>, M. Ghadrđan<sup>5</sup>

4 <sup>1</sup>Corresponding Author, Department of Civil Engineering, K.N. Toosi University of Technology, Tehran, Iran. Tel:  
5 +982188779473; Fax: +982188779476; E-mail address: nas\_moghaddas@kntu.ac.ir

6 <sup>2</sup>MSc graduated, Department of Civil Engineering, K.N. Toosi University of Technology, Tehran, Iran. Tel:  
7 +982188779473; Fax: +982188779476; E-mail address: tahereh.shaghaghi@gmail.com

8 <sup>3</sup>Department of Civil Engineering, Faculty of Engineering, University of Kharazmi, Tehran, Iran E-mail address:  
9 ghtavakoli@khu.ac.ir

10 <sup>4</sup>Nottingham Transportation Engineering Centre, University of Nottingham, Nottingham, UK. Tel: +441159513902;  
11 Fax: +441159513909; E-mail address: andrew.dawson@nottingham.ac.uk

12 <sup>5</sup>MSc graduated, Department of Civil Engineering, K.N. Toosi University of Technology, Tehran, Iran. Tel:  
13 +982188779473; Fax: +982188779476; E-mail address:mg1365@gmail.com

14

15 **Abstract:** Multiple layers of geosynthetic reinforcement, placed below foundations or in the supporting layers of road  
16 pavements, can improve section performance through several mechanisms, leading to reduction in stresses and  
17 deformations. This paper aims to present a new analytical solution, based on the theory of multi-layered soil system to  
18 estimate the pressure-settlement response of a circular footing resting on such foundations, specifically those  
19 containing geocell layers. An analytical model that incorporates the elastic characteristics of soil and reinforcement is  
20 developed to predict strain and confining pressure propagated throughout an available multi-layer system, is proposed.  
21 A modified elastic method has been used to back-calculate the elastic modulus in terms of strain and confining pressure  
22 with materials data extracted from triaxial tests on unreinforced and geocell-reinforced soil samples. The proposed  
23 model has been validated by results of plate load tests on unreinforced and geocell-reinforced foundation beds. The  
24 comparisons between the results of the plate load tests and proposed analytical method reflected a satisfactory accuracy  
25 and consistency, especially at expected, practical, settlement ratios. Furthermore, to have a better assessment of  
26 geocell-reinforced foundations' behavior, a parametric sensitivity has been studied. The results of this study show that  
27 the higher bearing pressure and lower settlement were achieved when number of geocell layer, secant modulus of  
28 geocell and the modulus number of the soil were increased. These results are in-line with the experimental results of  
29 the previous researchers. The study also permits the limits of effective and efficient reinforcement to be determined.

30

31 **KEYWORDS:** *Geosynthetic, analytical method, geocell layers, elastic modulus, bearing pressure, settlement*

## 32 1. Introduction

33 In the last decades, due to its cost savings, ease of construction and ability to improve the visual appearance,  
34 geosynthetic reinforced soil has been significantly exploited in geotechnical engineering applications such as  
35 road construction, railway embankments, lifeline provision, stabilization of slopes, and improvement of soft  
36 foundation beds (e.g., Collin et al., 1996; Raymond, 2002; Hufenus et al., 2006; Dash et al., 2007; Bathurst et al.,  
37 2009; Madhavi Latha and Somwanshi, 2009a; Zhang et al., 2009; Ling et al., 2009; Palmeira and Andrade, 2010;  
38 Pokharel et al., 2010; Boushehrian et al., 2011; Lambert et al., 2011; Yang et al. 2012; Thakur et al., 2012;  
39 Tavakoli Mehrjardi et al., 2012; Leshchinsky and Ling, 2013a,b; Yang and Han, 2013; Tanyu et al., 2013, Chen  
40 et al., 2013, Soudé et al., 2013; Avesani Neto et al., 2013; Kachi et al., 2013; Moghaddas Tafreshi et al., 2014;  
41 Indraratna et al., 2015). A desirable use of such reinforcements would be to improve the bearing capacity and  
42 settlement of footings. With this in mind, many researchers have investigated the beneficial ability of planar and  
43 cellular reinforcement (e.g. geocell) constructions and how best to arrange the inclusions so as to deliver  
44 effective reinforcement and to improve their bearing capacity and settlement response (Dash et al., 2007;  
45 Sitharam et al., 2007; Madhavi Latha and Rajagopal, 2007; Zhou and Wen, 2008; Chen and Chiu, 2008; Yoon et  
46 al., 2008; Sharma et al., 2009; Wesselo et al., 2009; Sireesh et al., 2009; Eid et al., 2009, Pokharel et al., 2010;  
47 Zhang et al., 2010a; Yang et al., 2012; Lambert et al., 2011; Kumar and Kaur, 2012; Tanyu et al., 2013; Tavakoli  
48 mehrjardi et al., 2013; Dash and Chandra Bora, 2013; Chen et al., 2013; Mehdipour et al., 2013; Biswas et al.,  
49 2013; Hegde and Sitharam, 2014; Huang, 2014, Song et al., 2014).

50 Recently, two of the current authors have shown that geocell reinforcement can be significantly more  
51 effective than a planar reinforcement, in improving the behaviour of foundation beds under static and repeated  
52 loads (Moghaddas Tafreshi and Dawson, 2010a;b). They attributed this to the superior confinement offered by  
53 the geocells in all directions, due to the frictional and passive resistance developed at the soil-geocell interfaces  
54 that increases the sand's bearing capacity and decreases the settlement of the foundation bed.

55 An analytical approach to the design of such footings and to explain their pressure-settlement behavior would  
56 be very useful. Although, there have been many experimental studies into the use of geocell reinforcement in  
57 civil engineering works, there are few analytical studies (e.g., Zhang et al. 2009; 2010a;b). Zhang et al. (2010a)  
58 presented a simple bearing capacity calculation method for a geocell-supported embankment on a soft subgrade  
59 based on the study of the reinforcement functions of a geocell layer beneath a road embankment. They indicated  
60 that their results were relatively close to the experimental results. Zhang et al. (2010b) idealized a geocell-  
61 reinforced mattress as a beam on a Winkler foundation in order to analyze its settlement response. Semi-analytic

62 solutions were developed to assess the deformations of, and internal forces in, the foundation ‘beam’. They  
63 reported that the interface resistance, related to the horizontal deformation of the composite beam (i.e., geocell-  
64 soil ‘beam’), had a reduction effect on the embankment settlement.

## 65 **2. Aim**

66 A literature review, briefly reported above, indicated that there remains a lack of analytical study into the  
67 behaviour of footings supported by a geocell-reinforced bed, particularly when that bed includes a multi-layered  
68 geocell. Therefore, this article seeks to redress this omission by providing a relatively simple analytical method,  
69 based on “n”-layered soil system theory (Hirai, 2008) and surface settlement of equivalent system (Vakili et al.,  
70 2008), for the evaluation of the pressure-settlement response of both unreinforced and multi-layered geocell-  
71 reinforced foundation beds. The results of this method have been compared with the results of plate load tests  
72 (Moghaddas Tafreshi et al., 2013) to investigate its validity. In addition, the effects of various parameters such as  
73 geocell and soil stiffness modulus, geocell layer height and diameter of plate load have been investigated so as to  
74 understand mechanisms for improving the pressure-settlements behaviour of such footings. Note that, although,  
75 the settlement-stress behavior of plate loading tests is not elastic, yet the aforementioned analytical method  
76 simulated the behavior as a Multiple Linear Elastic (MLE) model (i.e., non-linear elastic) permitting calculation  
77 of the elastic modulus of each layer, for each loading step.

## 78 **3. Problem statement**

79 Geosynthetic inclusions are most effective if used in the zone significantly stressed by the footing. Since, a  
80 concentrated stress bowl occupies a zone equal to or twice the depth of the footing width/diameter (the “effective  
81 depth” being approximately 1.2 – 2 m for a typical footing width/diameter), and the heights of commercially  
82 produced geocells are usually less than 200 mm (available cell depths produced by two key manufacturers in  
83 Europe and USA), a single thick layer of geocell beneath the footing is not possible for field construction. Even  
84 if it were, such a thick geocell layer would likely make compaction of cell-fill extremely difficult (Thakur et al.,  
85 2012; Moghaddas Tafreshi et al., 2014), consequently decreasing the performance of a thick single layer of  
86 geocell. Hence, practically, if such a depth of soil needs to be reinforced by geocells, it necessitates designers to  
87 use 3 to 4 layers of geocell with thickness  $\leq 200$  mm.

88 Hence, the use of several layers of geocell (say, three or four) each with a thickness  $\leq 200$ mm and with  
89 vertical spacing between successive layers of geocell is a practical alternative and could be a beneficial  
90 means of reinforcing the soil beneath a footing. The schematic cross-section of the foundation bed containing

91 geocell-reinforcement layers with the thicknesses of  $h_g$ , and of the footing, is shown in Fig. 1. In this figure,  
 92 the first geocell layer is located at a depth of  $u$  beneath the footing and the next geocell layers are placed after  
 93 an unreinforced soil thickness of  $h_s$ . It should be noted that, although there are three probable mechanisms by  
 94 which geocell transfers stress through the depth of foundation bed (“lateral resistance effect”, “vertical stress  
 95 dispersion effect” and “membrane effect”), this study tried to simulate all these factors by considering soil-  
 96 geocell layer as a composite material. Some simplification for a complicated problem like the current system  
 97 is inevitable. Here, the characteristics of the composite material have been defined according to the soil and  
 98 soil-geocell specimens in triaxial tests; and the simplifying assumptions made in the solution system mean  
 99 that the behavior of the geocell layers are considered to be uniform layers that only deform vertically. Since  
 100 the “ $n$ ”-layered soil system theory by (Hirai, 2008) and surface settlement of equivalent system (Vakili et al.,  
 101 2008) were employed for the evaluation of the pressure-settlement response of multi-layered geocell-  
 102 reinforced foundation beds, a summary of these methods is presented in Sections 5 and 6.

#### 103 4. Pressure-settlement variation of footing on unreinforced bed

104 For a semi-infinite soil medium of the elastic modulus  $E_n$  and Poisson’s ratio  $\nu_n$ , subjected to uniform  
 105 pressure  $q$  on a circular footing with radius  $a$ , the immediate settlement at the depth  $z$  below the center of flexible  
 106 footing is written as Eq. (1) (Harr, 1966). Eq. (1) is valid for a flexible footing and should be multiplied by  $\pi/4$   
 107 for a rigid footing.

$$w(z) = \frac{2aq(1-\nu_n^2)}{E_n} \left( \sqrt{1 + \frac{z^2}{a^2}} - \frac{z}{a} \right) \left\{ 1 + \frac{z/a}{2(1-\nu_n)\sqrt{1 + \frac{z^2}{a^2}}} \right\} \quad (1)$$

#### 108 5. N-Layered Soil System Theory (Hirai, 2008)

109 Hirai (2008) developed the elastic relationships of multilayer soil stiffness modulus that have been investigated,  
 110 previously, by Palmer and Barber (1940) and Odemark (1949). Fig. 2 shows a multi-layered soil system  
 111 composed of  $n$ -layers of soil subjected to vertical loads  $q$ . As shown in Fig. 2, the present procedure uses the  
 112 elastic moduli, i.e. Young’s modulus of  $E_m$ , Poisson’s ratio of  $\nu_m$  and thickness of  $H_m$  for  $m^{\text{th}}$  layer in  $n$ -layers of  
 113 multi-layered soil system. Parameters  $D$  and  $D_f$  are diameter and embedment depth of a footing, respectively.

114 The  $n$ -layered soil system shown in Fig. 2 was transformed into an equivalent two-layered soil system illustrated  
 115 in Fig. 3a. The equivalent elastic modulus of  $E_H$  (Hirai and Kamei, 2003; 2004) for  $(n-1)$  layers in Fig. 3a (where  
 116  $H=H_1+H_2+H_3+\dots + H_{n-1}$ ) was represented by:

$$E_H = \left[ \left\{ E_1 \frac{(1-\nu_n^2)}{(1-\nu_1^2)} \right\}^{\frac{1}{3}} \frac{H_1 - D_f}{H - D_f} + \sum_{j=2}^{n-1} \left\{ E_j \frac{(1-\nu_n^2)}{(1-\nu_j^2)} \right\}^{\frac{1}{3}} \frac{H_j}{H - D_f} \right]^3 \quad (2)$$

117 Next, the two-layered soil system in Fig. 3a was transformed into an equivalent single soil layer with elastic  
 118 modulus of  $E_n$  and Poisson's ratio of  $\nu_n$ , (the thickness of an equivalent single layer is  $H=H_e+H_n$ ) as shown in Fig.  
 119 3b, using the equivalent thickness relations (3) and (4) (Hirai and Kamei, 2003; 2004; Hirai, 2008). For the case  
 120 where  $E_H \geq E_n$ :

$$H_e - D_f = \left( \frac{E_H}{E_n} \right)^{1/3} (H - D_f) \quad (3)$$

121 and for the case where  $E_H \leq E_n$ :

$$H_e - D_f = \left[ 0.75 + 0.25 \left( \frac{E_H}{E_n} \right)^{1/3} \right] (H - D_f) \quad (4)$$

122 Likewise, Fig. 4 shows an equivalent system of soil layers to that previously illustrated in Fig. 2, but now each  
 123 soil layer has an equivalent thickness of  $H_{ie}$  and uniform  $E$  and  $\nu$  values for every layer ( $=E_n$  and  $\nu_n$ ). Thus the  
 124 system is reduced to a single layer system of thickness  $H_{1e}+H_{2e}+H_{3e}+\dots + H_{(n-1)e}+H_n$  and stiffness properties  $E_n$   
 125 and  $\nu_n$ . The equivalent thickness of each individual layer is required so as to obtain the thinning and strain of each  
 126 layer of the multilayered system as described in Section 7.2. According to the Palmer and Barber method (1940)  
 127 for a two-layer system and to Odemark's method (1949) for a multi-layered soil system, Eqs. (5a) and (5b),  
 128 respectively, were derived by Hirai (2008) for estimating the equivalent thickness of each layer for the case  
 129 where  $E_m \geq E_n$ :

$$H_{1e} - D_f = \left\{ \frac{E_1(1-\nu_n^2)}{E_n(1-\nu_1^2)} \right\}^{1/3} (H_1 - D_f) \quad (5a)$$

$$H_{me} = \left\{ \frac{E_m(1-\nu_n^2)}{E_n(1-\nu_m^2)} \right\}^{1/3} H_m \quad (m = 2 \sim n) \quad (5b)$$

130

131 For the case where  $E_m \leq E_n$ , by considering Terzaghi's approximate formula (1943), the equivalent thickness is  
 132 given by Eqs. (6a) and (6b):

$$H_{1e} - D_f = \left[ 0.75 + 0.25 \left\{ \frac{E_1(1-\nu_n^2)}{E_n(1-\nu_1^2)} \right\}^{1/3} \right] (H_1 - D_f) \quad (6a)$$

$$H_{me} = \left[ 0.75 + 0.25 \left\{ \frac{E_m(1-\nu_n^2)}{E_n(1-\nu_m^2)} \right\}^{1/3} \right] H_m \quad (m = 2 \sim n) \quad (6b)$$

133 where  $H_{1e}$  and  $H_{me}$  are the values of  $H_e$  for the first and subsequent layers ( $m=2$  to  $n$ ), respectively and  $E_1, \nu_1,$   
 134  $E_n, \nu_n$  and  $E_m, \nu_m$  are values of  $E_H$  and  $\nu$  for layers 1,  $n$  and  $m=2$  to  $n$ , respectively.

### 135 **6. Surface Settlement of Equivalent System (Vakili et al., 2008)**

136 [Vakili et al. \(2008\)](#) developed the method of Foster and Ahlvin (1959) to evaluate the surface settlement of the  
 137 equivalent system shown in Fig. 4. According to this method, the actual vertical surface deflection of a footing  
 138 ( $w$ ) was obtained by adding the amount of thinning,  $w_2$ , of the equivalent layer (with thickness of  $H_e$ ) between  
 139 the surface ( $z=0$ ) and a depth of  $z=H_e$  to the vertical deflection at a depth of  $z=H_e$  of a semi-infinite mass below  
 140 that depth (i.e. deflection of  $w_1$  at bottom of the equivalent layer). In the case of uniform pressure “ $q$ ” on a  
 141 flexible circular footing with radius “ $a$ ” (Fig. 4), supported by a semi-infinite mass,  $w_1$  is obtained by substituting  
 142 the value of  $z=H_e$  from Eq. (3)/ or Eq. (4) into Eq. (1) to obtain Eq. (7):

$$w_1 = \frac{2aq(1-\nu_n^2)}{E_n} \left( \sqrt{1 + \left( \frac{H_e}{a} \right)^2} - \frac{H_e}{a} \right) \left( 1 + \frac{H_e}{2a(1-\nu_n) \sqrt{1 + \left( \frac{H_e}{a} \right)^2}} \right) \quad (7)$$

143 Similarly, the vertical deflection at the center of loading on surface (i.e.  $w_0$  at depth of  $z=0$ ) of uniform equivalent  
 144 layer (i.e. for the footing on the equivalent layer), substituting the value of  $z=0$  into Eq. (1) results:

$$w_0 = \frac{2a(1-\nu_n^2)q}{E_n} \quad (8)$$

145 Eqs. (7) and (8) are valid for a flexible footing and should be multiplied by  $\pi/4$  for a rigid footing. The  
 146 vertical thinning of the equivalent layer (with thickness of  $H_e$  as in Fig 3b) between the loading surface ( $z=0$ ) and  
 147 a depth of  $z=H_e$  (i.e.  $(w_0-w_1)$ ), can be converted to the thinning,  $w_2$ , of the original layer (thickness  $H$  as in Figs. 2  
 148 and 3a), using Eq. (9):

$$w_2 = \frac{E_n}{E_H} (w_0 - w_1) \quad (9)$$

149 Hence, Eqs. (7) and (9) may be summed to obtain the actual total surface settlement of the circular footing  
 150 ( $w=w_1+w_2$ ).

## 151 7. Pressure-settlement variation of footing on multi-layer geocell-reinforced bed

### 152 7.1. Methodology

153 Fig. 5 shows a schematic model of a shallow circular footing with diameter,  $D=2a$ , located on a typical  $n$ -  
 154 layer foundation bed composed of “ $m$ ” geocell layers and “ $n-m$ ” soil layers, under the application of a  
 155 uniformly distributed surface load,  $q$ . The thicknesses of geocell and soil layers are  $h_g$  and  $h_s$ , respectively.  
 156 The first geocell layer is placed at a depth of  $u$  beneath the footing and the remaining geocell layers are  
 157 located after an unreinforced soil thickness of  $h_s$ . The effective depth,  $H_{eff}$ , is assumed as the depth to a point  
 158 below the footing at which only 10% of the applied stress on footing surface acts. The elastic modulus,  $E_i$ ,  
 159 and Poisson’s ratio,  $\nu_i$  ( $i=1, 2, 3, \dots, n$ ) of each layer is as given in Fig. 5.  $H_{n-1}$  is the thickness of the  $(n-1)^{th}$   
 160 layer which can be calculated using Eq. (10).

$$H_{n-1} = H_{eff} - u - mh_g - (m-1)h_s \quad (10)$$

161 The following simplifying assumptions are made in this analysis, as follows:

- 162 • The soil layers are homogeneous, isotropic and non-cohesive;
- 163 • The unreinforced and reinforced layers deform only in the vertical direction;
- 164 • The footing is circular with no embedment depth,  $D_f=0$ ;
- 165 • The behaviour of unreinforced and reinforced layers is assumed to be nonlinear elastic;
- 166 • Poisson’s Ratio is assumed to be in the range 0.2 - 0.3 (see below).

167 Note that, although ‘toothpaste’ lateral squeezing of soil between geosynthetically-reinforced soil layers is a  
168 possibility for plastic soils, granular soils are unlikely to experience this if the reinforcing layers confine the  
169 granular soil closely. As observed in the tests at near full-scale by [Wu et al. \(2013\)](#), it is then the  
170 reinforcement with the granular soil that controls, partly horizontal movement due to the frictional resistance  
171 developed between the reinforcement and the soil and due to the nearby position of the reinforcing layers  
172 disrupting potential shear planes/dislocation zones.

173 However, it is known that geocell layers don’t expand much horizontally once properly filled with granular  
174 soil and compacted ([Dash et al., 2007](#); [Pokharel, 2010](#)). Thus the proposed analytical model does not directly  
175 consider lateral deformation but, instead, allows for some, indirectly, by using:

176 (1) elasticity moduli of the soil and geocell-reinforced layers that were obtained from calibration of the  
177 proposed equations (see Section 8.1) to the data obtained in the triaxial test that included some lateral  
178 deformation, and

179 2) Poisson’s Ratio values of 0.2 – 0.3, for the unreinforced and geocell-reinforced layers of the  
180 foundation bed to compute the equivalent thickness of the multi-layered system (see Section 5), being in-line  
181 with typical values as used by [Mhaikar and Mandal \(1996\)](#) and [Zhang et al. \(2010c\)](#), as described later (see  
182 Section 8.1.2).

## 183 7.2. Incremental Formulation using Nonlinear Elastic Method

184 As mentioned in section 2, the “n”-layered soil system theory ([Hirai, 2008](#)) and surface settlement of  
185 equivalent system ([Vakili et al., 2008](#)) were employed to evaluate the pressure-settlement of footings  
186 supported by a multi-layer geocell-reinforced bed as shown in Fig. 5. Fig. 3 shows the process of substituting  
187 the n-layer system with an equivalent single-layer system, here with the limitation that  $D_f=0$ . To do so, firstly,  
188 the upper “n-1” layers of thicknesses  $H_1, H_2, H_3, \dots$  and  $H_{n-1}$  (Fig. 5) should be replaced by a single layer of  
189 thickness ( $H_{eff}=H_1+H_2+H_3+\dots+ H_{n-1}$ ) having an equivalent modulus of  $E_H$  in Fig. 6a ([Hirai, 2008](#)). The  
190 equivalent elastic modulus ( $E_H$ ) of layers 1 to  $n-1$ , is calculated by using Eq. (2) for the footing with no  
191 embedment depth ( $D_f=0$ ) as Eq. (11).



$$E_H = \left[ \sum_{j=1}^{n-1} \left\{ E_i \frac{(1-\nu_n^2)}{(1-\nu_j^2)} \right\}^{\frac{1}{3}} \frac{H_j}{H_{eff}} \right]^3 \quad (11)$$

192 where,  $H_i$  and  $E_i$  are the thickness and elastic modulus of  $i^{\text{th}}$  layer, respectively. The  $n$ -layer system in Fig. 5  
 193 is thus reduced to a two layers system as shown in Fig. 6a.

194 The two-layered system (Fig. 6a) can be reduced to an equivalent single-layer system (Fig. 6b) with elastic  
 195 modulus of  $E_n$  and an equivalent thickness of  $H_e$ . The equivalent thickness ( $H_e$ ) with the elastic modulus of  $E_n$   
 196 and Poisson's Ratio of  $\nu_n$  is then defined by Eq. (12a) for the case where  $E_H \geq E_n$  and by Eq. (12b) for the case  
 197 where  $E_H \leq E_n$ . Eq. (12a) and Eq. (12b) provided for the same Poisson's Ratio of the two layers in Fig. 6a  
 198 where  $E_n$  is the elastic modulus of the  $n^{\text{th}}$  layer.

$$H_e = \left( \frac{E_H}{E_n} \right)^{1/3} H_{eff} \quad (12a)$$

$$H_e = \left[ 0.75 + 0.25 \left( \frac{E_H}{E_n} \right)^{1/3} \right] H_{eff} \quad (12b)$$

199 Consequently, the use of Eq. (11) and Eq. (12) deliver an equivalent single homogeneous semi-infinite mass  
 200 of material which can be substituted for the  $n$ -layer system as shown in Fig. 6b.

201 Generally, the footing settlement (i.e, soil surface settlement),  $w$  should be calculated using Eqs. (7) to  
 202 (10). Since, the nature of footing pressure-settlement variation is nonlinear, the behavior of unreinforced  
 203 layers and reinforced layers (Geocell and soil inside of its pockets) are considered to act as MLE (Multiple  
 204 Linear Elastic) layers. The MLE model provides an ability to calculate the elastic modulus of each layer, for  
 205 each load step, using the confining pressure of the current and previous stages as described in Eqs. (13) to  
 206 (23).

207 To calculate the elastic modulus of the  $i^{\text{th}}$  layer, requires knowledge of the strain of layers 1 to  $n-1$ . To  
 208 compute these, the deformation and equivalent thickness of the  $i^{\text{th}}$  layer (Fig. 5) are required. Using Eq. (5)  
 209 and Eq. (6) for the footing with no embedment depth ( $D_f=0$ ), supported on a multi-layer system, the

210 equivalent thickness of each soil layer,  $H_{ie}$  with the same  $E_n$  and  $\nu_n$  was determined by Eq. (13a) for the case  
 211 where  $E_i \geq E_n$  and by Eq. (13b) for the case where  $E_i \leq E_n$ , respectively.

$$H_{ie} = \left\{ \frac{E_i (1 - \nu_n^2)}{E_n (1 - \nu_i^2)} \right\}^{1/3} H_i \quad (13a)$$

$$H_{ie} = \left[ 0.75 + 0.25 \left\{ \frac{E_i (1 - \nu_n^2)}{E_n (1 - \nu_i^2)} \right\}^{1/3} \right] H_i \quad (13b)$$

212 Then, from Eqs. (7) and (9), for a rigid circular footing with radius  $a$  subjected to uniform pressure  $q$ , the  
 213 thinning and strain of the  $i^{\text{th}}$  layer are defined as Eqs. (14) to (16):

$$w_i = \frac{2\pi a q (1 - \nu_n^2)}{4E_n} \left( \sqrt{1 + \left( \frac{\sum_{l=1}^{l=i} H_{le}}{a} \right)^2} - \frac{\sum_{l=1}^{l=i} H_{le}}{a} \right) \left( 1 + \frac{\sum_{l=1}^{l=i} H_{le}}{2a(1 - \nu_n) \sqrt{1 + \left( \frac{\sum_{l=1}^{l=i} H_{le}}{a} \right)^2}} \right) \quad (14)$$

$$w_{pi} = \frac{E_n}{E_i} (w_i - w_{i-1}) \quad (15)$$

$$\varepsilon_i = \frac{w_{pi}}{H_i} \quad (16)$$

214 Where:

215  $H_{ie}$ : equivalent thickness of the  $i^{\text{th}}$  layer based on the elastic parameters of the  $n^{\text{th}}$  layer

216  $w_i$ : displacement at a depth of  $\sum_{l=1}^{l=i} H_{le}$

217  $w_{pi}$ : the vertical deformation within the  $i^{\text{th}}$  layer of thickness  $H_{ie}$ , (due to actual thinning of the  $i^{\text{th}}$  layer)

218  $\varepsilon_i$ : the strain across the thickness of the  $i^{\text{th}}$  layer

219 In the  $j^{\text{th}}$  loading step, the displacement increment of soil surface due to loading increment of  $q_j - q_{j-1}$  can be  
 220 calculated by Eqs. (17) to (20):

$$\Delta w_1^j = \frac{2\pi a(q_j - q_{j-1})(1 - \nu_n^2)}{4E_n} \left( \sqrt{1 + \left(\frac{H_e}{a}\right)^2} - \frac{H_e}{a} \right) \left( 1 + \frac{H_e}{2a(1 - \nu_n) \sqrt{1 + \left(\frac{H_e}{a}\right)^2}} \right) \quad (17)$$

$$\Delta w_0^j = \frac{2\pi a(1 - \nu_n^2)(q_j - q_{j-1})}{4E_n} \quad (18)$$

$$\Delta w_2^j = \frac{E_n}{E_H} (\Delta w_0^j - \Delta w_1^j) \quad (19)$$

$$w^j = w^{j-1} + \Delta w_1^j + \Delta w_2^j \quad (20)$$

221 Where:

222  $\Delta w_1^j$  : vertical displacement increment on loading centerline at a depth of  $H_e$  for loading increment of  $q_j - q_{j-1}$ , (i.e.  
223 at the bottom of the equivalenced layer)

224  $\Delta w_0^j$  : vertical displacement increment at surface (of equivalent layer) beneath centre of load for loading  
225 increment of  $q_j - q_{j-1}$ ,

226  $\Delta w_2^j$  : vertical deformation (thinning) increment of the original layer of thickness of  $H$ ,

227  $w^j$  : vertical displacement at surface of system for loading of  $q_j$ .

228 Similarly, the strain increment for the  $i^{\text{th}}$  layer at the  $j^{\text{th}}$  loading step can be calculated using Eqs. (21) to (23)  
229 using the adjustments already employed to formulate Eqs. (14) and (16):

$$\Delta w_i^j = \frac{2\pi a(q_j - q_{j-1})(1 - \nu_n^2)}{4E_n} \left( \sqrt{1 + \left(\frac{\sum_{l=1}^{l=i} H_{le}}{a}\right)^2} - \frac{\sum_{l=1}^{l=i} H_{le}}{a} \right) \left( 1 + \frac{\sum_{l=1}^{l=i} H_{le}}{2a(1 - \nu_n) \sqrt{1 + \left(\frac{\sum_{l=1}^{l=i} H_{le}}{a}\right)^2}} \right) \quad (21)$$

$$(\Delta w_p)_i^j = \frac{E_n}{E_i} (\Delta w_i^j - \Delta w_{i-1}^j) \quad (22)$$

$$\varepsilon_i^j = \varepsilon_i^{j-1} + \frac{(\Delta w_p)_i^j}{H_i} \quad (23)$$

230 where:

231  $H_{ie}$ : equivalent thickness of the  $i^{\text{th}}$  layer based on the elastic parameters and thickness of the  $n^{\text{th}}$  layer as defined  
 232 by Eq (13),

233  $\Delta w_i^j$ : displacement increment of equivalent layer for layers 1 to  $i$  based on the elastic parameters of  $n^{\text{th}}$  layer in  
 234 depth of  $\sum_{l=1}^{l=i} H_{le}$  for loading increment of  $q_j - q_{j-1}$ ,

235  $(\Delta w_p)_i^j$ : deformation increment (thinning) of layer with thickness of  $H_i$  for loading increment  $q_j - q_{j-1}$ ,

236  $\varepsilon_i^j$ : strain of layer with thickness of  $H_i$  subjected to loading  $q_j$ .

## 237 8. Results and discussion

238 To validate the results of the method presented above, the pressure-settlement response of a footing on  
 239 unreinforced and geocell-reinforced beds was estimated and compared with the results of four static plate  
 240 load tests (Moghaddas Tafreshi et al., 2013). As Fig. 7 shows, they performed the static plate load tests of a  
 241 footing supported on unreinforced soil and reinforced soil with geocell layers in a test pit measuring  
 242 2000×2000 mm in plane and 700 mm in depth using a 300 mm diameter rigid plate. The vertical distances of  
 243 the first layer of geocell ( $u$ ) from the footing and also that from each other ( $h_s$ ) were 0.2 times the footing  
 244 diameter. Also, the width of the geocell layers ( $b$ ) was held constant at 5 times the footing diameter ( $b/D=5$ ).  
 245 Since the horizontal dimensions of the test pit were about seven times bigger than the diameter of the footing  
 246 model and it was observed that the soil surface bulging around the footing model extended less than 1.5 times  
 247 the footing diameter from the circumference of the footing, the boundary effect of the pit walls on the test  
 248 results was likely insignificant. Also, regarding the test pit depth, the zone of influence of the footing will be  
 249 over a depth of less than 2 diameters beneath the footing (the “effective depth”), so the boundary effect of  
 250 test pit base on the test results may also be considered to be insignificant. Thus it should be viable to compare  
 251 the analysis results with the experimental ones.

252 The soil was well graded sand (SW, according to the Unified Soil Classification System, ASTM D 2487-  
 253 11) with a specific gravity of 2.68 and passing through the 38 mm sieve. The geocell used in the tests was  
 254 non-perforated and fabricated from continuous polypropylene filaments as a non-woven geotextile, with

255 ultimate tensile strength of 13.1 kN/m and pocket size of  $110 \times 110 \times 100 \text{ mm}^3$  (length $\times$ width $\times$ height). The  
256 details of engineering properties of the geotextile and soil properties are given by [Moghaddas Tafreshi et al.,](#)  
257 [\(2013\)](#).

258 As part of this validation, the effects of several parameters including geocell and soil stiffness modulus,  
259 geocell layer height and number of geocell layers on pressure-settlement response of footing were  
260 investigated. The results of triaxial tests on unreinforced and geocell reinforced soil samples were used to  
261 estimate the elastic modulus of the different layers during the loading steps ([Noori, 2012](#)). The soil, geocell  
262 material and the density of the soil filled into the geocell pockets, used in both the plate load tests and triaxial  
263 tests were the same. Six triaxial tests on unreinforced and reinforced soil samples with one layer of geocell, at  
264 three confining pressures of 50, 100 and 150 kPa were conducted. The triaxial samples had a diameter of 100  
265 mm and a height of 200 mm as shown in Fig. 8. The geocell-soil composite layers are of 100 mm in  
266 diameter and 100 mm in height and positioned at mid-height of the specimen. The stress-strain response of  
267 unreinforced and geocell reinforced samples with single layer of the geocell-soil composite under three  
268 confining pressures are shown in Fig. 9. This figure indicates that the geocell reinforcement increases the  
269 deviator stress (i.e., shear strength) of the samples considerably compared to unreinforced samples,  
270 irrespective of confining pressure. This behavior is essentially due to the increase in confining effect of  
271 geocell layers which cause an internal confinement in reinforced samples. On the other hand, vertical stress  
272 applied to the infill induces a horizontal active pressure at the perimeter of the cell of geocell. The infill wall  
273 interface friction transfers load into the cell structure which, in turn, mobilises resistance in surrounding cells.  
274 It is also evident that cells that surround a loaded cell offer greater passive resistance due to the lateral strain  
275 in the vicinity of the load— consequently leading to an improvement in the overall performance in strength.

276 Note that, triaxial compression tests on a single geocell layer sandwiched between two soil layers may give  
277 different results compared to the test on a single, less constrained geocell. Since, the present analytical  
278 formulation was employed to simulate the results of plate load tests supported by geocell layers of 100 mm  
279 thickness, thus using a single layer of geocell with the same thickness in triaxial test sample with a height of  
280 200 mm was inevitable.

### 281 **8.1. Elastic modulus of unreinforced and geocell-reinforced layers**

282 Since the six triaxial tests were conducted at three specified confining pressures of 50, 100 and 150 kPa, thus  
283 the tangential elastic modulus at different strain levels can be obtained from the stress-strain responses in Fig. 9,

284 when the confining pressures are exactly 50, 100, and 150 kPa. Hence, at each stage of loading during the  
 285 analysis, a continuous function of confining pressure and axial strain is required to obtain the tangential elastic  
 286 modulus when the strain level and confining pressure being varied. Thus, in this section the elastic modulus of  
 287 unreinforced and geocell-reinforced soil layers in terms of strain and confining pressure,  $E=f(\sigma_3, \varepsilon)$  for each  
 288 loading step, was modeled non-linearly from the data of six triaxial tests at the three confining pressures of 50,  
 289 100 and 150 kPa (see Fig. 9).

### 290 8.1.1. Elastic modulus of unreinforced layers

291 Based on the data extracted from Fig. 9a, the vertical stress ( $\sigma_1=\sigma_3+\sigma_d$ ) of triaxial samples was found to be a  
 292 function of the confining pressure ( $\sigma_3$ ) and axial strain ( $\varepsilon$ ). Therefore a nonlinear regression model was  
 293 developed to estimate the vertical stress ( $\sigma_1$ ) for different values of  $\sigma_3$  and  $\varepsilon$ .

294 Several alternative modeling approaches were trialed before selecting, as optima, a non-linear power model  
 295 with of the largest multiple coefficient of determination,  $R^2=0.91$ , and a minimum value of standard error,  
 296  $E_s=0.11$ , to estimate the vertical stress ( $\sigma_1$ ) as a function of different parameters was obtained as Eq. (24):

$$\sigma_1 = 61.47 \sigma_3^{0.73} \varepsilon^{0.34} e^{-3.17\varepsilon} \quad (24)$$

297 Using Eq. (24), the absolute average percentage of error,  $e_{ave}$  and maximum percentage of error,  $e_{max}$  in  
 298 estimating the value of  $\sigma_1$  were found to be 2.5% and 4.6% respectively.

299 The tangential modulus of elasticity can be derived as the derivative of stress with respect to strain (from Eq.  
 300 (24)) as presented in Eq. (25a). The function of  $f(\varepsilon)$  is defined in Eq. (25b).

$$E = 61.47 \sigma_3^{0.73} * f(\varepsilon) \quad (25a)$$

$$f(\varepsilon) = (-3.17 e^{-3.17\varepsilon} \varepsilon^{0.34} + \frac{0.34 \varepsilon^{0.34}}{\varepsilon} e^{-3.17\varepsilon}) \quad (25b)$$

### 301 8.1.2. Elastic modulus of geocell-reinforced layers

302 [Madhavi Latha \(2000\)](#), based on the results of triaxial compression tests on geocell-encased sand, proposed  
 303 an empirical equation in the form of Eq. (26) to express the elastic modulus of the geocell reinforced sand ( $E_g$ ).

$$E_g = 4 \sigma_3^{0.7} (K_u + 200M)^{0.16} \quad (26)$$

304 Where:

305  $K_u$ : the dimensionless modulus number of the unreinforced sand in the hyperbolic model proposed by [Duncan](#)  
306 [and Chang \(1970\)](#),

307  $M$ : the secant tensile modulus of the geocell material (e.g., geotextile and geogrid) in  $kN/m$ , assessed at an  
308 average strain of 2.5% in load-elongation, and

309  $\sigma_3$ : the confining pressure in kPa.

310 In fact, the geocell layers are modeled as equivalent composite layers with enhanced stiffness and shear  
311 strength properties. The term in parentheses of Eq. (26) expresses the Young's modulus parameter of geocell-  
312 reinforced soil in terms of the secant modulus of the geocell material ( $M$ ) and the dimensionless modulus number  
313 of the unreinforced soil ( $K_u$ ).

314 However, due to the fact that the suggested relationship by [Madhavi Latha \(2000\)](#), Eq. (26), is not a function  
315 of axial strain level, it is modified to Eq. (27) as a function of both confining pressure ( $\sigma_3$ ) and axial strain ( $\varepsilon$ ).

$$E_g = a_1 \sigma_3^{b_1} (K_u + a_2 M^{b_2}) * f(\varepsilon) \quad (27)$$

316 The function of  $f(\varepsilon)$  is assumed as Eq. (25b) and then the parameters of  $a_1$ ,  $a_2$ ,  $b_1$  and  $b_2$  are obtained from the  
317 triaxial tests results of geocell-reinforced soil (Fig. 9b). The constants parameters in Eq. (27) depend on the type  
318 of infill soil and strength of geocell material, which must be calibrated according to the results of triaxial tests on  
319 soil and geocell, with the same properties that would be used in the foundation bed. Fitting Eq. (27) to the data of  
320 Noori (2012) yields the elastic modulus as a function of  $\sigma_3$ ,  $\varepsilon$ ,  $K_u$  and  $M$  as Eq. (28).

$$E_g = 0.12 \sigma_3^{0.73} (K_u + 100M^{0.1}) * f(\varepsilon) \quad (28)$$

321 At each loading step, the elastic modulus of unreinforced and reinforced layers were estimated using the  
322 confining pressure (at mid-height of the layer) and the strain computed at the end of the previous loading step.  
323 The confining pressure in the middle of each reinforced layer was obtained by multiplying the distributed  
324 vertical stress by the coefficient of lateral pressure ( $k_r$ ). The value of  $k_r$  is proposed by authors as Eq. (29), in  
325 which the value of lateral pressure coefficient for unreinforced soil  $k_{un}=0.5$  has been suggested by [Madhavi](#)  
326 [Latha \(2000\)](#). For the  $M=0$ , Eq. (29) results the lateral pressure coefficient of unreinforced soil ( $k_{un}$ ).

$$k_r = k_{un} (K_u + 100M^{0.1}) / K_u \quad (29)$$

327 Overall, Eqs. (25a) to (29) reveal that the proposed formulations would be able to consider the variation of  
328 geocell performance in regard to the strain level and confinement stress variations across the depth of the

329 foundation bed, provided the elastic modulus of the different layers (soil layers and the [geocell-reinforced layers](#))  
330 are allotted appropriate values that differ from layer-to-layer and from one loading step to the next. Based on the  
331 results of triaxial compression tests, the value of the hyperbolic parameter of [Duncan and Chang \(1970\)](#),  $K_u$ , is  
332 found as 483.3 (the authors' evaluation not reported here). Also, the secant modulus of the geocell material at  
333 2.5% strain,  $M$ , is given by the manufacturer as 114 kN/m ( $M= 114$  kN/m). Due to the confinement of the soil by  
334 the geocell wall, the Poisson's ratio of geocell-reinforced layers may be less than that in unreinforced layers. The  
335 range of Poisson's ratio for granular soil (i.e. sand in the present paper) is about 0.3-0.35 and for geocell filled  
336 with sand from 0.17 ([Mhaiskar and Mandal, 1996](#)) to 0.25 ([Zhang et al., 2010c](#)). Thus, a Poisson's ratio of 0.3 is  
337 used for unreinforced layers and a Poisson's ratio of 0.25, 0.2, and 0.2, is used respectively for reinforced layers  
338 with one, two and three layers of geocell.

## 339 **8.2. Validation of proposed analytical method**

340 The presented analytical method was validated by comparing the results of model analyses with plate load  
341 tests results ([Moghaddas Tafreshi et al., 2013](#)) for an unreinforced bed and for beds reinforced by one, two  
342 and three layers of geocell. Fig. 10 compares the results of the analytical method and tests in the form of  
343 footing pressure-settlement responses, for different values of geocell mass. These comparisons are done for  
344 parameters of  $K_u=483.3$ ,  $M= 114$  kN/m,  $h_g=100$  mm and  $D=300$  mm. Since, the analytical method has not  
345 considered any variation in the geocells' width; it is assumed that the width of the geocell-reinforced layers  
346 being sufficient to ensure the anchorage derived from the adjacent stable soil mass.

347 The predicted responses show a better match with the experimental ones at lower footing settlement  
348 levels (i.e.,  $s/D < 8\%$ ). For larger footing settlements (e.g.,  $s/D > 8\%$ ), the analytical predictions under-estimate  
349 the experimentally determined settlements, implying strain softening in the geocell-soil layers in-situ relative  
350 to the performance in the triaxial or that the assumption of no lateral strain is non-conservative. The  
351 difference between the predicted responses and experimental ones might more generally be attributed to the  
352 selected value of lateral pressure coefficient, the selected values of Poisson's ratio, the simplifying  
353 assumptions used in the analytical method, the discrepancies between the experimental and analytical  
354 systems and the differences in simulating the field and the experimental conditions of multiple layers.

355 Since the practical design of shallow footings is mostly governed by footing settlement, footing  
356 settlement must be limited to specific values, depending on the super-structure. Thus, the close comparison of  
357 analytical and experimental results in the lower range of settlement (i.e., less than 6% of the footing



358 diameter) is encouraging. This implies that the analytical method presented is capable of estimating the  
359 behavior of footings supported by geocell layers and may be conveniently applied as a tool to estimate the  
360 pressure-settlement response of footings over most practical ranges of geotechnical use.

### 361 **8.3. Predictive parametric study**

362 Using the analytical model presented, a parametric study was carried out to account for the variability of  
363 those parameters that could not be considered in the physical tests, so as to verify the model's predictive  
364 capability. Particularly, variation in the secant modulus of geocell ( $M$ ), the dimensionless modulus number of the  
365 soil ( $K_u$ ), the thickness of geocell layers ( $h_g$ ) and the number of geocell layers ( $N_g$ ) were investigated in this way.

366 Fig. 11a shows the effect of the secant modulus of the geocell ( $M$ ) on the pressure-settlement response of a  
367 foundation reinforced with three layers of geocell. The results reveal the beneficial effect of the reinforcement's  
368 rigidity (see Eq. (28)) in decreasing the footing settlements, so that at a given bearing pressure, the value of the  
369 settlement decreases as the secant modulus of geocell ( $M$ ) increases. The similar results reported by [Madhavi  
370 Latha et al. \(2006\)](#) for geocell-supported embankments showed that higher surcharge capacity and lower  
371 deformations are associated with increase in the value of the  $M$  parameter. This performance could be attributed  
372 to the internal confinement provided by geocell reinforcement with increase in  $M$ . The confinement effect is  
373 dependent on the secant modulus of the reinforcement, the friction at the soil-reinforcement interface and the  
374 confining stress developed on the infilling soil inside the geocell pocket due to the passive resistance provided by  
375 the 3D structure of geocell ([Sireesh et al., 2009](#); [Moghaddas Tafreshi and Dawson, 2010a](#)). In addition, as seen in  
376 Fig. 11a, there is a limiting value of  $M$  (=100 kN/m) beyond which no further load-settlement benefit is achieved.  
377 Almost certainly this is because the behavior of the unreinforced soil between the reinforced layers is now  
378 limiting the response of the overall system.

379 To see what the effect of  $K_u$  is, the variation of pressure-settlement of the reinforced bed with three layers  
380 of geocell is presented in Fig. 11b. The results show that the bearing capacity of a footing at a given  
381 settlement is significantly increased due to an increase in the  $K_u$  value. Thus, the role of the soil type and the  
382 soil compaction in performance of geocell-reinforced beds, which the composite model suggested in the  
383 present study, can take into account this effect. However, a dense sand matrix tends to dilate under footing  
384 penetration, thereby mobilizing higher strength in the geocell reinforcement, leading to greater performance  
385 improvement ([Madhavi Latha et al., 2009b](#)).

386 The rigidity of the geocell layer is predominantly influenced by the thickness of geocell. To have a better  
387 assessment of the effect of a geocell's thickness in a geocell-reinforced foundation, the variation of the  
388 pressure-settlement relationship of the unreinforced bed and of the reinforced bed with three layers of geocell  
389 is presented in Fig. 11c. The benefit of a thicker geocell mat is evident, so that a thicker geocell decreases the  
390 footing settlements, tending to improve its bearing capacity. This appears to be a consequence of greater  
391 opportunity of geocell-soil interaction (in the form of wall-friction and confining pressure imposed by the  
392 pocket walls) and the increased stiffness of the effective zone beneath the footing consequent upon an  
393 increase in the thickness of geocell. This is in-line with the findings of [Dash et al. \(2007\)](#), [Sitharam et al.](#)  
394 [\(2007\)](#), [Madhavi Latha et al. \(2006\)](#) [Moghaddas Tafreshi and Dawson \(2010a\)](#) who reported that the  
395 settlement of a trench's soil surface was decreased due to the provision of a thicker geocell in the backfill.  
396 Furthermore, the rate of reduction in footing settlement and the rate of enhancement in load carrying capacity  
397 of the footing can also be seen to reduce with increase in the value of  $h_g$ . The reason is that, as multiple,  
398 thicker reinforcement layers are used, then the reinforced zone extends deeper beyond the zone most  
399 significantly strained by the applied load, so that little further benefit accrues. From a practical point of view,  
400 as the thickness of a geocell layer is increased; the problem of lower achieved compaction in the geocell  
401 packets would be encountered, so that higher compactive effort is necessary as the thickness of vertical webs  
402 of the geocell is increased, owing to hindering of vertical densification ([Thakur et al., 2012](#); [Tavakoli](#)  
403 [Mehrjardi et al., 2013](#)). For this reason, multiple thin geocell layers may, in practice, be preferred to fewer,  
404 thicker layers.

405 Fig. 11d presents the bearing pressure-settlement response of the unreinforced and reinforced foundation  
406 beds with one, two, three layers of geocell. From this figure, it may be clearly observed that, as the number of  
407 geocell layers increases (i.e., the increase in the depth of the reinforced zone), both stiffness and bearing  
408 pressure at a specified settlement increase substantially. Likewise, at a given bearing pressure, the value of  
409 the settlement decreases as the number of geocell layers increases. However, the rate of reduction in footing  
410 settlement is seen to reduce with increase in the number of geocell layers. It is likely that the additional layers  
411 are interacting with soil that is strained less and less by the applied load, therefore delivering diminishing  
412 increments of additional reinforcement effect. [Yoon et al. \(2008\)](#) and [Moghaddas Tafreshi et al. \(2013\)](#) in  
413 their studies on the effect of multi-layered geocell reported a similar effect with increase in the number of 3D  
414 reinforcement layers.

## 415 9. Conclusions

416 In this study, an analytical approach based on the theory of multi-layered soil system theory (Hirai, 2008;  
417 Vakili et al., 2008) was developed to estimate the pressure-settlement response of a circular footing supported by  
418 unreinforced and multi-layered reinforced beds. Definition of elastic modulus for unreinforced and reinforced  
419 layers in terms of strain and confining pressure, along with the equivalent elastic method were the main  
420 processes of problem solution. The new method delivers predictions of load-settlement that are in good  
421 agreement with measured values for a geocell-reinforced application, and thus gives confidence of its usefulness  
422 for expected geotechnical applications. The results of the new model, as applied to geocell installations, can be  
423 summarized as follows:

- 424 (1) The response of pressure-settlement in both reinforced and unreinforced conditions is nonlinearly and  
425 significantly affected by the secant modulus of geocell, the dimensionless modulus number of the soil,  
426 thickness of geocell layers and the number of geocell layers.
- 427 (2) The results emphasized that the performance of geocell-reinforced foundation is always much better than  
428 when unreinforced.
- 429 (3) The analytical results show that the increase in the number of geocell layers, the secant modulus of the  
430 geocell and the dimensionless modulus number of the soil, strengthen the behavior of geocell-reinforced  
431 foundation against the surface loading, which is in-line with the experimental results of researchers.
- 432 (4) The parametric study shows a decrease in rate of enhancement in bearing pressure, at a given footing  
433 settlement with increase in the number of geocell layers, the secant modulus and the thickness of geocell  
434 layers.

435 It should be stated that the results obtained are based on a circular loading plate, one type of geocell  
436 reinforcement, fixed width of geocell layers and non-cohesive soil. Consequently, specific applications should  
437 only be made after considering the above limitations.

#### 438 **References**

- 439 American Society for Testing and Materials, 2011. Standard practice for classification of soils for engineering purposes  
440 (Unified Soil Classification System). ASTM International, West Conshohocken, PA, D 2487-11.
- 441 Avesani Neto, J.O., Bueno, B.S., Futai, M.M., 2013. A bearing capacity calculation method for soil reinforced with a  
442 geocell. *Geosynth. Int.* 20 (3), 129–142.

- 443 Bathurst, R.J., Nernheim, A., Walters, D.L., Allen, T.M., Burgess, P., Saunders, D.D., 2009. Influence of reinforcement  
444 stiffness and compaction on the performance of four geosynthetic – reinforced soil walls. *Geosynth. Int.* 16 (1), 43–  
445 49.
- 446 Biswas, A., Murali Krishna, A., Dash, S.K., 2013. Influence of subgrade strength on the performance of geocell-  
447 reinforced foundation systems. *Geosynth. Int.* 20 (6), 376–388.
- 448 Boushehrian, A.H., Hataf, N., Ghahramani, A., 2011. Modeling of the cyclic behavior of shallow foundations resting on  
449 geomesh and grid-anchor reinforced sand. *Geotext. Geomembr.* 29 (3), 242-248.
- 450 Chen, R.H., Chiu, Y.M., 2008. Model tests of geocell retaining structures. *Geotext. Geomembr.* 26 (1), 56-70.
- 451 Chen, R.H., Huang, Y.W., Huang, F.C., 2013. Confinement effect of geocells on sand samples under triaxial  
452 compression. *Geotext. Geomembr.* 37 (2), 35-44.
- 453 Chen, R.H., Wu, C.P., Huang, F.C., Shen, C.W., 2013. Numerical analysis of geocell-reinforced retaining structures.  
454 *Geotext. Geomembr.* 39 (4), 51-62.
- 455 Collin, J.G., Kinney, T.C., Fu, X., 1996. Full scale highway load test of flexible pavement systems with geogrid  
456 reinforced base courses. *Geosynth. Int.* 3 (4), 537–549.
- 457 Dash, S.K., Rajagopal, K., Krishnaswamy, N.R., 2007. Behaviour of geocell reinforced sand beds under strip loading.  
458 *Can. Geotech. J.* 44 (7), 905–916.
- 459 Dash, S.K., Chandra Bora, M., 2013. Improved performance of soft clay foundations using stone columns and geocell-  
460 sand mattress. *Geotext. Geomembr.* 41 (November), 26-35.
- 461 Duncan, J. M., Chang, C. Y., 1970. Nonlinear analysis of stress and strain in soils. *J. Soil Mech. and Found.* 96 (5),  
462 1629–1653.
- 463 Foster, C. R., Ahlvin, R. G., 1959. Stresses and deflections induced by a uniform circular load, *Proc. Highway Research*  
464 *Board.* 33, 467-470.
- 465 Harr, M.E., 1966. *Foundations of theoretical soil mechanics.* McGraw-Hill: New York.
- 466 Hegde, A., Sitharam, T.G., 2015. 3-Dimensional numerical modelling of geocell reinforced sand beds. *Geotext,*  
467 *Geomembr.* 43 (2), 171–181.

468 Hegde, A., Sitharam, T.G., 2015. 3-Dimensional numerical analysis of geocell reinforced soft clay beds by considering  
469 the actual geometry of geocell pockets. *Can. Geotech. J.* Published on the web 14 February 2015, 10.1139/cgj-2014-  
470 0387.

471 Hirai, H., Kamei, T.A., 2003. A method to calculate settlement, stress and allowable stress of multi-layered ground. *J. of*  
472 *Struct. Constr. Eng.* 573, 81–88.

473 Hirai, H., Kamei, T., 2004. A method to calculate settlement, stress, failure and allowable stress of multi-layered ground  
474 by equivalent thickness theory. *J. of Struct. Constr. Eng.* 581, 79–86.

475 Hirai, H., 2008. Settlements and stresses of multi-layered grounds and improved grounds by equivalent elastic method.  
476 *International. J. for Num. Analy. Meth. Geomech.* 32 (5), 523–557.

477 Eid, H.T., Alansari, O.A., Odeh, A.M., Nasr, M.N., Sadek, H.A., 2009. Comparative study on the behavior of square  
478 foundations resting on confined sand. *Can. Geotech. J.* 46 (4), 438-453.

479 Huang, C.C., 2014. Force equilibrium-based finite displacement analyses for reinforced slopes: Formulation and  
480 verification. *Geotext. Geomembr.* 42 (4), 394-404.

481 Hufenus, R., Rueegger, R., Banjac, R., Mayor, P., Springman, S.M., Bronnimann, R., 2006. Full-scale field tests on  
482 geosynthetic reinforced unpaved on soft subgrade. *Geotext. Geomembr.* 24 (1), 21–37.

483 Indraratna, B., Biabani, M., Nimbalkar, S., 2015. Behavior of Geocell-Reinforced Subballast Subjected to Cyclic Loading  
484 in Plane-Strain Condition. *J. Geotech. Geoenviron. Eng.* 141 (1), 10.1061/ (ASCE) GT.1943-5606.0001199.

485 Kachi, T., Kobayashi, M., Seki, M., Koseki, J., 2013. Reinforcement of railway ballasted track with geosynthetic bags for  
486 preventing derailment. *Geosynth. Int.* 20 (5), 316 –331.

487 Kumar, A., Kaur, A., 2012. Model tests of square footing resting on fibre-reinforced sand bed. *Geosynth. Int.* 19 (5), 385-  
488 392.

489 Lambert, S., Nicot, F., Gotteland, P., 2011. Uniaxial compressive behavior of scrapped tire and sand-filled wire netted  
490 geocell with a geotextile envelope. *Geotext, Geomembr.* 29 (5), 483-490.

491 Leshchinsky, B., Ling, H., 2013a. Numerical modeling of behavior of railway ballasted structure with geocell  
492 confinement. *Geotext. Geomembr.* 36 (1), 33–43.

493 Leshchinsky, B., Ling, H., 2013b. Effects of Geocell Confinement on Strength and Deformation Behavior of Gravel. *J.*  
494 *Geotech. Geoenviron. Eng.* 139 (2), 340-352.

- 495 Ling, H., Leshchinsky, D., Wang, J.P., Mohri, Y., Rosen, A., 2009. Seismic Response of Geocell Retaining Walls:  
496 Experimental Studies. *J. Geotech. Geoenviron. Eng.* 135 (4), 515-524.
- 497 Madhavi Latha, G.M., 2000. Investigation on the behavior of geocell supported embankments. Ph.D. Thesis, Department  
498 of Civil Engineering, Indian Institute of Technology Madras, Chennai.
- 499 Madhavi Latha, G.M., Rajagopal, K., Krishnaswamy, N. R., 2006. Experimental and theoretical investigations on  
500 geocell-supported embankments. *Int. J. of Geomech. ASCE*, 6 (1), 30–35.
- 501 Madhavi Latha, G.M., Rajagopal, K. 2007. Parametric finite element analyses of geocell supported embankments. *Can.*  
502 *Geotech. J.* 44 (8), 917-927.
- 503 Madhavi Latha, G.M., Somwanshi, A., 2009a. Bearing capacity of square footings on geosynthetic reinforced sand.  
504 *Geotext. Geomembr.* 27 (4), 281–294.
- 505 Madhavi Latha, G.M., Dash, S. K., Rajagopal, K., 2009b. Numerical simulation of the behavior of geocell reinforced. *Int.*  
506 *J. of Geomech. ASCE*, 9 (4), 143–152.
- 507 Mehdipour, I., Ghazavi, M., Ziaie Moayed, R., 2013. Numerical study on stability analysis of geocell reinforced slopes  
508 by considering the bending effect. *Geotext. Geomembr.* 37 (April), 23-34.
- 509 Mhaiskar, S.Y., Mandal, J.N., 1996. Investigations on soft clay subgrade strengthening using geocells. *Construc. Build.*  
510 *Mater.* 10 (4), 281–286.
- 511 Moghaddas Tafreshi, S.N., Dawson, A.R., 2010a. Comparison of bearing capacity of a strip footing on sand with geocell  
512 and with planar forms of geotextile reinforcement. *Geotext. Geomembr.* 28 (1), 72–84.
- 513 Moghaddas Tafreshi, S.N., Dawson, A.R. 2010b. Behaviour of footings on reinforced sand subjected to repeated loading  
514 – Comparing use of 3D and planar geotextile. *Geotext. Geomembr.* 28 (5), 434–447.
- 515 Moghaddas Tafreshi, S.N., Khalaj, O., Dawson, A.R., 2013. Pilot-scale load tests of a combined multi-layered geocell  
516 and rubber-reinforced foundation. *Geosynth. Int.* 20 (3), 143–161.
- 517 Moghaddas Tafreshi, S.N., Khalaj, O., Dawson, A.R., 2014. Repeated loading of soil containing granulated rubber and  
518 multiple geocell layers. *Geotext. Geomembr.* 42 (1), 25-38.
- 519 Noori, B., 2012. Experimental investigation of the behavior of geocell reinforced rubber-soil mixture, Msc thesis, Faculty  
520 of Civil Engineering, K.N. Toosi University of Technology, Tehran, Iran.

- 521 Odemark, N., 1949. Investigations as to the elastic properties of soils and design of pavements according to the theory of  
522 elasticity. Statens Vaginstutute: Meddelande, Stockholm, Sweden, vol. 77.
- 523 Palmeira, E.M., Andrade, H.K.P.A., 2010. Protection of buried pipes against accidental damage using geosynthetics.  
524 Geosynth. Int. 17 (4), 228–241.
- 525 Palmer, L.A., Barber, E.S., 1940. Soil displacement under a circular loaded area. Proceedings of the Highway Research  
526 Board, 20, 279–286.
- 527 Pokharel, S. K., Han, J., Leshchinsky, D., Parsons, R. L., Halahmi, I., 2010. Investigation of factors influencing behavior  
528 of single geocell-reinforced bases under static loading. Geotext. Geomembr. 28 (6), 570-578.
- 529 Pokharel, S. K., 2010. Experimental Study on Geocell-Reinforced Bases under Static and Dynamic Loading, PhD thesis,  
530 Univ. Kansas, USA.
- 531 Raymond, G.P., 2002. Reinforced ballast behaviour subjected to repeated load. Geotext. Geomembr. 20 (9), 39-61.
- 532 Sharma, R., Chen, Q., Abu-Farsakh, M., Yoon, S., 2009. Analytical modeling of geogrid reinforced soil foundation.  
533 Geotext. Geomembr. 27 (1), 63–72.
- 534 Sireesh, S., Sitharam, T.G., Dash, S.K., 2009. Bearing capacity of circular footing on geocell–sand mattress overlying  
535 clay bed with void. Geotext. Geomembr. 27 (2), 89–98.
- 536 Sitharam, T.G., Sireesh, S., Dash, S.K., 2007. Performance of surface footing on geocell-reinforced soft clay beds.  
537 Geotech. Geolo. Eng. 25 (5), 509–524.
- 538 Song, F., Xie, Y.L., Yang, Y.F., Yang, X.H., 2014. Analysis of failure of flexible geocell-reinforced retaining walls. in  
539 the centrifuge. Geosynth. Int. 21( 6,) 342 –351.
- 540 Soudé, M., Chevalier, B., Grédiac, M., Talon, A., Gourvès, R., 2013. Experimental and numerical investigation of the  
541 response of geocell-reinforced walls to horizontal localized impact. Geotext. Geomembr. 39 (August), 39-50.
- 542 Tanyu, B.F., Aydilek, A.H., Lau, A.W., Edil, T.B., Benson, C.H. 2013. Laboratory evaluation of geocell-reinforced  
543 gravel subbase over poor subgrades. Geosynth. Int. 20 (2), 47 –61.
- 544 Tavakoli Mehrjardi, Gh., Moghaddas Tafreshi, S.N., Dawson, A.R., 2012. Combined use of geocell reinforcement and  
545 rubber–soil mixtures to improve performance of buried pipes. Geotext. Geomembr. 34 (October), 116-130.

- 546 Tavakoli Mehrjardi, Gh., Moghaddas Tafreshi, S. N., Dawson, A. R., 2013. Pipe response in a geocell reinforced trench  
547 and compaction considerations. *Geosynth. Int.* 20 (2), 105-118.
- 548 Terzaghi K. *Theoretical Soil Mechanics*. Wiley: New York, 1943.
- 549 Thakur, J.K., Han, J., Pokharel, S.K., Parsons, R.L., 2012. Performance of geocell-reinforced recycled asphalt pavement  
550 (RAP) bases over weak subgrade under cyclic plate loading. *Geotext. Geomembr.* 35 (December), 14-24.
- 551 Yang, X., Han, J., Pokharel, S.K., Manandhar, C., Parsons, R.L., Leshchinsky, D., Halahmi, I., 2012. Accelerated  
552 pavement testing of unpaved roads with geocell-reinforced sand bases. *Geotext. Geomembr.* 32, (June), 95-103.
- 553 Yang, X., Han, J., 2013. Analytical Model for Resilient Modulus and Permanent Deformation of Geosynthetic-  
554 Reinforced Unbound Granular Material. *J. Geotech. Geoenviron. Eng.* 139 (9), 1443-1453.
- 555 Yoon, Y. W., Heo, S. B., Kim, S. K., 2008. Geotechnical performance of waste tires for soil reinforcement from chamber  
556 tests. *Geotext. Geomembr.* 26 (1), 100-107.
- 557 Vakili Ninyo, J., Moore, I., 2008. A simplified method for evaluation of pavement layers moduli using surface deflection  
558 data. The 12th International Conference of International Association for Computer Methods and Advances in  
559 Geomechanics (IACMAG), Goa India, 1-6.
- 560 Wesselo, J., Visser, A.T., Rust, E., 2009. The stress-strain behaviour of multiple cell geocell packs. *Geotext. Geomembr.*  
561 27 (1), 31-38.
- 562 Wu, J.T.H., Pham, T.Q. Adams, M.T., 2013. *Composite Behavior of Geosynthetic Reinforced Soil Mass*. Denver, Co.,  
563 University of Colorado Denver, Dept. of Civil Engineering ; McLean, VA : Federal Highway Administration, Office  
564 of Infrastructure Research and Development, 2013-07 (FHWA-HRT-10-077), 214 pp.
- 565 Zhang, L., Zhao, M., Zou, X., Zhao, H. 2009. Deformation analysis of geocell reinforcement using Winkler model.  
566 *Comput. Geotech.* 36 (6), 977-983.
- 567 Zhang, L., Zhao, M., Shi, C., Zhao, H., 2010a. Bearing capacity of geocell reinforcement in embankment engineering.  
568 *Geotext. and Geomembr.* 28(5), 475-482.
- 569 Zhang, L., Zhao, M., Zou, X., Zhao, H. 2010b. Analysis of geocell-reinforced mattress with consideration of horizontal-  
570 vertical coupling. *Comput. Geotech.* 37 (6), 748-756.
- 571 Zhang, L., Qiangkang, Gu., Guoping, Cen., 2010c. Effect of Geo-Cell Reinforced Soil Structure Used in Flexible Airfield  
572 Pavement. *iclem logistics for sustained economic development*, ASCE. 1629-1635.



573 Zhou, H.B., Wen, X.J., 2008. Model studies on geogrid- or geocell-reinforced sand mattress on soft soil. Geotext.  
 574 Geomembr. 26(3), 231–238.

575 **Nomenclature**

$a$	Loading plate radius ( $m$ )
$b$	Width of the geocell layers ( $m$ )
$a_1, a_2, b_1$ and $b_2$	Model parameters to estimate the elastic modulus of geocell-reinforced layers
$D$	Loading plate diameter ( $m$ )
$D_f$	Embedment depth of footing ( $m$ )
$E_g$	Elastic modulus of layer of geocell and soil ( $kPa$ )
$E_H$	Equivalent elastic modulus of upper soil layer of thickness $H$ ( $kPa$ )
$E_i, E_j, E_m, E_n$	Elastic modulus of layer $i, j, m, n$ ( $kPa$ )
$f(\varepsilon)$	Function to consider the strain level in estimating the elastic modulus of unreinforced and geocell-reinforced layers
$H_e$	Equivalent thickness ( $m$ )
$H_{1e}$	Equivalent thickness of the first layer ( $m$ )
$H_{me}$	Equivalent thickness of the $m^{th}$ layer ( $m$ )
$H_{eff}$	Effective depth ( $m$ )
$H_{ie}$	Equivalent thickness of the each layer ( $m$ )
$h_g$	Height of geocell layers ( $m$ )
$H_m$	Thickness of $m^{th}$ layer ( $m$ )
$h_s$	Vertical spacing of the geocell layers ( $m$ )
$k_r$	Lateral pressure coefficient for geocell-reinforced layers
$K_u$	Dimensionless modulus number of the unreinforced sand in the hyperbolic model
$k_{un}$	Lateral pressure coefficient for unreinforced layers
$M$	Secant tensile modulus of the geocell material at an average strain of 2.5% ( $kN/m$ )
$MLE$	Multiple Linear Elastic
$n$	Number of layers of multilayered system
$N_g$	Number of geocell layers
$u$	Vertical distance of the first layer of geocell from the footing ( $m$ )

$q$	Uniform pressure on a circular footing with radius “a” ( $kPa$ )
$w$	Actual total surface settlement at the center of the circular loading surface ( $m$ )
$w^j$	Vertical displacement at surface of system for loading of $q_j$ ( $m$ )
$w_0$	Vertical deflection at the center of loading on surface (at depth of $z=0$ ) of uniform equivalent layer ( $m$ )
$w_1$	Vertical deflection at bottom of the equivalent layer ( $m$ )
$w_i$	Vertical deflection on top of $i^{\text{th}}$ equivalent layer ( $m$ )
$w_{pi}$	Vertical thinning of $i^{\text{th}}$ original layer with thickness of $H_i$ ( $m$ )
$w_2$	Vertical thinning of the original layer with thickness of $H$ ( $m$ )
$z$	Depth of the backfill ( $m$ )
$\Delta w$	Vertical deformation (thinning) increment ( $m$ )
$\Delta w_i^j$	Displacement increment of equivalent layer for $i^{\text{th}}$ layer ( $m$ )
$(\Delta w_p)_i^j$	Deformation increment (thinning) of layer with thickness of $H_i$ for loading increment $q_j - q_{j-1}$ ( $m$ )
$\Delta w_1^j$	Vertical displacement increment on loading centerline at a depth of $H_e$ for loading increment of $q_j - q_{j-1}$ ( $m$ )
$\Delta w_0^j$	Vertical displacement increment at surface (of equivalent layer) beneath centre of load for loading increment of $q_j - q_{j-1}$ ( $m$ )
$\Delta w_2^j$	Vertical deformation (thinning) increment of the original layer of thickness of $H$ ( $m$ )
$\varepsilon_i$	Strain across the thickness of the $i^{\text{th}}$ layer (%)
$\varepsilon_i^j$	Strain of layer with thickness of $H_i$ subjected to loading $q_j$ (%)
$\varphi$	Angle of shearing resistance of soil being reinforced ( $degree$ )
$\nu_n$	Poisson’s ratio of layer $n$
$\sigma_d$	Deviatoric stress ( $kPa$ )
$\sigma_1$	Vertical stress ( $kPa$ )
$\sigma_3$	Confining pressure ( $kPa$ )




Fig. 1. Schematic of multi-layered geocell-reinforced foundation bed

577

578

579

580





Fig. 2. Multi-layered soil systems (Hirai, 2008)

581


582

583

584



**Fig. 3.** (a) Equivalent two-layered soil system for Fig. 2 (b) Equivalent single layer soil system with the same  $E_n$  and  $v_n$  for Fig. 3a. (Hirai, 2008)



**Fig. 4.** Equivalent single soil layer with equivalent thickness of “ $H_{1e}+H_{2e}+H_{3e}+\dots + H_{(n-1)e}+H_n$ ” and  $E_n$  and  $v_n$  for Fig. 2 (Hirai, 2008)

588

589

590


591

592

593

594

595



596

Fig. 5. “n” layer geocell-reinforced soil system containing “m” layers of geocell.

597






Fig. 6. Substituting n-layer system sequentially with (a) Equivalent two-layered system for n-layer system in Fig. 5 (b)


Equivalent single layer system with the same  $E_n$  and  $v_n$  for two-layered system in Fig. 6a.




**Fig. 7.** Geometry of the test configurations used to validate the results of the method presented ( $D=300$  mm,  $u=h_s=0.2D=60$  mm,  $h_g=100$  mm and  $b/D=5$  (Moghaddas Tafreshi et al., 2013)).



**Fig. 8.** Configurations used in triaxial tests (a) unreinforced (b) reinforced with one layer of geocell (Noori, 2012).



(a)



(b)

**Fig. 9.** Stress-axial strain curves for unreinforced and geocell reinforced samples under confining pressure of 50, 100 and 150 kPa (a) unreinforced samples, (b) geocell reinforced samples (Noori, 2012).

603

604

605

606

607

608

609

610


611

612


613

614


615




(a)



(b)




(c)




(d)

Fig. 10. Comparison of analytical and experimental results for (a) unreinforced bed, (b) reinforced bed with one layer of geocell, (c) reinforced bed with two layers of geocell, (d) reinforced bed with three layers of geocell







(a)



(b)



(c)



(d)

**Fig. 11.** Variation of pressure-settlement response of geocell-reinforced bed for different (a) secant modulus of geocell ( $M$ ), (b) soil dimensionless modulus ( $K_u$ ), (c) thickness of geocell layers ( $h_g$ ), and (d) number of geocell layers ( $N_g$ )

618

619

620

621

622