

# Strathprints Institutional Repository

Altrabalsi, Hana and Stankovic, Vladimir and Liao, Jing and Stankovic, Lina (2016) Low-complexity energy disaggregation using appliance load modelling. AIMS Energy, 4 (1). pp. 884-905. ISSN 2333-8326 , http://dx.doi.org/10.3934/energy.2016.1.1

This version is available at http://strathprints.strath.ac.uk/55232/

**Strathprints** is designed to allow users to access the research output of the University of Strathclyde. Unless otherwise explicitly stated on the manuscript, Copyright © and Moral Rights for the papers on this site are retained by the individual authors and/or other copyright owners. Please check the manuscript for details of any other licences that may have been applied. You may not engage in further distribution of the material for any profitmaking activities or any commercial gain. You may freely distribute both the url (<u>http://strathprints.strath.ac.uk/</u>) and the content of this paper for research or private study, educational, or not-for-profit purposes without prior permission or charge.

Any correspondence concerning this service should be sent to Strathprints administrator: <a href="mailto:strathprints@strath.ac.uk">strathprints@strath.ac.uk</a>



http://www.aimspress.com/

AIMS Energy, 4(1): 884–xxx DOI:10.3934/energy.2016.1.884 Received 26 October 2015 Accepted 23 December 2015 Published

# Research article

# Low-complexity energy disaggregation using appliance load modelling

#### Hana Altrabalsi, Vladimir Stankovic, Jing Liao\*and Lina Stankovic

Department of Electronic and Electrical Engineering, University of Strathclyde, Glasgow, UK

\* Correspondence: Email: jing.liao@strath.ac.uk; Tel: +441415482679. The work was presented in part at *IEEE Symposium Series on Computational Intelligence* (SSCI) Applications in Smart Grid, Orlando, FL, December 2014.

**Abstract:** Large-scale smart metering deployments and energy saving targets across the world have ignited renewed interest in residential non-intrusive appliance load monitoring (NALM), that is, disaggregating total household's energy consumption down to individual appliances, using purely analytical tools. Despite increased research efforts, NALM techniques that can disaggregate power loads at low sampling rates are still not accurate and/or practical enough, requiring substantial customer input and long training periods. In this paper, we address these challenges via a practical low-complexity low-rate NALM, by proposing two approaches based on a combination of the following machine learning techniques: k-means clustering and Support Vector Machine, exploiting their strengths and addressing their individual weaknesses. The first proposed supervised approach is a low-complexity method that requires very short training period and is fairly accurate even in the presence of labelling errors. The second approach relies on a database of appliance signatures that we designed using publicly available datasets. The database compactly represents over 200 appliances using statistical modelling of measured active power. Experimental results on three datasets from US, Italy, Austria and UK, demonstrate the reliability and practicality.

**Keywords:** energy disaggregation; appliance modelling; non-intrusive appliance load monitoring

### 1. Introduction

Large scale deployment of smart meters for residential customers is well underway in many European and other countries. For example, it is anticipated that by 2020 all UK households who give their permission will be equipped with an automatic meter reading system that measures and displays in real time aggregate energy usage with an in-home display unit [1]. This large governmental investment promises significant improvements in energy demand via automatic, more efficient and more informed billing. However, to provide deeper energy feedback, information about consumption of individual appliance is necessary. Indeed, up to 20% of reduction in energy consumption is expected via appliance-feedback and specific appliance replacement programs [2].

Monitoring individual appliances using individual appliance-specific sensors in a house is often impractical and expensive, especially since the number of electrical devices in the home is rapidly increasing. On the other hand, energy disaggregation via non-intrusive appliance load monitoring (NALM) offers a non-intrusive, purely computational, software-based approach to separate aggregate load obtained from a single electricity meter into individual appliance loads.

NALM appeared in the research literature in the 1980's [3], and since then, many NALM algorithms have been proposed that improve the initial design of [3] and adapt to advances in sensor technology, capturing energy measurands at a range of sampling rates, generally in the order of kHz. See [2, 4, 5, 6, 7], for examples of NALM applications. However, with large-scale smart metering deployments on the way, there is an increased interest in NALM algorithms that work at lower sampling rates, in the order of seconds and minutes. It is not only the cost of the sensing technology [2], but also computational and storage cost as well as implementation efficiency that are key drivers towards wide deployment of low-sampling smart meters. For example, in the USA most utilities capture data at 15-min intervals. UK smart meters, as defined by the Smart Metering Equipment Technical Specification (SMETS) proposal by UK Department of Energy and Climate Change provide readings is available to households that install a Consumer Access Device in their homes to read the smart meter measurements directly [1]. However, so far, there are no widely available efficient solutions for NALM, that offer high accuracy and low complexity at such low sampling rates [4, 5].

Based on the requirement for labelled training, all NALM methods can be grouped into supervised and unsupervised techniques (though hybrid, semi-supervised approaches are also possible). Supervised NALM techniques (see, for example, [8, 9, 10]) require a labelled dataset for training, are commonly based on event detection, and generally provide the highest disaggregation accuracy. They rely on different optimization and pattern recognition approaches, such as rule-based, neural networks, or Bayes-based classification. However, these approaches are less practical and prone to errors since the training usually relies on customer-filled appliance diaries, that are often unreliable.

Unsupervised approaches do not require a labelled dataset for training, and are currently probabilistic [11, 12, 13, 14], based on sparse coding [15], or time-series and motif mining [16], [17]. All these approaches, however, still require substantial customer input and depend on the availability of time periods when only one appliance is running for building efficient probabilistic models [11, 12, 13] or database of signatures [17].

In this paper, based on our initial conference paper [18], we propose an efficient low-complexity supervised NALM approach that combines k-means and Support Vector Machine (SVM). In particular, to benefit from the high classification performance of non-linear SVMs and low computational cost of k-means clustering, we effectively combine conventional k-means and SVM obtaining a hybrid method that outperforms k-means and SVM classification individually. We use k-means to cleverly select a subset of input data used to train SVM. By training the SVM only on a small set of representative samples, we are able to significantly reduce processing time. Note that, combining k-means and SVM has been reported before, but not in the context of NALM. Recognizing that in a majority of cases a large portion of the input data is redundant for training, in [19], k-means is used to decrease the number of support vectors and the training set size. Similarly, in [20, 21], k-means is employed to select a subset of original data for SVM training. The clustered SVM of [22] trains a linear SVM on each of the k-means clusters, in a divide-and-conquer manner.

To make the above approach practical and reduce or remove customer effort in maintaining a time-diary, a database of appliance signatures is created. Such a database is then used to develop a novel approach that requires no training from the household, and hence no input from the customer. The designed database is a compact collection of appliance power load signatures (active power measurements over a duty cycle) plus statistical features, such as, mean, variance, auto-correlation, and a statistical model for each appliance that are then used for load disaggregation. The database is populated using open source datasets from the USA [23], Austria and Italy [24], and our measurements in 20 UK houses [7]. Similar attempts have recently been reported in [25] but for USA houses only and high sampling rates.

The main contributions of the paper are:

- A low-complexity NALM approach, trained on measurements from the house whose aggregate load NALM is being applied on; this is termed Approach 1 using House-specific training data;
- A generic database of appliance signatures populated from 34 houses in UK, Europe, and US, containing over 200 appliance signatures. The database<sup>\*</sup> can be used with different energy disaggregation algorithms as well as for appliance mining and load prediction
- A low-complexity NALM approach that uses the developed database for training, irrespective of the house, and hence does not require customer input; this is termed Approach 2 using House-agnostic training data.

The developed approaches are tested in real settings using real house measurements. We tested the supervised approach for different training periods and artificially introduced errors in the training set.

The rest of the paper is organized as follows. Section 2 provides a brief review on NALM. Section 3 describes the proposed NALM algorithms and the database of appliance signatures. The last two sections discuss the simulation results, conclusion and future work.

# 2. Background and literature review

Non-intrusive Appliance Load Monitoring (NALM), also referred to as NILM or NIALM [3], disaggregates total power readings and identifies each appliance in use at any point in time based on the available measured total household consumption.

Traditional event-based NALM methods [3] consist of signal pre-processing, edge detection and feature extraction followed by classification. After acquisition, signal pre-processing can be

<sup>\*</sup>The database is made publicly accessible.

done in the form of power normalization, filtering (for signal smoothing and getting rid of sudden peaks), and thresholding to remove small power loads that would appear as noise as well as the base-load, from appliances that are always running. Next, edge detection is done to identify events of appliances switching on and off. Edge detection is followed by extracting the features in the identified event windows. Classification is then used to group sets of extracted features which have similar characteristics, such as power levels, time profile, reactive components etc.

In this paper, we focus on low complexity, low-rate NALM algorithms, where sampling rates are in the range of seconds and minutes. In particular, we test the proposed methods using 1sec, 8sec, and 1min sampling rates. The sampling rate influences the type of features that can be used. For example, low-rate NALM approaches can use only steady-state parameters, such as active or real power [12], reactive power [3, 4], power factor [26], voltage or current waveform [27, 28].

The simplest approach, from an implementation point of view, is to use a current transformer (CT) sensor with a clamp to measure alternating current and an AC-to-AC power adapter with a circuit to measure voltage. This way, active and reactive power components can be calculated from the measured current and voltage. However, measuring voltage in a simple way requires additional plug points, which are often not available close to the electricity meter. Moreover, processing, communicating and storing two dimensional data (active and reactive power) is often impractical, especially because the reactive component is not needed for billing purposes. That is why, in this paper, we consider disaggregation using only active power values, obtained, for example, from the electric current measured via a simple CT sensor, which is a type of metering massively deployed for automated meter reading.

Recent work on NALM has mainly focused on state-based probabilistic methods. In [11] four different methods for low-rate NALM are proposed using (conditional) factorial Hidden Markov Model (HMM) and Hidden semi-Markov models. The obtained accuracy was in the range of 72% to 99% for 3sec sampling rate in seven different houses with an average accuracy of 83%. This method cannot disaggregate base load, that is, the lowest most frequent value extracted from the aggregate load data, which is a good indication of the number of appliances being left on standby or background appliances such as boiler control units, fridges and freezers. The method is not of low computational complexity, and is prone to converge to a local minimum.

In [12] a factorial HMM is used for disaggregation of active power load at 1min sampling rate. The method builds initial models for state transition probabilities using knowledge of appliance-specific power operation that can be obtained, for example, from study and understanding of the appliance operation. To obtain reliable results, it is necessary to correctly set the *a priori*-values for each state of each appliance, which in turn is strongly dependent on the particular aggregate dataset on which NALM is being performed. Indeed, a similar factorial HMM-based approach is tested in [23], where it is shown that the disaggregation accuracy drops by up to 25% when different houses are used to set the initial models compared to the case when the same house is used for building the models (training) and testing. Results are reported for REDD dataset [23] with sampling rates of 1sec and 3sec.

In [29] and [8] a decision-tree (DT) classifier is used for pattern matching. The DT-based algorithm developed in [8], is a low-complexity, supervised approach that uses only rising and falling active power edges to build a DT model that is used for classification. The method is not

scalable, since re-training is needed whenever a new appliance is added, but is fast and performs very well even when the training period is very short.

In [13], an unsupervised Additive Factorial Approximate Maximum A-Posteriori (AFMAP) inference algorithm is proposed using differential factorial HMMs. First, all snippets of active power data are extracted using a threshold and modelled by an HMM; next the k-nearest-neighbor graph is used to build nine motifs that are treated as HMMs over which AFMAP is run. The results show average accuracy of 87.2% using 7 appliances and sampling rate of 60Hz. In [14] Hierarchical Dirichlet Process Hidden Semi-Markov Model (HDP-HSMM) factorial structure is used removing some limitations of the approach of [11], but at increased complexity. The results of [14] are reported for five appliances using 20sec resolution with 18 24-hour segments across four houses from the REDD dataset [23] outperforming the EM-based method of [23].

A powerful classification technique used for NALM is SVM. SVM-based NALM has shown good performance [5], it is scalable, and is a well established method for classifying noisy data. Non-linear classifiers, such as kernel SVM, that map the input feature space into a high dimensional space and find the optimal separating hyperplane between two classes to separate them, is one of the most effective classification methods, but has at least quadratic training time complexity.

The main problem with the above state-based and SVM-based approaches is that they are not suitable for real-time applications due to their high computational complexity. See [30] for some examples. The low-complexity HMM-based method proposed in [31] reduced execution time 72.7 times, but still requires 11.4 seconds for disaggregating two appliances and 94 minutes for 11 appliances.

Motivated by increased demand for near real-time approaches with minimal to no customer input, in the next section, we first propose a low-complexity supervised NALM approach that remedies the first problem of high complexity and then, build a database of signatures tackling the second issue of customer input, in the form of time-diaries, for example.

#### 3. Methodology

In this section, we describe our disaggregation algorithms, starting with our first approach using house-specific training data, followed by the design of the appliance power load signature database and finally our second approach using house-agnostic training data from the database.

The disaggregation procedure always comprises three steps: event detection, feature extraction, and classification, and the proposed two methods differ only in the classification step. We use edge detection [8] to isolate appliance events. Event detection isolates windows of events where an appliance is switched on or off (see the conference version [18] for more details). From each detected event window, different features are extracted and stored. Tested extracted features include (1) all active power readings in the event window, (2) rising/falling edge, (3) maximum/minimum active power value, (4) area, calculated as the area of the irregular polygon formed by the active power (Watt) samples in the event window, i.e., the energy of that event window in Joules. The optimal features to use, for each appliance, will be selected using the training dataset. Extracted features from each detected event are matched to the pre-defined appliance classes using a trained classifier.

#### 3.1. Proposed Approach 1 using house-specific training data

In the first approach, training is always done on aggregate data using a labeled dataset, which is obtained from time-diaries or sub-metering of the particular house, whose aggregate load is being disaggregated.

First, we test two well-known techniques to perform classification and pattern matching: kmeans and SVM. First we adapt k-means, which we term trained k-means, to perform supervised clustering similarly to [32]. Trained k-means uses a labelled dataset to classify the input data based on minimum distance classification. By a labelled dataset, we mean a collection of event windows with labels indicating which appliance was running. For example, if a microwave was switched on, the resulting event window of active power samples will then be labelled as microwave. During training, aggregate samples with Appliance A label from the entire training dataset are grouped, forming the Appliance A class. Like conventional k-means, the centroid of each appliance class is set as its head. Note that, the number of classes is always equal to the number of known appliances in the household. When a new testing sample (feature vector - active power load) is introduced, it is compared with all heads, and the minimum distance determines the classification outcome.

SVM-based algorithms are optimal classifiers in the presence of noise and proven to perform well for NALM applications [5]. We train binary classifiers to separate one appliance at a time. After an appliance has been classified, its contribution is removed, the threshold used for edge detection is adapted, and dissagregation is attempted on the next appliance.

While the trained k-means-based NALM is time efficient, it provides low disaggregation accuracy. On the other hand, as shown in next section, the SVM-based NALM method significantly outperforms the trained k-means-based approach, but requires up to 10 times more execution time. In order to design a high-performance, low-complexity solution, we propose to use SVM on a substantially reduced training set, obtained using trained k-means.



Figure 1. Filtering data samples in the proposed algorithm. Red rhomboids inside the circle centred at cluster head c will not be fed into the SVM training module.

To combine k-means and SVM, we first train k-means as explained above using the entire training dataset. As a result, k classes, each corresponding to one appliance, are formed with a centroid as head. Next, all feature vectors falling in Class i that are at an Euclidean distance larger than r from their head, form a subset of feature vectors  $C_i$  that is removed from Class i and used to train an SVM for Appliance i. r is a pre-set threshold, unique for each house, obtained heuristically, that is used to tradeoff complexity and performance. See Fig. 1 for an illustration. Note that, in this way, SVM will be trained using a significantly reduced dataset obtained from the trained k-means classifier, and hence the combined k-means+SVM complexity will be reduced, compared to SVM classification alone. Algorithm 1 shows the training steps, where d(x, y) denotes the Euclidean distance between vectors x and y.

Algorithm 1 Training: Perform training on the extracted features of the collected dataset.

function TRAIN(Labelled training dataset $L$ , $ \mathbf{M} $ , $r$ )	
$k =  \mathbf{M} $	▷ Number of Appliances
$[\mathbf{Cluster}, \mathbf{c}] = kmeans(k, L)$	▷ Call kmeans function
	$\triangleright$ Returns <b>Cluster</b> distribution and cluster heads <b>c</b> .
for $i = 1:k$ do	
$\mathbf{C_i} = \{\emptyset\}$	
$\mathbf{for}  \forall l \in \mathbf{Cluster_i}  \mathbf{do}$	$\triangleright$ <b>Cluster</b> <sub>i</sub> denotes <i>i</i> -th cluster in <b>Cluster</b>
if $d(l, c_i) \geq r$ then	$\triangleright c_i$ denotes <i>i</i> -th element of <i>k</i> -length vector <b>c</b>
$\mathbf{C}_{\mathbf{i}} = \mathbf{C}_{\mathbf{i}} \bigcup \{l\}$	
end if	
end for	
$SVMTrain(\mathbf{C_i})$	▷ Call conventional SVM training function
end for	
end function	

Algorithm 2 Testing: Perform testing on the extracted features of the collected dataset.

function TEST(Testing dataset, Clusters, c,  $|\mathbf{M}|, r$ )  $k=|\mathbf{M}|$   $\triangleright$  Number of Appliances for i = 1 : k do  $\mathbf{C}_i = \{\emptyset\}$ for  $\forall l \in \mathbf{Cluster}_i$  do if  $d(l, c_i) \ge r$  then  $\mathbf{C}_i = \mathbf{C}_i \bigcup \{l\}$ elseClassify sample i to the appliance corresponding to  $c_i$ end if end for  $SVMTest(\mathbf{C}_i)$   $\triangleright$  Call conventional SVM testing function end for end for

During testing, in general, if the Euclidean distance between a tested sample and any cluster head is smaller than a pre-set threshold, then the sample is classified to the closest cluster head. Otherwise, the sample is input to the SVM classifier. The proposed combined method has low execution time, since many samples will be classified rapidly using k-means, and only a small amount of samples that are far away from their heads, will be fed to the SVM classifier. However, the proposed algorithm maintains high performance, since SVM improves classification for samples that would most likely be incorrectly classified using the trained k-means.

Testing is straightforward and shown in Algorithm 2. Samples at distance less than r from a cluster head are classified to the appliance corresponding to that cluster head. All other samples are classified using SVM.



Figure 2. Probability density distribution of six REFIT dataset appliances, characterised by Gaussian mixture distribution. Fitted data shows appliance power sampled at 8 sec for five households over a period of 5 weeks.

#### 3.2. Database of appliance signatures

All domestic appliances are designed to work within a certain active power range, which can often be found in the appliance instruction manual. However, in practice, the actual active power measured will deviate due to electrical noise, interference, ageing, etc. The probability density function (PDF) of active power captures the electrical behaviour of an appliance, e.g., Figures 2 and 3 show the pdf for several domestic appliances in the REFIT and GREEND datasets. Due to the typical low sampling rates ( $\leq 1$  Hz) expected of smart meters, we focus only on steady state operation, automatically removing transient values from each appliance operation during data cleaning. As shown in Figures 2 and 3, the active power follows a Gaussian mixture distribution. See Subsection 4.4, which validates Gaussian modelling using root-mean squared error (RMSE) with respect to the true power load curve obtained through sub-metering.

A database of 280 unique appliance-load profiles is constructed from REDD [23], GREEND [24] and REFIT [7] datasets, with appliances ranging from standard kitchen appliances, such as kettle, toaster, microwave, cold appliances, washing machines and dishwashers, to electronics such as TV, Hi-Fi, PCs. Each database entry comprises the duty cycle for each appliance at the dataset's original sampling rate. Additionally, just like [11], each appliance's power load profile is modelled using a Gaussian mixture model, obtained via curve fitting. The model is represented in the database by its mean, variance, PDF and the first two correlation coefficients, calculated as:

$$R(\tau) = \frac{\sum_{t} (X_t - \mu)(X_{t+\tau} - \mu)}{\sigma^2},$$
(1)

where  $X_t$  is active power measurement at time instance  $t, \mu$  is the mean power value,  $\sigma^2$  is the



Figure 3. Probability density function for four different appliances from the GREEND dataset. Histograms are showing true data obtained via submetering.

variance and  $\tau$  is the sample lag.

We aim to build one general model for each type of appliance, i.e., one generic refrigerator model that would best fit all refrigerator makes and models encountered in our dataset houses. While this kind of generalization may not work for some appliances like televisions, all monitored washing machines and dishwashers have similar signatures. Figure 4 shows Gaussian distribution models for different Televisions (TVs). It is obvious from the figure that energy consumptions of different TV makes and models are very different. Figures 5a and 5b show the Gaussian distribution model for the washing machine and dishwasher obtained using the data from all GREEND houses. It can be seen that an efficient general model can be formed that represents well different appliance brands, which is due to the fact that all tested washing machines and dishwashers in our dataset have signatures that are similar, in the sense that there are clearly identifiable cycles, each with a similar operational power range.

Some appliances, referred to as *multi-state appliances*, such as washing machine or dishwasher, have several operating states. For example, the washing machine typically comprises three distinct states: wash, rinse and spin. The number of Gaussian components in the Gaussian mixture model is thus set to the number of operating states. Standby modes are neglected using proper thresholds for each appliance.



Figure 4. Different distributions of different TV types from the GREEND dataset. Histograms are showing true data obtained via sub-metering.

#### 3.3. Approach 2 using house-agnostic training data

Using the appliance active power signatures from the database, a general appliance model is generated for each appliance type, using the PDF of this appliance type. Note that the appliance PDF is generated from the active power signatures of that appliance, obtained from different makes and models in different houses in our datasets. This way, we generate one *general* Gaussian mixture model for each appliance type (e.g., washing machine, kettle, etc.), described by its mean and variance.

Based on the generated model, we design two methods. The first method draws samples from the obtained Gaussian mixture distribution that are used to form a training dataset. Effectively, the labelled dataset, in the case of Approach 1, that needs to be obtained via time-diary or sub-metering, is replaced by data samples generated from the Gaussian distribution for that particular appliance. Then, Algorithm 1 can readily be used to perform labelling, without any need for a time diary or sub-metering. The testing approach is the same as in the supervised method above.

The second proposed method, called Mean-variance General Model approach, uses only mean and variance of the generated general Gaussian mixture model. That is, unlike the previous approach, this approach does not draw samples from the model, which in turn implies that no other features (such as those shown in Table 1) can be used, besides mean and variance for classification of k-means and SVM. Due to its limited feature space, this approach is not expected to perform well, due to statistical similarities of appliance signatures.



Figure 5. Washing machine and dishwasher general models.

Note that both approaches can be used with different event-based supervised methods. That is, the designed general appliance model can replace training. We test both house-specific and house-agnostic training-based approaches next.

#### 4. Results and Discussion

In this section we present our experimental results and discuss our main findings. We use the publicly available REDD dataset [23] and GREEND dataset [24] with 1min and 1sec resolution, respectively, as well as our measurements that constitutes the REFIT dataset [7] acquired at 8sec resolution. The training size varied in the experiments, but testing is always performed on four weeks worth of data. We used Spring, Summer and Autumn periods for training and testing.

We organize the results as follows. First, the performance of the proposed Approach 1 with house-specific training, with respect to k-means and SVM approaches separately, is assessed. We show that combining k-means and SVM, as proposed in the previous section, leads to significant reduction in processing time while providing similar accuracy to that of SVM-based disaggregation. Then, we discuss feature selection and show that different classification features are suitable for different appliances. Hence, we propose that the choice of feature(s) to use for each appliance is made during training.

The third set of results assesses accuracy of the proposed approach when the training period varies and labelling errors occur. We show that the proposed approach is not sensitive to the size of the training period and presence of labelling errors. We use HMM-based [12], k-means-based, and the SVM-based approach as benchmarks.

Finally, we show that the proposed statistical modelling methodology introduces very small RMSE. Appliance models are then fed to the disaggregation module using house-agnostic training data. This provides close performance to the approach using house-specific training data, but without the requirement for training on the specific house data.

		k-means	SVM	Proposed Combined
Features	Appliance	$F_M$	$F_M$	$F_M$
		(%)	(%)	(%)
Area & duration	MW	0	0	25.9
	Stove	0	0	0
	Refrigerator	92.1	92.1	80.1
	Toaster	0	2.6	4.7
	Dishwasher	0	1.7	8
Min & Area	MW	0	0	0
	Stove	0	0	44.4
	Refrigerator	92.1	72.7	92.4
	Toaster	0	31.7	27.8
	Dishwasher	0	0	0
Max, dur. & Area	MW	0	0	0
	Stove	0	0	0
	Refrigerator	92.4	92.1	92.6
	Toaster	30.7	65.8	76.5
	Dishwasher	0	26.08	29.2
Max, area & Max/mean	MW	0	0	0
	Stove	0	2.1	0
	Refrigerator	92.1	92.4	93
	Toaster	0	37.7	72.5
	Dishwasher	0	0	28.5

Table 1. Comparison between the three methods using  $F_M$  for REDD data House 2.

# 4.1. Performance metrics

The evaluation metrics used are precision (PR), recall (RE) and F-Measure ( $F_M$ ), commonly used in NALM literature ([8, 17]) and defined as:

$$PR = TP/(TP + FP) \tag{2}$$

$$RE = TP/(TP + FN) \tag{3}$$

$$F_M = 2 * (PR * RE)/(PR + RE), \tag{4}$$

where true positive (TP) presents the correctly detected event, false positive (FP) represents an incorrect detection, and false negative (FN) indicates that the appliance used was not identified.

#### 4.2. Comparison with k-means and SVM

First, we evaluate the improvement obtained by combining k-means and SVM into a combined approach. Tables 1 and 2 show results obtained using House 2 from the REDD dataset (see the conference version [18] for other results) for the trained k-means-based, SVM-based, and

	k-m	eans	SV	'M	Proposed Combined		
Features	train test		$\operatorname{train}$	test	$\operatorname{train}$	test	
	(sec)	(sec)	(sec)	(sec)	(sec)	(sec)	
Area & duration	0.27	0.27	1.5	0.91	0.38	0.69	
Min & Area	0.24	0.29	1.19	0.72	0.15	0.53	
Max, dur. & Area	0.29	0.23	1.15	0.88	0.16	0.71	
Max, area & Max/mean	0.21	0.28	1.11	0.8	0.19	0.61	

Table 2. Comparison between the three methods using Execution time (training and testing) for REDD data House 2.

the combined algorithm. All three algorithms always use the same edge detection and feature extraction method explained in the previous section.

In House 2, we trained the algorithms with the following five known appliances: refrigerator, stove, microwave (MW), toaster, and dishwasher. All other household appliances were considered to be unknown and hence they contribute to noise. The training size contains 7000 samples or roughly one week of data, while testing was performed on 4 weeks of data. All experiments were run on an HP Pavilion 15 Notebook PC with 8GB RAM, 1TB Hard drive and AMD A10 with 2.2 GHz Radeon HD dual Graphics processor (quad core). Execution time in Table 2 shows overall time spent for training (for all appliances with one-week worth of data) and testing (four weeks).

We tested different two-, three-, four, and five-dimensional classifiers by extracting different features (event window area, time duration, minimum or maximum power value in the event window or maximum-to-mean value ratio) and present results for the best two two-dimensional and two three-dimensional classifiers.

Marked with bold typeface are the better performing features for each appliance. One can see that for different appliances different features give the best performance. For example, only *Area and Duration* classification returns a non-zero disaggregation accuracy for the microwave. Since we are classifying one appliance at a time, it is possible to adapt classification features from appliance to appliance. Thus, during training, the best features to use are identified per appliance which are then used during testing. In the following, we refer to this method, as the proposed combined method.

It can be seen from the tables that the SVM-based method outperforms the trained k-means, except for the refrigerator, but requires more time for both training and testing. For example, the best SVM-based NALM result for the toaster is obtained for the 3D classifier using maximum, duration and area is 2.5 times more accurate than the best k-means-based performance, but is over 3 times slower when performing training and testing.

The combined approach clearly outperforms both the k-means and SVM-based approaches for all appliances, through the appropriate selection of features for every appliance. While execution time for k-means is the smallest as expected, the combined approach executes faster than the SVM-based approach, confirming that combining both k-means and SVM approaches reduces the SVM execution time. Indeed, the proposed method reduces the operation time of SVM by reducing the number of samples fed to the SVM classifier, through clustering.



Figure 6. TP, FP, and FN for each appliance, after disaggregation by kmeans, SVM and the proposed combined method for House 2 in the REDD dataset. MW = microwave, DishW = Dishwasher.



Figure 7.  $F_M$  for the four methods for three REDD houses and three different training set sizes.

The performance of the three approaches can be explained by looking at Figure 6 which shows TP, FP, and FN values for the three approaches for all five appliances. The proposed, combined approach has the largest number of TPs and lowest number of FNs. k-means approach has generally low FP, but high FN and low TP. For example, for the microwave k-means and SVM yields TP = 0, FP = 32 and 0, respectively, and FN = 39. On the other hand, the proposed approach detects instances of the appliance running at TP = 32, with few omissions FN = 7, and FP = 176. Thus, the proposed approach detected almost all occurrences of microwave, but had too high sensitivity detecting the microwave running when it was not, due to very short microwave's duty cycle. This reduced the overall  $F_M$  for House 2 as shown in Table 8.

AIMS Energy

#### 4.3. Accuracy and Complexity

First, we test accuracy of the algorithms when the training time varies. Intuitively, by increasing the training time, the performance should improve, since more samples will be available to train classifiers. However, longer training time increases complexity and burden on customers if time diaries are used. That is why, it is desirable to have methods that do not require long training periods.

Figure 7 shows the average results for three REDD houses, benchmarked against the following three methods: the trained k-means based approach, the SVM-based approach and the HMM-based method of [12]. All methods used the same period for training and testing. K-means, SVM, and the proposed method use the optimal features (see Table 2).

 $F_M$  results are given for 3 different training sizes, namely 2000 (roughly 2 days), 5000 (roughly 5 days), and 7000 samples (roughly one week). Testing is done using four-week worth of data.

It can be seen that the proposed combined method either outperforms HMM-based and SVM-based approaches or provides a similar accuracy. k-means based approach provides lower disaggregation accuracy. Relatively high  $F_M$  obtained by k-means is somewhat misleading and can be explained by low FP values, despite low TP and high FN values (see Figure 6). On the other hand, high FP value for microwave, reduced overall  $F_M$  for the proposed method.

The methods are not sensitive to the variation of the training size. The HMM-based method only requires one appliance event running alone for a full duty cycle period to build a model. If other appliances are on, model generation will not be successful. A drop in the performance of the HMM method, as the size of the training set is reduced, is due to the fact that the appliances are not modeled properly and hence are not disaggregated. Note that the SVM-based and proposed method can have slightly better performance for smaller training sets due to better quality of the training data. In average over all three houses, the proposed method outperforms all other approaches for training sizes of 2000 and 7000 and is the second-best method for the training size of 5000 after k-means, whose  $F_M$  is not a true reflection of the performance (see Figure 6).

Table 8, in the appendix, shows the execution time which includes time spent on training and testing. The training execution time of the proposed method slightly increases as the training set size increases but it is still significantly lower than that of the HMM-based approach for all houses and all training sizes. Indeed, the proposed method needs roughly 18 and 3.5 times less time for testing than HMM and SVM, respectively, and 13 and 2.5 times less time for training than HMM and SVM, respectively. In average over all three houses, the proposed method is 2.75 times and 2 times faster for training and testing, respectively, than the SVM method and over 90 and 50 times faster, for training and testing, respectively, than the HMM-based method.

Table 3 shows the accuracy of the approaches when labelling errors occur as  $F_M$  vs the error rate for three different appliances. The error rate is the percentage of wrongly labelled data during training. Note that the proposed method is fairly not sensitive to the labelling errors except for the toaster whose operation is very short and easily confused with other appliances.

Error ra	Error rate		Toaster	Dishwasher	
	0 %	93.6	46.7	0	
K-means	5~%	91.9	57.4	0	
	15~%	91.8	2.4	0	
	20~%	91.9	2.4	0	
	0 %	92.5	69.13	26	
SVM	5~%	92.2	43.6	44.4	
	15~%	92	45.3	0	
	20~%	91.7	0	0	
	$0 \ \%$	94.3	79.1	29.2	
Proposed	5~%	91.8	11.4	17.39	
	15~%	93.3	11.9	42.8	
	20~%	91.9	8.9	45.3	
	0%	87.69	64.9	12.32	
HMM	HMM 5 %		64.9	12.32	
	15~%	83.42	49.97	12.32	
	20%	83.55	46.97	12.32	

Table 3.  $F_M$  results for House 2 obtained by introducing errors in the labelled dataset used for training.

Table 4. RMSE, mean [W], variance, 1st order correlation coefficient and 2nd order correlation coefficient for different TV's in Houses 4 and 5 from GREEND dataset. GM denotes the general model obtained by considering data from all GREEND houses.

Appliance	Mean value	Variance	RMSE	1st Cor.	2nd Cor.
House4 Kitchen TV	42.14	2.88	5.68 E-2	0.2698	0.2455
House4 living room TV	16.68	48.41	4.9 E-3	0.0962	0.0184
House5 LCD TV	35.25	2.46	3.77  E-4	0.0199	0.0768
	56.24	1.07			
House 5 Plasma TV	144.47	13.94	8.3 E-3	0.1442	0.0746
	201.45	34.67			
GM TV	28.5	4.117	0.0169		
	55.98	6.047			
	190.8	72.37			

# 4.4. Modelling Validation

In this section, we validate the proposed Gaussian mixture mathematical model for the pdf of active power for domestic appliances as described in Section 3.

We test suitability of three models for representing power signature: Gaussian, Laplace and Log-normal. Figure 8 presents the RMSE for each of the three distribution models. The values are obtained by averaging in time and across different houses. It can be seen that the Gaussian mixture model is the best fit for all appliances, especially for high loads such as kettle and

899



Figure 8. RMSE of Gaussian, Laplace and Log-normal models for 13 appliances from REFIT and GREEND datasets, and the REFIT aggregate meter reading, all shown on a log-scale.

toaster. As expected, the Gaussian mixture model is also the best for the aggregate readings, since it is a sum for nearly independent processes. This validates our approach of using the Gaussian mixture model (red line in Figure 2) to build the distribution model of all appliances. We also note that RMSE is insignificantly small except for low-consumers such as TV and Stereo Player. These findings are similar to those reported in [11].

Table 4 shows that regardless of the TV model, each individual TV appliance is modelled well resulting in relatively small RMSE error. However, when a general model is built, encompassing all the TVs in the dataset, where the pdfs varied widely, the RMSE is relatively high. The implications of this are that drawing on the general model for TV for training the unsupervised method would not result in high accuracy. A supervised approach trained on that household's dataset would be more effective in the case of TV.

Table 5 confirms that the RMSE obtained using the general model averaging appliance data from all the houses, is still small across all GREEND houses.

#### 4.5. Approach based on house agnostic training data

Tables 6 and 7 show, for two appliances, the relative performance of the following methods: Approach 1 - Regular training using house-specific training data which uses real labelled data from the specific house for training; Approach 2 - disaggregation using house-agnostic training data that uses features derived from the Gaussian distribution models and draws samples from the Gaussian distribution to train the k-means and SVM, and finally, the mean-variance approach using the mean and variance features directly from our Gaussian General model directly from our datasbase, called General Model (GM). As benchmarks, we used HMM-based and SVMbased methods. The models were built using at least three houses from the GREEND dataset

RMSE Mean value Variance 1st Cor. Appliance 2nd Cor. H0 WM 80.1 93.8 4.2 E-3 0.0751 -0.10591955.6 73.07 H1 WM 40.473.97 3.8 E-3 0.022 -0.11261991.7 90.92 H3 WM 94.7 115.59 1.91 E-2 0.0609 -0.08381957.8 69.51H4 WM 54.993.71 3.3 E-3 0.0298-0.2105597.4 13.772241946.1 GM WM 139.23.2 E-3 119.932009.3 90.45H0 DW 776.17 E-5 0.1925 0.1226 14.0577.8 1953.3H1 DW 13.728.94.5 E-5 -0.042-0.1111 1796 29.54H2 DW 18.133.199.97 E-5 -0.066-0.11862071.3 38.79 GM DW 48 42.566.7 E-3 2480368.2

Table 5. RMSE, mean [W], variance, 1st order correlation coefficient and 2nd order correlation coefficient for different washing machines and dishwashers of different GREEND houses. GM denotes the general model obtained by considering data from all GREEND houses.

and tested using two different houses. We selected washing machine and dishwasher since these are the only two appliances present in at least 5 houses, and also known to be significant.

Tables 6 and 7 show that the proposed approach using house-agnostic training data shows competitive performance to that of disaggregation using house-specific training data. The GM method could not detect washing machine events with only mean and variance as features, whereas the approach using house-agnostic training data used 2D classifiers with different features such as maximum load value, area and duration. The reason for this is that mean and variance of dishwashers in our dataset are very fairly standard, which is not the case with washing machines. Hence, we can conclude that it is necessary to train the disaggregation methods, drawing samples from the database, rather than using the features directly for the classification.

#### 5. Conclusion

Designing accurate NALM algorithms for low sampling data is challenging. In this paper we proposed two low-complexity solutions based on combining k-means and SVM. Appliances from a range of datasets are fitted to appliance-specific Gaussian Mixture models. The approach using house-agnostic training data uses a database of signatures to draw samples from the Gaussian Mixture models for training. The approach using house-specific training data is accurate even

		House-	specific training	House	e-agnost	GM		
Η	%	SVM	Combined	HMM	SVM	Combined	SVM	Combined
	PR	63.88	100	0.5	78.57	72.54	0	0
H1	RE	100	65.21	95.5	71.73	80.43	0	0
	$F_M$	77.96	78.94	1.04	75.00	76.28	0	0
	PR	83.33	87.50	2.14	83.33	88.23	6.26	9.09
H2	RE	100	93.33	96.4	100	100	3.33	3.33
	$F_M$	90.90	90.32	4.19	90.90	93.75	4.34	4.87

Table 6. Results of washing machine disaggregation in GREEND House 1 (H1) and House 2 (H2), using three different methods. Houses 3, 4 and 5 are used for training.

Table 7. Results of dishwasher disaggregation in GREEND House 2 (H2) and House 3 (H3), using three different methods. Houses 1, 4 and 5 are used for training.

		House-s	specific training	House	e-agnosti	GM		
Η	%	SVM Combined		HMM	SVM	Combined	SVM	Combined
	$\mathbf{PR}$	97.01	97.01	24.68	92.06	88.40	92.29	94.20
H2	RE	100	100	3.19	89.23	93.84	100	100
	$F_M$	98.48	98.48	5.66	90.62	91.04	96.29	97.01
	$\mathbf{PR}$	87.50	87.50	2.51	87.50	87.50	83.33	83.33
H3	RE	100	100	82	100	100	71.42	71.42
	$F_M$	93.33	93.33	4.88	93.33	93.33	76.92	76.92

when the training period is short and training errors are present and competitive to state-of-theart approaches. Training using house-agnostic data yields performance close to the case where training is done via house-specific data for large loads such as washing machine and dishwasher.

Our study provides the opportunity to make a trade-off between accuracy and complexity or execution time. Generally what we observed is that the time savings far outweigh the accuracy. The next steps are further development of the database of signatures based on crowdsourcing and testing the proposed methods using different datasets.

#### Acknowledgments

This work is supported in part by the UK Engineering and Physical Sciences Research Council (EPSRC) projects REFIT EP/K002368, under the Transforming Energy Demand in Buildings through Digital Innovation (BuildTEDDI) funding programme.

#### Conflict of interest

No conflict of interest. All authors contributed to paper writing, data analysis and algorithm design. Hana Altrabalsi implemented the proposed algorithms, ran simulations and generated

the results.

# References

- 1. Smart metering equipment technical specifications: Second version: Part 2. Department of Energy & Climate Change UK, Dec. 2013.
- 2. Armel KC, Gupta A, Shrimali G, et al. (2013) Is disaggregation the holy grail of energy efficiency? The case of electricity. *Energy Policy* 52: 213–234.
- 3. Hart G, Nonintrusive Appliance Load Data Acquisition Method, *MIT Energy Laboratory Technical Report*, Sept. 1984.
- 4. Zeifman M, Roth K (2011) Nonintrusive appliance load monitoring: Review and outlook. *IEEE Trans Consumer Electronics* 57: 76–84.
- Zoha A, Gluhak A, Imran MA, et al. (2012) Non-intrusive load monitoring approaches for disaggregated energy sensing: A survey. Sensors 12: 16838–16866.
- Perez KX, Cole WJ, Baldea M, et al. (2014) Meters to models: Using smart meter data to predict home energy use. in Process. ACEEE Summer Study on Energy Efficiency in Buildings, Pacific Grove, CA.
- Murray D, Liao J, Stankovic L, et al., A data management platform for personalised realtime energy feedback. in *Proc EEDAL-2015 8th Int Conf Energy Efficiency in Domestic Appliances and Lighting*, Lucerne-Horw, Switzerland, Aug. 2015.
- 8. Liao J, Elafoudi G, Stankovic L, et al. Power disaggregation for low-sampling rate data. 2nd Int. Non-intrusive Appliance Load Monitoring Workshop, Austin, TX, June 2014.
- 9. Marchiori A, Hakkarinen D, Han Q, et al. (2011) Circuit-level load monitoring for household energy management, *IEEE Pervas Comput* 10: 40-48.
- 10. Berges M, Goldman E, Matthews HS, et al. (2011) User-centered non-intrusive electricity load monitoring for residential buildings. J Comput Civil Eng 25: 471-480.
- 11. Kim H, Marwah M, Arlitt M, et al., Unsupervised disaggregation of low frequency power measurements, in *Proc 11th SIAM Int Conf Data Mining*, Mesa, AZ, April 2011.
- Parson O, Ghosh S, Weal M, et al. (2012) Non-intrusive load monitoring using prior models of general appliance types. in Proc. the 26th Conf. Artificial Intelligence (AAAI-12), Toronto, CA, pp. 356–362.
- 13. Kolter J, Jaakkola T (2012) Approximate inference in additive factorial HMMs with application to energy disaggregation. in *J Machine Learning* 22: 1472–1482.
- 14. Johnson MJ, Willsky AS (2013) Bayesian nonparametric Hidden Semi-Markov Models. J Machine Learning Research 14: 673–701.
- 15. Kolter J, Batra S, Ng AY, Energy Disaggregation via Discriminative Sparse Coding. in *Proc Advances in Neural Inform Processing Sys 23 (NIPS 2010).*
- Shao H, Marwah M, Ramakrishnan NA, Temporal motif mining approach to unsupervised energy disaggregation. in Proc. the 1st Int Workshop Non-Intrusive Load Monitoring, Pittsburgh, PA, May 2012.

- 17. Elafoudi G, Stankovic L, Stankovic V, Power disaggregation of domestic smart meter readings using Dynamic Time Warping. *ISCCSP-2014 IEEE Intl Symp Communications, Control, and Signal Processing,* Athens, Greece, May 2014.
- Altrabalsi H, Liao J, Stankovic L, et al., A low-complexity energy disaggregation method: Performance and robustness. SSCI-2014 IEEE Symp Comput Intelligence Applications in Smart Grid, Orlando, FL, Dec. 2014.
- Xia XL, Lyu MR, Lok LM, et al., Methods of decreasing the number of support vectors via k-mean clustering. in Proc ICIC 2005, LNCS 3644, pp. 717–726, Spinger-Verlag Berlin Heidelberg, 2005.
- Wang j, Wu x, Zhang C (2005) Support vector machines based on K-means clustering for real-time business intelligence systems. Int J Business Intelligence and Data Mining 1: 54–64.
- 21. Yao Y, Liu Y, Yu Y, et al. (2013) K-SVM: An effective SVM algorithm based on k-means clustering. *J Computers* 8: 2632–2639.
- 22. Gu Q, Jan J, Clustered Support Vector Machines. in *Proc AISTATS-2013 16th Int Conf* Artificial Intelligence and Statistics, Scottsdale, AZ, 2013.
- 23. Kolter J, Johnson M. REDD: A public data set for energy disaggregation research. in Workshop on Data Mining Applications in Sustainability (SIGKDD), San Diego, CA, 2011.
- 24. Monacchi A, Egarter D, Elmenreich W, et al. GREEND: An Energy Consumption Dataset of Households in Italy and Austria. *in Proc IEEE SmartGridComm*, Venice, Italy, Nov. 2014.
- 25. Gao J, Giri S, Kara EC, et al. (2014) PLAID: a public dataset of high-resolution electrical appliance measurements for load identification research: demo abstract. in Proc the 1st ACM Conference on Embedded Systems for Energy-Efficient Buildings, 198-199.
- 26. Ruzzelli AG, Nicolas C, Schoofs A, et al. (2010) Real-time recognition and profiling of appliances through a single electricity sensor. in Proc IEEE SECON-2010 7th Annual Conf Sensor Mesh and Ad Hoc Communications and Networks, 1–9.
- Laughman C, Lee K, Cox R, et al. (2003) Power signature analysis. *IEEE Power and Energy Magazine* 1: 56–63.
- 28. Liang J, Ng SKK, Kendall G, et al. (2010) Load signature study part I: Basic concept, structure, and methodology. *IEEE Trans Power Delivery* 25: 551–560.
- Berges M, Goldman E, Matthews HS, et al., Learning systems for electric consumption of buildings. in Proc 2009 ASCE Int Workshop Computing in Civil Engineering, Austin, TX, 2009.
- 30. Barker s, Kalra s, Irwin D, et al., NILM redux: The case for emphasizing applications over accuracy. *NILM-2014 Workshop*, Austin, TX, June 2014.
- Markonin S, Bajic IV, Popowich F, Efficient sparse metric processing for nonintrusive load monitoring. 2nd Int Non-intrusive Appliance Load Monitoring Workshop, Austin, TX, June 2014.
- 32. Al-Harbi SH, Rayward-Smith VJ (2006) Adapting k-means for supervised clustering. Appl Intell 24: 219–226.

904

# 6. Appendix

Table 8. F-measure [%] and Execution time for training and testing [sec] for the three REDD houses (H) using three different training sizes (t. size) given in number of samples.

			HMM k-means			S	SVM				Proposed		
Η	t. size	$\operatorname{train}$	test	$F_M$	$\operatorname{train}$	test	$F_M$	$\operatorname{train}$	test	$F_M$	$\operatorname{train}$	test	$F_M$
	2000	15.18	21.29	73.53	0.18	0.18	71.9	0.37	0.57	73.8	0.19	0.32	73.2
1	5000	23.79	19.27	75.58	0.25	0.25	71.2	0.76	0.65	74.2	0.27	0.25	71.7
	7000	28.32	22.90	77.06	0.2	0.2	73	0.83	0.78	80.37	0.7	0.26	77.52
	2000	18.38	18.56	81.03	0.09	0.25	89.69	0.43	0.72	85.9	0.1	0.32	84.7
$\mathcal{Z}$	5000	21.13	18.03	82.38	0.06	0.2	84.6	0.84	0.72	87.1	0.3	0.34	84.4
	7000	22.77	18.09	82.38	0.23	0.23	84.7	1.15	0.79	85.5	0.25	0.55	82.17
	2000	20.52	10.99	69.92	0.07	0.18	86.5	0.33	0.35	83.1	0.12	0.2	96.58
6	5000	22.46	13.91	72.76	0.09	0.14	96.58	0.56	0.45	81.5	0.15	0.26	88
	7000	30.22	16.19	72.76	0.24	0.24	97	0.69	0.53	80.6	0.11	0.28	95.58



 $\odot$  2016, Jing Liao, et al., licensee AIMS Press. This is an open access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0)