" TOP COPY

# WORKING PAPER NO. 10

LOCH FLEET: BATHYMETRY AND SEDIMENT DISTRIBUTION

N.J. ANDERSON

AND

R.W. BATTARBEE

PROGRESS REPORT FOR THE CEGB-SSEB LOCH FLEET PROJECT

MARCH 1985

Palaeoecology Research Unit, U.C.L.

#### CEGB-SSEB LOCH FLEET PROJECT

# PROGRESS REPORT, MARCH 1985

### Bathymetric survey

A bathymetric survey of Loch Fleet was carried out during the last week of July 1984. x, y co-ordinates were determined using plane tables and polar alidades from two shore stations and the base-line distance was fixed trigonometrically using a standard theodolite. z was determined using a calibrated Elliot graphic echo-sounder (model G500S/2) mounted in an inflatable boat. x, y and z point fixes were co-ordinated by CB radio during continuous traversing and the position and frequency of points was decided subjectively according to the frequency of slope changes indicated by the echo-sounder. In all 353 points were located with a mean x, y precision of approximately 3 metres and a z precision of 12.5 cm.

The fixed points were subsequently digitised and contoured using the MAPICS digital mapping system. Figures 1 and 2 show the distribution of points and the contoured bathymetry respectively. Morphometric data were calculated using software supplied by Mapics Ltd., and Table 1 shows data for lake area and lake volume and other morphometric variables.

	1984	1910 (Murray and Pullar)
Area (ha)	17.06	18.13
Vol. (m <sup>3</sup> )	1.051 x 10 <sup>6</sup>	1.16 x 10 <sup>6</sup>
Z <sub>max</sub> (m)	16.80	16.45
Z (m)	6.15	6.64

Table 1 Comparison of bathymetric data for Loch Fleet. Surveyed July 1984 during low water level conditions. Water surface 55 cm below temporary bench mark chiselled into granite boulder.

The lake was originally surveyed by Murray and Pullar in 1910, and Figure 3 shows a copy of their results. Table 1 compares the morphometric data. Although the Murray and Pullar survey was carried out in considerably less detail the morphometric values are very similar.

### Sediment sampling

Both surface sediment sampling and sediment coring were carried out during July 1984. Surface sediment samples were needed to assess the spatial distribution of diatoms in the accumulating zone of the lake, to provide samples for chemical analysis, and in order to make a map of sediment type. Sediment cores were required to evaluate recent sediment stratigraphy and to choose the most suitable core for detailed analysis. All sites were fixed by shore survey as described above.

- 1. Kajak coring. Short surface sediment cores were taken with the Kajak corer at 29 sites in zones where organic mud is accumulating. Each of the short cores was extruded in the boat and the O-1 cm sample was retained for diatom analysis. The remaining sediment was discarded. The location of these sites is shown in Figure 4. Diatom analysis will be carried out on all these samples.
- 2. Ekman grab sampling. Ekman grab samples were taken at the same stations as the Kajak samples, in the zone of organic sediment accumulation, as well as throughout the rest of the lake basin where minerogenic sediments occurred. Only in areas of the lake bottom covered by boulders or solid rock was it impossible to take samples. The distribution of these sites is shown in Figure 5 and a map of sediment types based on these samples is shown in Figure 6. Since no grain-size analyses have been carried out divisions between categories are subjectively based on a x 20 stereoscopic examination of the samples and on loss on ignition values. A contour

map of these values is shown in Figure 7. Table 2 gives details of sediment type according to the Troels-Smith classification and lists loss on ignition values for individual samples. Subsamples of the Ekman grab material have been sent to Dr. Gordon Glover, NCB Rotherham, for chemical and mineralogical analysis.

Ekman	% LOI	Troels-Smith	Ekman	% LOI	Troels-Smith
No.			No.		
1	29.32	Ld3 Dgl	47	16.96	As2 Ag1 Ld1
2	45.16	Ld4 Dg+	48	2.01	As3 Gal
3	51.09	Ld4 Dg+	49	23.76	Ld4 Dg+
4	44.17	Ld4 Dg+	50	1.21	As2 Ag1 Gal
5	45.06	Ld4 Dg+	51	29.18	Lđ4 Ag+ Dg+
6	51.80	Ld4 Dg+	52	6.58	Gs2 Ld2 Dg+
7	52.58	Ld4 Dg+ Ag+	53	1.50	As2 Dgl Gal
8	43.04	Ld4 Dg+	54	2.35	Gg2 Asl Agl
9	2.05	As2 Agl Gal	55	1.04	Gg3 Asl Ld+
10	32.55	Ld3 Gsl	56	0	O*
11	5.07	Gg4	57	0	Stony/Moss
12	2.54	Gg3 Ldl	58	0	0*
		_	59	5.14	Gs3 Ldl Dg+
20	48.04	Ld4 Dg+ Ga+	60	9.14	=
21	42.11	Ld4 Dg+ Ga+	61	24.88	<del>-</del>
22	5.53	Ld3 Gal	62	1.70	Gg3 Ldl
23	44.33	Ld4 Dg+	63	1.37	
24	1.67	Gs3 Ldl Dg+	64	1.36	-
25	7.49	Ld4 Ga+	65	0	<del>-</del>
26	1.51	Gs3 Ggl Ld+ Dg+	66	1.97	As3 Gal
27	41.74	Ld3 Gal Dg+	67	0	LFe4 iron oxide concretion
28	36.02	Ld4 Dg+	68	14.07	Ld4 Ga+ Dg+
29	50.49	Ld4 Dl+	69	1.81	Gg4 Ld+
30	47.37	Ld4 Dg+	70	11.19	Ld4 Ga+ Dg+
31	47.01	Ld4 Dg+	71	28.57	Ld4 Ga+ Dg+
32	47.13	Ld4 Dg+	72	0	O*
33	44.44	Ld4 Dg+	73	1.73	Gg3 Ldl
34	46.12	Ld4 Dg+	74	1.78	Gg3 Gal Ld+
35	1.51	Ga2 Asl Agl	75	2.69	Gs2 As2 Ld+
36	42.81	Ld4 Ga+ Dg+	76	5.59	As3 Agl
37	8.19	Ag3 Ld1	77	1.35	Gs3 Ldl
38	0	O*	78	0	O*
39	22.54	Ld4 Dg+ Ag+	79	0	Stony/Moss
40	1.33	Gg3 Gsl Ld+	80	0	O*
41	5.88	Gg3 Gsl Ld+	81	0	O*
42	1.73	As3 Gal	82	0	Stony/Moss
43	1.32	As2 Agl Gal	83	0	O*
44	1.68	As3 Agl Gal	84	25.87	Ld3 Agl
45	42.29	Ld4 Ga+	85	40.67	<del>-</del>
46	48.96	Ld4 Dg+	86	3.15	Gs3 Ldl

<sup>\* =</sup> No retrieval.

Table 2 % loss-on-ignition and Troels-Smith classification for Ekman grab samples.

# References

- Battarbee, R.W., Appleby, P.G., Odell, K. and Flower, R.J. 1985

  210
  Pb dating of Scottish lake sediments, afforestation and accelerated soil erosion. Earth Surface Processes and Landforms

  10, 137-142.
- Murray, J. and Pullar, L. 1910 Bathymetrical Survey of the Scottish

  Fresh-water Lochs Vol. 5, Edinburgh: Challenger Office.




Fig. 1 Distribution of points used to derive bathymetry.




Fig. 2 Bathymetry.




Fig. 3 Bathymetry as surveyed by Murray and Pullar (1910).




Fig. 4 Location of Kayak core samples.




Fig. 5 Location of Ekman Grab samples.




Fig. 6 Distribution of main surface sediment types.




Fig. 7 Distribution of organic matter, as determined by loss-on-ignition.




Fig. 8 Location of Mackereth minicores and Livingstone cores.




Fig. 9a % LOI Mackereth minicores.




Fig. 9b % Dry weight Mackereth minicores.




Fig. 10a % LOI Livingstone cores.




Fig. 10b % Dry weight Livingstone cores.

#### PALAEOECOLOGY RESEARCH UNIT

### WORKING PAPERS

- No l Patrick, S. & Battarbee, R.W. 1981 The influence of sanitary and other social changes on the eutrophication of Lough Erne since 1850: Project introduction and a consideration of the potential role of metabolic wastes. 43 pp.
- No 2 Battarbee, R.W. 1983 Diatom analysis of River Thames foreshore deposits exposed during the excavation of a Roman waterfront site at Pudding Lane, London. 18 pp.
- No 3 Patrick, S. & Battarbee, R.W. 1983 Rural sanitation in the Lough Erne catchment: History and influence on phosphorus loadings. 26 pp.
- No 4 Patrick, S. 1983 The calculation of per capita phosphorus outputs from detergents in the Lough Erne catchment. 23 pp.
- No 5 Patrick, S. 1983 Phosphorus loss at sewage works in the Lough Erne region. 36 pp.
- No 6 Flower, R.J. & Battarbee, R.W. 1983 Acid lakes in the Galloway uplands, South West Scotland: catchments, water quality and sediment characteristics. 56 pp.
- No 7 Patrick, S. 1984 The influence of industry on phosphorus loadings in the Lough Erne region. 46 pp.
- No 8 Battarbee, R.W. and Flower, R.J. 1985 Palaeoecological evidence for the timing and causes of lake acidification in Galloway, southwest Scotland. 79 pp.
- No 9 Raven, P.J. 1985 The use of aquatic macrophytes to assess water quality changes in some Galloway locks; an exploratory study. 76 pp.

For copies or further information, please contact Dr. R.W. Battarbee, Palaeoecology Research Unit, Department of Geography, University College London, 26 Bedford Way, London WClH OAP.