



UNIVERSITI PUTRA MALAYSIA

**LOCATION-BASED APPROACH FOR ROUTE MAINTENANCE IN
DYNAMIC SOURCE ROUTING PROTOCOL**

Muhammad Farhan Sjaugi

FSKTM 2008 9

**LOCATION-BASED APPROACH FOR ROUTE MAINTENANCE IN
DYNAMIC SOURCE ROUTING PROTOCOL**

By

Muhammad Farhan Sjaugi

**Thesis Submitted to the School of Graduate Studies, Universiti
Putra Malaysia, in Fulfilment of the Requirements for
Degree of Master of Science**

August 2008



DEDICATION

*Dedicated to my lovely parents,
to my lovely fiancée and
to Indonesia*



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**LOCATION-BASED APPROACH FOR ROUTE MAINTENANCE IN
DYNAMIC SOURCE ROUTING PROTOCOL**

By

Muhammad Farhan Sjaugi

November 2008

Chairman: Associate Professor Mohamed Othman, PhD

Faculty: Computer Science and Information Technology

Earlier, the idea of mobile computers and ad hoc networks was not on the mind of anyone. All specifications and implementations for the computer networks during that time were designed for wired systems. This is a big challenge for computer engineer since these two systems have different characteristics. Wireless network means dynamic topology, dynamic structure and no infrastructure, while wired network is the opposites. Basically mobile wireless network has the same standard layers of structure, with modifications and functionality that differ from the earlier networks because of the absence of infrastructure.

To facilitate communication within the network, a routing protocol is used to discover routes between nodes. Building a MANET routing protocol is not an easy job, since efficiency and correctness become the main concern. Some approach had been proposed to make routing protocol becomes efficient and correct.



Dynamic Source Routing (DSR) protocol is known to be a simple routing protocol in MANET. DSR is based on the concept of source routing. For this protocol, mobile nodes are required to maintain route caches that contain the source routes of which the mobile is aware. Entries in the route cache are continually updated as new routes are learned. There are two major phases of the protocol - route discovery and route maintenance. Route discovery uses route request and route reply packets. Route maintenance uses route error packets and acknowledgments.

Although DSR can respond a route quickly, it yields a long delay when a route is rebuilt. This is because when source node receives RERR packet, it will try to find alternative routes from route cache. If alternative routes are not available, source node, then, will enter route discovery phase to find new routes. Finding a route in wireless network require considerable resources, such as time, bandwidth, and power because it relies on broadcasting. In some case any packets may still reach its destination, but with some delay. This delay is very expensive and leads to undesired effect, especially in real time networks and the networks with QoS, where the packet delay and packet delivery is the main concern.

The objectives of this research are to propose new algorithm to detect route failure as early warning message to the protocol to take further action, and to propose new algorithm for DSR route maintenance to response the early warning message from route failure detection algorithm. The proposed algorithms based on node location information that may be collected through Global Positioning System (GPS).



This thesis introduces two new route maintenance strategies by utilizing node location information. These new route maintenance strategies are called as DISTANCE (DIstance baSed rouTe maintenANCE) and ADISTANCE (Adaptive DISTANCE). The algorithms work by adding another node (called bridge node) into the source list to prevent the link from failure. From the simulation result, both algorithms improve the performance of DSR in terms of packet sending ratio, delay and routing overhead.

Abstrak disertasi yang diserahkan kepada Senat Universiti Putra Malaysia bagi memenuhi keperluan untuk ijazah master sains

**PENDEKATAN BERASASKAN LOKASI BAGI
PENYELENGGARAAN PENGHALAAN LALUAN DALAM
PROTOKOL PENGHALAAN SUMBER DINAMIK**

Oleh

Muhammad Farhan Sjaugi

November 2008

Pengerusi: Profesor Madya Mohamed Othman, PhD

Fakulti: Sains Komputer dan Teknologi Maklumat

Pada peringkat awal tiada siapa pun terfikir tentang komputer mudah alih dan rangkaian ad hoc. Pada masa itu, semua spesifikasi dan pelaksanaan untuk rangkaian komputer hanya menggunakan rangkaian berwayar sahaja. Ini merupakan satu cabaran yang besar kepada jurutera komputer kerana kedua-dua rangkaian ini mempunyai sifat-sifat yang berbeza. Rangkaian tanpa wayar bercirikan struktur yang dinamik dan tanpa infrastruktur, manakala rangkaian berwayar membawa maksud yang sebaliknya. Pada asasnya rangkaian mudah alih tanpa wayar mempunyai lapisan piawai yang sama dengan rangkaian berwayar kecuali dengan beberapa pengubahsuaian dan fungsi yang berbeza daripada rangkaian berwayar kerana kekurangan dari segi infrastruktur.

Untuk memudahkan komunikasi dalam rangkaian, protokol penghalaan laluan digunakan untuk mencari laluan diantara nod-nod. Membina protokol pencarian laluan MANET bukanlah suatu kerja yang mudah kerana kecekapan dan ketepatan menjadi hal yang utama. Beberapa pendekatan penyelidikan telah dicadangkan untuk menjadikan protokol penghalaan laluan lebih cekap dan tepat.

Protokol Penghalaan Sumber Pantas (DSR) adalah satu protokol pencarian laluan yang ringkas dalam MANET. Protokol ini berdasarkan kepada konsep laluan daripada sumber. Protokol ini mengekalkan simpanan laluan sementara yang mengandungi laluan-laluan sumber yang diketahui oleh setiap nod. Simpanan laluan sementara dikemaskini secara berterusan apabila laluan yang baru dikenalpasti. Terdapat dua fasa utama dalam protokol ini - Pencarian Laluan dan Penyelenggaraan Laluan. Pencarian Laluan menggunakan paket permintaan-laluan dan paket laluan-balas. Penyelenggaraan Laluan menggunakan paket ralat-laluan dan paket perakuan.

Walaupun DSR boleh bertindak balas dengan cepat, ia menghasilkan kelewatan apabila laluan dinina semula. Ini kerana apabila nod sumber menerima paket ralat-laluan, ia akan cuba untuk mencari laluan alternatif daripada simpanan laluan sementara. Jika tiada laluan alternatif yang boleh digunakan, nod sumber akan memasuki fasa Pencarian Laluan untuk mencari laluan yang baru. Mencari laluan didalam rangkaian tanpa wayar memerlukan pertimbangan sumber yang banyak, seperti masa, lebar jalur dan tenaga kerana ia bergantung kepada penyiaran. Dalam kes tertentu, paket boleh sampai ke destinasi tetapi dengan lewat. Kelewatan ini boleh menyebabkan kesan yang tidak diinginkan, terutama

sekali dalam rangkaian masa nyata dan rangkaian dengan QoS, dimana kelewatan paket dan penghantaran paket merupakan hal yang paling utama.

Objektif penyelidikan ini adalah untuk mencadangkan algoritma yang baru untuk mengesan kegagalan laluan sebagai mesej amaran awal kepada protokol supaya tindakan selanjutnya boleh diambil dan juga mencadangkan algoritma baru untuk penyelenggaraan laluan DSR agar boleh bertindak balas terhadap mesej amaran awal daripada algoritma pengesan kegagalan laluan. Algoritma yang dicadangkan adalah berdasarkan maklumat lokasi nod yang dikumpul menggunakan Sistem Kedudukan Global (GPS).

Tesis ini memperkenalkan dua strategi penyelenggaraan laluan dengan menggunakan maklumat lokasi nod. Strategi penyelenggaraan laluan ini dipanggil sebagai Penyelenggaraan Laluan Berasaskan Jarak (DISTANCE) dan Penyelenggaraan Laluan Adaptif Berasaskan Jarak (ADISTANCE). Algoritma ini bertindak dengan menambah nod lain (dipanggil nod jambatan) ke dalam senarai sumber untuk mengelakkan kegagalan sambungan. Berasaskan kepada hasil eksperimen simulasi, kedua-dua algoritma ini memperbaiki prestasi DSR dalam penghantaran paket, kelewatan dan beban laluan.

ACKNOWLEDGEMENTS

First and foremost, Alhamdulillah for giving me the strength, patience, courage, and determination in completing this work. All grace and thanks belongs to Almighty Allah.

Many special thanks go to my supervisor Associate Professor Dr. Mohamed Othman, for his invaluable advice, helpful guidance and who always provides valuable recommendations and suggestions to my inquiries tranquilly and accurately.

I would like to take this opportunity to express my sincere appreciation and thanks to the member of the supervisory committee, Dr.Mohd. Fadlee A.Rasid for his advice and comments during the completion of this thesis.

Sincere and heartfelt thanks to the Faculty of Computer Science and Information Technology and the staff of the Postgraduate office, Library and Universiti Putra Malaysia, for providing a studying and research environment.

Finally, many thanks to my parents, my fiancée, family members and friends for their love, constant support, patient and encouragement in all my endeavors.

Muhammad Farhan Sjaugi

Date: 16 September 2008



I certify that an Examination Committee met on 22nd of August 2008 to conduct the final examination of Muhammad Farhan Sjaugi on his Master of Science thesis entitled "Location-Based Approach for Route Maintenance in Dynamic Source Routing Protocol" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Masrah Azrifah Azmi Murad, Ph.D.

Lecturer

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Chairman)

Zuriati Ahmad Zulkarnain, Ph.D.

Lecturer

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Member)

Shamala K. Subramaniam, Ph.D.

Lecturer

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Member)

Mahamod Ismail, Ph.D.

Professor

Faculty of Engineering

Universiti Kebangsaan Malaysia

(Independent Examiner)

GULAM RUSUL RAHMAT ALI, Ph.D.

Professor, Deputy Dean

School of Graduate Studies

Universiti Putra Malaysia

Date:



This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Mohamed Othman, PhD

Associate Professor

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Chairman)

Mohd. Fadlee A.Rasid, PhD

Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Member)

AINI IDERIS, PhD

Professor and Dean

School of Graduate Studies

Universiti Putra Malaysia

Date: 13 November 2008



DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

Muhammad Farhan Sjaugi

Date: 16 September 2008



TABLE OF CONTENTS

DEDICATION	ii
ABSTRACT	iii
ABSTRAK	vi
ACKNOWLEDGEMENTS	ix
APPROVAL	x
DECLARATION	xii
LIST OF TABLES	xvi
LIST OF FIGURES	xvii
1INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	3
1.3 Objective	4
1.4 Scope	4
1.5 Contributions of Research	5
1.6 Thesis Organization	5



2	LITERATURE REVIEW	7
2.1	Introduction	7
2.2	Mobile Wireless Adhoc Network	7
2.2.1	Routing Protocol in MANET	8
2.2.2	Proactive Routing Protocol	9
2.2.3	Reactive Routing Protocol	11
2.3	DSR Protocol Model	13
2.3.1	Routing Stage	14
2.3.2	Optimization Stage	15
2.3.3	Route Maintenance Stage	15
2.3.4	Route Failure Detection	16
2.3.5	DSR Route Maintenance	17
2.4	Summary	19
3	METHODOLOGY	21
3.1	Introduction	21
3.2	Improving DSR Route Maintenance	21
3.3	Preventive Route Maintenance Framework	22
3.4	Route Failure Detection	23
3.5	Route Failure Prevention	23

	xv
3.6	Location Information Exchange 24
3.7	Performance Analysis 24
3.7.1	Scalable Wireless Adhoc Network Simulator 25
3.7.2	Simulation Setup 27
3.7.3	Performance Parameters 28
3.7.4	Assumptions 29
3.8	Summary 30
4	DISTANCE BASED ROUTE MAINTENANCE 31
4.1	Introduction 31
4.2	The DISTANCE Algorithm 31
4.2.1	Unsafe Link Detection 32
4.2.2	Route Expansion 33
4.2.3	Packet Header Format 34
4.3	Case Study 36
4.4	Simulation Results and Discussion 38
4.4.1	Performance on Varying Mobility Speed 38
4.4.2	Performance on Varying Node Density 41
4.5	Summary 42



5	ADAPTIVE DISTANCE BASED ROUTE MAINTENANCE	43
5.1	Introduction	43
5.2	The ADISTANCE Algorithm	43
5.2.1	Unsafe Link Detection	45
5.2.2	Route Expansion	46
5.2.3	Packet Header Format	47
5.3	Case Study	48
5.4	Simulation Results and Discussion	49
5.4.1	Performance on Varying Mobility Speed	50
5.4.2	Performance on Varying Node Density	52
5.5	Overall Comparison of Protocols	53
5.6	Summary	56
6	CONCLUSION AND FUTURE RESEARCH DIRECTION	57
6.1	Conclusion	57
6.2	Future Research Direction	59
	REFERENCES	60



A Random Waypoint Mobility Model	63
BIODATA OF THE AUTHOR	64
LIST OF PUBLICATIONS	65



LIST OF TABLES

3.1 Simulation Parameters	28
-------------------------------------	----



LIST OF FIGURES

2.1	The Dynamic Source Routing Protocol Model. The highlighted area is what this research focus on	13
3.1	The Preventive Route Maintenance Framework for DSR .	22
3.2	The Scalable Wireless Adhoc Network Simulator Framework, adopted from [5]	26
3.3	The Snapshot of SWANS	26
4.1	The BridgeNode-Request Packet Format	35
4.2	The BridgeNode-Reply Packet Format	35
4.3	Node D move to D', makes link from node C to node D' becomes unsafe	36
4.4	Node C sends a local broadcast packet to find candidate nodes for bridging the link	37
4.5	New routes after expansion	37
4.6	Average Packet Delivery Ratio vs Mobility Speed	39
4.7	Average Packet Delivery Time vs Mobility Speed	40
4.8	Average Number of Routing Overhead vs Mobility Speed	40
4.9	Average Packet Delivery Ratio vs Number of Nodes	41
4.10	Average Packet Delivery Time vs Number of Nodes	42
4.11	Average Number of Routing Overhead vs Number of Nodes	42



5.1	The BridgeNode-Request Packet Format	48
5.2	Node D move to D', makes link from node C to node D' becomes unsafe	48
5.3	Node D' sends a local broadcast packet to get candidate nodes for bridging the link	49
5.4	New routes after expansion	49
5.5	Average Packet Delivery Ratio vs Mobility Speed	51
5.6	Average Packet Delivery Time vs Mobility Speed	51
5.7	Average Number of Routing Overhead vs Mobility Speed	51
5.8	Average Packet Delivery Ratio vs Number of Nodes	52
5.9	Average Packet Delivery Time vs Number of Nodes	52
5.10	Average Number of Routing Overhead vs Number of Nodes	53
5.11	Average Packet Delivery Ratio vs Mobility Speed	53
5.12	Average Packet Delivery Time vs Mobility Speed	54
5.13	Average Number of Routing Overhead vs Mobility Speed	54
5.14	Average Packet Delivery Ratio vs Number of Nodes	54
5.15	Average Packet Delivery Time vs Number of Nodes	55
5.16	Average Number of Routing Overhead vs Number of Nodes	55
A.1	The example of Random Waypoint mobility model. Each node can move freely inside the boundary area.	63



CHAPTER 1

INTRODUCTION

1.1 Background

Earlier, the idea of mobile computers and ad hoc networks was not on the mind of anyone. All specifications and implementations for the computer networks during that time were designed for wired systems. This is a big challenge for computer engineer since these two systems have different characteristics. Wireless network means dynamic topology, dynamic structure and no infrastructure, while wired network is the opposites. Most of wired network design and implementation must be modified or redesigned in order to operate in the wireless network. Basically mobile wireless network has the same standard layers of structure, with modifications and functionality that differ from the earlier networks because of the absence of infrastructure.

There are currently two variations of mobile wireless networks. The first is known as infrastructured network. The bridges for these networks are known as base stations. A mobile unit within these networks connects to, and communicates with, the nearest base station that is within its communication radius. As the mobile travels out of range of one base station and into the range of another, a “handoff” occurs from the old base station to the new, and the mobile is able to continue communication seamlessly throughout the network. Typical applications of this type of network include office wireless local area networks (WLANs).



The second type of mobile wireless network is Ad-hoc network. Unlike infrastructured network, in this type of network a base station is needless. Mobile nodes communicate to each other by either directly or through intermediate nodes. Ad-hoc network becomes popular since it can be applied in many situations, such as emergency search-and-rescue operations, classroom, meetings or conference, and many more. Ad-hoc network also can be mobile, called Mobile Ad-hoc Network or MANET.

To facilitate communication within the network, a routing protocol is used to discover routes between nodes. Building a MANET routing protocol is not an easy job, since efficiency and correctness become the main concern. Some approach had been proposed to make routing protocol becomes efficient and correct.

Today there is quite a lot of mobile device such as cell phone and Personal Digital Assistance, which is equipped with Global Positioning System (GPS). Mostly the application of GPS is intended for navigation purposes such as road tracking. Besides using GPS to knowing current location, it also can be used for routing purposes. Each node may know another nodes location by exchanging their current location (in this thesis, the current location is referred as location information).

Dynamic Source Routing (DSR) protocol is known to be a simple routing protocol in MANET. DSR is based on the concept of source routing. For this protocol, mobile nodes are required to maintain route caches that contain the source routes of which the mobile is aware. Entries in the route cache are continually updated



as new routes are learned. There are two major phases of the protocol - route discovery and route maintenance. Route discovery uses route request and route reply packets. Route maintenance uses route error packets and acknowledgments [8].

An advantage of DSR is that nodes can store multiple routes in their route cache, which means that the source node can check its route cache for a valid route before initiating route discovery, and if a valid route is found there is no need for route discovery. This is very beneficial in network with low mobility. Since the routes stored in the route cache will be valid longer. Another advantage of DSR is that it does not require any periodic beaconing (or hello message exchanges), therefore nodes can enter sleep mode to conserve their power. This also saves a considerable amount of bandwidth in the network [1].

1.2 Problem Statement

Although DSR can respond a route quickly, it yields a long delay when a route is rebuilt. This is because when source node receives RERR packet, it will try to find alternative routes from route cache. If alternative routes are not available, source node, then, will enter route discovery phase to find new routes. Finding a route in wireless network require considerable resources, such as time, bandwidth, and power because it relies on broadcasting. In some case any packets may still reach its destination, but with some delay. This delay is very expensive and leads to undesired effect, especially in real time networks and the networks with QoS, where the packet delay and packet delivery is the main concern.



1.3 Objective

The objectives to be achieved in this thesis are:

1. Propose new algorithm to detect route failure as early warning message to the protocol to take further action, i.e route maintenance. The proposed algorithm will be based on geographical location information that may be collected through Global Positioning System (GPS).
2. Propose new algorithm for DSR route maintenance to response the early warning message from route failure detection algorithm. Once the message is received, several action will be to be taken to reconstruct the routing path. The proposed route maintenance algorithm also will be based on geographical location information.

1.4 Scope

This research will focus on:

1. The exploitation of node location information into MANET routing protocol for route maintenance purpose, in this case this research will focus on DSR routing protocol.
2. Route failure because of node movement only is considered in this thesis. Route failure because of node disappearance or dropped from the network is not considered.
3. Network/Routing layer only.