



UNIVERSITI PUTRA MALAYSIA

**FACE DETECTION TECHNIQUE BASED ON SKIN COLOR AND
FACIAL FEATURES**

KHALID MOHAMED ALAJEL.

FK 2005 9

**FACE DETECTION TECHNIQUE BASED ON SKIN COLOR AND FACIAL
FEATURES**

By

KHALID MOHAMED ALAJEL

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in
Fulfilment of the Requirements for the Degree of Master of Science**

December 2005



Dedicated

to

My Parents, Wife, Brothers and Sisters



Abstract of thesis presented to the Senate of the Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science

FACE DETECTION TECHNIQUE BASED ON SKIN COLOR AND FACIAL FEATURES

By

KHALID MOHAMED ALAJEL

December 2005

Chairman: Khairi Bin Yusof, PhD

Faculty: Engineering

Face detection is an essential first step in face recognition systems with the purpose of localizing and extracting the face region from the background. Apart from increasing the efficiency of face recognition systems, face detection technique also opens up the door of opportunity for application areas such as content based image retrieval, video encoding, video conferencing, crowd surveillance and intelligent human computer interfaces.

This thesis presents the design of face detection approach which is capable of detecting human faces from complex background. A skin color modeling process is adopted for the face segmentation process. Image enhancement is then used to improve the face candidate before feeding to the face object classifier based on Modified Hausdroff distance. The results indicate that the system is able to detect human faces with reasonable accuracy.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

TEKNIK PENGESANAN MUKA BERDASARKAN WARNA KULIT DAN CIRI.CIRI MUKA

Oleh

KHALID MOHAMED ALAJEL

Disember 2005

Pengerusi: Khairi Bin Yusof, PhD

Fakulti: Kejuruteraan

Pengesanan muka merupakan langkah pertama yang penting dalam pengesanan muka dengan tujuan melokalisasikan dan mengesktrakkan bahagian muka daripada latar belakang. Selain meningkatkan keberkesanan sistem pengesanan muka, teknik pengesanan muka juga membuka peluang kepada bidang.bidang aplikasi seperti pengeluaran imej berdasarkan kandungan, pengenkodan video, pengawasan dan antara muka manusia.komputer bestari.

Tesis ini mempersembahkan reka bentuk pendekatan pengesanan muka yang mampu mengesan muka manusia dalam latar belakang kompleks. Sistem pemodelan warna kulit digunakan untuk sistem segmentasi muka. Penambah baikan imej juga kemudian digunakan untuk meningkatkan calon muka sebelum membekalkan kepada pengelas objek muka berpandukan jarak Modified Hausdorff. Keputusan yang diperoleh menunjukkan sistem ini mampu mengesan muka manusia dengan ketepatan yang munasabah.



ACKNOWLEDGEMENTS

First of all, I would like to express my greatest gratitude to Allah the almighty, for his help and support during the course of life and moment of truth. Alhamdollilah.

I would like to express my gratitude to my supervisor, Dr. Khairi Bin Yosuf. I fell privilege to have him as my advisor. I am profoundly grateful for his tremendous support, commends, encouragement, quick response and mentoring through my research. Sincere appreciation is also due to Associate Professor Dr. Abdul Rahman Ramli and Dr. Elsadig Ahmed, members of the supervisory committee for their help, wise council, guidance, encouragement, quick response, valuable suggestions and guidance for execution of the research project as well as critical reviewing of the manuscript.

The author would like to thank his lovely father and mother the best that anybody could have for their unconditional love and continual support that made me strong in completing this thesis. Also I would like to thank my brothers and sisters for their constant support and encouragement throughout my life.

I would like to thank my beloved wife for her unwavering support and understanding as I went through this process. She always been and will always be my biggest support.

I certify that an Examination Committee met on 23th December 2005 to conduct the final examination of Khalid Mohamed Alajel on his Master of Science thesis entitled “Face Detection Technique Based on Skin Color and Facial Features” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Syed Javaid Iqbal, PhD

Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Sabira Khatun, PhD

Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Mohd Adzir Mahdi, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Kasmiran Jumari, PhD

Professor
Faculty of Engineering
Universiti Kebangsaan Malaysia
(External Examiner)



HASANAH MOHD. GHAZALI, PhD

Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: **19 JAN 2006**



This thesis submitted to the Senate of University Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

Khairi Bin Yosuf, PhD

Lecture

Faculty of Engineering

University Putra Malaysia

(Chairman)

Abdul Rahman Ramli, PhD

Associate Professor

Faculty of Engineering

University Putra Malaysia

(Member)

Elsadig Ahmed Babiker, PhD

Lecture

Faculty of Engineering

University Putra Malaysia

(Member)



AINI IDERIS, PhD

Professor/Dean

School of Graduate Studies


Universiti Putra Malaysia

Date: 07 FEB 2006



DECLARATION

I here by declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or currently submitted for any other degree at UPM or other institutions.



KHALID MOHAMED ALAJEL

Date: 1.1.2006

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL	ix
DECLARATION	ix
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xv
CHAPTER	
1 INTRODUCTION	1.1
1.1 Background	1.1
1.2 Problem Statement	1.4
1.3 Objectives	1.5
1.4 Thesis Outline	1.5
2 LITERATURE REVIEW	
2.1 Introduction	2.1
2.2 Prior Work on Face Detection	2.2
2.3 Face Detection Approach	2.6
2.3.1 Feature based Approach	2.6
2.3.1.1 Edges	2.8
2.3.1.2 Gray Information	2.10
2.3.1.3 Color	2.11
2.3.1.4 Motion	2.14
2.3.1.5 Generalized Measures	2.15
2.3.1.6 Feature Analysis	2.16
2.3.1.7 Active Shape Models	2.19
2.3.2 Image Based Approach	2.20
2.3.2.1 Linear Subspace	2.20
2.3.2.2 Neural Network	2.21
2.3.2.3 Statistical Approach	2.22
2.4 Hausdorff Distance Approach	2.24



2.4.1	Modified Hausdorff Distance	2.25
2.5	Approach by this Thesis	2.26
3	METHODOLOGY	
3.1	Introduction	3.1
3.2	System Overview	3.1
3.3	Skin Color Segmentation	3.4
3.3.1	Skin Color Filtering	3.5
3.3.2	Enhancement	3.12
3.3.2.1	Connected Component Labeling	3.13
3.3.2.2	Median Filtering	3.15
3.3.2.3	Image Dilation	3.17
3.4	Modified Hausdorff Object Classification	3.19
3.4.1	Sobel Edge Detector	3.20
3.4.2	Modified Hausdorff Distance	3.23
3.4.3	Thresholding	3.26
3.5	Conclusions	3.27
4	RESULTS AND DISCUSSION	
4.1	Formation of Skin Color Filter	4.1
4.2	Skin Color Segmentation	4.3
4.2.1	Skin Color Filtering	4.3
4.2.2	Thresholding	4.5
4.2.3	Connected Component Labeling	4.8
4.2.4	Median Filtering	4.10
4.2.5	Image Dilation	4.12
4.3	Modified Hausdorff Object Classification	4.14
4.3.1	Sobel Edge Detector	4.14
4.3.2	Modified Hausdorff Object Matching	4.16
4.3.3	Constraint of the System	4.18
4.4	Modified Hausdorff Distance Object Matching with Test Images	4.21
4.5	Comparison of Face Detection Techniques	4.28
5	CONCLUSIONS AND RECOMMENDATIONS	
5.1	Summary	5.1
5.2	Future Research Directions	5.2



REFERENCES	R.1
APPENDICES	A.1
BIODATA OF THE AUTHOR	C.1



LIST OF TABLES

Table		Page
4.1	Edges Detected using Sobel Edge Detector for Images in Figure 4.1(a).(e)	4.15
4.2	Face Detection Result based on Mean Hausdorff Distance Method	4.17
4.3	Face Detection Result using Test Images	4.22
4.4	Face Detection Result using Modified Hausdorff Distance Method	4.26
4.5	Face Detection Result	4.29



LIST OF FIGURES

Figure		Page
3.1	Face Detection System Block Diagram	3.2
3.2	Face Detection System Flow Chart	3.3
3.3	Subsystem of Skin Color Segmentation	3.5
3.4	Skin Color Filter Creation Process	3.7
3.5	Input Image	3.10
3.6	Skin Probability Distribution	3.11
3.7	Segmented Skin Color Image	3.12
3.8	8 Connectivity Relationship Illustration	3.13
3.9	Connected Components on the Skin Color Filtered Image	3.15
3.10	Calculating the median value of a pixel neighbourhood	3.16
3.11	Median Filtered Image	3.17
3.12	Preprocessed Skin Color Image	3.19
3.13	Subsystem for Modified Hausdorff Object Classification	3.20
3.14	Sobel Convolution Masks	3.21
3.15	Gray Scale Image $I(x, y)$	3.22
3.16	Face Edges Detected Using Sobel Operator in Two Directions	3.23
3.17	Combined Face Edges Using OR Operation between the two Face Edges in Figure 3.15	3.24
4.1A	Sample Images from Face Database – Part 1	4.1
4.1B	Sample Images from Face Database – Part 2	4.2
4.2	Skin Color Distribution for Image in Figure 4.1(a) – (e)	4.4

4.3	Thresholding Result for Images in Figure 4.2(a) – (e)	4.5
4.4	Manual Thresholding using Step of 0.1 for Image in Figure 4.2(b)	4.7
4.5	Connected Component Labeling for Images in Figure 4.3(a)-(e)	4.9
4.6	Median Filtering Results for Images in Figure 4.5(a)-(e)	4.10
4.7	Image Dilation Results for Images in Figure 4.6(a)-(e)	4.12
4.8	Face Detection on Image under Excess Lighting	4.18
4.9	Face Detection on Subject with Beard and Wearing Dark Glasses	4.19
4.10	Face Detection on Subject Covered by Scarf	4.20
4.11	Test Images used for Face Detection Test	4.25



LIST OF ABBREVIATIONS

HCI	: Human Computer Interaction
PDM	: Point Distributed Models
PPED	: Projected Principal Edge Distribution
RFM	: Relational Face Model
PCA	: Principal Components Analysis
SVM	: Support vector machine
OCSVM	: One.Class SVM
BDF	: Bayesian Discriminating Features
SEW2HD	: Spatially Eigen.Weighted ‘Doubly’ Hausdorff Distance



CHAPTER 1

INTRODUCTION

1.1 Background

Face detection is a necessary first step in face recognition systems with the purpose of localizing and extracting the face region from the background. Apart from increasing the efficiency of face recognition systems, face detection technique also opens up the door of opportunity for application areas such as content-based image retrieval, video encoding, video conferencing, crowd surveillance and intelligent human-computer interfaces. (Hjelmas and Low, 2001; Seo *et al.*, 2000).

Early efforts in face detection started as early as the beginning of the 1970's. In those researches, simple heuristic and anthropometric techniques are used and are largely due to various assumptions such as plain background, frontal face. Any change of image conditions would usually bring about fine-tuning of the whole system or even complete redesign.

Human face is a dynamic object and displays high degree of variability in appearance. In real life situations, different illuminations and distance from imaging device, occlusion and rotation of head in different axis are bound to happen and this causes massive challenge to the detection algorithm. Most systems assume certain orientation of the face to simplify the problem such as frontal or near frontal face orientation. (Liu, 2003;



Samal and Lyengar, 1992; Kotropoulos and Pitas, 1997; Kim *et al.*, 2002; Suzuki and Shibata, 2004).

Generally speaking, face detection techniques can be classified to two schools of philosophy which is: (i) image based techniques and (ii) feature based techniques. Image based techniques address face detection as a general recognition problem whereby pattern recognition is applied to the whole image which has undergone certain transformation. The face knowledge is therefore implicit to the users and mapping and training schemes are utilized to achieve what is known as recognition. Feature based technique on the other hand has an explicit knowledge on the face detection problem whereby features representing face as defined by the designer are first extracted from images. Face detection are thus achieved by verifying to a certain degree of confidence that features extracted from images represent face.

Color analysis on images has long been used as a technique which can give additional dimension to image compared to grey scale image. Classification is easier to handle in color space compared to gray scale. It is a known fact that skin color of different races tend to cluster in close proximity in normalized color space or chromaticity space. This has also brought about the possibility of modeling skin color distribution as Gaussian distribution. Using this skin color model, skin candidate region is identified based on certain threshold value.



The problem of matching two images has been an active topic of research in computer vision and target track for the last two decades. Image matching methods can be well used to find correspondence between a template and given portion of an image having the most partial similarity. The partiality stems from many factors, such as different time, viewing condition, occlusion, noise, etc. In the past, there were various methods that can be well used for locating a model in an image and be divided into two categories: area based matching and feature based matching. (Zhijia. Z., *et al*, 2003).

The use of variants of the Hausdorff distance has recently become more and more popular in the image matching application. Hausdorff distance is a robust technique used in image matching problem. It has the advantage of being scale invariant, illumination invariant and robust in complex background. Given two images A and B , Hausdorff distance between the two images can be formulated as follow:

$$H(A, B) = \max (h(A, B), h(B, A))$$

$$\text{where } h(A, B) = \max_{a \in A} \min_{b \in B} \|a-b\| \quad (1.1)$$

$h(A, B)$ is known as the directed Hausdorff distance from set A to set B . In other words, Hausdorff distance is the maximum shortest distance between points on A and B respectively. In order to minimize the effect due to outliers, a modified Hausdorff distance is used instead.



1.2 Problem Statement

Skin color has long been used for detecting skin color region and even in head detection system for searching head region. The major problem with using skin color model however is that it is subject to variation in illumination and hence not robust enough in detecting head candidate. One more prominent problem is that most of the time, object which appears to have skin color is not necessarily the human face, worse, it may not even be part of the human skin. It is therefore impossible to rely solely on skin color alone as an effective face detection strategy.

Hausdorff distance is a robust technique in image matching. Traditionally, it has always been used in gray scale image to locate image candidate which is a closest match to an object. In order to search for the possible image candidate, the system generally needs to scan through the whole image until it reaches the targeted candidate. As the image size grows, so does the computing power needed to locate the image candidate.

It is therefore believed that using skin color filter along with Hausdorff distance will target the shortcomings of both these strategies. Skin color filter will help identify the image candidate so that Hausdorff distance will be able conserve computing power on the image candidate while Hausdorff distance will verify the validity of the image candidate which is not possible by using skin color filter alone.



1.3 Objectives

Face detection is a complex task which consists of a series of structured steps. The aim of this thesis is to research the necessary steps needed to construct a system which will lead to successful detection of human face from any input images either downloaded or captured using an imaging device.

The primary objective of this thesis is to produce a face detection approach which is robust enough to be used in images or video with complex background and scale invariant. It should also be robust enough to detect multiple faces which could occur within a single image.

The secondary objective is to improve on the general detection rate of the proposed Hausdorff detection method and to reduce false detection rate at the same time.

1.4 Thesis Outline

This thesis is organized in five chapters. Chapter one consists of introduction, which covers background of research problem, research objectives and thesis outline. Chapter two consists of literature review which discuss on the various prior works done in face detection using different approaches, while the third chapter consists of the methodology. The fourth chapter consists of the result obtained within this study. Finally, the fifth chapter summarizes the research finding and suggests potential work.

CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

Face detection is the necessary first step in face recognition system (Hjelmas and Low 2001; Seo *et al.*, 2002). It carries the objectives of localizing face region and to extract it out of an image. Successful face detection will enable face recognition to be carried out smoothly and more efficiently and at the same time reduce false recognition. Human can do this almost effortlessly but for a computer, sophisticated algorithm with efficient computation is the only solution to this problem. Face detection is also applied to other areas which are equally important such as content based image retrieval, video conferencing, crowd surveillance and intelligent Human Computer Interaction (HCI).

Human face is a dynamic object and displays high degree of variability in appearance. In real life situations, different illuminations and distance from imaging device, occlusion and rotation of head in different axis are bound to happen and this causes massive challenge to the detection algorithm. Most systems assume certain orientation of the face to simplify the problem such as frontal or near frontal face orientation (Liu 2003; Samal and Lyengar 1992; Kotropoulos and Pitas 1997; Kim *et al.*, 2004; Suzuki and Shibata 2004).



Early efforts in face detection started as early as the beginning of the 1970's. In those researches, simple heuristic and anthropometric techniques are used and are largely due to various assumptions such as plain background, frontal face. Any change of image conditions would usually bring about fine-tuning of the whole system or even complete redesign.

2.2 Previous Work on Face Detection

Face detection has become one of hottest topics in the field of computer vision and pattern recognition in the past decades because of its potential applications, such as biometrics, intelligent human computer interaction, and so on. Face detection is a key step of automatic face analysis. The purpose of face detection is to look for and locate face patches in given images, and its performance has great effect on face tracking, face recognition, expression analysis and human gesture analysis. In recent years, a lot of face detection methods have been published.

Menser and Muller (1999) presented a face detection algorithm for color images with complex background. This algorithm includes color information into a face detection approach based on principal components analysis (PCA). A skin color probability image is generated by doing a color analysis and the PCA is performed on this new image instead of the luminance image. The presented face detection algorithm combines a skin color analysis with an eigenspace approach. The incorporation of color information reduces the influence of the image background and improves the detection performance especially in images where the size of the facial area is relatively small. This work focused on the adjustment of the error criterion and the



automatic adaption of the global detection threshold only. The algorithm can be extended to face tracking in image sequences. Experiments show that color information improves the robustness of the detection significantly.

Balasuriya and Kodikara (2000) attempted to unravel the classical problem of automated human face recognition. A near realtime, fully automated computer vision system was developed to detect and recognise expressionless, frontal view human faces in static images. In the implemented system, automated face detection was achieved using a deformable template algorithm based on image invariants. The natural symmetry of human faces was utilised to improve the efficiency of the face detection model. The deformable template was run down the line of symmetry of the face in search of the exact face location. Once the location of the face in an image was known, this pixel region was extracted and the test subject was recognized using principal component analysis, also known as the eigenface approach.

Prem Kuchi *et al.* (2000) developed an algorithm to detect and track human face(s) in a color image sequence. The algorithm starts with human skin color modeling and uses it in isolating skin pixels (probable face regions). Skin color is found to be a powerful feature for isolating potential face candidates. It is also useful for detecting multiple human faces in an image. It is orientation independent. Connected Component Operators are applied on the thresholded skin probability image to isolate the final face components. The combination of the six operators used proved to be very effective. Skin color analysis followed by the use of shape based Connected Operators makes the system invariant to change in scale. For a higher detection performance, the structuring element used during open/close operations

automatic adaption of the global detection threshold only. The algorithm can be extended to face tracking in image sequences. Experiments show that color information improves the robustness of the detection significantly.

Balasuriya and Kodikara (2000) attempted to unravel the classical problem of automated human face recognition. A near realtime, fully automated computer vision system was developed to detect and recognise expressionless, frontal view human faces in static images. In the implemented system, automated face detection was achieved using a deformable template algorithm based on image invariants. The natural symmetry of human faces was utilised to improve the efficiency of the face detection model. The deformable template was run down the line of symmetry of the face in search of the exact face location. Once the location of the face in an image was known, this pixel region was extracted and the test subject was recognized using principal component analysis, also known as the eigenface approach.

Prem Kuchi *et al.* (2000) developed an algorithm to detect and track human face(s) in a color image sequence. The algorithm starts with human skin color modeling and uses it in isolating skin pixels (probable face regions). Skin color is found to be a powerful feature for isolating potential face candidates. It is also useful for detecting multiple human faces in an image. It is orientation independent. Connected Component Operators are applied on the thresholded skin probability image to isolate the final face components. The combination of the six operators used proved to be very effective. Skin color analysis followed by the use of shape based Connected Operators makes the system invariant to change in scale. For a higher detection performance, the structuring element used during open/close operations