



UNIVERSITI PUTRA MALAYSIA

**PERFORMANCE EVALUATION OF A MODIFIED CARRIER SENSE
MULTIPLE ACCESS WITH COLLISION DETECTION PROTOCOL**

SHAMIMA KABIR.

FK 2005 63

**PERFORMANCE EVALUATION OF A MODIFIED CARRIER SENSE
MULTIPLE ACCESS WITH COLLISION DETECTION PROTOCOL**

SHAMIMA KABIR

**MASTER OF SCIENCE
UNIVERSITI PUTRA MALAYSIA**

2005



**PERFORMANCE EVALUATION OF A MODIFIED CARRIER SENSE
MULTIPLE ACCESS WITH COLLISION DETECTION PROTOCOL**

**By
SHAMIMA KABIR**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in
Fulfilment of the Requirements for the Degree of Master of Science.**

February 2005



Abstract of the thesis submitted to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science

**PERFORMANCE EVALUATION OF A MODIFIED CARRIER SENSE
MULTIPLE ACCESS WITH COLLISION DETECTION PROTOCOL**

By

SHAMIMA KABIR

February 2005

Chairman: Sabira Khatun, PhD

Faculty: Engineering

Using Carrier Sense Multiple Access with Collision Detection (CSMA/CD), Ethernet Local Area Networks (LANs) suffers from capture effect in packet loss. As a result of capture effect, some nodes may be locked-out of using the medium for a period of time. Hence, CSMA/CD based Ethernet is unsuitable for real-time multimedia traffic. It does not guarantee delay bound, behaves poorly under heavy load conditions.

To overcome these shortcomings and enhance performance of CSMA/CD based LAN, three new concepts are added to the conventional CSMA/CD. Firstly, each node in the LAN has a finite buffer. A node competes for access to the medium after its buffer is full. It will transmit all packets in the buffer if access is permitted. To minimize the waiting delay of packets in the buffer prior to transmission, a time-out period is set, beyond which a node tries to transmit considering its buffer is full.



Due to buffer, the number of nodes trying to transmit at a time is reduced, thereby collision rate is reduced. Capture effect, locked-out probability, bandwidth loss and backoff delays are also reduced. To support all types of traffic (mainly real-time traffic), the optimum buffer size obtained is 10 packets/buffer. Using this buffer, multimedia traffic can be sent in a streamed fashion within a delay bound. Secondly, the maximum retransmission attempt limit and backoff limit are reduced to 10 and 8 times respectively to guarantee a tolerable delay for multimedia applications. A new special-jamming signal is introduced. It gives transmission priority to the node that already has finished its maximum retransmission attempt. This prevents packet loss and quality degradation of received normal data traffic and multimedia traffic.

The final one is the priority scheduler, which is activated when multiple nodes send the special-jamming signal at a time. It gives permission to the node having either the lowest time-stamp or the smallest source address (SA) to transmit while other nodes wait until their access is permitted accordingly.

The proposed protocol is based on bus topology for a single channel LAN. Throughput, transmission efficiency, average delay and percentage of collision of the proposed network is evaluated against number of nodes, bus length and offered load within two environments, i.e. Fast Ethernet and Gigabit Ethernet. The results show significant performance improvement. Throughput, transmission efficiency are increased more than 10% in average. On the other hand, average delay and percentage of collision are reduced to less than 2 ms and 3.5% respectively compared to the conventional CSMA/CD based LAN.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

Penilaian Prestasi untuk Capaian Berbilang Deria Pembawa Terubah Suai dengan Protokol Pengesanan Pelanggaran

Oleh

SHAMIMA KABIR

Februari 2005

Pengerusi: Sabira Khatun, PhD

Fakulti: Kejuruteraan

Dengan menggunakan CSMA/CD, 'LAN Ethernet' terbeban dengan kesan tangkapan daripada pembelakangan algoritma CSMA/CD. Disebabkan kesan tangkapan ini, beberapa nod mungkin akan terkunci akibat daripada menggunakan medium pada suatu jangkamasa yang tertentu. Oleh yang demikian, CSMA/CD yang berasaskan Ethernet tidak sesuai untuk menyokong trafik pelbagai mediamasa. Ia tidak menjanjikan keterikatan pelambatan dan juga berkeadaan terlalu lemah di bawah kondisi bebanan berat. Oleh yang demikian, ini akan membawa kepada pelambatan yang berlebihan yang mana di sebabkan oleh berlebihan pelanggaran yang berlaku.

Untuk mengatasi masalah tersebut, tiga jenis konsep baru di masukkan di dalam system yang sedia ada bagi mempertingkatkan kepada CSMA/CD untuk satu saluran LAN optik. Ethernet/IEEE 802.3 dicadangkan. Ini adalah kerana, kemampuan Ethernet untuk meningkatkan jangkamasa pemancaran hingga ke satu gigabit di dalam satu saat. Cadangan ini akan merangkumi kepada topologi bus fizikal. Bagi bentuk topologi, semua nod-nod diletakkan sekata di sepanjang bus.



Merujuk kepada konsep yang pertama, setiap nod di dalam LAN mempunyai kapasiti bufer yang tertentu. Suatu nod berlumba untuk mendapatkan laluan di dalam medium selepas bufernya penuh serta kesemua paket-paketnya telah di hantar. Bagi mengurangkan lembapan masa untuk paket-paket tersebut kepada pemancaran, suatu masa rehat ditetapkan, di mana suatu nod itu cuba untuk dipancarkan walaupun bufernya sudah penuh. Oleh yang demikian, bilangan nod-nod yang berkeadaan demikian akan berkurangan dan masa pelanggaran juga berkurangan. Justeru, kesan penangkapan juga berkurangan dengan menghalang suatu nod itu daripada menghantar bilangan paket secara berlebihan.

Yang keduanya, penghantaran balik tertinggi dan tahap pembelakangan adalah dikurangkan kepada 10 dan 8 setiap satu bagi menjanjikan pelembapan yang munasabah bagi aplikasi-aplikasi pelbagai media. Suatu kaedah isyarat gangguan-istimewa diperkenalkan adalah untuk memberikan keutamaan kepada nod-nod yang sudah menghabiskan penghantaran tertinggi di dalam penghantaran paket-paket. Oleh yang demikian, isyarat ini akan menghalang kehilangan paket dalam masa yang sama kualiti pengurangan bagi penerimaan data di dalam trafik biasa dan pelbagai media trafik.

Yang terakhir adalah keutamaan jadual yang diaktifkan apabila lebih daripada satu nod menghantar isyarat gangguan-istimewa yang dihantar pada masa yang sama. Ia memberi kebenaran kepada nod untuk mempunyai samada paling rendah tahap masa yang ditentukan atau sumber alamat (SA) yang paling kurang bagi memancarkan paket-paket sementara menunggu nod-nod lain menerima kelulusan kemasukan secara teratur.

Pencapaian rangkaian (i.e. throughput, penghantaran yang efisien, purata pelambatan dan peratusan pelanggaran) berdasarkan kepada cadangan CSMA/CD dikaji dengan beberapa parameter rekabentuk (i.e. bilangan nod, jarak bus, dan bebanan yang ditawarkan). Pengkajian ini dilakukan di dalam dua keadaan, iaitu 'Fast Ethernet' dan 'Gigabit Ethernet'. Keputusan menunjukkan suatu pencapaian yang memberangsangkan di mana hasil output dan efisien pemancaran meningkat kepada purata sebanyak 10%. Dalam masa yang sama, purata pelembaran dan peratusan pelanggaran dapat dikurangkan kepada 2 ms dan 3.5% setiap satu berbanding dengan system yang ada sekarang.

ACKNOWLEDGEMENTS

First of all, thanks to Allah, the Almighty for his blessings, kindness and guidance that allow all this possible.

I would like to express my utmost gratitude to my supervisor and co-supervisor, Dr. Sabira Khatun and Associate Professor Dr. Mohamad Khazani Abdullah for their great patience in guiding me throughout the process of completing this thesis. Without their brilliant ideas, suggestions and financial support this project could never been succeed. Appreciation also goes to the other committee member, Dr. Mohamad Adzir for his feedback and comments, which helped a lot in improving the project.

Special thank goes to Siti Barirah Ahmad Anas and Kharina Khairi for their helpful suggestions and to Ahmad Ashrif Bin Abu Bakar for translating the thesis abstract in bahasa Melayu.

Last but not least, my deepest appreciation goes to my husband, Mustafizur Rahman for being supportive all this while and my parents for their blessings and encouragement to make this possible.




I certify that an Examination Committee met on 18th February 2005 to conduct the final examination of Shamima Kabir on her Master of Science thesis entitled "Performance Evaluation of a Modified Carrier Sense Multiple Access with Collision Detection Protocol" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Syed Javaid Iqbal, PhD
Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Borhanuddin Mohd. Ali, PhD
Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Adznan Jantan, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Abu Bakar Mohammad, PhD
Professor
Faculty of Electrical Engineering
Universiti Teknologi Malaysia
(Independent Examiner)



GULAM RUSUL RAHMAT ALI, PhD
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 22 APR 2005



This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

Sabira Khatun, PhD
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Mohamad Khazani Abdullah, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Mohamad Adzir Mahdi, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)




AINI IDERIS, PhD
Professor/ Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: **12 MAY 2005**



DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



SHAMIMA KABIR

Date: 20.04.2005

TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	iv
ACKNOWLEDGEMENTS	vii
APPROVAL	viii
DECLARATION	x
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xvii
LIST OF NOTATIONS	xx
CHAPTER	
1 INTRODUCTION	1
1.1 Background	1
1.2 Motivation and Problem Statements	2
1.3 Proposed Modifications	5
1.4 Justification of Proposed Modifications	7
1.5 Aim and Objectives	8
1.6 Simulation Parameters and Topology	9
1.7 Thesis Organization	9
2 REVIEW ON LOCAL AREA NETWORKS	12
2.1 Optical Networks Today	12
2.2 LAN Technologies	15
2.3 Ethernet	19
2.4 Gigabit Ethernet	23
2.4.1 Full-Duplex	25
2.4.2 Half-Duplex	26
2.5 Ethernet on Optical Fiber	30
2.6 Ethernet MAC Protocol: CSMA/CD	31
2.7 Collision Detection Technology	37
2.8 Studies on Improving CSMA/CD Performance	44
2.9 Conclusions	49
3 PROPOSED CSMA/CD MAC PROTOCOL FOR SINGLE CHANNEL LAN	50
3.1 Network Structure	50
3.2 Physical Layer Structure	52
3.3 Transmitter and Comparator Unit Operation	54
3.4 Description of the Proposed MAC Protocol	56
3.5 Conclusions	62
4 DEVELOPMENT OF SIMULATION MODEL	63
4.1 Operating Assumptions	63
4.2 Packet Generation	64
4.3 Simulation Parameters of Fast Ethernet	65



4.4	Simulation Parameters of Gigabit Ethernet	68
4.5	Design and Performance Parameters	69
	4.5.1 Throughput	70
	4.5.2 Transmission Efficiency	71
	4.5.3 Average Delay	71
	4.5.4 Percentage of Collisions	72
4.6	Simulation Tool	72
4.7	Conclusions	73
5	EVALUATION OF NETWORK PERFORMANCES FOR FAST ETHERNET AND GIGABIT ETHERNET	74
5.1	Optimization of Buffer Size	74
	5.1.1 The effect of Buffer Size on Throughput	75
	5.1.2 The effect of Buffer Size on Transmission Efficiency	76
	5.1.3 The effect of Buffer Size on Average Delay	77
	5.1.4 The effect of Buffer Size on Percentage of Collision	78
5.2	Throughput Performance	80
	5.2.1 The effect of Number of Nodes	80
	5.2.2 The effect of Bus Length	82
	5.2.3 The effect of Offered Load	83
5.3	Transmission Efficiency Performance	86
	5.3.1 The effect of Number of Nodes	86
	5.3.2 The effect of Bus Length	88
	5.3.3 The effect of Offered Load	89
5.4	Average Delay Performance	90
	5.4.1 The effect of Number of Nodes	90
	5.4.2 The effect of Bus Length	92
	5.4.3 The effect of Offered Load	94
5.5	Percentage of Collision Performance	96
	5.5.1 The effect of Number of Nodes	96
	5.5.2 The effect of Bus Length	97
	5.5.3 The effect of Offered Load	98
5.6	Conclusions	100
6	CONCLUSIONS AND FUTURE WORK	102
6.1	Thesis Contributions and Conclusions	102
6.2	Future Research	104
	REFERENCES	106
	APPENDICES	115
	BIODATA OF THE AUTHOR	155



LIST OF TABLES

Table		Page
4.1	Simulation variables for Fast Ethernet.	67
4.2	Simulation variables for Gigabit Ethernet.	69
5.1	Results of the proposed CSMA/CD protocol.	100



LIST OF FIGURES

Figure		Page
2.1	Basic ideas behind the three generations of fiber usage in networks.	13
2.2	Some physical topologies of typical optical networks (T=transmitter, R=receiver).	15
2.3	Three widely used LAN technologies.	16
2.4	The mapping of IEEE 802 protocol set with the OSI layer of the ISO reference model.	17
2.5	The relationship between (a) physical and (b) logical topologies.	19
2.6	Standard Ethernet Frame format.	20
2.7	A general Ethernet implementation for a network station.	21
2.8	Gigabit Ethernet protocol stack.	25
2.9	Carrier-extended Frame for Gigabit Ethernet.	28
2.10	Frame Bursting in Gigabit Ethernet.	29
2.11	The MAC and the OSI model.	32
2.12	Collision detection in CSMA/CD.	34
2.13	Transceiver using pulse-width violation collision detection.	39
2.14	Directional bus network.	40
2.15	Hybrid star system.	41
2.16	Active star repeater.	43
3.1	Network structure of the proposed protocol; (a) general structure, (b) structure of a single node.	51
3.2	Single-channel logical bus topology.	52
3.3	Physical Architecture of the proposed transmitter circuit. LD/Drive: Laser Diode and driving circuit. PD/Pre Amp: Photo detector and pre-amplifier circuit.	53



3.4	Data packet format of the proposed protocol.	54
3.5	Jamming signal and special-jamming signal format.	55
3.6	Flow chart of the proposed CSMA/CD protocol.	57
3.7	Buffer fulfillment algorithm.	58
3.8	Channel sense algorithm.	59
3.9	Collision detection and the proposed modification.	60
5.1	Throughput versus buffer size of the proposed protocol.	75
5.2	Transmission efficiency versus buffer size of the proposed protocol.	77
5.3	Average delay versus buffer size of the proposed protocol.	78
5.4	Percentage of collisions versus buffer size of the proposed protocol.	79
5.5	Throughput versus number of nodes of the proposed protocol.	80
5.6	Throughput versus bus length of the proposed protocol.	83
5.7	Throughput versus offered load of the proposed protocol.	84
5.8	Comparison of throughput versus offered load of the proposed and conventional CSMA/CD protocol.	85
5.9	Efficiency versus number of nodes of the proposed protocol.	86
5.10	Comparison of efficiency versus number of nodes of the proposed and conventional system.	88
5.11	Transmission efficiency versus bus length of the proposed protocol.	89
5.12	Efficiency versus offered load of the proposed protocol.	90
5.13	Average packet delay versus number of nodes of the proposed protocol.	91
5.14	Average packet delay versus bus length of the proposed protocol.	93
5.15	Average delay versus offered load of the proposed protocol.	94
5.16	Comparison of average delay versus offered load of the proposed and conventional protocol.	95
5.17	Percentage of collision versus number of nodes of the proposed protocol.	96



5.18	Percentage of collision versus bus length of the proposed protocol.	97
5.19	Percentage of collision versus offered load of the proposed protocol.	98
5.20	Comparison of percentage of collision versus offered load of the proposed and conventional CSMA/CD protocol.	99



LIST OF ABBREVIATIONS

ANSI	American National Standards Institute
ATM	Asynchronous Transfer Mode
BEB	Binary Exponential Backoff
BER	Bit Error Rate
BLAM	Binary Logarithmic Arbitration Method
CSMA	Carrier Sense Multiple Access
CSMA/CD	Carrier Sense Multiple Access with Collision detection
CSMA/RI	Carrier Sense Multiple Access with Reservation by Interruption
CU	Comparator Unit
DCR	Deterministic Contention Resolution
DFPQ	Distribute Fair Priority Queue
DiffServ	Differentiated Services
DQDB	Distributed Queue Duel Bus
DTE	Data Terminal Equipment
ECE	Ethernet Capture Effect
EMI	Electro Magnetic Interference
EPA	Equilibrium Point Analysis
FC	Fiber Channel
FCFS	First-Come-First-Served
FCS	Frame Check Sequence
FDDI	Fiber Distributed Data Interface
FOIRL	Fiber Optic Inter Repeater Link
FTP	File Transfer Protocol



FTTX	Fiber-To-The-X
HomePNA	Home Phonline Networking Aliance
IEEE	Institute of Electrical and Electronic Engineers
ISO	International Standards Organization
LAN	Local Area Network
LD	Laser Diode
LED	Light Emitting Diode
LLC	Logical Link Control
MAC	Medium Access Control
MAN	Metropolitan Area network
MAU	Media Attachment Unit
MDI	Medium Dependent Interface
MII	Medium Independent Interface
OSI	Open Systems Interconnection
PCS	Physical Coding Sublayer
PD	Photo Detector
PMA	Physical Medium Attachment
PMD	Physical Medium Dependent Sublayer
QoS	Quality of Service
RETHETHER	Real-time ETHERnet
SA	Source Address
SBVS	Stony Brook Video Server
SDH	Synchronous Digital Hierarchy
SONET	Synchronous Optical NETWORK
TDMA	Time Division Multiple Access



VoIP

Voice over IP

WAN

Wide Area Network



LIST OF NOTATIONS

N	Number of nodes
a	Ratio of channel propagation delay to packet transmission time
T_x	Transmitter
R_x	Receiver
R_j	Nominal rate at node j
T	Time-out period
d	Fiber optic bus length
v	Propagation speed
c	Light velocity
n	Fiber index
S	Throughput
E	Transmission efficiency
D	Average delay



CHAPTER 1

INTRODUCTION

In this chapter, the background of fiber optics networks and problems of the conventional Carrier Sense Multiple Access with Collision detection (CSMA/CD) based Local Area Networks (LANs) are given to provide the motivation of this research. It also provides an overview of the research accomplishment.

1.1 Background

Fiber optic cables have been widely used in today's communication systems. They are the best medium that can provide a large bandwidth at a very low loss. Most of the backbone copper cables have been replaced by fibers. The fiber installation is even expanded to the smaller network such as junction and access network where the Fiber-To-The-X (FTTX) series emerged as the solution. The main objective is to provide an end-to-end fiber connectivity to provide a better transmission performance and bandwidth utilization. Therefore, fiber implementation in the local area networks have been proposed and implemented by many organizations.

Now-a-days, there are a lot of fiber installations in large network areas. When it comes to the smaller area, the installation is back to the conventional copper cable. For this reason, the fiber-copper interfacing needs to be considered. Though the speed of the combined fiber-copper network architecture is faster than the all copper based system, bottleneck still occurs due to the different bandwidth and transmission capacity of these two media. To overcome this problem, fiber

connection is implemented in the small geographical area such as LAN. As a result, end-to-end fiber connectivity is achieved.

The key advantage of optical LAN is a large number of nodes can be connected to the network without using amplifiers [1]. This is due to its small network area, thus shorter length of fiber is needed.

1.2 Motivation and Problem Statements

Fiber optic LANs typically use one of the two methods for medium access, which are random access protocols (CSMA/CD) and controlled access protocols (token passing). In fiber LAN, when two or more nodes attempt to transmit at the same time, the performance of CSMA/CD is less predictable. The degradation in terms of channel utilization and throughput occurs as some bandwidth is wasted by collisions and backoff delays. If there are many nodes competing to share the bandwidth, an overload condition may occur. In this case, throughput of Ethernet LANs reduces drastically as much of the capacity is wasted by the CSMA/CD algorithm [2].

Using CSMA/CD, the sharing is not necessarily fair. When the nodes connected to the LAN have little data to send, the network exhibits almost equal access time for each node. However, if a node has large number of frames to transmit, it may dominate the network resulting Ethernet Capture Effect (ECE) [2-8]. Such conditions may occur, for instance, when a node in a LAN acts as a source of high quality packetised video. Ethernet Capture Effect means, one node in the LAN has an increased probability of holding the channel and sending consecutive frames

even though other nodes are contending for access. The effect is primarily noticeable when an Ethernet/IEEE 802.3 LAN is under high load [3]. This short term unfairness occurs because of the CSMA/CD backoff algorithm.

The problem with the CSMA/CD backoff scheme is that, the node that is successful in sending its frame after a collision starts with a new frame having the collision counter set to zero. All other nodes involved in the collision try to retransmit their old frames, and therefore keep their old collision counter values. As a result, if the successful node has another frame to send, it will likely be involved in a new collision with the same nodes that were involved in the previous collision. The successful node chooses its random wait time in a narrower range than the other nodes. This increases its probability of being successful again in the new collision. For every consecutive collision, the probability for the winner to win again (against the same set of competing nodes) increases, and quickly tends to 1 [3-4]. This increase of probability leads to the unfairness that is called the Ethernet capture effect [3]. Under these situations some nodes may be locked out of using the medium for a period of time.

The use of higher speed transmission (e.g. 100 Mbps) significantly reduces the probability of capture and the use of full duplex cabling eliminates the effect [2]. Actually full duplex operation is restricted to point-to-point links connecting exactly two nodes. Since there is no contention for a shared medium, collision can not occur and the CSMA/CD protocol is unnecessary. Frames may be transmitted at will, limited only by the required separation of the minimum inter frame gap.