



UNIVERSITI PUTRA MALAYSIA

**A MATRIX USAGE FOR LOAD BALANCING
IN SHORTEST PATH ROUTING**

NOR MUSLIZA MUSTAFA

FSKTM 2009 3

**A MATRIX USAGE FOR LOAD BALANCING
IN SHORTEST PATH ROUTING**

By

NOR MUSLIZA MUSTAFA

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in fulfillment of the Requirements for the Degree of Master of Science**

February 2009



DEDICATION

*Dedicated to my parents,
to my hubby,
to my kids,
and to all my brothers and sisters.*

Abstract of thesis presented to the Senate of Universiti Putra Malaysia
in fulfillment of the requirements for the degree of Master of Science

**A MATRIX USAGE FOR LOAD BALANCING
IN SHORTEST PATH ROUTING**

By

NOR MUSLIZA MUSTAFA

February 2009

Chair : Associate Professor Mohamed Othman, PhD
Faculty : Computer Science and Information Technology

The Open Shortest Path First (OSPF) protocol is a hierarchical interior gateway protocol (IGP) for routing in Internet Protocol. Traffic flows routed along shortest path and splits the load equally at nodes where a number of outgoing links on the shortest paths to the same destination IP address. Network operator defines shortest paths based on a link weights value assigned to each link in the network. The OSPF link weight-setting problem seeks a set of link weights to optimize a cost function and network performance, typically associated with a network congestion measure. This research highlight the importance of managing network resource and avoiding congested point in the current widely deployed shortest path routing.

The previous Evenly Balancing Method (EBM) and Re-Improved Balancing Method (R-IBM) used demand matrix, which requires constant monitoring of routers with high time executions in the optimization process. The problems are to find another matrix that can replace or minimize the usage of demand matrix with low time executions process. A new proposed Matrix Usage Method (MUM) is developed. MUM selects the shortest path routing in order to provide a balancing load and

optimized the usage of link in the network. The simulation results show that the routing performance of the new proposed method MUM is better than the routing performance of the previous Evenly Balancing Methods (EBM) and Re-Improved Balancing Method (R-IBM) due to providing counting selection technique in the shortest path routing. MUM times executions are also improved comparing with the previous work.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

**MATRIX PENGGUNAAN UNTUK KAEDAH PENGIMBANGAN BEBAN
DI DALAM PENGHALAAN LALUAN TERPENDEK**

Oleh

NOR MUSLIZA MUSTAFA

Februari 2009

Pengerusi: Profesor Madya Mohamed Othman, PhD

Fakulti: Sains Komputer dan Teknologi Maklumat

Protokol OSPF merupakan protokol hirark i dalaman untuk penghalaan di dalam protokol Internet. Pengaliran trafik dilaksanakan di atas laluan terpendek dan membahagikan beban sama rata kepada nod, di mana beberapa pautan keluar berada di atas laluan terpendek ke destinasi IP yang sama. Operator rangkaian mengenalpasti laluan terpendek melalui nilai pautan pemberat yang ditetapkan kepada setiap pautan di dalam rangkaian. Masalah penetapan pautan pemberat OSPF ialah mencari set pautan pemberat untuk mengoptimumkan fungsi kos dan prestasi rangkaian, yang pada kebiasaannya melibatkan pengukuran kesesakan rangkaian. Penyelidikan ini menekankan kepentingan menguruskan sumber rangkaian dan penghindaran pautan sesak di dalam penghalaan laluan terpendek yang ada.

Di dalam penyelidikan sebelum ini kaedah pengimbangan sama (EBM) dan kaedah pengimbangan yang diperbaiki (R-IBM) telah menggunakan matrik permintaan yang memerlukan pengawasan yang tetap ke atas router dengan pengurangan jumlah masa yang tinggi di dalam proses pengoptimuman. Masalahnya ialah untuk mencari matrik lain yang boleh menggantikan atau mengurangkan penggunaan matrik permintaan dengan proses pengurangan jumlah masa yang rendah. Satu kaedah baru yang

dinamakan sebagai Kaedah Matrix Penggunaan (MUM) dibangunkan. MUM memilih penghalaan laluan terpendek di dalam menyediakan keseimbangan beban dan mengoptimumkan penggunaan pautan di dalam rangkaian. Keputusan simulasi menunjukkan bahawa prestasi penghalaan bagi kaedah MUM adalah lebih baik daripada prestasi penghalaan kaedah sebelum ini iaitu Kaedah Pengimbangan Sama (EBM) dan Kaedah Pengimbangan Yang Diperbaiki (R-IBM) dengan menyediakan teknik pengiraan pilihan di dalam penghalaan laluan terpendek. Dari aspek pengurangan jumlah masa MUM juga diperbaiki berbanding penyelidikan yang terdahulu.

ACKNOWLEDGEMENTS

Mostly, all grace and thanks belongs to Almighty Allah for giving me the strength of mind and patience in completing this research. Many special thanks go to my supervisor Associate Professor Dr. Mohamed Othman and the member of the supervisory committee, Dr. Zuriati Zukarnain for their valuable advice, helpful guidance and recommendations to my research calmly and precisely.

I would like to take this opportunity to express my sincerely appreciation and thanks to Dr Makarem Abdul Qader Bamatraf and Dr. Bernard Fortz from AT&T Labs for their ideas, cooperation, and patient in replying any issues regarding their optimization model that used as a benchmark in this research.

Sincere and deepest thanks to the staff of Faculty of Computer Science and Information Technology, Graduate School Office, Library and Universiti Putra Malaysia for providing a studying and research environment.

Finally, many thanks to my parents, my hubby, my kids, my brothers and sisters, all the family members and friends for their worship, continuous support in all my efforts.

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Mohamed Othman, PhD

Associate Professor

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Chairman)

Zuriati Zulkarnain, PhD

Associate Professor

Faculty of Computer Science and Information Technology

Universiti Putra Malaysia

(Member)

HASANAH MOHD GHAZALI, PhD

Professor and Dean

School of Graduate Studies

Universiti Putra Malaysia

Date: 17 July 2009

DECLARATION

I declare that the thesis is my original work except for quotations and citations, which have been properly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.

NOR MUSLIZA MUSTAFA

Date: 17 July 2009

TABLE OF CONTENTS

		Page
	DEDICATIONS	ii
	ABSTRACT	iii
	ABSTRAK	v
	ACKNOWLEDGEMENTS	vii
	APPROVAL	viii
	DECLARATION	x
	LIST OF TABLES	xiii
	LIST OF FIGURES	xv
	LIST OF ABBREVIATIONS	xviii
CHAPTER		
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problem Statement	4
	1.3 Research Objectives	5
	1.4 Research Scope	5
	1.5 Research Contributions	6
	1.6 Thesis Organization	6
2	LITERATURE REVIEW	7
	2.1 Introduction	7
	2.2 Traffic Engineering	10
	2.2.1 Traffic Engineering Requirements	12
	2.2.2 Traditional Routing in the Internet	13
	2.2.3 Equal Cost Multiple Path (ECMP)	17
	2.2.4 Traffic Engineering Extensions of OSPF	19
	2.3 Routing Technologies	19
	2.4 Routing Optimization in OSPF	20
	2.5 OSPF Traffic Engineering Framework	21
	2.5.1 Measurement Stage	23
	2.5.2 Routing Stage	27
	2.5.3 Optimization Stage	30
	2.5.4 Reconfiguration Stage	31
	2.6 Fundamental Principles and Constraints	32
	2.7 Related Works	33
	2.7.1 Optimization Using Link Weights	35
	2.7.2 Optimization Using Link Weights and Splitting Ratios	40
	2.7.3 Adaptive Approaches for Load Balancing	41
	2.8 Studying and Solving Problems	42
	2.8.1 Evenly Balancing Method (EBM) Model	42
	2.8.2 Re-Improved Balancing Method (R-IBM) Model	45
	2.8.3 Importance of Solving Previous Work Problems	50
	2.9 Summary	51



3	RESEARCH METHODOLOGY	53
3.1	Introduction	53
3.2	Routing Formulation	53
3.2.1	Cost Function	54
3.2.2	Normalized Cost Function	55
3.2.3	Optimal Routing	56
3.2.4	OSPF Link Weights Setting Problem	57
3.3	Simulation Model	58
3.3.1	Input Part	61
3.3.2	Shortest Path Routing Part	61
3.3.3	Link Weights Optimization Part	61
3.3.4	Output Part	62
3.4	Framework Weaknesses and Requirements	63
3.5	OSPF Link Weights Method	64
3.6	Performance Metrics	66
3.6.1	Routing Cost	66
3.6.2	Time Executions	68
3.6.3	Convergence	69
3.7	Summary	70
4	MATRIX USAGE BALANCING IN OSPF ROUTING	71
4.1	Introduction	71
4.2	Proposed Matrix Usage Method (MUM)	71
4.2.1	MUM Algorithm	72
4.2.2	Load Distribution Algorithm	75
4.2.3	Local Congestion Detection Method (LCDM) Algorithm	80
4.2.4	Update Link Weight Algorithm	82
4.2.5	Search-MUM Algorithm	86
4.3	Results and Discussions	96
4.3.1	Results in Routing Cost	97
4.3.2	Routing Cost Improvements against Unit	111
4.3.3	Routing Cost Improvement against EBM	113
4.3.4	Routing Cost Improvement against R-IBM	114
4.3.5	Result in Time Executions	116
4.3.6	Time Executions Improvements against EBM	129
4.3.7	Time Executions Improvements against R-IBM	130
4.3.8	Time Execution Improvement against all tested network	131
4.3.9	The Importance of Time Executions Reduction	133
4.3.10	Optimization Convergence	133
4.4	Summary	139
5	CONCLUSION AND FUTURE WORK	141
5.1	Conclusion	141
5.2	Future Works	143
	REFERENCES	144
	APPENDICES	149
	BIODATA OF THE STUDENT	159
	LIST OF PUBLICATIONS	160

LIST OF TABLES

Table		Page
2.1	The topologies used in this research	27
4.1	Cost Average and Best Cost for hier50a network	100
4.2	Cost Average and Best Cost for hier50b network	101
4.3	Cost Average and Best Cost for hier100 network	102
4.4	Cost Average and Best Cost for wax50a network	104
4.5	Cost Average and Best Cost for wax50b network	105
4.6	Cost Average and Best Cost for wax100 network	106
4.7	Cost Average and Best Cost for rand50a network	108
4.8	Cost Average and Best Cost for rand50b network	109
4.9	Cost Average and Best Cost for rand100 network	110
4.10	Cost Average and Best Cost improvements against Unit	112
4.11	Cost Average and Best Cost improvements against EBM	113
4.12	Cost Average and Best Cost improvements against R-IBM	115
4.13	Time Average and Best Time for hier50a network	118
4.14	Time Average and Best Time for hier50b network	119
4.15	Time Average and Best Time for hier100 network	120
4.16	Time Average and Best Time for wax50a network	122
4.17	Time Average and Best Time for wax50b network	123
4.18	Time Average and Best Time for wax100 network	124
4.19	Time Average and Best Time for rand50a network	126
4.20	Time Average and Best Time for rand50b network	127
4.21	Time Average and Best Time for rand100 network	128
4.22	Time Average improvement against EBM	129

4.23	Time Average improvements against R-IBM	131
4.24	Time Average improvements for all tested network	132
4.25	Convergence speed up averages for all tested networks	134

LIST OF FIGURES

Figure		Page
2.1	Shortest path routing within ASes with OSPF link weights	9
2.2	OSPF Traffic-engineering Framework (Makarem, 2007)	23
2.3(a)	Load distribution of $d^{(1, 5)}$ between node exchanges	29
2.3(b)	Load distribution of $d^{(1, 5)}$ and $d^{(2, 5)}$ between nodes exchanges	29
2.4(a)	One shortest path between u and t before EBM balancing	47
2.4(b)	Three available paths between u and t after EBM balancing	47
2.5	One shortest path between u and t before EBM balancing	48
2.6	Arising of RCL problem after EBM balancing	49
2.7	Solving of RCL problem after EBM balancing.	50
3.1	Proposed Simulator Architecture	60
4.1	Pseudo code for <i>MUM procedure</i>	75
4.2	Pseudo code for <i>ClearShortestPathLoad procedure</i>	76
4.3	Pseudo code for <i>ScanShortestPaths procedure</i>	77
4.4	Pseudo code for <i>StoreShortestPathLoad procedure</i>	77
4.5	Pseudo code for <i>StoreShortestPathLoad procedure</i>	78
4.6	Pseudo code for <i>LoadDistribution procedure</i>	79
4.7	Pseudo code for <i>PathDistributionLoad procedure</i>	80
4.8	Pseudo code for <i>RestoreLoadDistribution procedure</i>	80
4.9	Pseudo code for <i>LCDM procedure</i>	82
4.10	Pseudo code for <i>UpdateLinkWeights procedure</i>	84
4.11	Pseudo code for <i>RestoreOldLinkWeights procedure</i>	84
4.12(a)	The available paths ($AP^{s,t}$) from s to destination t before optimized when link a_3 is congested.	85

4.12(b)	The best available paths ($AP_{best}^{s,t}$) from s to destination t after optimized by setting the $w'_{a_3} = 2$ that avoid a congestion link.	86
4.13	Pseudo code for <i>search-MUM procedure</i>	87
4.14	Pseudo code for <i>UsageCounter procedure</i>	88
4.15	Pseudo code for <i>LoadCounter procedure</i>	89
4.16(a)	One shortest path from s to t before <i>search- MUM</i>	92
4.16(b)	One shortest path from s to t after <i>search-MUM</i>	92
4.17(a)	One shortest path from s to t before <i>search- MUM</i>	94
4.17(b)	Three shortest paths from s to t after setting $w'_{a_2} = 2$, after <i>search-MUM</i>	94
4.18(a)	Before optimized balancing, shows three shortest path (available path) may send more traffic over congested links.	95
4.18(b)	After optimized balancing by setting $w'_{a_1} = 3$, only two shortest path (best available path) may avoid the congested links.	96
4.19	Cost Average for hier50a network	100
4.20	Cost Average for hier50b network	101
4.21	Cost Average for hier100 network	102
4.22	Cost Average for wax50a network	104
4.23	Cost Average for wax50b network	105
4.24	Cost Average for wax100 network	106
4.25	Cost Average for rand50a network	108
4.26	Cost Average for rand50b network	109
4.27	Cost Average for rand100 network	110
4.28	Cost Average and Best Cost improvements against Unit	112
4.29	Cost Average and Best Cost improvements against EBM	114
4.30	Cost Average and Best Cost improvements against R-IBM	115
4.31	Time Average for hier50a network	118

4.32	Time Average for hier50b network	119
4.33	Time Average for hier100 network	120
4.34	Time Average for wax50a network	122
4.35	Time Average for wax50b network	123
4.36	Time Average for wax100 network	124
4.37	Time Average for rand50a network	126
4.38	Time Average for rand50b network	127
4.39	Time Average for rand100 network	128
4.40	Time Average improvements for all tested network against EBM	130
4.41	Time Average improvements for all tested network	132
4.42	Convergence for hier50a network	135
4.43	Convergence for hier50b network	135
4.44	Convergence for hier100 network	136
4.45	Convergence for wax50a network	136
4.46	Convergence for wax50b network	137
4.47	Convergence for wax100 network	137
4.48	Convergence for rand50a network	138
4.49	Convergence for rand50b network	138
4.50	Convergence for rand100 network	139

LIST OF ABBREVIATIONS

AS	Autonomous System
BGP	Border Gateway Protocol
EBM	Evenly Balancing Method
ECMP	Equal Cost Multiple Path
EGP	Exterior Gateway Protocol
IETF	Internet Engineering Task Force
IGP	Interior Gateway Protocols
IP	Internet Protocol
IS-IS	Intermediate System-Intermediate System
ISP	Internet Service Provider
LCDM	Local Congestion Detection Method
MUM	Matrix Usage Method
OSPF	Open Shortest Path First
QoS	Quality of Service
RIP	Routing Information Protocol
R-IBM	Re-using avoided Congested Links – Improved Balancing Method
SNMP	Simple Network Management Protocol
TCP	Transmission Control Protocol

CHAPTER 1

INTRODUCTION

1.1 Background

The Internet is a collection of routing domains into many routing domains called Autonomous Systems (ASes) that interact to control the delivery of Internet Protocol (IP) traffic. As the amount and criticality of data being carried on IP networks grows, managing network resources to ensure reliable and acceptable performance becomes increasingly important. Open Shortest Path First (OSPF) is the most commonly used intra-domain Internet routing protocol (Fortz and Thorup, 2004) (Retvari and Cinkler, 2004). Routers are such protocol to exchange link weights and construct a complete view of the topology inside the AS. Then, each router computes shortest paths (path length in the sum of link weights) and creates a table that controls the forwarding of each IP packet to the next hop in its route. OSPF provides shortest path first routing, simple load balancing by Equal Cost Multi Path (ECMP), which the traffic is split equally between equal cost path and resources to manipulate routing through setting the administrative link weights. In the case of multiple shortest paths, OSPF will use load balancing and split the traffic flow equally over several shortest paths (Moy, 1998). Dijkstra's shortest path computation algorithm is widely employed in OSPF implementations.

Normally, size of the network increases OSPF implementations can become unbalanced due to processing overload caused by extremely flooding and/or by regularly Dijkstra executions during periods of network instability. OSPF implementations also apply various mechanisms to help scalability. Network operators assign link weights. The lower the link weight, the greater the chance that traffic will be routed on that link. Cisco is the major router vendor that assigns OSPF link weights as inverse of the link capacity (Cisco, 2006).

In general, the current shortest path routing suffers a problem of arising congested links (Fortz *et al.*, 2002b) (Fortz and Thorup, 2004). It is due to the extremely usage of the shortest paths, while the other paths are unutilized. Many ISP's have a huge infrastructure based on routers running shortest path protocols like OSPF (Retvari and Cinkler, 2004). Congested links could appear if they have lower link weights because all the traffic from any source to any destination will follow the shortest paths, while still other links or paths unutilized (Fortz and Thorup, 2002a). OSPF is known to be a simple routing protocol in two senses. Firstly, its routing is completely determined by one weight for each link. Secondly, it provides simple load balancing by splitting traffic loads almost equally among equal cost paths. (Retvari and Cinkler, 2004).

Importance in traffic-engineering mechanisms has prompted router vendors to define various extensions in presenting a protocol to enable traffic-engineering deployment. In general, traffic-engineering issues have been

studied under QoS routing. Traffic demand patterns clearly play a role in determining the frequency of traffic-engineering related link state advertisements. If the frequency of such advertisements is very low, the information available in every routers link state database can become very musty. It has been shown that musty information may limit the benefits of richer network connectivity. It has also been suggested that in order to exploit on solid network topologies, link state updates should be more standard and as a result, there is a need for techniques for dealing the extreme link state traffic. The first work was done by (Fortz and Thorup, 2000a) (Fortz and Thorup, 2000b) and published in (Fortz and Thorup, 2004). They argued that a smart OSPF link weights setting could improve its efficiency and will distribute traffic over network links efficiently. They also proved that OSPF link weights setting is a NP-hard (Non-deterministic Polynomial) complete problem and proposed a taboo search with evenly balancing method to set the link weights optimally. Many optimization algorithm, utilize the same framework of Fortz were developed (Ericson *et al.*, 2002) (Buriol *et al.*, 2002) (Buriol *et al.*, 2005) to optimize OSPF link weights in genetic algorithms. In (Roughan *et al.*, 2003) combined traffic matrix estimation with traffic-engineering of OSPF in order to estimates the traffic matrix and then optimizes OSPF link weights using the framework described in (Fortz *et al.*, 2002b).

1.2 Problem Statement

This research is dutiful to solve the following problems:

- **Traffic Demand Matrix Problem:** Previous works such as (Fortz and Thorup, 2000a)(Fortz and Thorup, 2000b)(Fortz and Thorup, 2002a)(Fortz *et al.*, 2002b)(Ericsson *et al.*, 2002)(Buriol *et al.*, 2005)(Roughan *et al.*, 2003)(Fortz and Thorup, 2004)(Villamizar, 2002)(Michael and Nemeth, 2002)(Miguel *et al.*, 2005)(Abrahamson *et al.*, 2002)(Ashwin, 2004)(Ashwin *et al.*, 2005)(Miguel *et al.*, 2005)(Wing *et al.*, 2005)(Makarem, 2007) using the same traffic demand matrix in their experiment. The problem is to find another matrix to optimize the link weights instead of using demand matrix. It is because the way to measure the demand matrix is a difficult task and need a constant monitoring of routers in a certain time.
- **Time Executions Problem:** Previous balancing methods those optimize link weights (Fortz and Thorup, 2000a) (Fortz and Thorup, 2000b) (Fortz and Thorup, 2004) (Ericsson *et al.*, 2002) (Buriol *et al.*, 2002) (Buriol *et al.*, 2005) (Makarem, 2007) suffer from a problem to minimize the time executions which is needed for the optimization process. This problem deals with the research of designing the link weights optimization methods efficiently.

1.3 Research Objectives

The objective of this research is:

- To improve the routing performance of load balancing in the traditional routing communications without any adaptations to the routing protocols or the forwarding mechanisms of the operational network.

1.4 Research Scope

This research will focus on the performance optimization of operational networks such as a company, a university or service provider. These types of operational networks are known as Autonomous Systems (ASes) that interact to control and deliver IP traffic. The performance optimization will be considered on reducing traffic congestions and managing network resources efficiently. Reducing traffic congestions in ASes that operates under the intra-domain routing protocol OSPF will also reduce the traffic congestions in the entire Internet, hence improving its performance. The performance optimization of OSPF networks will be limited to its link weights. This limitation is due to the need of maintaining traditional routing policy while dealing with the rapid changes of the new technologies in the network fields that provides dynamic Quality of Service (QoS).

1.5 Research Contributions

The contributions of this research are:

This research solved the problems to find another alternative matrix to optimize the link weights instead of using demand matrix and reducing the time executions in optimization process to achieve the optimal/near optimal routing performance. Solving this problem helps in analyzing and understands the technique of counting and selecting routing path. New Matrix Usage Method (MUM) that supports a counting selection technique gives a new direction to improve OSPF routing. The routing paths are based on the link weights of operational network. MUM method aims to maintain the current widely deployed traditional routing, meanwhile profitable the capabilities of counting selection.

1.6 Thesis Organization

This thesis is organized as follows. Chapter 2 gives a detailed background about the previous work. Chapter 3 details the research methodology. Chapter 4 presents our new proposed balancing method that applies counting selection technique and the improvement achieved for the time that is needed for the optimization process. The conclusion and the future works will be found in Chapter 5.