



UNIVERSITI PUTRA MALAYSIA

ELECTRICAL TRANSPORT AND RELATED DIELECTRIC PHENOMENA IN COCONUT-SHELL ACTIVATED CARBON

W. MOHAMAD DAUD BIN W. YUSOFF

FSAS 1991 1

ELECTRICAL TRANSPORT AND RELATED DIELECTRIC PHENOMENA IN COCONUT-SHELL ACTIVATED CARBON

By

W. MOHAMAD DAUD BIN W. YUSOFF

Thesis Submitted in Fulfilment of the Requirements for the Degree of Doctor of Philosophy in the Faculty of Science and Environmental Studies Universiti Pertanian Malaysia

August 1991



ACKNOWLEDGEMENTS

I would like to express my gratitute to my supervisors, Professor Dr. Hj. Badri bin Muhammad and Dr. Mansor bin Hashim, for the invaluable guidance, continuing advice, encouragement and discussions they have given me throughout the course of this research.

I would also like to thank the following:

Dr. Sobri bin Hashim, Timbalan Ketua Pengarah of Unit Tenaga Nuklear, Bangi (until 1990) and his staff members for their kind help.

En. Abbas bin Ab. Rahman of Glass Blowing Workshop for his kind help.

En. Nordin bin Abdul Kadir and En. Shahsol Karib bin Kamaruddin of Mechanical and Electronic Workshop for their technical assistance.

Various colleagues and staff members of the Physics and Chemistry Department for their kind help and cooperation.

The Jabatan Perkhidmatan Awam and Universiti Pertanian Malaysia for finacial support and study leave.

My wife and children for their patience and understanding.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS				ii
LIST OF TABLES	• • • • • • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	vii
LIST OF FIGURES	• • • • • • • • • •			viii
LIST OF PLATES				xiii
LIST OF SYMBOLS	AND ABBREVI	ATIONS		xiv
ABSTRACT				xviii
ABSTRAK	• • • • • • • • • •			xxi

CHAPTER

Ι	THE BASIS AND OBJECTIVES OF THIS RESEARCH	1
II	STRUCTURAL ASPECTS OF ACTIVATED CARBON	7
	Introduction	7
	Formation Process of Activated Carbon	8
	Physical Properties of Activated Carbon	9
	COND REDECTED OF DE DEMONTARE CONDUCTION AND	
111	DIELECTRIC POLARISATION IN SOLIDS	14
	Introduction	14
	DC Electrical Conductivity, σ_{dc}	15
	Amorphous Semiconductor	16

iii



Band Model	18
Conduction Mechanisms in Amorphous Semiconductors	21
Dielectric Response Rarameters, ϵ' and ϵ''	25
Polarisation	25
Some Fundamental Equations of Dielectric Theory	29
AC Electrical Conductivity, $\sigma_{\rm ac}$	48
Thermoelectric Power, S	51
Magnetoresistance, $\Delta \rho / \rho$	55
Brief Review: Electrical Properties of Carbon Materials	56
SAMPLE PREPARATION AND ANALYSIS OF STRUCTURE AND COMPOSITION	59
Introduction	59
Preparation of Material and Samples	60
Structural and Microstructural Analysis	63
Compositional Analysis	64
ELECTRICAL CONDUCTION EXPERIMENTS	65
Introduction	65
Preparation of Specimens and Apparatus	66
Preparation of Specimens	66
Experimental Set-ups and Apparatus	66
Working Expression for $\sigma_{\rm dc}, \sigma_{\rm ac}, \epsilon', \epsilon'', S and \Delta \rho / \rho$	80

IV

V

Conductivity Experiments	83
DC Conductivity Measurements	83
Initial Investigation of Temperature	
Variation of DC Conductivity	87
AC Measurement	90
Errors of $\sigma_{\rm de}$, $\sigma_{\rm ac}$, ϵ' and ϵ''	92
Thermoelectric Power Experiment	99
Experimental Technique	99
Error of S	.101
Magnetoresistance Experiment	102
Experimental Set-up and Measurement	102
Error of Δρ/ρ	104
EXPERIMENTAL RESULTS	106
Introduction	106
Results of Morphological and	
Compositional Analyses	107
Results of DC Conductivity Measurement	120
Results of AC Conductivity Measurement	129
Frequency Response of Measured	
Conductivity, $\sigma_{_{ac}}$	129
Temperature Dependence of AC	
Conductivity	136
Analysis of σ_{ac} Using Complex Plane	140
Results of Deduced Dielectric Response	154
Results of Thermoelectric Power Measurement	169
Results of Magnetoresistance Measurement	173

VI

	Probable Explanation for Conduction and	176
		170
	Introduction	176
	DC and AC Electrical Conduction	177
	Dielectric Behaviour	190
	A Possible Model for Dielectric and Conduction Processes	195
	Summary of Main Results	205
	Conclusion	208
VII	FUTURE RESEARCH IN THE PHYSICS OF COCONUT-SHELL ACTIVATED CARBON	210
REFEREN	CES	214
APPENDIX	K	
A	Equations of G _M and C _M	220
В	Equation of G _{eff} due to series resistance	222
С	Published paper	224
VITA	• • • • • • • • • • • • • • • • • • • •	227



LIST OF TABLES

Table		Page
1	A Brief Description of FTIR Spectrum.	113
2	Concentration of Trace Elements in Activated Carbon Sample.	115
3	Percentage of C, H and N.	117
4	Dimension of the Sample and Types of Electrode Used in Electrical Measurement.	121
5	Sample Conductivities at 1/T=0 and Activation Energies in Various Temperature Ranges.	124
6	Low and High Frequency Conductance Data:	150
7	Impedance at Various Frequencies.	202



LIST OF FIGURES

Figure

Page

1	Schematic diagram comparing: (a) a three-dimensional graphite lattice with (b) a turbostratic structure of activated carbon.	11
2	Secondary structure of activated carbon showing the carbon-carbon network attached with residual hydrocarbons and functional groups.	13
3	Examples of some functional groups present in activated carbon.	13
4	Band models in semiconductor materials.	17
5	Dependence of conductivity on temperature.	24
6	Model of conduction processes in amorphous semiconductor.	24
7 ·	Polarisation types and effects in a dielectric.	28
8	Plots of ε' , ε'' and tan δ against $\omega \tau$.	33
9	Schematic representation of the various types of dielectric response of solids.	37
10	Maxwell's two-layer condenser (a), and its electrical model (b).	41
11	Influence of DC conductivity on the losses in interfacial polarisation - DC conductivity increasing between I and IV.	41
12	Frequency dependence of tan δ for various structures of binary mixture (i), and the model of binary mixture (ii).	42
13	Complex plane plots for series R-C circuit.	46



14	A typical plot of frequency dependence on conductivity.	52
15	Apparatus used for the preparation of activated carbon.	61
16	General experimental set-ups.	67
17	Schematic diagrams of electrodes cell.	70
18	Sample chamber and electrodes cell.	72
19	Thermoelectric power chamber and electrodes cell.	73
20	Temperature calibration set-up in cylinder heater.	76
21	Laboratory-assembled electrometer.	78
22	Electrical circuit for DC conductivity measurement.	86
23	Experimental current-versus-time plots.	86
24	Temperature dependence of DC conductivity for samples A1 and A2.	89
25	Temperature dependence of DC conductivity for sample A3.	89
26	Electrical circuit for AC measurements.	91
27	Measuring equivalent circuit.	96
28	Electrical circuit for thermoelectric power measurement.	100
29	Principal arrangement for measurement of thermoelectric power.	100
30	Electrical circuit for magnetoresistance measurement.	103
31	Calibration curve of magnetic field vs energising current.	105
32	X-ray diffraction pattern of coconut-shell activated carbon.	108

33	FTIR spectrum of coconut-shell activated carbon.	114
34	TGA profile of raw coconut-shell (a), and the prepared coconut-shell activated carbon (b).	119
35	Variation of DC conductivity against temperature for different samples.	122
36	Variation of DC conductivity against temperature for different samples using two-terminal electrodes.	125
37	Variation of DC conductivity against temperature for different samples using three-terminal electrodes.	126
38	Plots of DC conductivity against T ^{-1/4} for low temperature regions of Figure 36.	127
39	Plots of DC conductivity against T ^{-1/4} for low temperature regions of Figure 37.	127
40	Frequency dependence of conductivity of sample A7 at various temperatures.	130
41	Frequency dependence of conductivity of sample A9 at various temperatures.	131
42	Variation of AC conductivity with temperature after subtraction of frequency-independent conductivity at low frequencies.	135
43	Comparison of theoretical and experimental values of AC conductivity at 296K.	135
44	Temperature dependence of AC conductivity at different fixed frequencies.	137
45	Deduction of activation energy from conductivity-peak dispersion as in Figure 44(a).	139
46	Comparison of experimental conductivity and theoretical conductivity curves calculated from equation [78].	139
47	Complex impedance plots for sample A7.	142
48	Complex admittance plots for sample A7.	143

49	Complex impedance plots for sample A9.	144
50	Complex admittance plots for sample A9.	145
51	Schematic illustration of an equivalent circuit for series combination of volume (1) and barrier (2) admittance, represented by respective conductances, G, and capacitors, C. The complex impedance plot, Z, and complex admittance plot, Y, of its corresponding circuit are shown in the second and third rows, respectively.	146
52	Theoretical curve of frequency-dependent conductance.	149
53	Temperature dependence of low and high frequency conductivities.	151
54	Effect of DC bias on AC conductance.	153
55 (a)	Relative permittivity, x' , and loss factor, x'' , for sample A7 measured from 103 to 263K.	155
55 (b)	Relative permittivity, \varkappa' , and loss factor, \varkappa'' , for sample A7 measured from 296 to 485K.	156
56(a)	Relative permittivity, x' , and loss factor, x'' for sample A9 measured from 126 to 272K.	157
56 (b)	Relative permittivity, \varkappa' , and loss factor, \varkappa'' , for sample A9 measured from 299 to 399K.	158
57	Variation of relative permittivity with temperature at different frequencies.	159
58	Temperature dependence of the dispersion of loss factor from Figure 55(b).	161
59	Temperature dependence of the dispersion of loss factor from Figures 56(a)–(b).	162
60	A plot of relaxation frequency against 10 ³ /T deduced from Figure 58.	163
61	A plot of relaxation frequency against 10 ³ /T deduced from Figure 59.	163
62	Cole-Cole plot showing the effect of DC conductivity on the plot shape.	165

63	Cole-Cole plot after subtraction of the effect of DC conductivity.	166
64	Master plot of relative permittivity, \varkappa' , and loss factor, \varkappa'' , for various temperatures.	168
65	A plot of thermoelectric power against reciprocal temperature for two different samples.	170
66	Variation of magnetoresistance with magnetic fields at diffrent temperatures.	174
67	Modulus plot of M″ against frequency at various temperatures.	181
68	Deduction of activation energy from dispersion of peak M" in lower frequency region of Figure 67.	182
69	Logarithmic plot of the absolute value of the slope s against temperature.	185
70	Model of electrical current flow in coconut-shell activated carbon.	197
71	RC circuit network for activated carbon.	203
72	Theoretical plots of capacitance, C', and C" based on the circuit network of Figure 71.	203
73	Model of ω^2 dependence of conductance.	222



LIST OF PLATES

Plate		Page
1	Features of coconut-shell activated carbon revealed by SEM showing regions of highly dense surface.	110
2	Features of coconut-shell activated carbon revealed by SEM showing regions of highly porous surface structure.	111



LIST OF SYMBOLS AND ABBREVIATIONS

£	dielectric permittivity (F/m)
٤	permittivity of free space
٤	static dielectric permittivity
e	dielectric permittivity at very high frequency
ε(ω)	dielectric permittivity as a function of angular frequency
х'	relative dielectric permittivity
х"	loss factor
×*	complex dielectric permittivity
μ	micron
Ģ	resistivity (ohm/cm)
σ	conductivity (mho/cm)
σ(ω)	conductivity as a function of angular frequency
τ	relaxation time (sec)
6)	angular frequency (Hz)
(i) P	peak angular frequency
α	propotional to
Å	Angstrom unit
eV	electron volt
exp	exponential



ć	$=\sqrt{-1}$
k	Boltzmann constant
kHz	kilohertz
ln	natural logarithm
log	logarithm
mHz	millihertz
AC	alternating current
В	susceptance (mho)
С	capacitance (F)
Cʻ	real part of capacitance
C"	imaginary part of capaci
с*	complex capacitance
°C	degree Celsius
CFO	Cohen-Fritzsche-Ovshinky
CHN	carbon, hydrogen and nitrogen
DC	direct current
DVM	digital voltmeter
Е	activation energy (eV)
Е _с	energy at conduction band
E F	Fermi energy
E	energy at valence band
FTIR	Fourier transform infrared
G	conductance (mho)
Н	magnetic field (Tesla)
Hz	Hertz

xv

I	current (ampere)
Im	immaginary part
J	current density
К	Kelvin
MHz	megahertz
NAA	neutron activation analysis
OSC	oscillator
R	resistance (ohm)
Re	real part
SEM	scanning electron micrograph
Т	absolute temperature (Kelvin)
TGA	thermogravimetric analysis
UPM	University Pertanian Malaysia
UTN	Unit Tenaga Nuklear
V	voltage (volt)
X	reactance (ohm)
XRD	x-ray diffraction
Y	admittance (mho)
Yʻ	real part of admittance
Υ"	imaginary part of admittance
Y*	complex admittance
Z	impedance (ohm)
Zʻ	real part of impedance
Ζ″	imaginary part of impedance
z*	complex impedance



<u>Subscripts</u>

eff	effective
long	longitudinal
MM	Maxwell-Wagner
max	maximum
P	parallel
8	series
tr	transverse



Abstract of thesis submitted to the Senate of Universiti Pertanian Malaysia in fulfilment of the requirements for the degree of Doctor of Philosophy.

ELECTRICAL TRANSPORT AND RELATED DIELECTRIC PHENOMENA IN COCONUT-SHELL ACTIVATED CARBON

By

W. MOHAMAD DAUD BIN W. YUSOFF

August 1991

- Supervisors : Professor Dr. Hj. Badri bin Muhammad. Dr. Mansor bin Hashim.
- Faculty : Faculty of Science and Environmental Studies, Universiti Pertanian Malaysia.

The electrical properties of coconut-shell activated carbon have not been thoroughly investigated and are, therefore, not well understood. In order to study these properties meaningfully, a fairly satisfactory knowledge of the structure, microstructure and composition of the material is needed.

Since the material's constitution has been little studied and dealt with in the relevant published literature, investigation of the structure and composition of 'the material has to be done in a comprehensive manner. The experimental investigation is divided into two categories. Firstly, the basic experimental work, which is considered important in order to provide supportive evidence to any proposed model of charge-carrier conduction and dielectric behaviour, consists of

xviii

work on x-ray diffractometry, neutron activation analysis, Fourier transform infra-red spectroscopy, scanning electron microscopy, thermoelectric power and magnetoresistance. Secondly, the main experiments consist of work on direct current conductivity and alternating current conductivity measurement.

The results of the basic experiments indicate that activated carbon prepared from coconut shells is essentially amorphous, containing many functional groups, potassium, sodium and several other trace elements. It has a highly porous microstructure. The thermopower-temperature plot obtained suggests that holes are the majority carriers below 385K while at higher temperatures electrons are the majority carriers.

The experimental results of the variation of the direct current conductivity with temperature and the dependence of the alternating current conductivity upon frequency at various fixed temperatures reveal three distinguishable regions. First, a variable-range hopping conduction mechanism operates among localised states near the Fermi level at temperatures below 200K; second, a hopping conduction mechanism occurs among localised states in the band tail for temperatures between about 200 and 385K and third, a percolation conduction mechanism is dominant at and above the mobility edge for temperatures above 385K. The graph of alternating-current conductivity versus

xix



temperature shows that the conductivity is strongly influenced by a certain polarisation process. The results of dielectric-response measurements and the results of the equivalent-circuit analysis show that interfacial polarisation is the most probable process responsible for the observed dielectric behaviour.



Abstrak tesis yang dikemukakan kepada Senat Universiti Pertanian Malaysia bagi memenuhi syarat untuk ijazah Doktor Falsafah.

PENGANGKUTAN ELEKTRIK DAN PENONENA DIELEKTRIK BERKAITAN DALAN KARBON AKTIF TENPURUNG-KELAPA

Oleh

V. NORANAD DAUD BIN V. YUSOPP

Одов 1991

- Penyelia : Professor Dr. Hj. Badri bin Muhammad. : Dr. Mansor bin Hashim.
- Fakulti : Fakulti Sains dan Pengajian Alam Sekitar, Universiti Pertanian Malaysia.

Sifat elektrik bagi karbon aktif dari tempurung kelapa didapati tidak diselidiki secara menyeluruh, oleh yang demikian sifat tersebut tidak diketahui dengan sepenuhnya. Untuk menyelidiki sifat elektrik ini secara bermakna, sedikit sebanyak pengetahuan tentang struktur, mikrostruktur dan kandungan bahan adalah diperlukan.

Oleh kerana sifat bahan hanya sedikit sahaja diketahui dan hanya boleh diperolehi dari penerbitan ilmiah yang bersesuaian, maka penyelidikan dari segi struktur dan kandongan bahan perlu dilakukan secara menyeluruh. Penyelidikan eksperimen ini terbahagi kepada dua kategori. Pertama, eksperimen asas, yang dianggap mustahak bagi menyokong sebarang cadangan model untuk kekonduksian pembawa-cas dan sifat dielektrik; iaitu pembelauan sinar-x, analisis pengaktifan neutron, spektroskopi jelmaan



Fourier infra-merah, mikroskop elektron imbasan, kuasa termoelektrik dan magnetorintangan. Kedua, eksperimen utama yang terdiri dari pengukuran kekonduksian arus terus dan kekonduksian arus ulang alik.

Hasil eksperimen asas menunjukkan karbon aktif yang disediakan dari tempurung kelapa adalah bersifat amorfus, mengandungi banyak kumpulan berfungsi, kalium, naterium dan beberapa jumlah kecil unsur-unsur lain. Ianya juga mempunyai mikrostruktur dengan keliangan yang tinggi. Dari plot termokuasa melawan suhu didapati lohong adalah pembawa cas utama pada suhu di bawah 385K sementara pada suhu tinggi elektron adalah pembawa utama.

Hasil eksperimen perubahan kekonduksian arus terus terhadap suhu dan pergantungan kekonduksian arus ulang alik terhadap frekuensi pada beberapa suhu tertentu menunjukkan mekanisma kekonduksian dalam karbon aktif tempurung-kelapa terbahagi kepada tiga bahagian. Pertama, mekanisma kekonduksian loncatan julat-berubah berlaku di antara keadaan-keadaan tempatan yang berhampiran dengan paras Fermi pada suhu di bawah 200K; kedua, mekanisma kekonduksian loncatan berlaku di antara keadaan-keadaan tempatan dalam daerah jalur ekor untuk suhu sekitar 200 hingga 385K dan ketiga, mekanisma kekonduksian perkolasi yang menonjol pada dan bahagian atas sisi kelincahan untuk suhu melebihi 385K.



xxii

Graf kekonduksian arus ulang alik terhadap suhu menunjukkan kekonduksian sangat dipengaruhi oleh proses pengutupan tertentu. Hasil pengukuran sambutan-dielektrik dan hasil analisis litar-setara menunjukkan pengutupan antaramukaan adalah berkemungkinan besar bertanggungjawab bagi tabiat dielektrik yang diamati.



CHAPTER I

THE BASIS AND OBJECTIVES OF THIS RESEARCH

Activated carbons which are porous carbonaceous materials have been the subject of numerous laboratory investigations, particularly adsorption studies. A literature survey on the properties of activated carbon shows that the investigations were largely concerned with the materials' chemical behaviour. Only a few papers have been published on the studies on their physical properties. The latter type of study is mainly focused on the microscopic nature of electrical conduction. In addition, most of the works on the electrical properties of carbonaceous materials have been carried out on graphite, coke, carbon black and amorphous carbon thin films. Activated carbon (charcoal) prepared from biological materials such as wood, coconut shells, bamboo etc. have been the subject of still fewer electrical investigations. In this work, a material of this type will be the object for an experimental analysis.

At the outset, however, it must be stated that the research work will commence with a material whose structural details are far from clear, except for a generally accepted picture of disordered turbostratic structure (Mattson and Mark Jr., 1971).

