



UNIVERSITI PUTRA MALAYSIA

**STRUCTURAL AND DIELECTRIC PROPERTIES OF SUBSTITUTED
STANNATE COMPOUNDS**

IFTETAN AHMAD TAHA

FSAS 2003 30

**STRUCTURAL AND DIELECTRIC PROPERTIES OF SUBSTITUTED
STANNATE COMPOUNDS**

IFTETAN AHMAD TAHA

DOCTOR OF PHILOSOPHY

UNIVERSITI PUTRA MALAYSIA

2003



**STRUCTURAL AND DIELECTRIC PROPERTIES OF SUBSTITUTED
STANNATE COMPOUNDS**

By

IFTETAN AHMAD TAHA

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfilment of the Requirements for the Degree of Doctor of
Philosophy**

October, 2003



DEDICATION

*To My Father
with respect and Love
I dedicate this work*



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Doctor of Philosophy

STRUCTURAL AND DIELECTRIC PROPERTIES OF SUBSTITUTED STANNATE COMPOUNDS

By

IFTETAN AHMAD TAHA

October, 2003

Chairman: Professor Abdul Halim Shaari, Ph.D.

Faculty: Science and Environmental Studies

The alkaline-earth stannates having the general chemical formula $M\text{SnO}_3$ ($M = \text{Ca, Sr and Ba}$) have been projected as potential electronic ceramics such as thermally stable capacitors, humidity sensor, carbon dioxide sensor. There is no reliable technical information on the effect of substitutional doping on $M\text{SnO}_3$ system that appears to exist in the published literature. In view of the information gaps in the reported research, vigorous and systematic investigation has been carried out on two systems; SrSnO_3 and Mg_2SnO_4 .

The two systems $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ where $M = \text{Ca and Nb}$ and $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ where $N = \text{Ba, La and Zn}$, have been thoroughly studied with respect to synthesis, processing and characterisation – physical, microstructural and electrical. Conventional solid state technique has been used in the preparation of the samples. Two sintering temperatures are employed for $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ system; 1300 °C for 24 h and 1500 °C for 6 h. While for $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ system the



sintering temperatures are 1300 °C for 24 h and 1400 °C for 12 h. The effect of substitutional doping and sintering temperature on the structural, microstructural and dielectric properties of the two systems have been studied

The results of the X-ray diffraction analysis on the $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ system revealed that a single-phase solid solution has formed with Ba as substitutional element. The system has low solid solubility when substituted with La and Zn. The results of the XRD analysis on the $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ system showed that a single phase solid solution has formed with Nb – substituted sample up to $x = 0.05$. The system has low solid solubility when substituted with Ca.

Scanning electron micrographs of the samples for all the compositions in the $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ and $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ systems, in general showed that the grains were spherical in shape and associated with some degree of porosity. In some samples even after sintering at temperature as high as 1500 °C / 6 h, there is still some degree of porosity. For Ca-substituted sample with $x = 0.4$ sintered at 1500 °C / 6 h, the shape of the grains has totally changed from spherical to cubic.

A thorough analysis of the measured electrical data in the frequency range of 10^{-2} to 10^6 Hz for $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ samples substituted with Ba and La showed that the effect of changing sintering temperature and duration from 1300 °C / 24 h to 1400 °C / 12 h has resulted in a decrease in the relative permittivity and loss tangent. In Nb-substituted $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ samples with $0 \leq x \leq 0.1$ increasing sintering temperature to 1500 °C / 24 h has resulted in the increase of the relative permittivity. In general, low capacitance, high resistance (in the order of 10^9 -

$10^{10}\Omega$) and low dielectric loss were the most observed features of all compositions in the two systems under study.

The equivalent circuit of $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ and $\text{Sr}_{1-x}\text{La}_x\text{SnO}_{3\pm\delta}$ samples with $x = 0, 0.1, 0.2, 0.4, 0.6, 0.8$ and 1 samples sintered at $1300\text{ }^\circ\text{C} / 24\text{ h}$ can be expressed by the combination of parallel network of quasi-dc, dipole, and C_{inf} in series with the electrode resistance (R_s)

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia bagi memenuhi keperluan untuk ijazah Doktor Falsafah

STRUKTUR DAN SIFAT DIELEKTRIK BAGI SEBATIEN STANNAT GANTIAN

Oleh

IFTETAN AHMAD TAHA

Oktober 2003

Pengerusi: Profesor Abdul Halim Bin Shaari, Ph.D.

Fakulti : Sains dan Pengajian Alam Sekitar

Stannat-alkalin-bumi yang mempunyai formula kimia am $M\text{SnO}_3$ ($M=\text{Ba}$, La dan Zn) telah diutarakan sebagai seramik elektronik yang berpotensi seperti kapasitor stabil terma, sensor kelembapan, sensor karbon dioksida. Tiada maklumat teknikal yang boleh dipercayai kesan penggantian keatas sistem $M\text{SnO}_3$ yang boleh didapati daripada sorotan ilmiah. Memandangkan terdapat jurang maklumat dalam penyelidikan yang telah dilaporkan, satu kajian sistematik dan mendalam telah dijalankan keatas sistem, SrSnO_3 dan Mg_2SnO_4 .

Kedua-dua sistem tersebut iaitu $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$ dengan $M=\text{Ca}$ dan Nb , dan $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$ dengan $N=\text{Ba}$, La dan Zn , telah dikaji sepenuhnya dari segi sintesis, pemerosesan dan penentuan ciri fizik, mikrostruktur dan elektrik. Teknik keadaan pepejal lazim telah digunakan dalam penyediaan sampel. Dua suhu pensinteran telah digunakan untuk sistem $\text{Mg}_{2-x}\text{M}_x\text{SnO}_{4\pm\delta}$: iaitu $1300\text{ }^\circ\text{C}$ selama 24 jam dan $1500\text{ }^\circ\text{C}$ untuk selama 6 jam. Sementara untuk sistem $\text{Sr}_{1-x}\text{N}_x\text{SnO}_{3\pm\delta}$, suhu

sintering adalah 1300 °C selama 24 jam dan 1400 °C untuk selama 12 jam. Kesan penggantian pendopan dan suhu sinteran keatas struktur, mikrostruktur dan ciri elektrik sistem tersebut telah dikaji.

Keputusan analisis pecahan sinar-X keatas sistem $Sr_{1-x}N_xSnO_{3\pm\delta}$ menunjukkan satu larutan pepejal fasa tunggal telah terbentuk dengan Ba sebagai unsur gantian. Sistem tersebut mempunyai kelarutan pepejal yang rendah bila digantikan dengan La dan Zn. Keputusan analisis XRD keatas sistem $Mg_{2-x}M_xSnO_{4\pm\delta}$ telah menunjukkan bahawa satu larutan pepejal fasa tunggal terbentuk pada sampel yang digantikan dengan Nb sehingga 0.05 sistem ini mempunyai larutan pepejal yang apabila digantikan dengan Ca.

Mikrograf imbasan elektron keatas sampel untuk semua kandungan dalam sistem $Mg_{2-x}M_xSnO_{4\pm\delta}$ dan $Sr_{1-x}N_xSnO_{3\pm\delta}$, secara umumnya menunjukkan butiran adalah berbentuk sfera dan berkait rapat dengan darjah keporosan. Terdapat iuga sampel yang masih menunjukkan darjah keporosan walaupun disinter pada suhu setinggi 1500 °C / 6 jam. Untuk sampel gantian Ca dengan $x = 0.4$ yang disinter pada suhu 1500 °C / 6 jam dari berubah bentuk sfera ke kubus.

Satu analisis yang menyeluruh bagi data elektrik yang diukur dalam julat frekuensi 10^{-2} hingga 10^6 Hz untuk sampel $Sr_{1-x}N_xSnO_{3\pm\delta}$ yang digantikan dengan Ba dan La menunjukkan bahawa kesan peningkatan suhu sinteran dari 1300 °C / 24 jam hingga 1400 °C/ 12 jam telah menyebabkan penurunan dalam ketelusan relatif dan kehilangan tangen. Dalam $Mg_{2-x}M_xSnO_{4\pm\delta}$ yang digantikan oleh Nb dengan $0 \leq x \leq 0.1$ persinteran sehingga 1500 °C / 24 jam telah menghasilkan

penambahan ketelusan relatif. Secara umum, kapasitan rendah, kerintangan tinggi (pada peringkat 10^9 - 10^{10} Ω) dan kehilangan dielektrik rendah adalah sifat yang paling banyak dicerap bagi semua komposisi di dalam sistem yang dikaji.

Litar setara bagi sistem $Sr_{1-x}Ba_xSnO_3$ dan $Sr_{1-x}La_xSnO_{3\pm\delta}$, dengan $x = 0, 0.1, 0.2, 0.4, 0.6, 0.8$ dan 1 yang disinter pada 1300 °C/ 24 jam boleh diungkap secara kombinasi rangkaian selari kuasi-dc, dwikutub dan C_{inf} sesiri dengan rintangan elektrod (R_s).

ACKNOWLEDGEMENTS

Firstly, I am very grateful to “ ALLAH ” s.w.t. for giving me the strength, and patient to complete this research within the specified time.

It is my pleasure to extend my sincere gratitude to, Professor Dr. Abdul Halim Shaari for his continuous supervision, guidance. Also I want to express my acknowledgment to my co-supervisor Associate Professor Dr. Wan Mohd. Daud Wan Yusoff for his assistance and fruitful discussion. I am also pleased to thank my co-supervisor Professor Dr. Lee Chnoong Kheng for her comments, suggestions throughout the research work

I am grateful to all the lecturers in the Physics Department for their kindness. Special thanks are due to Dr. Noorhana Yahya and Dr. Jumiah Hassan, for their assistance, discussion and moral support.

I would like to express my sincere gratitude to my lab mates: Dr. Imad Hamadneh, Ms. Ari Sulisty Rini, Zohra, Mr. Kabashi, Mr. Mustafa, Mr. Ali, Mr. Ramadan, Mrs. Azizah, Mrs. Halema, Ms. Huda, Mr. Som and also I want to thank all postgraduate students in the Physics Department.

I want to thank Ms. Azilah, Mrs. Faridah, Mr. Ho and all members of Electron Microscopy Unit, UPM for their kind assistance.



My very special thanks go to my family in Iraq, my father Prof. Ahmad Al-Haje Taha from Mosul University, Iraq, my mother for her prayer for me and my kids, my lovely sisters, my brother-in-law, Mr. Radwan for their support from far.

Finally, I want to thank my husband Associate Professor Dr. Waleed A. Thanoon from Faculty of Engineering for his generous support and assistance during my studies. Thanks to my kids Dalia, Kaldoon and Zadoon for their love, understanding and time they missed their mother.

May Allah Bless You All



I certify that an Examination Committee met on 2nd October to conduct the final examination of Ifetan Ahmad Taha on her Doctor of Philosophy thesis entitled "Structural And Dielectric Properties Of Substituted Stannate Compounds" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Dr. Zainal Abidin Talib, Ph.D.

Associate Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Chairman)

Dr. Ibrahim Abu Talib, Ph.D.

Professor,
School of Applied Physics,
Faculty of Science and Technology
Universiti Kebangsaan Malaysia.
(External Examiner)

Dr. Abdul Halim Shaari, Ph.D.

Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)

Dr. Lee Choong Kheng, Ph.D.

Professor,
Department of Chemistry,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)

Dr. Wan Mohd. Daud Wan Yusoff, Ph.D.

Associate Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)



GULAM RUSUL RAHMAT ALI, Ph.D.
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date : 9 JAN 2004

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfillment of the requirements for the degree of Doctor of Philosophy. The members of the Supervisory Committee are as follows:

Dr. Zainal Abidin Talib, Ph.D.

Associate Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Chairman)

Dr. Abdul Halim Shaari, Ph.D.

Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)

Dr. Lee Choong Kheng, Ph.D.

Professor,
Department of Chemistry,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)

Dr. Wan Mohd. Daud Wan Yusoff, Ph.D.

Associate Professor,
Department of Physics,
Faculty of Science and Environmental studies,
Universiti Putra Malaysia.
(Member)



AINI IDERIS, Ph.D.
Professor/ Dean,
School of Graduate Studies
Universiti Putra Malaysia

Date : 21 JAN 2004

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

Signature



IFTETAN AHMAD TAHA

Date : 8 . 01 . 2004

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	vi
ACKNOWLEDGMENT	ix
APPROVAL SHEETS	xi
DECLARATION FORM	xiv
TABLE OF CONTENT	xvii
LIST OF FIGURES	xiv
LIST OF PLATES	xxv
LIST OF ABBREVIATION	xxvi
 CHAPTER	
1	INTRODUCTION 1
	Relevance of Electronic Ceramics 1
	Ceramic Insulator and Capacitor Materials 3
	General Introduction of Alkaline – Earth Stannates 4
	Scope of the Present Study 5
	Objectives 6
	Layout of the Thesis 6
2	LITERATURE REVIEW 8
	Magnesium Stannate (Mg_2SnO_4) and Related Compounds 8
	MgO- Nb_2O_5 System and Related Compounds 12
	$MnSnO_3$ and Related Compounds 12
	Strontium Stannate ($SrSnO_3$) and Related Compounds 13
	Barium Stannate ($BaSnO_3$) and Related Compounds 16
	Calcium Stannate ($CaSnO_3$) and Related Compounds 21
	$ZnSnO_3$ and Relevance 23
3	THEORY 25
	Introduction 25
	Synthesis Processing 25
	Mixing and Milling 25
	Compacting 26
	Calcination 27
	Sintering 28
	Ceramic Structures 28
	Perovskite Structure 30
	Spinel Structure 31
	Solid Solutions 31
	Dielectric Theory 32
	Dielectric Material 32
	Dielectric Polarization 35
	Electronic Polarization 36
	Ionic Polarisation 36



	Molecular Polarisation	38
	Space Charge Polarisation	38
	Frequency Dependence of Relative Permittivity ϵ_r	38
	Impedance Spectroscopy	40
	AC conductivity	47
	Effect of DC Conduction	47
	Dielectric Response Model	48
4	PREPARATION AND CHARACTERISATION TECHNIQUES	55
	Preparation Method	55
	Solid State Synthesis	56
	Magnesium Stannate-Substituted Samples $Mg_{2-x}M_xSnO_{4\pm\delta}$	56
	Strontium Stannate-Substituted Samples $Sr_{1-x}M_xSnO_3$	57
	Characterization Technique	60
	X-ray Diffraction Technique	60
	Scanning Electron Microscopy	62
	Dielectric Spectroscopy	63
	Sources of Errors	65
	Sol – Gel Synthesis	65
	Chemical Reaction in Sol-Gel Process	66
	Process Mg_2SnO_4 by Sol-Gel	66
	Characterization Technique for Sol – Gel	67
	Infrared Spectroscopy (IR)	67
	Thermal Analysis	67
5	RESULTS AND DISCUSSION	70
	Structural and Microstructural Properties	70
	Magnesium Stannate-Substituted Samples	70
	Structural Analysis	70
	Microstructural Analysis	83
	Strontium Stannate-Substituted samples	91
	Structural Analysis	91
	Microstructural Analysis	99
6	RESULTS AND DISCUSSION	108
	Dielectric Properties	108
	Magnesium Stannate-Substituted Samples	108
	1-Substitution with Ca	109
	Frequency Response of ϵ' , ϵ'' , C' , C'' and $\tan \delta$	109
	Complex Plane Analysis	118
	Frequency Response of AC Conductivity, σ_{ac}	129
	2-Substitution with Nb	129
	Frequency Response of ϵ' , ϵ'' , C' , C'' and $\tan \delta$	129
	Complex Plane Analysis	141
	Frequency Response of AC Conductivity, σ_{ac}	150
	Strontium Stannate-Substituted Sample	152
	1-Substitution with Ba	152
	Frequency Response of ϵ' , ϵ'' , C' , C'' and $\tan \delta$	152
	Complex Plane Analysis	169
	Frequency Response of AC Conductivity, σ_{ac}	180

	2-Substitution with La	182
	Frequency Response of ϵ' , ϵ'' , C' , C'' and $\tan \delta$	182
	Complex Plane Analysis	195
	Frequency Response of AC Conductivity, σ_{ac}	202
	3-Substitution with Zn	205
	Frequency Response of ϵ' , ϵ'' , C' , C'' and $\tan \delta$	205
	Complex Plane Analysis	211
	Frequency Response of AC Conductivity, σ_{ac}	214
7	Structural, Microstructural and Dielectric Properties of Mg_2SnO_4 Prepared by Sol -Gel Technique.	215
8	CONCLUSION AND FUTURE WORK	237
	Conclusion	237
	1- $Sr_{1-x}M_xSnO_3$	238
	2- $Mg_{2-x}M_xSnO_{4\pm\delta}$	239
	Suggestions for Future Research	242
	REFERENCE	244
	APPENDIX	252
	A Size and Oxidation State of the Ions Involved in This Research	253
	B1 $Mg_{2-x}Ca_xSnO_{4\pm\delta}$ Powders where $x = 0.1, 0.2, 0.4, 0.6, 0.8,$ and 1 Calcined at $1500 / 6$ h	254
	C1 Standard XRD Pattern for Mg_2SnO_4	255
	C2 Standard XRD Pattern for $CaSnO_3$	255
	C3 Standard XRD Pattern for SnO_2	256
	C4 Standard XRD Pattern for $MgNb_2O_6$	256
	C5 Standard XRD Pattern for $Mg_4Nb_2O_9$	257
	C6 Standard XRD Pattern for $Mg_5Nb_4O_{15}$	257
	C7 Standard XRD Pattern for $SrSnO_3$	258
	C8 Standard XRD Pattern for $BaSnO_3$	258
	C9 Standard XRD Pattern for $La_2Sn_2O_7$	259
	C10 Standard XRD Pattern for $ZnSnO_3$	259
	D1 EDAX Spectrum and Semi Quantitative analysis of $Mg_{1.4}Ca_{0.6}SnO_{4\pm\delta}$ Sample Sintered at $1300^\circ C / 24$ h	260
	D2 EDAX Spectrum and Semi Quantitative Analysis of $Mg_{1.6}Ca_{0.4}SnO_{4\pm\delta}$ Sample Sintered at $1500^\circ C / 6$ h	261
	D3 EDAX Spectrum and Semi Quantitative Analysis of $Mg_1Ca_1SnO_{4\pm\delta}$ Sample Sintered at $1500^\circ C / 6$ h	262
	D4 EDAX Spectrum and Semi Quantitative Analysis of $Mg_{1.9}Nb_{0.1}SnO_{4\pm\delta}$ Sample Sintered at $1300^\circ C / 24$ h	263
	D5 EDAX Spectrum and Semi Quantitative Analysis of $Mg_{1.6}Nb_{0.4}SnO_{4\pm\delta}$ Sample Sintered at $1300^\circ C / 24$ h	264
	D6 EDAX Spectrum and Semi Quantitative Analysis of $BaSnO_3$ Sample Sintered at $1400^\circ C / 12$ h	265
	D7 EDAX Spectrum and Semi Quantitative Analysis of $Sr_{0.9}La_{0.1}SnO_3$ Sample Sintered at $1300^\circ C / 24$ h	266
	D8 EDAX Spectrum and Semi Quantitative Analysis of	

	Sr_{0.8}Zn_{0.2}SnO₃ Sample Sintered at 1300 °C / 24 h	267
E	Dielectric Response Model for Quasi-dc Behavior	268
F	Papers Published and Presented Throughout this Thesis	269
VITA		270



LIST OF FIGURES

Figure	Page
3.1: Perovskite Structure (Pumpuch, 1976)	30
3.2: Spinel Structure (A.R. von Hippel)	31
3.3: Polarization figure	34
3.4: Schematic representation of different mechanisms of polarisation (A.R. Von Hippel, 1954)	37
3.5: Variation of the total polarisation and dielectric absorption as a function of frequency (Wei, 1999)	39
3.6: Brickwork model of grain and grain boundary regions in a ceramic placed between metal electrodes (Irvine 1990)	42
3.7: Sample plots with associated simplified equivalent circuit for each of the four complex planes	45
3.8: General classification of all types of dielectric responses found in solids. The upper set of diagrams represent the shape of the $\log \chi'(\omega)$ - dotted curves, and $\log \chi''(\omega)$ - solid curves, The lower set of diagrams represent the corresponding complex plots from (Jonscher, 1983)	46
3.9: General classification of all types of dielectric responses found in solids. The upper set of diagrams represent the shape of the $\log \chi'(\omega)$ -dotted curves, and $\log \chi''(\omega)$ -solid curves, The lower set of diagrams represent the corresponding complex plots from (Jonscher, 1983)	52
3.10: Different types of dielectric dispersion behavior	54
4.1: Flow chart of the synthesis of $Mg_{2-x}M_xSnO_{4\pm\delta}$ ceramic by solid-state route	58
4.2: Flow chart of the synthesis of $Sr_{1-x}M_xSnO_3$ ceramic by solid-state route	59
4.3: Flow chart of the synthesis of $Mg_2SnO_{4\delta}$ by sol-gel technique	69
5.1: XRD patters for powders prepared by solid – state route calcined at different temperatures	73
5.2: XRD patterns of powders of $Mg_{2-x}Ca_xSnO_{4\pm\delta}$ calcined: (A) at 1100 °C for 24 h; (B) at 1300 °C for 24 h	78



5.3:	XRD patterns of powders of $Mg_{2-x}Nb_xSnO_{4\pm\delta}$ where $(0 \leq x \leq 0.1)$ calcined at 1100 °C for 24 h	80
5.4:	XRD patterns of powders of $Mg_{2-x}Nb_xSnO_{4\pm\delta}$ where $(0 \leq x \leq 1)$ calcined at: (A) 1100 °C for 24 h; (B) 1300 °C for 24 h	81
5.5:	Microstructural evolution of $Mg_{2-x}Ca_xSnO_{4\pm\delta}$ samples $(0 \leq x \leq 2)$ sintered at 1300 °C for 24 h	85
5.6:	Microstructural evolution of $Mg_{2-x}Ca_xSnO_{4\pm\delta}$ samples $(0.2 \leq x \leq 1)$ sintered at 1500 °C for 6 h	86
5.7:	Microstructural evolution of $Mg_{2-x}Nb_xSnO_{4\pm\delta}$ samples $(0.01 \leq x \leq 0.1)$ sintered at 1300 °C for 24 h	88
5.8:	Microstructural evolution of $Mg_{2-x}Nb_xSnO_{4\pm\delta}$ samples where $(0.2 \leq x \leq 1)$ sintered at 1300 °C for 24 h	89
5.9:	Microstructural evolution of $Mg_{2-x}Nb_xSnO_{4\pm\delta}$ samples $(0 \leq x \leq 1)$ sintered at 1500°C for 6 h	90
5.10:	XRD patterns of $Sr_{1-x}Ba_xSnO_3$ powders calcined at 1100 °C for 24 h	93
5.11:	XRD patterns of $Sr_{1-x}La_xSnO_3$ powders calcined at: (A) 1100 °C for 24 h; (B) 1300 °C for 24 h	95
5.12:	XRD patterns of $Sr_{1-x}Zn_xSnO_3$ powders $(0 \leq x \leq 1)$ calcined at 1100 °C for 24 h	98
5.13:	Microstructure evolution of $Sr_{1-x}Ba_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h	100
5.14:	Microstructure evolution of $Sr_{1-x}Ba_xSnO_3$ samples (where $0 \leq x \leq 1$) sintered at 1400 °C for 12 h	101
5.15:	Microstructural evolution of $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h	104
5.16:	Microstructure evolution of $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1400 °C for 12 h	105
5.17:	Microstructure evolution of $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h	106
5.18:	Microstructure evolution of $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1400 °C for 12 h	107
6.1:	Variation of relative permittivity ϵ_r for $Mg_{2-x}Ca_xSnO_{4\pm\delta}$ samples sintered at 1300 °C for 24 h as a function of frequency at 25°C	110

6.2:	Variation of $\tan \delta$ for $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples sintered at 1300 °C for 24 h, (a) at all the frequency range; (b) at high frequency range only	112
6.3:	Frequency response of C' , C'' of $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples sintered at 1300 °C for 24 h	114
6.4:	Frequency response of ϵ' , ϵ'' of $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples ($0 \leq x \leq 2$) sintered at 1300 °C for 24 h	116
6.5:	Impedance and modulus plots for Mg_2SnO_4 samples sintered at 1300 °C for 24 h measurement taken at 25 °C	119
6.6:	Spectroscopic plots for Mg_2SnO_4 samples sintered at 1300 °C for 24 h measurement taken at 25 °C	120
6.7:	Impedance plots for $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	122
6.8:	Modulus plots for $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	124
6.9:	Frequency response of AC conductivity of: (a) Mg_2SnO_4 ; (b) $\text{Mg}_{2-x}\text{Ca}_x\text{SnO}_{4\pm\delta}$ samples sintered at 1300 °C for 24 measurement taken at 25 °C	127
6.10:	Variation of relative permittivity ϵ_r for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ samples ($0.01 \leq x \leq 0.1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C	130
6.11:	Variation of loss tangent ($\tan \delta$) for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ samples ($0.01 \leq x \leq 0.1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C.	130
6.12:	Variation of relative permittivity for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ samples sintered at 1500 °C for 6 h as a function of frequency at 25 °C (a): for $0.01 \leq x \leq 0.05$; (b) for $0.2 \leq x \leq 0.8$	132
6.13:	Variation of loss tangent ($\tan \delta$) for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ samples sintered at 1500 °C for 6 h as a function of frequency at 25 °C (a): for $0.01 \leq x \leq 0.05$; (b) for $0 \leq x \leq 0.8$	133
6.14:	Variation of relative permittivity ϵ_r for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ ($0 \leq x \leq 0.05$) samples sintered at 1300 °C for 24 h and 1500 °C for 6 h as a function of Nb concentration at 1 kHz	134
6.15:	Variations of C' , C'' for $\text{Mg}_{2-x}\text{Nb}_x\text{SnO}_{4\pm\delta}$ samples ($0 \leq x \leq 0.1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	136

6.16:	Variations of ϵ' , ϵ'' for $Mg_{2-x}Nb_xSnO_{4+\delta}$ samples ($0 \leq x \leq 0.8$) sintered at 1300 °C for 24 h measurement taken at 25 °C	138
6.17:	Impedance for $Mg_{2-x}Nb_xSnO_{4+\delta}$ samples ($0.01 \leq x \leq 0.8$) sintered at 1300 °C for 24 h measurement taken at 25 °C	143
6.18:	Modulus for $Mg_{2-x}Nb_xSnO_{4+\delta}$ samples ($0.01 \leq x \leq 0.8$) sintered at 1300 °C for 24 h measurement taken at 25 °C	146
6.19:	Impedance plots for $Mg_{2-x}Nb_xSnO_{4+\delta}$ (where $0 \leq x \leq 0.05$) samples sintered at 1500 °C for 6 h measurement taken at 25 °C	148
6.20:	Modulus plot for $Mg_{2-x}Nb_xSnO_{4+\delta}$ (where $0 \leq x \leq 0.05$) samples sintered at 1500 °C for 6 h measurement taken at 25 °C	149
6.21:	Frequency response of AC conductivity of $Mg_{2-x}Nb_xSnO_{4+\delta}$ samples (where $0 \leq x \leq 0.1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	151
6.22:	Frequency response of AC conductivity for $Mg_{2-x}Nb_xSnO_{4+\delta}$ samples ($0 \leq x \leq 0.8$) sintered at 1500 °C for 6 h measurement taken at 25 °C	152
6.23:	Variation of relative permittivity for $Sr_{1-x}Ba_xSnO_3$ samples ($0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C, (a): at all frequencies range; (b) at high frequencies only	154
6.24:	Variation of $\tan\delta$ for $Sr_{1-x}Ba_xSnO_3$ samples ($0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C, (a): at all frequencies range; (b) at high frequencies only	155
6.25:	Variation of relative permittivity ϵ_r for $Sr_{1-x}Ba_xSnO_3$ samples (where $0 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C: (a) all frequencies range; (b) at high frequencies only	157
6.26:	Variation of $\tan\delta$ for $Sr_{1-x}Ba_xSnO_3$ samples (where $0 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C, (a): at all frequencies range; (b) at high frequencies only	158
6.27:	Variation of experimental and theoretical value obtained from equivalent circuit of C' , C'' for $Sr_{1-x}Ba_xSnO_3$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C	159
6.28:	Equivalent circuit model represents dielectric response for Figure 6.27	161



6.29:	Frequency response of real and imaginary permittivity (ϵ' , ϵ'') of $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h	165
6.30:	Frequency response of ϵ' , ϵ'' of $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ (where $0 \leq x \leq 1$) samples sintered at 1400 °C for 12 h	167
6.31:	Impedance plots for $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ (where $0 \leq x \leq 1$) samples sintered at 1300 °C for 24 h measurement taken at 25 °C	170
6.32:	Modulus plots for Sr_{1-x} sintered at 1300 °C for 24 h measurement taken at 25 °C	172
6.33:	Spectroscopy plots for $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ samples sintered at 1300 °C for 24 h measurement taken at 25 °C	175
6.34:	Impedance plots for $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ samples (where $0 \leq x \leq 1$) sintered at 1400 °C for 12 h measurement taken at 25 °C	178
6.35:	Variation of $\log \sigma_{ac}$ for $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C	181
6.36:	Variation of $\log \sigma_{ac}$ for $\text{Sr}_{1-x}\text{Ba}_x\text{SnO}_3$ samples (where $0 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C	181
6.37:	Variation of relative permittivity for $\text{Sr}_{1-x}\text{La}_x\text{SnO}_3$ samples (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C, at all frequencies range; (b) at high frequencies only.	184
6.38:	Variation of loss tangent ($\tan \delta$) for $\text{Sr}_{1-x}\text{La}_x\text{SnO}_{3\pm\delta}$ (where $0 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C, at all frequencies range; (b) at high frequencies only	185
6.39:	Variation of relative permittivity for $\text{Sr}_{1-x}\text{La}_x\text{SnO}_{3\pm\delta}$ samples ($0 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C	186
6.40:	Variation of $\tan \delta$ for $\text{Sr}_{1-x}\text{La}_x\text{SnO}_{3\pm\delta}$ samples ($0 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C	186
6.41:	Variation of experimental and theoretical value obtained from equivalent circuit of C' , C'' for $\text{Sr}_{1-x}\text{La}_x\text{SnO}_{3\pm\delta}$ samples sintered at 1300 °C for 24 h as a function of frequency at 25 °C	189
6.42:	Equivalent circuit model represent dielectric response for Figure 6.41 (a and f)	192

6.43:	Frequency response of real and imaginary permittivity (ϵ' , ϵ'') of $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h	193
6.44:	Impedance plots for $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	196
6.45:	Modulus plots for $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h measurement taken at 25 °C	198
6.46:	Combined spectroscopic plots of M'' and Z'' for $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples sintered at 1300 °C for 24 h as a function of frequency at 25 °C	199
6.47:	Variation of $\log \sigma_{ac}$ for $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C	203
6.48:	Variation of $\log \sigma_{ac}$ for $Sr_{1-x}La_xSnO_{3\pm\delta}$ samples (where $0.1 \leq x \leq 1$) sintered at 1400 °C for 12 h as a function of frequency at 25 °C	204
6.49:	Variation relative permittivity for $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C / 24 h as a function of frequency at 25 °C	207
6.50:	Variation $\tan \delta$ for $Sr_{1-x}Zn_xSnO_3$ samples samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C: (a) at all frequencies range; (b) at high frequencies only	208
6.51:	Frequency response of real and imaginary permittivity (ϵ' , ϵ'') of $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h	209
6.52:	Impedance plots for $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) samples sintered at 1300 °C for 24 h measurement taken at 25 °C	212
6.53:	Variation of $\log \sigma_{ac}$ for $Sr_{1-x}Zn_xSnO_3$ samples (where $0.1 \leq x \leq 1$) sintered at 1300 °C for 24 h as a function of frequency at 25 °C	214
7.1:	TGA, DTA and DTG curves of the Mg-Sn precursor gel	216
7.2:	Infrared spectra of Mg_2SnO_4 : (a) dried gel, powders calcined at: (b) 300 °C, (c) 600 °C, (d) 800 °C, and (e) 1000 °C	217
7.3:	XRD patterns for powders prepared by sol-gel route calcined at different calcination temperatures	219
7.4:	Diagrammatic representation of the composition of MgO and SnO_2 grains at various stages of calcination	221
7.5:	XRD pattern for samples prepared by solid – state route (SS) and sol gel route (SG) sintered in air at 1200 °C for 24 h	221

