



UNIVERSITI PUTRA MALAYSIA

**OPTIMUM OPERATION PARAMETERS OF THE COMBINATION OF
A MIXED-FLOW DRYER AND CONTINUOUS IN-BIN AERATION
FOR PADDY UNDER MALAYSIAN CONDITIONS**

SAKDA INTARAVICHAI

FK 1994 4

**OPTIMUM OPERATION PARAMETERS OF THE COMBINATION OF
A MIXED-FLOW DRYER AND CONTINUOUS IN-BIN AERATION
FOR PADDY UNDER MALAYSIAN CONDITIONS**

By

SAKDA INTARAVICHAI

**Dissertation Submitted in Fulfilment of the Requirements for
the Degree of Doctor of Philosophy in the Faculty of
Engineering,
Universiti Pertanian Malaysia.**

July 1994



ACKNOWLEDGEMENTS

The author wishes to express his appreciation to Associate Professor Dr. Mohd. Nordin Ibrahim, Department of Process Engineering and Environment, for his constant guidance, encouragement and strong support throughout this work.

The author is also greatly indebted to Professor Dr. Mohd. Zohadie Bardaie for serving on the author's supervisory committee and for his kind interest and advice throughout this study. His gratefulness is extended also to Dr. Johari Endan who also serves on the supervisory committee for his constructive suggestions and comments.

The author is truly grateful to Mr. D.M. Bruce, Silsoe Research Institute, UK and Associate Professor Dr. Hussain bin Mohd. Salleh for their kindness in supplying the source code for the computer programme used in the study.

Acknowledgement is due to SEARCA and Kasetsart University for their grant during the period of this study. Special thanks is extended to all the staff at LPN rice complex, Sungei Besar, Selangor, Malaysia, for their exceptional cooperation during the author's experimental work. All staff in the Department of Process Engineering and Environment, and the Graduate School are appreciated for their hospitality and assistance.

Last but not least, the author is forever indebted to his parents and his wife for their unending moral support.



TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS	ii
LIST OF TABLES	vii
LIST OF FIGURES	ix
LIST OF ABBREVIATIONS	xii
ABSTRACT	xv
ABSTRAK	xvii
CHAPTER	
I INTRODUCTION	1
Paddy Drying Situation in Malaysia	4
Objectives of the Study	6
II LITERATURE REVIEW	8
Principles of Paddy Drying	8
Importance of Paddy Drying	8
Classification of Paddy Dryer	9
Equilibrium Moisture Content of Paddy	14
Operating Parameters for Paddy Drying	17
Performance of the Heated Mechanical Paddy Dryer	20
Performance of the Continuous-Flow Dryer	23
Performance of a Mixed-Flow Dryer	28
Operation of Continuous In-Bin Aeration	29



	Grain Drying Simulation	33
	Thin Layer Drying Approach	33
	Thin Layer Drying Model	34
	Deep Bed Grain Drying	37
	Mathematical Model for Mixed-Flow Dryer	44
	Simulation Model for Continuous In-Bin Aeration of Paddy	46
	Optimization of Grain Drying Operation	48
III	MATERIALS AND METHODS	52
	Modification of the Computer Simulation Programme	52
	Simulation of the Mixed-Flow Dryer Performance	54
	Experimental Procedure	56
	The Reference Dryer	56
	Paddy Samples	59
	Weather Conditions	59
	Drying Tests	60
	Measurement of Paddy Moisture Content	61
	Germination Test	62
	Measurement of Temperature of Drying Air	62
	Measurement of Temperature of Paddy Grain	63
	Measurement of Airflow	63
	Measurement of Throughput Capacity of Grain	64
	Measurement of Fuel Consumption	65
	Measurement of Electrical Energy Consumption	66
	Simulation of Continuous In-Bin Aeration	66



	Formulating the Optimization Model	67
	Optimization Model for the Mixed-Flow Dryer	68
	Optimization Model for the Continuous In-Bin Aeration	74
	Optimization of the Mixed-Flow Paddy Dryer with Continuous In-Bin Aeration Operation	78
IV	RESULTS AND DISCUSSION	82
	Model Validation	82
	General Performance of the Mixed-Flow Paddy Dryer	87
	Effect of Drying Air Conditions on Specific Energy Requirement	89
	Effect of Drying Air Conditions on Grain Moisture Content	94
	Effect of Drying Air Conditions on Grain Temperature	97
	Effect of Drying Air Conditions on Grain Germination	100
	Effect of Drying Air Conditions on Grain Throughput Capacity	102
	Performance of the Continuous In-Bin Aeration	102
	Change of Grain Temperature and Moisture Content	105
	Dry Matter Loss	109
	Optimum Working Parameters	115
	Sensitivity Study	118
	Comparison of the Optimum Working Parameters with Existing Operation	121
	Discussion	123

V	SUMMARY AND CONCLUSIONS	129
	REFERENCES	134
	ADDITIONAL REFERENCES	142
	APPENDIX	145
	VITA	167



LIST OF TABLES

Table		Page
1	Parameters of the Derived Prediction Equations for the Dryer Operation Obtained from Non-Linear Least Squares Analysis	72
2	Experimental Results Obtained from the Existing Mixed-Flow Paddy Dryer Operation	83
3	Sample Outputs Obtained from the Modified Computer Simulation Model for the Mixed-Flow Paddy Dryer	146
4	Simple Correlation Analysis Among the Variables in the Dryer Operation	148
5	Non-Linear Least Square Summary Statistics for DNY	150
6	Non-Linear Least Square Summary Statistics for MCO	152
7	Non-Linear Least Square Summary Statistics for GTO	153
8	Non-Linear Least Square Summary Statistics for GRM	155
9	Sample Outputs Obtained from the Simulation Runs of the Storage Model	156
10	Weather Conditions at the Experimental Site	158
11	Simple Correlation Analysis Among the Variables in the Aeration	162



12	Non-Linear Least Square Summary Statistics for FGT	163
13	Non-Linear Least Square Summary Statistics for FMC	165
14	Statistical Analysis Results of T Test Procedures	166



LIST OF FIGURES

Figure		Page
1	Some Typical Batch Dryers Used in Drying Paddy	12
2	A Cascade Mixed-Flow Dryer Used in Paddy Drying	13
3	Variation of Grain Viability in Relation to the Drying Air Temperature	20
4	A Comparison of Specific Energy Requirement of a Range of Grain Drying System	27
5	The Combination of Grain Moisture Content and Grain Temperature Required to Prevent Grain Deterioration during Storage Period	31
6	The Elemental Thin Layer Grain Drying Simulation	35
7	Schematic Dimensions of the Tested Mixed-Flow Dryer	57
8	The Arrangement of Inlet and Outlet Air Ducts Inside the Drying Tower of the Tested Mixed-Flow Dryer	58
9	The Schematic of Variables Flow of the Mixed-Flow Paddy Dryer with Continuous In-Bin Aeration Operation	79
10	Logic Diagram of the Optimum Search Procedure	80
11	Comparison of Final Grain Moisture Contents Obtained from the Experiments and Simulation Runs	84



12	Comparison of Output Grain Temperatures Obtained from the Experiments and Simulation Runs	85
13	Comparison of Specific Energy Requirements Obtained from the Experiments and Simulation Runs	86
14	Specific Energy Requirements of the Mixed-Flow Dryer as the Function of Drying Air Conditions ..	91
15	Specific Energy Requirements as the Function of Airflow at Various Air Temperatures	92
16	Specific Energy Requirements as the Function of Air Temperature at Various Airflow Rates	93
17	Output Grain Moisture Contents under Different Drying Air Conditions of the Mixed-Flow Dryer	95
18	Grain Moisture Content Reductions Obtained from Different Drying Air Conditions of the Mixed-Flow Dryer	96
19	Output Grain Temperatures under Different Drying Air Conditions of the Mixed-Flow Dryer	98
20	Output Grain Temperatures as the Function of Airflow Rate at Different Drying Air Temperatures	99
21	Output Grain Germination as the Function of Air Temperature at Different Airflow Rates	101
22	Grain Throughput Capacity of the Mixed-Flow Dryer at Different Drying Air Conditions	103
23	Output Grain Throughput Capacity of the Mixed-Flow Dryer as the Function of Drying Air Temperature at Various Drying Airflow Rates	104
24	Grain Moisture Content Changed by the Continuous In-Bin Aeration at Different Airflow and Period	107



25	Grain Temperature Drop for Continuous In-Bin Aeration at Different Airflow and Period	108
26	Characteristics of Paddy under Continuous In-Bin Aeration Using of 0.22 m ³ /mt.min Airflow Rate	111
27	Characteristics of Paddy under Continuous In-Bin Aeration Using of 0.44 m ³ /mt.min Airflow Rate	112
28	Characteristics of Paddy under Continuous In-Bin Aeration Using of 0.88 m ³ /mt.min Airflow Rate	113
29	Characteristics of Paddy under Continuous In-Bin Aeration Using of 1.76 m ³ /mt.min Airflow Rate	114
30	Optimum Working Policy Obtained from the Empirical Optimization Models	116
31	Various Optimum Working Parameters for the Mixed-Flow Paddy Dryer and Continuous In-Bin Aeration Combination	120
32	The Average Weather Quality in Terms of DI	127
33	The Logic Diagram of the Generalized Reduced-Gradient Algorithm	128
34	The Optimum Working Parameters Found in the Study	132



LIST OF ABBREVIATIONS

A	Air Duct Cross-Sectional Area, m ²
AFO	Drying Airflow Rate, kg/m ² .hr
AFR	Aeration Airflow Rate, m ³ /mt.min
ATM	Drying Air Temperature, °C
AREA	Bin Cross-Sectional Area, m ²
B	Air Pressure, mm bar
C	Paddy Variety Effect, Empirical Constant
c	Specific Heat, kJ/(kg.K)
DEPTH	Grain Depth, m
DI	Weather Deterioration Index, Dimensionless
DML	Dry Matter Loss, Percent
DNY	Drying Specific Energy Requirement, MJ/kg of Water Removed
E _d	Drying Efficiency, Percent
E _t	Total Energy Supplied, MJ
EMC	Equilibrium Moisture Content, Decimal Dry Basis
ERH	Equilibrium Relative Humidity of Paddy, Decimal
FGT	Grain Temperature after Aeration, °C
FMC	Grain Moisture Content after Aeration, Percent Dry Basis
G _a	Dry Weight Air Flow Rate, kg/m ² .hr
GF	Grain Throughput Capacity, mt/m ² .hr
GFO	Grain Throughput Capacity, mt/m ² .hr
GT	Grain Temperature, °C
GTO	Grain Temperature Leaving the Dryer, °C
GRM	Grain Germination, Percent



H	Absolute Humidity, kg Moisture/kg Dry Air
HRS	Aeration Period, hr
h	Convective Heat Transfer Coefficient, W/(m.K)
h_{fg}	Heat of Vaporization, kJ/kg
I	Dryer Performance Index, Dimensionless
IGT	Initial Grain Temperature, °C
IMC	Initial Moisture Content, Percent Dry Basis
k	Drying Constant, sec ⁻¹
L	Latent Heat of Vaporization, kJ/kg
M	Average Moisture Content, Decimal Dry Basis
MC	Grain Moisture Content, Percent Dry Basis
MCO	Grain Moisture Content Leaving the Dryer, Percent Dry Basis
N	Number of Drying Passes
Pct	Percent
P_s	Saturation Vapour Pressure at a Given Temperature, Pa
POW	Energy Requirement for Aeration, kWh
Q	Volume Air Flow Rate, m ³ /s
QP	Quality Factor of Dried Paddy, Dimensionless
R	Grain Dry Matter to Air Ratio, kg Dry Matter/kg Air
R_w	Wet Grain to Air Ratio, kg Wet Grain/kg Air
RH	Relative Humidity, Percent
RHA	Equilibrium Relative Humidity of Air, Decimal
S	Specific Grain Surface Area, m ² /m ³
T	Temperature, °C
T_{ab}	Absolute Temperature, °K
U	Drying Uniformity Factor, Dimensionless



V_c	Corrected Air Velocity, m/s
V_m	Measured Air Velocity, m/s
W_o	Output Weight of Paddy, mt
X	Column Matrix of the Variables X
X	Bed-Depth Coordinate, m
Y	Bed-Width Coordinate, m
YR	Milled Rice Head Yield, Percent
Z	Objective Function
δH	Heat Utilization, MJ
Θ	Grain Temperature, °C
σ_{mc}^2	Variation of Paddy Moisture Content, Percent
ρ	Dry Weight Density, kg/m ³
Δ	Incremental
∇	Gradient

As Subscript / Superscript

a	Air
db	Dry Basis
eq	Equilibrium
f	Final
in	Initial
k	Iteration
p	Product
t	Time
v	Vapour
w	Water
wb	Wet Basis
α	Closeness Value

Abstract of dissertation submitted to the Senate of Universiti Pertanian Malaysia in fulfilment of the requirements for the Degree of Doctor of Philosophy.

**OPTIMUM OPERATION PARAMETERS OF THE COMBINATION OF
A MIXED-FLOW DRYER AND CONTINUOUS IN-BIN AERATION
FOR PADDY UNDER MALAYSIAN CONDITIONS**

By

SAKDA INTARAVICHAI

JULY 1994

Chairman: Assoc. Prof. Dr. Mohd. Nordin Ibrahim

Faculty: Engineering

The design of a mechanical paddy dryer or any improvement of the dryer can be successfully done by incorporating all significant variables concerned in its operation through an optimization model. All constraints employed in the optimization model should satisfy local requirements and suitabilities.

This study was conducted to determine the optimum parameters for the operation of a mixed-flow paddy dryer followed by continuous in-bin aeration. The aeration was provided to enhance the mixed-flow dryer operation. The optimization study was done by incorporating the working parameters of each operation in two separate empirical non-linear optimization models. The two models were associated in such a way that the optimum results of the mixed-flow drying were the inputs to the aeration stage, and vice versa.



A computer simulation programme was used to obtain all pertinent information of each operation prior to developing the optimization model. A major modification was done to the mixed-flow drying simulation programme to make it suitable for simulating paddy drying under local conditions so that it can be used to evaluate the performance of an existing mixed-flow dryer. The simulated results of this programme agreed reasonably well with the actual tests conducted on the dryer.

The optimum result showed that only two passes of the dryer operation and one period of the in-bin aeration were required for drying fresh wet paddy from moisture content of 30.50 to about 16.00 percent dry basis. Different optimum drying air temperature and airflow rate were obtained from each pass of the drying. The values of 70.48 degree Celsius and 10.00 kg/m².min were respectively the optimum drying air temperature and airflow rate of the first drying pass. For the second pass, the optimum drying air temperature of 77.05 degree Celsius and airflow rate of 5 kg/m².min were obtained. An optimum aeration period of 32.31 hours with airflow rate of 0.77 m³/mt.min was required following the first drying pass. The grain germination of 94.71 percent and dry matter loss of 0.6 percent were the optimum grain quality criteria obtained from the study. An average specific energy requirement of 5.13 MJ/kg of water removed at the net grain output capacity of 6.88 mt/hr were recorded for the optimum conditions.

Compared to the status of current operation, the optimum result obtained showed there is some potential towards improving the existing mixed-flow paddy drying and eventually improving the drying capacity of the rice complex.

optimum pengeringan aliran bercampur menjadi input kepada peringkat pengudaraan dan sebaliknya.

Program penyelakuan komputer digunakan untuk memperolehi kesemua maklumat yang berkaitan bagi setiap operasi sebelum sebuah model pengoptimuman dibangunkan. Satu pengubahsuaian penting telah dilakukan bagi mengubahsuai program penyelakuan pengeringan aliran bercampur untuk menjadikannya sesuai untuk penyelakuan pengeringan padi dengan keadaan tempatan supaya ianya boleh digunakan untuk memperolehi pemahaman mengenai prestasi pengering aliran bercampur yang sedia ada. Keputusan penyelakuan secocok dengan hasil dari kajian.

Keputusan optimum menunjukkan bahawa hanya dua laluan melalui operasi pengering dan satu tempoh pengudaraan di dalam pengering tong diperlukan untuk mengeringkan padi basah dari kandungan lembapan 30.50 kepada 16.00 peratus asas kering. Suhu udara pengeringan optimum dan kadar aliran udara yang berlainan diperolehi bagi setiap laluan mengering. Nilai-nilai 70.48 darjah Celsius dan 10.00 kg/min/m² masing-masing adalah suhu udara pengering optimum dan kadar aliran udara bagi laluan mengering yang pertama. Bagi laluan kedua, suhu udara mengering 77.05 darjah Celsius dan kadar aliran udara mengering optimum 5 kg/min/m² diperolehi. Tempoh pengudaraan optimum selama 32.31 jam dengan kadar aliran udara 0.77 m³/min/mt diperlukan selepas laluan mengering yang pertama. Percambahan bijian pada kadar 94.71 peratus dan kehilangan bahan kering sebanyak 0.6 peratus adalah nilaitara mutu bijian optimum yang diperolehi dari kajian ini. Purata keperluan tenaga tentu sebanyak 5.13 MJ/kg air pada

Abstrak disertasi yang dikemukakan kepada Senat Universiti Pertanian Malaysia bagi memenuhi syarat-syarat untuk memperolehi Ijazah Doktor Falsafah.

**PARAMETER OPERASI YANG OPTIMUM BAGI KOMBINASI
PENGERING ALIRAN BERCAMPUR DAN PENGUDARAAN
BERTERUSAN DI DALAM PENGERING TONG BAGI
PADI DENGAN KEADAAN DI MALAYSIA**

oleh

SAKDA INTARAVICHAI

JULAI 1994

Pengerusi: Assoc. Prof. Dr. Mohd. Nordin Ibrahim

Fakulti: Kejuruteraan

Rekabentuk pengering padi mekanikal atau sebarang perubahan kepadanya boleh dilakukan dengan jayanya dengan menggabungkan pembolehubah penting yang terlibat di dalam pengendaliannya melalui satu model pengoptimuman. Segala kekangan yang digunakan di dalam model pengoptimuman ini mestilah memenuhi keperluan dan kesesuaian tempatan.

Kajian ini bertujuan untuk memastikan parameter optimum bagi pengendalian pengering padi aliran bercampur diikuti oleh pengudaraan di dalam tong secara berterusan. Pengudaraan dibuat bagi meningkatkan operasi pengering padi aliran bercampur. Kajian pengoptimuman dilakukan dengan menggabungkan parameter kerja setiap operasi di dalam dua model pengoptimuman tak lurus ghalib yang berasingan. Kedua-dua model tersebut dikaitkan dengan cara di mana keputusan



muatan keluaran bijian bersih sebanyak 6.88 tm/jam adalah terlibat dengan keadaan optimum.

Berhubung dengan prestasi operasi semasa, keputusan optimum yang diperolehi menunjukkan ada potensi untuk meningkatkan operasi pengering padi aliran bercampur yang tersedia, dan akhirnya meningkatkan kemampuan pengeringan kompleks padi berkenaan.

CHAPTER I

INTRODUCTION

Generally, paddy drying and storage operations will affect unit operation performance as well as grain quality. This implies that each operation will only be achieved if both operation performance and grain quality are simultaneously considered. The general criteria in operating a particular mechanical dryer or storage facility is to try to maximize operation performance with minimum deterioration in paddy grain quality. A major decision in each operation would be to control the operating parameters so as to obtain the best possible return.

Paddy drying is the process of removing moisture from wet paddy to a moisture content in equilibrium with the surrounding atmosphere or to such a level that decreases biological and chemical activities that reduce the quality of the paddy. Drying is a very complex process. It involves the simultaneous transfer of heat and mass. During drying, heated air or near ambient air is blown through the bulk of wet paddy, by means of which the energy required for evaporation is provided to the paddy. Moisture is removed as a result of the difference in vapour pressure between the paddy surface and the ambient air surrounding it. Meanwhile, moisture migrates to the surface of the grain because of the moisture gradient between the inner parts and the surface. Finally, the water evaporating from the paddy surface is removed by the air moving through



the grain. Drying will occur until equilibrium is reached between the inner part and the surface, and between the surface and the ambient air. The process takes place simultaneously in a device called mechanical dryer.

Consequently, to achieve the ultimate goal of drying the paddy, the drying parameters must be properly controlled. Basically, they consist of the dimensional specification of the dryer, initial moisture content of the paddy, the drying air temperature, the airflow rate, the grain throughput capacity, the final moisture content and the temperature of paddy, and the energy consumption in the process. Various systems of the mechanical paddy dryer can be employed. With increasing scarcity of energy resources the efficiency of these systems are becoming increasingly important. Incorrect selection and control of a dryer leads to misapplication, excessive utilization costs and loss in quality and quantity of paddy grain. To ensure efficient use, all pertinent working parameters should be controllable. Moreover, for the innovation and improvement of a mechanical paddy dryer, the working parameters necessary for the dryer operation should be predictable in order to achieve the desired goal of efficient drying.

One possible way to increase the efficiency of the paddy drying operation is by providing in-bin aeration. This operation can be accomplished when paddy is in a storage bin for a period of time so that the drying unit can be operated over a longer period. This results in increased drying efficiency and eventually, more profitable use of the facilities in a rice complex. However, during this period the paddy grain quality may decline due to pests and biological activities brought about by unsuitable weather. Dry matter loss is the main substantial loss in the aeration period. In order to increase the efficiency of the drying operation

as well as to maintain paddy grain quality, the in-bin aeration should complement the drying operation. Accordingly, paddy grain moisture content and temperature, aeration airflow rate, weather condition, the amount of paddy in the storage bin and the aeration period should be incorporated in the overall consideration. Though the in-bin aeration is considered as a simple operation, its effectiveness is highly influenced by the aforementioned factors. Therefore, it is necessary to know and understand the interrelationship between the factors, and finally, to be able to quantify suitable values for each parameter to achieve the optimum storage working policy.

In order to make optimum use of paddy drying and in-bin aeration, the optimum values of the process parameters should be substantially quantified. Due to the fact that there are many factors affecting the operating performance of paddy drying and storage, the best possible working parameters can be obtained only by performing an optimization study. In this study, the optimization models will be formulated by using the aforementioned parameters subject to the specific domains of each parameter in conjunction with the existing operation of a rice processing complex. Providing the optimum working parameters for both paddy drying and storage operations will increase the drying capacity of a rice processing complex resulting in better quality dried paddy. Generally, a relatively large percentage of energy is consumed in drying cereal grain i.e. about 20 to 30 percent of the total energy consumption in the grain production process (Stevens and Thompson, 1976). Furthermore, the energy consumption in storage using continuous aeration of ambient air could be defined as energy used to force the air to pass through the grain bulk. Thus, the

objective function of the optimization models under this study is to minimize energy consumption of the operation.

There are many researches on the simulation of paddy drying and storage whose objectives are mostly aimed at developing computer simulation models of the relevant process mechanism, and eventually, to use the validated model to predict the behaviour of pertinent operating parameters in the process. This study is an attempt to exploit computer simulation models for paddy drying and storage, in order to contribute some improvements towards paddy drying, storage operation and design.

Paddy Drying Situation in Malaysia

During the sixties, Malaysian farmers normally dried their paddy naturally under the sun. At that time paddy production was based on traditional practice. A major change in rice production occurred during the late sixties when the Malaysian Government played a major role in development by allocating a large budget for improving the paddy irrigation system. As a consequence, double cropping, new high yielding rice varieties, and mechanical dryers were introduced into the new paddy production system.

By 1980, the government agency called " Lembaga Padi dan Beras Negara" (LPN) established 28 rice complexes nationwide, equipped with the LSU mixed-flow dryer and milling facilities. Meanwhile, use of batch dryers prevailed. All established rice complexes are controlled by the government. In 1983, 70 percent of total paddy production nationwide was dried by batch and sun drying,

while 17 to 20 percent were dried using the continuous-flow dryers available at the rice processing complexes. The rest were still dried naturally by the sun (Hussain, 1990).

By 1984, the total mechanical drying capacity of all commercial mills nationwide was 617,210 metric tonnes per year. However, only 53 percent of the paddy were dried at the government rice complexes (Nordin, 1989). The remaining 47 percent were dried by private commercial mills and the farmers themselves.

Currently, there are four categories of mechanical paddy dryers used in Malaysian rice production. They are the LSU mixed-flow dryer, the flat bed dryer, the moisture extraction unit (MEU), and a new pilot conveyer dryer (Nordin, 1990). In addition, the in-bin counterflow dryer is proposed to be added to the rice complexes (Hussain, 1990).

The LPN rice processing complexes are faced with the problem of over-supply of wet paddy. This is due to the fact that most farmers prefer to sell their wet paddy to the LPN since LPN impose a lower price deduction. About 350 metric tonnes were procured daily by the LPN rice complex at Sungei Besar during the dry season (Nordin, 1989). With this average amount, it is not possible for the rice complex which is most accessible to the farmers to complete the drying of wet paddy on the day of procurement. This results in considerably long queues waiting to unload paddy from the trucks. The waiting time for a truck to finish unloading wet paddy resulted in paddy grain deteriorating due to dry matter loss and damp grain heating.