



# **UNIVERSITI PUTRA MALAYSIA**

# SOLID STATE BIOCONVERSION OF OIL PALM EMPTY FRUIT BUNCHES INTO COMPOST BY SELECTED MICROBES

HASSAN ABDEL HADI HASSAN

FK 2001 11



## SOLID STATE BIOCONVERSION OF OIL PALM EMPTY FRUIT BUNCHES INTO COMPOST BY SELECTED MICROBES

By

HASSAN ABDEL HADI HASSAN

Thesis Submitted in Fulfilment of the Requirement for the Degree of Master of Science in the Faculty of Engineering Universiti Putra Malaysia

October 2001





# قَالُواْ سُبُحَىنَكَ لَا عِلْمَ لَنَآ إِلَّا مَا عَلَّمُتَنَآ إِنَّكَ أَنتَ ٱلْعَلِيمُ ٱلْحَكِيمُ عَلَيْ الله Surat Al-Baqara.

Especially dedicated to my parents



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the Degree of Master of Science

SOLID STATE BIOCONVERSION OF OIL PALM EMPTY FRUIT BUNCHES INTO COMPOST BY SELECTED MICROBES

By

HASSAN ABDEL HADI HASSAN

October 2001

Chairman:

Associate Professor Azni Bin Hj Idris, Ph.D.

Faculty:

Engineering

The palm oil industry plays a major role in the economic development of

several tropical countries. In processing oil palm fruit for oil extraction, palm oil

mills produce a considerable amount of solid wastes in the form of fibres, nut

shells and empty fruit bunches (EFB). For every 100 tonnes of fresh fruit bunches

processed there will be approximately 20 tonnes of nutshells, 7 tonnes of fibres

and 26 tonnes of empty bunches discharged from the mill. In order to prevent

environmental pollution, disposal of the oil palm wastes needs prudent handling

and consideration.

The composting process is currently viewed primarily as a waste

management method to stabilise organic wastes. Composting is a management

system that uses microbial activity to degrade raw organic material. The stabilised

end product (compost) is widely used as a soil amendment to improve soil

structure and to provide plant nutrients. These beneficial uses of compost can

improve healthy plant production, reduce the use of chemical fertilisers and

conserve natural resources.

3

UPM

The main objective of this study is to develop an alternative technology for the production of compost from oil palm empty fruit bunches (EFB), using a solid state biconversion technique (SSB), by selected microorganisms. SSB is a process whereby an insoluble substrate, with sufficient moisture, but not free water, can be converted to compost by different microorganisms. It is a simple and cost effective way of treating the organic waste, which requires no complex controls.

Three efficient cellulolytic cultures Aspergillus niger, Trichoderma reesei and Phanerochaete chrysosporium were used as inoculum in this study. The strains used did not produce any toxic by-products during the bioconversion processes and they were able to utilise lignin and grow on lignocellulosic materials. Shredded and partially dried EFB (280g) were allowed to compost for 8 weeks using ammonium sulfate as a source of nitrogen with the addition of single and mixed culture innoculum of A.niger, T.resie and P.chrysosporium, and compared to the natural process as control. The composting process was carried out in 1L flasks and the controlling parameters such as moisture content, temperature and aeration were optimised.

The investigation showed that due to inoculation, the period of composting was reduced to four weeks compared to normal composting time of 24 - 32 weeks. In addition to this, the quality of the compost was improved and there was greater production of nitrate and ammoniacal nitrogen due to the accelerated decomposition. During four week period, the total carbon degraded to 54% with mixed culture showing a maximum decomposition, followed by *P. chrysosporium* 53.4%, *A. niger* 41%, T. reesie 34.6% and control 22.7%.



A maximum increase of total nitrogen content of 92.1% was recorded with mixed culture followed by 77.4% with *P.chrysosporium*, 67.6% with *A.niger*, 64.7% with *T.reesie* and 39% with control. The C/N ratio of 47 in EFB compost improved to 11.34 with mixed culture, to between 12.32 - 18.67 with single cultures and to 26.14 with control. There was a 60% reduction in the C/N ratio over the control.

The addition of mixed culture is therefore shown to be more effective than single culture and natural composting (control). The SSB technique was found to be feasible technology with high potential for EFB conversion into compost. The compost prepared by such techniques was rich in nitrogen, phosphorus, potassium and humus content. The observations of this study will provide future guidelines for the production of non-hazardous environmental friendly organic fertilisers.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

PENGHASILAN BAJA KOMPOS DARIPADA SERABUT KELAPA SAWIT MENGGUNAKAN KAEDAH BIODEGRADASI DALAM KEADAAN PEPEJAL DENGAN BANTUAN MIKROB TERPILIH

#### Oleh

#### HASSAN ABDEL HADI HASSAN

#### Oktober 2001

Pengerusi: Profesor Madya Azni Bin HJ. Idris, Ph.D.

Fakulti: Kejuruteraan

Industri minyak kelapa sawit merupakan sumber utama kepada perkembangan ekonomi negara-negara tropika. Proses perkilangan minyak kelapa sawit banyak menghasilkan sisa pepejal dalam bentuk gentian, isirung dan serabut kelapa sawit (EFB). Bagi setiap 100 tan metrik buah kelapa sawit segar yang diproses, lebih kurang 20 tan isirung, 7 tan gentian dan 26 tan serabut kelapa sawit dihasilkan sebagai bahan buangan. Perhatian yang serius perlu diambil ke atas proses pelupusan bahan buangan ini bagi mengelakkan kesan pencemaran alam sekitar.

Proses pengkomposan kini mendapat perhatian serius dan merupakan cara atau teknologi terkini dalam menstabilkan bahan buangan organik ini. Teknologi ini menggunakan tindakbalas mikrob untuk proses biodegradasi bahan buangan ini. Proses biodegradasi ini menghasilkan baja kompos yang digunakan secara meluas sebagai agen pembaik struktur tanah, penghasilan zat-zat untuk pertumbuhan pokok dan agen penentang hakisan tanah. Kebaikan dan faedah baja kompos ini seterusnya boleh meningkatkan tahap pertumbuhan pokok,



mengurangkan kos penanaman dengan mengurangkan penggunaan baja kimia dan seterusnya melindungi sumber asli di Malaysia.

Objektif utama kajisan ini adalah untuk mancari satu alternatif bagi penghasilan kompos dari serabut kelapa sawit, iaitu menggunakan telenik biodegradasi dalam keadaan pepejal (SSB) dengan bantuan mikrob yang terpilih. Biodegradasi dalam keadaan pepejal (SSB) ialah satu proses di mana substrat tak larut dengan kelembapan yang sesuai ditukar menjadi kompos oleh pelbagai mikrob. Proses ini adalah mudah dan kos efektif sebagai cara melupuskan sisa organik tanpa memerlukan proses kawalan yang kompleks.

Tiga kultur selulolitik yang efisien (Aspergillus niger, Trichoderma reesei and Phanerochaete chrysosporium) telah digunakan sebagai inocula dalam kajian ini. Mikrob ini tidak menghasilkan produk sampingan yang toksik sepanjang proses biodegradasi, malahan ia dapat menggunakan lignin dan tumbuh di atas bahan lignoselulosik. Sebanyak 280g kepingan-kepingan kecil EFB separa kering dalam kultur tunggal dan kultur kelompok yang terdiri daripada A. niger, T. reesei dan P. chrysosporium, dibiarkan kompos selama lapan minggu dengan menggunakan ammonium sulfat sebagai sumber nitrogen. Proses semulajadi telah dijadikan kawalan sebagai perbandingan dengan kultur tunggal dan kelompok. Proses pengkomposan dijalankan dengan menggunakan kelalang 1L dan parameter kawalan yang dioptimumkan ialah seperti kandungan kelembapan, suhu dan proses pengudaraan.



Berdasarkan pemerhatian yang dibuat, tempoh pengkomposan telah berkurangan kepada empat minggu disebabkan penginokulan jika dibandingkan menggunakan cara normal iaitu 24 hingga 32 minggu. Kualiti kompos juga bertambah baik dan terdapat peningkatan penghasilan nitrate dan ammoniacal nitrogen disebabkan penguraian yang lebih cepat. Dalam tempoh empat minggu jumlah karbon telah didegradasi sebanyak 54% menggunakan kultur campuran diikuti P.chrysosporium 53.4%, A.niger 41%, T.reesie 34.6% and kawalan 22.7%.

Dengan menggunakan kultur campuran, peningkatan maksimum jumlah kandungan nitrogen sebanyak 92.1% telah direkodkan, 77.4% menggunakan P.chrysosporium, 67.6% menggunakan A.niger, 64.6% menggunakan T.reesie dan 39% menggunakan kawalan.nisbah C/N daripada 47 didalam kompos EFB meningkat 11.34 menggunakan kultur campuran, antara 12.32 hingga 18.67 menggunakan satu kultur dan 26.14 menggunakan kawalan. Ini menunjukkan pengurangan sebanyak 60% nisbah C/N berbanding kawalan.

Penggunaan kultur kelompok adalah lebih efektif daripada kultur tunggal dan pengkomposan semulajadi. Proses biodegradasi dalam keadaan pepejal (SSB) sangat berpotensi untuk menjadi teknologi terkini untuk penghasilan baja kompos dari serabut kepala sawit. Baja kompos yang dihasilkan melalui teknologi ini terbukti kaya dengan kandungan nitrogen, fosforus, potassium dan humus. Diharapkan agar hasil kajian ini akan menjadi panduan asas untuk penghasilan baja organik yang mesra alam.



#### **ACKNOWLEDGEMENTS**

In the name of Allah, Most gracious, Most Merciful

I am deeply grateful to ALLAH " A.W " for giving me the opportunity to study with strength and patience to complete this work. I would like to thank not just the few that inspired me, but also those who have accepted my mistakes and shortcomings. I am especially grateful to those who have taken time to look at the various stages of my study in spite of their busy schedules.

First and foremost, I would like to express my deepest gratitude and special thanks to the chairman of my supervisory committee Assoc. Prof. Dr. Azni Bin Hj Idris for his kind supervision, guidance, continuous support and encouragement throughout the course of the study. My appreciation is also extended to the members of my supervisory committee Assoc. Prof. Dr. Fakhru'l Razi Ahmadun and Assoc. Prof. Dr. Mohamed Ali Hassan for their help, guidance and valuable suggestions during the course of this study.

I am very much appreciative of the assistance given to me by all the staff members of the Department of Chemical & Environmental Engineering. I also wish to express my thanks to all the laboratory assistants in the Fermentation Laboratory from the Department of Biotechnology, UPM, for their technical assistance.



Special thanks are due to my fellows in the Laboratories of the Department of Chemical and Environmental Engineering Abul, Isam, Ibrahim, Nasr, Kalvin and Zhangir for their kindness and co-operation, and to all my friends in the Faculty of Engineering who have helped me in one way or another. Sincere thanks are also extended to all friends inside and outside UPM, for their correspondence and concern during the period of my stay in Malaysia.

It is also a pleasure to record my warmest gratitude to my father, mother, brothers, sisters and relatives for their prayers and moral input during my study. Special thanks are due to my sister Ahlam Abdel Hadi who shared with me the away from home dreams during our stay together on UPM campus. Words cannot express my profound gratitude to my beloved wife Rasha Abdel Rahim for her encouragement, understanding and patience throughout my study.

I am also grateful to Assoc. Prof. Dr. Azni Bin Hj Idris for having offered me the Graduate Assistantship through his IRPA project for pursuing the graduate study at Universiti Putra Malaysia.



I certify that an Examination Committee met on 19<sup>th</sup> October 2001 to conduct the final examination of Hassan Abdel Hadi Hassan on his Master of Science thesis entitled "Solid State Bioconversion of Oil Palm Empty Fruit Bunches into Compost by Selected Microbes" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Sa'ari Mustapha, Ph.D.
Associate Professor
Department of Chemical and Environmental Engineering
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Azni Bin Hj Idris, Ph.D.
Associate Professor
Department of Chemical and Environmental Engineering
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Fakhru'l Razi Ahmadun, Ph.D.
Associate Professor
Department of Chemical and Environmental Engineering
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Mohamed Ali Hassan, Ph.D.
Associate Professor.
Department of Biotechnology
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Member)

MOHD GHAZLI MOHAYIDIN, Ph.D. Professor/Deputy Dean of Graduate School, Universiti Putra Malaysia

Date: 8 NOV 2001

This thesis submitted to the Senate of Universiti Putra Malysia has been accepted as fulfilment of requirement for the degree of Master of Science.

AINI IDERIS, Ph.D.

Professor

Dean of Graduate School, Universiti Putra Malaysia

Date: 13 DEC 2001



## **DECLARATION**

I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

Hassan Abdel Hadi Hassan

Date: 6/11/2001

## TABLE OF CONTENTS

		Page
DEDICAT	'ION	2
ABSTRACT		
ABSTRAK		
ACKNOWLEDGEMENTS		
APPROVAL  DECLARATION  LIST OF TABLES		
		13
		16
LIST OF F	FIGURES	17
LIST OF P	PLATES	18
CHAPTE	R	
I	INTRODUCTION	19
_	General	
	Justification	21
	Objectives	22
II	LITERATURE REVIEW	23
	Composting and Compost	
	Definition of Composting	
	The need for Composting	
	Principles of Composting	
	Solid State Bioconversion Technique	
	Definition	28
	Advantages of SSB compared to LSB	28
	Future Potential of SSB	
	Microbial Basis of Processes	34
	Microbial Types	34
	Biodegradation of lignocellulosic materials	38
	Cell Wall Constituents	39
	Lignin degradation	
	Oil Palm Empty Fruit Bunches	42
	Current Trend in Utilisation of EFB	
	Other EFB Composting Works	
	Commercial Scale Composting of EFB in Malaysia	
	Factors Affecting Decomposition	
	Particle Size	
	Moisture Content	
	Aeration	
	Turnings	
	Temperature	
	Hydrogen ion Activity (pH values)	
	C/N ratio	
	Effect of Compost on Soil	
	The Compost Maturity	
	Prospects of Marketing	68



III	MATERIALS AND METHODS	<b>7</b> 0	
	Chemical Reagents	70	
	Oil palm Empty Fruit Bunches (EFB)		
	Physical Analysis of EFB		
	Chemical Analysis of EFB		
	Solid State Bioconversion Technique		
	Process Methodology of SSB		
	The stability of cellulolytic fungi on EFB		
	Microorganisms and Maintenance		
	Preparation of Inoculum and Medium Composition		
	Treatment of Oil Palm Empty Fruit Bunches		
	Cellulolytic Fungi as Inoculant in Composting		
	Analysis of Compost		
	Physical Analysis		
	Chemical Analysis		
	Biological Analysis (Germination Test)		
	Diological Analysis (Germination Test)	65	
IV	RESULTS AND DISCUSSIONS	87	
- '	Characterisation of Oil Palm EFB		
	Physical Characteristics of EFB		
	Chemical Characteristics of EFB		
	The Stability of Celluloytic Fungi in EFB		
	Physical Analysis during Composting of EFB using		
	SSB Technique with Cellulolytic Inoculum	98	
	Temperature		
	Moisture Content		
	Structure and Texture		
	Colour changes		
	Odour Changes		
	Chemical Analysis during Composting of EFB using	103	
	SSB Technique with Cellulolytic Inoculum	107	
	Changes of pH during Composting of EFB		
	The changes in Organic C, Total N and C/N ratio		
	Phosphorous Content		
	Potassium Content		
	Humus Content	118	
	Comparison of Nutrient values with	101	
	Commercial Compost Product		
	Biological Analysis (Germination Test)		
	Percentage Germination		
	Shoot Growth and Root Growth		
	Germination Index	124	
V	CONCLUSION AND RECOMMENDATIONS	120	
¥	Conclusion		
	Recommendations		
	Kecolillicinations	132	
DEE	FERENCES	123	
	APPENDICES		
	LIOGRAPHICAL DATA		
JIII.	wao gamar republic buranta	1 20	



# LIST OF TABLES

Table		Page
1	Chemical Characteristics of EFB	88
2	Changes of Temperature during Composting of EFB	98
3	Changes in Moisture content during Composting of EFB	103
4	Changes of pH during Composting of EFB	107
5	Changes in Organic C, N and C/N ratio during Composting of (EFB)	113
6	Changes in Total P, K and Humus content during Composting of EFB	118
7	Nutrient values of Finished Compost product Compared with Commercial Compost Product	122
8	Results of Germination Test	123



# LIST OF FIGURES

Figure		Page
1	Principles of Composting	26
2	Temperature Variations in Composting Process	61
3	pH Variations in Composting Process	64
4	Total Land uses in Malaysia	69
5	Schematic Flow Diagram of the SSB of EFB into Compost	80
6	Radial Growth of A. niger supplemented by EFB	92
7	Radial Growth of T. reesie Supplemented by EFB	93
8	Radial Growth of P. chrysosporium Supplemented by EFB	94
9	Changes of Temperature during Composting of EFB	99
10	Changes of pH during Composting of EFB	109
11	Carbon Profile during Composting of EFB	114
12	Nitrogen Profile during Composting of EFB	115
13	C/N ratio Profile during Composting of EFB	116
14	Phosphorus Profile during Composting of EFB	119
15	Potassium Profile during Composting of EFB	120
16	Comparison of Shoot and Root Growth	126
17	Comparison of Germination Index for different Treatments	127



# LIST OF PLATES

Plate		Page
1	Oil Palm Empty Fruit Bunches from the Mill	56
2	Shredded Oil Palm EFB	81
3	Optical Micrograph of A. niger(100x)	95
4	Optical Micrograph of T. reesie(100x)	96
5	Optical Micrograph of P. chrysosporium(100x)	97
6	Finished Compost Product of EFB treated by M.culture	106
7	Results of Germination Test	128



## **CHAPTER I**

## **INTRODUCTION**

#### General

The recycling of organic wastes as fertiliser for maintenance of soil quality and improved crop productivity is of economic importance. The burning of rural and urban refuse without energy recuperation or disposal in landfills are wasteful processes, which should be avoided.

The major advances in agriculture have taken place by the use of non-renewable petroleum and its products. The cost of non-renewable sources has, however, risen sharply during the last decade, increasing the prices of fertilizers and pesticides.

Composting is a microbiological, non-polluting and safe method for disposal and recycling of organic wastes by bioconversion to fertilisers. Bioconversion by this method eliminates environmental pollution. Moreover, sites for dumping refuse on the outskirts of cities are gradually shrinking due to progressive urban expansion. Traditional methods of composting are proving unsuitable for disposal of the huge quantities of city wastes generated. Besides compostable materials, these city wastes contain non-compostable components such as metals, stones, glass, etc. In this context, mechanisation of composting, particularly for large cities, has several advantages, such as: converting of large quantity of city refuse and thus increasing environmental sanitation; minimising



pollution; recovering discarded materials; and producing better quality compost in a shorter time.

Waste material generated by the society can be classified into three major categories: agricultural wastes, industrial wastes and domestic wastes. Industrial wastes are produced by various industries, and waste characteristics vary greatly from one industry to another. In Malaysia, the major agro-industrial wastes are produced by the oil palm industry. Currently more than one third of the total cultivated area in Malaysia is under oil palm cultivation, generating a huge quantity of organic wastes every day.

Recently there has been wide interest in the utilisation of agro-industrial wastes. This is evident in countries where agriculture is an important part of the economy. These organic wastes are also potential sources of pollution.

Initially empty fruit bunches from the mill were incinerated producing bunch ash, which causes air pollution. At present oil palm empty bunches are either distributed in the field as mulch or incinerated, and the ash produced used as potash fertiliser for the palms. With the present stringent DOE regulation on air pollution, most of EFB produced by oil palm mills are used for mulching and oil palm mills should get rid or treat all mill effluent, to a required minimum level.

With the above concerns in mind, this study proposes to evaluate the utilisation of agro-industrial by-products of the oil palm industry, with emphasis

on the use empty fruit bunches (EFB) as organic fertiliser by means of composting using the solid state bioconversion technique.

The recycling of renewable organic wastes to meet the challenges of the 21<sup>st</sup> century for fertiliser, food and feed is of the utmost importance. This research was undertaken to improve the traditional method of composting by hastening the process through inoculation of cellulolytic fungi, such as species of *Aspergillus niger*, *Trichoderma reesie* and *Phynarochaeta chrysosporium*.

## **Justification**

Generally tropical soil is less fertile when compared to temperate soils. Soils in temperate zones possess an average organic matter content of 5 to 10 percent whereas tropical soils, especially those in the plains, have only 1 percent organic matter (Gaur, 1980). But nearly all of the nutrients are returned by the trees and this cycle goes on. Something should be done to the soil to improve its fertility and also to facilitate root penetration and the growth of the tree itself. Composts are known to last longer than chemical fertilisers in the soil, thus releasing nutrients in a sustained manner. The application of the compost is the right solution to land areas where the topsoil is degraded in terms of its chemical composition and fertility.

The oil palm empty fruit bunches contain a lot of nutrients useful to plants.

Normally the length of time for composting process varies from 6 to 8 months.

This time can be shortened to 1 month by inoculating the mixture with certain

microorganisms, and cutting the bunch into smaller fractions. The cutting of EFB into smaller fractions can produce a greater surface area for attacking and destroying the natural resistance of vegetation to microbial invasion.

# **Objective**

The main objective of this study is to develop an alternative technology for production of compost from oil palm empty fruit bunches (EFB), using a solid state biconversion technique, by selected microorganisms.



#### CHAPTER II

#### LITERATURE REVIEW

## **Composting and Compost**

## **Definition of Compsting**

There is a need to separate the two terms (Stentiford, 1993):

Composting: referring to the biodegradative process;

Compost: The product of a composting process, which is suitable for use in agriculture or horticulture.

Composting is a bio-oxidative process leading to a highly stabilised organic product called compost, which may then contribute directly to soil conditioning and fertility (Bertoldi, 1985). According to Gaur (1982) composting may be defined as a biochemical process in which diverse and mixed groups of microorganisms break down organic materials to a humus like substance which is similar in properties to farm yard manure. Composting is the biological decomposition of the organic constituents of wastes under controlled conditions (Golueke, 1977).

Haug (1993) stated that composting is defined as the biological decomposition and stabilisation of organic substrates under conditions which allow development of thermophilic temperatures as a result of biologically produced heat, with a final product sufficiently stable for storage and application



to land without adverse environmental effects. He also added that composting is a form of waste stabilisation, but one that requires special conditions of moisture and aeration to produce thermophilic temperatures. Composting is usually applied to solid or semi solid materials, making composting somewhat unique among the biological stabilisation processes used in sanitary and biochemical engineering.

Gaur (1987) wrote that composting is the most environmentally successful process for waste recycling by:

- a. Reducing moisture content and thereby reducing weight.
- b. Making the material of consistent size to facilitate even application.
- c. Inactivating weed seeds.
- d. Avoiding odours usually associated with manures and sewage sludge.

Mitchell (1993) reported that composting is a process which can be carried out using low or high technology, but it is basically a socio-economic process since it removes or renders harmless a waste which might otherwise result in undesirable and offensive fermentation. In low technology applications the agricultural wastes are placed in piles and occasionally turned. A succession of microbes arises from the original microflora. Readily utilisable substrates are degraded mainly to carbon dioxide and water, leaving a product containing substrates that are more difficult for microbes to degrade (especially lignocellulose) and this product is then suitable for use as a soil conditioner. These biologically stable wastes represent much less of a pollutant to the environment than the original agricultural by-products.

