

Technical University of Denmark



Viscoelastic properties of doped-ceria under reduced oxygen partial pressure

Teocoli, Francesca; Ni, De Wei; Esposito, Vincenzo

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Teocoli, F., Ni, D. W., & Esposito, V. (2014). Viscoelastic properties of doped-ceria under reduced oxygen partial pressure. Abstract from International Conference on SINTERING 2014, Dresden, Germany.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Viscoelastic properties of doped-ceria under reduced oxygen partial pressure

Francesca Teocoli, De Wei Ni, Vincenzo Esposito

Abstract

The viscoelastic properties of $\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_{1.95-\delta}$ (CGO) powder compacts are characterized during sintering and cooling under reduced oxygen partial pressure ($pO_2 < 10^{-12}$ atm) and compared with conventional sintering in air. Highly defective doped ceria in reducing conditions shows peculiar thermo-mechanical properties due to fast mass diffusion phenomena activated at low temperatures by Ce^{4+} to Ce^{3+} reduction. The combined effect of chemical reduction and temperature results in both (I) thermally activated enhanced mass diffusion mechanisms during the early stage of the sintering, and (II) consequent dramatic microstructural changes (fast grain growth and densification) which are rapidly completed during the final stage of the sintering.