

Technical University of Denmark



Mid-infrared supercontinuum generation in chalcogenide step-index fibers pumped at 2.9 and 4.5 μ m

Kubat, Irnis; Agger, Christian; Møller, Uffe Visbech; Seddon, Angela; Tang, Zhuoqi; Sujecki, Slawomir; Benson, Trevor M.; Furniss, David; Lamrini, Samir; Scholle, Karsten; Fuhrberg, Peter; Napier, Bruce; Farries, Mark; Ward, Jon; Moselund, Peter M.; Bang, Ole

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Kubat, I., Agger, C., Møller, U. V., Seddon, A., Tang, Z., Sujecki, S., ... Bang, O. (2014). Mid-infrared supercontinuum generation in chalcogenide step-index fibers pumped at 2.9 and 4.5 μ m. Abstract from Photonic Fiber and Crystal Devices: Advances in Materials and Innovations in Device Applications VIII, San Diego, CA, United States.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

The Mid-InfraRed (MIR) spectral range (2-12 μ m) contains the spectral fingerprint of many organic molecules, which can be probed nondestructively for e.g. detection of skin cancer. For this SuperContinuum (SC) laser sources are good candidates since they can have broadband bandwidths together with high spectral densities. Here we consider a MIR SC laser sources based on chalcogenide step-index fibers with exceptionally high numerical aperture of ~ 1 pumped either with Er:ZBLAN and Pr:CHALC fiber laser operating at 2.9 and 4.5 μ m, respectively, having $P_0=1$ kW, $T_0=50$ ps, $\nu_R = 4$ MHz and $P_{avg}=200$ mW.

The optical properties of fibers (dispersion, nonlinearity and confinement loss) are modeled using the finite element tools based on measured refractive indices of the core and the cladding chalcogenide compositions.

Generation of MIR SC is investigated using the Generalized Nonlinear Schrödinger Equation using actual measured fiber loss obtained using FTIR spectrometry. Pumping the fiber at 2.9 μ m and 4.5 μ m yields a SC spanning the 3-10 and 3-12.5 μ m range with around 10 and 20mW converted into the 8-10 μ m band, respectively.

Using specially designed CHALC SIF in conjunction with pulsed MIR fiber lasers at 2.9 and 4.5 μ m it is thus possible to generate a MIR SC spanning almost the entire spectral region of interest with ample power being converted into the MIR.

This research has been supported by the European Commission through the Framework Seven (FP7) project MINERVA (317803; www.minerval-project.eu).