

Technical University of Denmark



Sustainable Process Synthesis-Intensification

Babi, Deenesh Kavi; Holtbruegge, Johannes; Lutze, Philip; Górak, Andrzej; Woodley, John; Gani, Rafiqul

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Babi, D. K., Holtbruegge, J., Lutze, P., Górak, A., Woodley, J., & Gani, R. (2014). Sustainable Process Synthesis-Intensification. Poster session presented at 8th International Conference on Foundations of Computer-Aided Process Design, Cle Elum, WA, United States.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.


- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Introduction

- Industry **needs improvements** related to:
- The use of sustainable technologies/processes
 - ↓ **Capital/Operation cost**
 - The efficient use of raw materials
 - ↓ **Waster generation**
 - The environmental and life cycle issues
 - ↓ **Energy consumption**

Multi-level Framework




1st: Unit-Ops+Task scale

Problem Definition: Find intensified process design options for the production of DMC by minimizing the objective function:


$$\text{Min } F_{obj} = \left(E_i C_{Ut,i} + \frac{C_{Equip}}{t_{proj}} \right) / m_{prod}$$

Base Case Design: Consists of 5 unit operations: 1 reactor and 4 distillation columns.




Sustainability Analysis: Consists of 5 unit operations: 1 reactor and 4 distillation columns.

Process hot-spots & targets



Economic, Sustainability, LCA:


- ↑ Utility cost ↑ Energy Demand
- ↑ Energy Demand ↑ EWC in CP
- ↑ Energy Demand ↑ CO2 footprint



Targets (e.g.):

- Reduce energy demand
- Reduce number of Unit-Ops
- Explore the possibility for using "hybrid" Unit-Ops
- Improve Sustainability & LCA factors

Concepts



2nd : Tasks+Phenomena Scale

Process Analysis (e.g.):

Thermodynamic insights

Identification of PBBs

Task	Component	PBBs
R-Task	PCa+MeOH	M,R,C
S-Task-1	PG _{LK} +PCa _{HK}	M,2phM,H,C,PC,PT,PS by VL
S-Task-2	MeOH _{LK} +PG _{HK}	M,2phM,H,C,PC,PT,PS by VL
S-Task-3	MeOH _{LK} +DMC _{HK}	M,2phM,H,C,PC,PT,PS by VL

LK-Light key
HK-Heavy key


Excerpt of properties used for the generation of the binary ratio matrix

	f _i	T _b	RG	SolPar	VM
MeOH/PC	1.52	2.2	1.13	2.1	
MeOH/DMC	1.08	2.09	1.46	2.09	
MeOH/PG	1.36	2.03	1.1	1.82	
PC/DMC	1.42	1.05	1.3	1.01	
PC/PG	1.12	1.08	1.12	1.16	
DMC/PG	1.27	1.03	1.46	1.15	


T_b-normal boiling point
RG-radius of gyration
SolPar-Solubility parameter
VM-molar volume

Hints separation based on molecular size possible

SPBs




Basic Structures




Note: The objective is to convert input (PCa + MeOH) to output (DMC + PG). One basic structure (unless combined) will not achieve this

Note: This basic structure fulfills two S-tasks

Task fulfilled



Flowsheet alternative



3rd: Comparison

