

Technical University of Denmark



## Simulation Tool for GNSS Ocean Surface Reflections

**Høeg, Per; von Benzon, Hans-Henrik; Durgonics, Tibor**

*Published in:*  
Geophysical Research Abstracts

*Publication date:*  
2015

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Høeg, P., von Benzon, H-H., & Durgonics, T. (2015). Simulation Tool for GNSS Ocean Surface Reflections. Geophysical Research Abstracts, 17.

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



## **Simulation Tool for GNSS Ocean Surface Reflections**

Per Høeg, Hans-Henrik von Benzon, and Tibor Durgonics

Technical University of Denmark, DTU Space, Geodesy, Kongens Lyngby, Denmark (hoeg@space.dtu.dk)

GNSS coherent and incoherent reflected signals have the potential of deriving large scale parameters of ocean surfaces, as barotropic variability, eddy currents and fronts, Rossby waves, coastal upwelling, mean ocean surface heights, and patterns of the general ocean circulation. In the reflection zone the measurements may derive parameters as sea surface roughness, winds, waves, heights and tilts from the spectral measurements. Previous measurements from the top of mountains and airplanes have shown such results leading.

The coming satellite missions, CYGNSS, COSMIC-2, and GERS on the International Space Station, are focusing on GNSS ocean reflection measurements. Thus, simulation studies highlighting the assumptions for the data retrievals and the precision and the accuracy of such measurements are of interest for assessing the observational method.

The theory of propagation of microwaves in the atmosphere is well established, and methods for propagation modeling range from ray tracing to numerical solutions to the wave equation. Besides ray tracing there are propagation methods that use mode theory and a finite difference solution to the parabolic equation. The presented propagator is based on the solution of the parabolic equation. The parabolic equation in our simulator is solved using the split-step sine transformation. The Earth's surface is modeled with the use of an impedance model. The value of the Earth impedance is given as a function of the range along the surface of the Earth. This impedance concept gives an accurate lower boundary condition in the determination of the electromagnetic field, and makes it possible to simulate reflections and the effects of transitions between different mediums. A semi-isotropic Philips spectrum is used to represent the air-sea interaction.

Simulated GPS ocean surface reflections will be presented and discussed based on different ocean characteristics. The spectra of the simulated surface reflections will be analyzed and compared with existing observations.

The analysis of both the simulated surface reflection signals and the measured reflection signals will reveal spectral structures of the reflected signals leading to the extraction of sea surface roughness, ocean wave heights, surface wind speed and direction.