Technical University of Denmark



Topology Optimisation of Thermomechanical Functionally Graded Materials and Material Interfaces

Alexandersen, Joe; Lazarov, Boyan Stefanov; Sigmund, Ole

Publication date: 2014

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA):

Alexandersen, J., Lazarov, B. S., & Sigmund, O. (2014). Topology Optimisation of Thermomechanical Functionally Graded Materials and Material Interfaces. Abstract from 13th International Symposium on Multiscale, Multifunctional and Functionally Graded Materials, São Paulo, Brazil.

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- . You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Topology Optimisation of Thermomechanical Functionally Graded Materials and Material Interfaces

Joe Alexandersen¹, Boyan S. Lazarov², Ole Sigmund³

Department of Mechanical Engineering, Technical University of Denmark ¹joealex@mek.dtu.dk, ²bsl@mek.dtu.dk, ³sigmund@mek.dtu.dk

Abstract

The work applies topology optimisation to the design of functionally graded materials (FGMs) and material interfaces for thermomechanical problems. It is well known, that the mismatch in stiffness and thermal expansion coefficient of two materials give rise to high stresses at the interface. One way to alleviate this is to use the concept of FGMs [1]. The FGMs are here designed using topology optimisation, which is a material distribution method used for finding an optimal structural layout for a given problem subject to design constraints [2]. Density-based multi-material topology optimisation is utilised to optimise the material composition and distribution in order to achieve a high thermal throughput, while maintaining an acceptable stress level.

The work considers the design of local material microstructures with the objective of optimising the macrostructural response. In contrast to homogenisation techniques, connectivity among the local microstructural cells is ensured by analysing the full macrostructure with all microstructural details being fully-resolved by the finite element method. This is computationally challenging and the work will therefore explore the use of a coarse-scale spectral preconditioner [3] to the coupled thermomechanical problems.

The problems investigated are inspired by those of plasma facing components (PFCs), thermal barrier coatings (TBCs) and thermal protection systems (TPSs).

References

- [1] F Erdogan, Fracture mechanics of functionally graded materials, MRS Bulletin, 20 (01), 43-44 (1995)
- [2] MP Bendsøe, O Sigmund, Topology Optimization: Theory, Methods and Applications. Springer (2003)
- [3] BS Lazarov, Topology optimization using multiscale finite element method for high-contrast media, in: Large-Scale Scientific Computing, Lecture Notes in Computer Science, Springer (2014), in print.

Keywords: topology optimisation, thermomechanical, functionally graded materials, material interfaces, stress constraints

Presenting and corresponding author: Joe Alexandersen