Technical University of Denmark



Synthesis of biorefinery networks using a superstructure optimization based approach

Bertran, Maria-Ona; Anaya-Reza, Omar; Lopez-Arenas, Maria Teresa; Woodley, John; Gani, Rafiqul

Publication date: 2015

Document Version Peer reviewed version

Link back to DTU Orbit

Citation (APA):

Bertran, M-O., Anaya-Reza, O., Lopez-Arenas, M. T., Woodley, J., & Gani, R. (2015). Synthesis of biorefinery networks using a superstructure optimization based approach. Abstract from 10th European Congress of Chemical Engineering, Nice, France.

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Synthesis of biorefinery networks using a superstructure optimization based approach

Maria-Ona Bertran¹, Omar Anaya-Reza², Maria Teresa Lopez-Arenas³, John Woodley¹, Rafiqul Gani¹

¹ CAPEC-PROCESS, Department of Chemical and Biochemical Engineering, Technical University of Denmark, Søltofts Plads, Building 229, DK-2800 Kgs. Lyngby, Denmark

² Posgrado en Energía y Medio Ambiente, Universidad Autónoma Metropolitana-Iztapalapa, Av. San Rafael Atlixco 186, 09430 Mexico, D.F., Mexico

³ Departamento de Procesos y Tecnología, Universidad Autónoma Metropolitana-Cuajimalpa, Av. Vasco de Quiroga 4871, 05348 Mexico, D.F., Mexico

Petroleum is currently the primary raw material for the production of fuels and chemicals. Consequently, our society is highly dependent on fossil non-renewable resources. However, renewable raw materials are recently receiving increasing interest for the production of chemicals and fuels, so a new industrial system based on biomass, an inexpensive, abundant and renewable raw material, is being established with sustainability as the main driving force [1]. The processing facilities for the production of multiple products (including biofuels and chemicals) from biomass are referred as biorefineries [2].

The optimal synthesis of biorefinery networks problem is defined as: given a set of biomass derived feedstock and a set of desired final products and specifications, determine a flexible, sustainable and innovative processing network with the targets of minimum cost and sustainable development taking into account the available technologies, geographical location, future technological developments and global market changes.

The problem of optimal design of biorefinery networks is solved in this work through three different stages: (i) synthesis stage, (ii) design stage, and (iii) innovation stage. At the synthesis stage, the considered alternatives are represented in a superstructure, from which a mixed-integer linear or nonlinear programming (MILP or MINLP) problem is derived and solved in order to find the optimal processing network for a pre-defined objective function. Next, at the design stage, the selected processing network is simulated and analyzed and targets for improvement are identified. Finally, a more sustainable design is achieved at the innovation stage by generating innovative solutions that satisfy the targets from the design stage.

This work is concerned with the first stage: the synthesis stage. Various biorefinery processing alternatives are represented in a superstructure and the associated data is collected and stored in a database. Once a specific biorefinery synthesis problem is formulated, the superstructure is reduced in order to include only the relevant alternatives. The superstructure is reduced based on constraints from the problem formulation, such as location or raw material. The reduced superstructure is then represented using mathematical models - the modelling approach by Quaglia et al. [3] is used - and solved to find the optimal network. The applicability of the proposed approach is shown through a practical case study for the production of valuable products (i.e. lysine and lactic acid) from sugarcane molasses; these alternatives are considered with respect to availability and demands in Mexico [4].

References

[1] M. Hechinger, A. Voll, W. Marquardt, Comput. Chem. Eng. 34 (2010) 1909-1918.

- [2] B. Kamm, M. Kamm, Appl. Microbiol. Biotechnol. 64 (2) (2004) 137-145.
- [3] A. Quaglia, B. Sarup, G. Sin, R. Gani, Comput. Chem. Eng. 38 (2012), 213-223.
- [4] T. Lopez-Arenas, O. Anaya-Reza, R. Quintero, M. Sales-Cruz, Comp. Aided Chem. Eng. 33 (2014) 1723-1728.

[word count: 374 words]

Authors of the abstract come from :: University or Research Institution

Highlight 1: Database of biorefinery processing alternatives.

Highlight 2: Optimal design of biorefinery networks using superstructure optimization.

Highlight 3: Production of valuable products from molasses (Mexico).

Keywords: Biorefinery, Process modelling, Process system engineering, Sustainibility, Waste valorization Topic: Computer-aided Engineering/Process systems engineering/ECCE10/Optimal design