

Technical University of Denmark



## Optimizing basin-scale coupled water quantity and water quality management with stochastic dynamic programming

**Davidson, Claus; Liu, Suxia; Mo, Xingguo; Engelund Holm, Peter; Trapp, Stefan; Rosbjerg, Dan; Bauer-Gottwein, Peter**

*Published in:*  
Geophysical Research Abstracts

*Publication date:*  
2015

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Davidson, C., Liu, S., Mo, X., Engelund Holm, P., Trapp, S., Rosbjerg, D., & Bauer-Gottwein, P. (2015). Optimizing basin-scale coupled water quantity and water quality management with stochastic dynamic programming. *Geophysical Research Abstracts*, 17, [EGU2015-6457].

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



## **Optimizing basin-scale coupled water quantity and water quality man-agement with stochastic dynamic programming**

Claus Davidsen (1,2,3), Suxia Liu (2), Xingguo Mo (2), Peter Engelund Holm (3,4), Stefan Trapp (1), Dan Rosbjerg (1), and Peter Bauer-Gottwein (1)

(1) Technical University of Denmark, Department of Environmental Engineering, Kongens Lyngby, Denmark (clad@env.dtu.dk), (2) Key Laboratory of Water Cycle and Related Land Surface Processes, Institute of Geographic Sciences and Natural Resources Research, Chinese Academy of Sciences, Beijing, China, (3) Sino-Danish Center for Education and Research (SDC), Aarhus C, Denmark, (4) Department of Plant and Environmental Sciences, Faculty of Science, University of Copenhagen, Frederiksberg, Denmark

Few studies address water quality in hydro-economic models, which often focus primarily on optimal allocation of water quantities. Water quality and water quantity are closely coupled, and optimal management with focus solely on either quantity or quality may cause large costs in terms of the other component. In this study, we couple water quality and water quantity in a joint hydro-economic catchment-scale optimization problem. Stochastic dynamic programming (SDP) is used to minimize the basin-wide total costs arising from water allocation, water curtailment and water treatment.

The simple water quality module can handle conservative pollutants, first order depletion and non-linear reactions. For demonstration purposes, we model pollutant releases as biochemical oxygen demand (BOD) and use the Streeter-Phelps equation for oxygen deficit to compute the resulting minimum dissolved oxygen concentrations. Inelastic water demands, fixed water allocation curtailment costs and fixed wastewater treatment costs (before and after use) are estimated for the water users (agriculture, industry and domestic). If the BOD concentration exceeds a given user pollution threshold, the user will need to pay for pre-treatment of the water before use. Similarly, treatment of the return flow can reduce the BOD load to the river. A traditional SDP approach is used to solve one-step-ahead sub-problems for all combinations of discrete reservoir storage, Markov Chain inflow classes and monthly time steps. Pollution concentration nodes are introduced for each user group and untreated return flow from the users contribute to increased BOD concentrations in the river. The pollutant concentrations in each node depend on multiple decision variables (allocation and wastewater treatment) rendering the objective function non-linear. Therefore, the pollution concentration decisions are outsourced to a genetic algorithm, which calls a linear program to determine the remainder of the decision variables. This hybrid formulation keeps the optimization problem computationally feasible and represents a flexible and customizable method.

The method has been applied to the Ziya River basin, an economic hotspot located on the North China Plain in Northern China. The basin is subject to severe water scarcity, and the rivers are heavily polluted with wastewater and nutrients from diffuse sources. The coupled hydro-economic optimization model can be used to assess costs of meeting additional constraints such as minimum water quality or to economically prioritize investments in waste water treatment facilities based on economic criteria.