

Technical University of Denmark



## Landfill gas generation and emission at danish waste disposal sites receiving waste with a low organic waste content

**Mou, Zishen; Scheutz, Charlotte; Kjeldsen, Peter**

*Published in:*

Proceedings Sardinia 2015, Fifteenth International Waste Management and Landfill Symposium

*Publication date:*

2015

*Document Version*

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*

Mou, Z., Scheutz, C., & Kjeldsen, P. (2015). Landfill gas generation and emission at danish waste disposal sites receiving waste with a low organic waste content. In Proceedings Sardinia 2015, Fifteenth International Waste Management and Landfill Symposium Cagliari, Italy: CISA Publisher.

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# LANDFILL GAS GENERATION AND EMISSION AT DANISH WASTE DISPOSAL SITES RECEIVING WASTE WITH A LOW ORGANIC WASTE CONTENT

Z. MOU, C. SCHEUTZ AND P. KJELDTSEN

*Department of Environmental Engineering, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark.*

**SUMMARY:** The landfill gas (LFG) generation from four Danish landfills was estimated using three first-order-decay (FOD) models; the LandGEM model (developed by the US EPA), the IPCC (developed by the Intergovernmental Panel on Climate Change) and the Afvalzorg model (developed by a Dutch company). The last two models are multi-phase models, which defines waste fractions into traditional MSW and low-organic waste categories, respectively. Both the LandGEM and the IPCC model estimated significantly larger methane (CH<sub>4</sub>) generation in comparison to the Afvalzorg model. The Afvalzorg model could better show the influence of not only the total disposed waste amount, but also various waste categories, and was found more suitable to estimate LFG generation from landfills receiving low-organic waste. Four major waste categories currently being disposed at Danish landfills (mixed bulky, shredder, dewatered sludge and street cleansing waste) and temporarily stored combustible waste were sampled and characterized in terms of TS, VS, TC, TOC, and biochemical methane potential (BMP). Decay rates (k values), were determined by conducting anaerobic degradation experiments and applying FOD equations to the experimental results. The LFG generation from four Danish landfills was estimated by the Afvalzorg model using the experimentally based BMP and k values and compared to whole landfill emission rates measured by applying a tracer gas dispersion method. The results showed that the revised modelled LFG generation rates were in good agreement with field emission measurements, indicating that the revised model with site-specific data could provide a practical and accurate estimation of LFG emissions.

## 1. INTRODUCTION AND OBJECTIVE

Waste degradation at landfills is one of the major anthropogenic sources of methane (CH<sub>4</sub>) generation and emissions in the world (Bogner et al., 2008). According to the EU Council Directive 1999/31/EC on the landfilling of waste, landfilling in Europe is limited to inert materials, which are not biodegradable or combustible (waste not containing significant fractions of organic matter) (EU, 1999; 2002). Consequently, more and more EU member states (for example the Netherlands as of 1996, Denmark as of 1997, and Germany as of 2005) have banned landfilling of organic waste. Although most currently disposed waste has low-organic contents, previous studies have shown significant CH<sub>4</sub> emissions at Danish landfills (Scheutz et al., 2011).

According to the European Pollutants Release and Transfer Registers (E-PRTR) Regulation 166/2006/EC, operators of landfills with a total capacity of 25,000 ton or receiving more than 10 ton per day must quantify and report their pollutant emissions to the general public and their national government (CEC, 2006). Therefore it is important for landfill operators to have a reliable guideline to measure, calculate and estimate landfill gas (LFG) emissions for the E-PRTR reporting. Due to difficulties in precisely monitoring a whole site's CH<sub>4</sub> emissions, first order decay (FOD) landfill gas generation models are currently widely used to estimate CH<sub>4</sub> emissions from landfills. FOD models are recommended by both researchers and state regulators for estimating CH<sub>4</sub> generation from waste degradation. Most of the models are based on two primary parameters; a biochemical CH<sub>4</sub> potential (BMP) and an FOD rate constant (k) of the landfilled material. However, the BMP and FOD default values provided by most models are based on traditional municipal solid waste (MSW) fractions and the models are therefore not appropriate for modelling gas generation from landfills receiving waste with a low organic content.

The overall objective of this research project was to study CH<sub>4</sub> generation from low-organic waste disposed at Danish landfills and to provide new guidelines for estimating CH<sub>4</sub> emission from modern landfills to report to the E-PRTR. In this research, four categories of waste (street cleansing, mixed bulky, shredder, and sludge waste) with a low-organic content and temporarily stored combustible waste were sampled from four Danish landfills and characterized in the lab (Mou et al., 2014). BMP and k values of all sampled waste were quantified (Mou et al., 2015a). By applying site-specific data, CH<sub>4</sub> generation and emission estimated by original and revised FOD models were evaluated and compared (Mou et al., 2015b). Field CH<sub>4</sub> emission measurements using a tracer dispersion method of four Danish landfills were used to test the applicability of the revised Afvalzorg model. The oral presentation and proceeding paper provide an overview of the conclusions of a four year PhD project conducted at Technical University of Denmark (Mou, 2014).

## **2. COMPARISON OF LANDFILL GAS GENERATION MODELS**

This study reviewed several currently used FOD LFG models in terms of their default parameter values and defined waste categories. Depending on whether various k values were defined for different waste categories, there are two kinds of models: multi- and single-phase FOD models. The single-phase model has no function for distinguishing various decay rates between different waste categories. The multiphase model required waste amount by fractions as input data. Three FOD models were selected to estimate LFG generation from Danish landfills. The single-phase LandGEM model was developed by the US EPA and was intended to model the LFG generation from traditional MSW disposal sites with relative homogeneous waste fractions. The IPCC (developed by the Intergovernmental Panel on Climate Change) and the Afvalzorg (developed by a Dutch company) models are multi-phase models, which define waste fractions into traditional MSW and low-organic waste categories, respectively. For running the models, actual waste data from four Danish landfills (AV Miljø, Audebo, Glatved, and Odense) were used as input data. Most disposed waste at Danish landfills had insignificant or very low organic fractions. Original waste data were translated into various waste fractions defined in the multi-phase models. By applying default values for the BMPs and k values, the annual and normalized CH<sub>4</sub> generation (kg CH<sub>4</sub> ton<sup>-1</sup> waste) from the beginning of disposal until year 2020 and year 2100 at the four landfills were estimated by the three FOD models (using both default and

revised parameter values). Figure 1 shows the annual CH<sub>4</sub> generation rates as functions of time at the four landfills. In comparison to the multi-phase model outcomes, the LandGEM model estimated significantly larger CH<sub>4</sub> generation because it defined only one relatively high BMP value (122 CH<sub>4</sub> ton<sup>-1</sup> waste, wet weight) for low-organic waste. The IPCC model estimated only 25 to 33% of the annual CH<sub>4</sub> generation estimated by the LandGEM model until year 2020. The Afvalzorg model estimated only approximately 10% of the annual CH<sub>4</sub> generation estimated by the LandGEM model. Moreover, in comparison to the IPCC model, the Afvalzorg model could better show the influence of not only the total disposed waste amount, but also various waste categories. Therefore, the Afvalzorg model was found more suitable to estimate LFG generation from landfills receiving low-organic waste.




Figure 1. Annual CH<sub>4</sub> generation rates as functions of time at the (a) AV Miljø; (b) Audebo; (c) Glatved; and d) Odense landfill, estimated by the original Afvalzorg, IPCC and LandGEM models with default parameter values (the right Y axis only applies to the LandGEM curve in all four figures) (Mou et al., 2014).

### **3. DETERMINATION OF BMP AND k VALUES**

To further calibrate the BMPs and k values of Danish waste fractions, four major disposed waste categories (mixed bulky, shredder, dewatered sludge and street cleansing waste) and temporarily stored combustible waste were sampled and characterized in terms of TS, VS, TC, and TOC. In general, waste samples showed lower TOC contents than traditional MSW fractions. The same category of waste samples from different landfills showed similar results. By incubation experiments at 55 °C over 77 days, the BMPs of all waste samples were determined. As main fractions at Danish landfills, mixed bulky and shredder waste had similar BMPs, which was in the range of 5.4-9.1 kg CH<sub>4</sub> ton<sup>-1</sup> waste (wet weight) on average. The sludge waste and temporarily stored combustible waste showed BMP values of 51.8-69.6 and 106.6-117.3 kg CH<sub>4</sub> ton<sup>-1</sup> waste on average, respectively. For determining k values, anaerobic degradation experiments were set up in duplicate and incubated for 405 days, during which the cumulative CH<sub>4</sub> generation was continuously monitored. Applying FOD equations to the experimental results, k values of all waste samples were determined. Likewise, similar waste categories obtained from different Danish landfills showed similar results. Sludge waste had the highest k values, which were in the range 0.156-0.189 yr<sup>-1</sup>. The combustible and street cleansing waste showed k values of 0.023-0.027 yr<sup>-1</sup> and 0.073-0.083 yr<sup>-1</sup>, respectively. The lowest k values were obtained for mixed bulky and shredder wastes ranging from 0.013 to 0.017 yr<sup>-1</sup>. Most low-organic waste samples showed lower BMPs and k values in comparison to the default numeric values in current FOD models.

### **4. METHANE GENERATION AND EMISSION RATES**

By using lab-determined results, the Afvalzorg model was revised and estimated smaller cumulative CH<sub>4</sub> generation results in comparison to running the model with default values (Figure 2). Based on CH<sub>4</sub> recovery data (provided by the landfill operators) and estimated CH<sub>4</sub> oxidation factor of 10%, fugitive CH<sub>4</sub> emissions from whole-sites and a specific cell for shredder waste at the Odense landfill were aggregated based on the revised Afvalzorg model outcomes. Former studies have established a tracer dispersion method as a reliable and accurate approach for quantifying whole-site fugitive landfill CH<sub>4</sub> emissions, which were applied at the same landfills (Mønster et al, 2014). Aggregated CH<sub>4</sub> emissions were in good agreement with field measurements (Figure 3), indicating that the revised FOD model with site-specific data could provide a practical and accurate estimation for LFG emissions. Additionally, by using only one k value for each waste category instead of identifying various degradable fractions, the Afvalzorg model could be revised as a less complicated and more practical model for the Danish scenario.




Figure 2. CH<sub>4</sub> generation rates as functions of time estimated by the revised Afvalzorg model using site-specific waste input data (both Y axes apply to all curves). (Mou et al., 2014).




Figure 3. Comparison of aggregated fugitive CH<sub>4</sub> emissions (kg hr<sup>-1</sup>) and measured wholesite CH<sub>4</sub> emissions at four Danish landfills and one specific waste cell for shredder waste at the Odense landfill (Mou et al., 2014).

## REFERENCES

- Bogner, J., Pipatti, R., Hashimoto, S., Diaz, C., Mareckova, K., Diaz, L., Kjeldsen, P.; Monni, S., Faaij, A.; Sutamihardja, R. T. M., et al. (2008): Mitigation of global greenhouse gas emissions from waste: conclusions and strategies from the Intergovernmental Panel on Climate Change (IPCC) Fourth Assessment Report. Working Group III (Mitigation). *Waste Management & Research*, 26, 11–32.
- CEC (Council of the European Communities), 2006. Regulation of the European Parliament and of the Council of 18 January 2006 concerning the establishment of a European Pollutant Release and Transfer Register and amending Council Directives 91/689/EEC and 96/61/EC (No 166/2006), Brussels, Belgium.
- Mou, Z.S., Scheutz, C., Kjeldsen, P. (2015b): Evaluation and application of site-specific data to revise the first-order decay model for estimating landfill gas generation and emissions at Danish landfills. *Journal of the Air and Waste Management Association*, 65, (6), 686-698.
- Mou, Z.S., Scheutz, C., Kjeldsen, P. (2015a): Evaluating the methane generation rate constant (k value) of low-organic waste at Danish landfills. *Waste Management*, 35, 170-176.
- Mou, Z.S., Scheutz, C., Kjeldsen, P. (2014): Evaluating the biochemical methane potential (BMP) of low-organic waste at Danish landfills. *Waste Management*, 34, 11, 2251-2259.
- Mou, Z.S. (2014): Landfill gas generation and emission at Danish waste disposal sites receiving low-organic waste. PhD Thesis, Oct. 2014. Kgs. Lyngby, Department of Environmental Engineering, Technical University of Denmark.
- Mønster, J.G., Samuelsson, J., Kjeldsen, P., Rella, C.W., Scheutz, C. (2014): Quantifying methane emission from fugitive sources by combining tracer release and downwind measurements – a sensitivity analysis based on multiple field surveys. *Waste Management*, 34 (8), 1416-1428.
- Scheutz, C., Fredenslund, A.M., Nedenskov, J., Samuelsson, J., Kjeldsen, P. (2011): Gas production, composition and emission at a modern disposal site receiving waste with a low-organic content. *Waste Management* 31, 946-955.
- EU (European Union), 1999. Council Directive 1999/31/EC of 26 April 1999 on the landfill of waste. Available from <<http://eurlex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:1999:182:0001:0019:EN:PDF>> (Accessed August 2015).
- EU, 2002. Council Decision of 19 December 2002 establishing criteria and procedures for the acceptance of waste at landfills pursuant to Article 16 of and Annex II to Directive 1999/31/EC. Available from <http://eurlex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2003:011:0027:0049:EN:PDF>. (Accessed August 2015).