Optimal Traffic Allocation for Multi-Stream Aggregation in Heterogeneous Networks - DTU Orbit (08/11/2017)

Optimal Traffic Allocation for Multi-Stream Aggregation in Heterogeneous Networks

This paper investigates an optimal traffic rate allocation method for multi-stream aggregation over heterogeneous networks that deals with effective integration of two or more heterogeneous links for improved data throughput and enhanced quality of experience. The heterogeneity and the dynamic nature of radio access networks are considered as important factors for performance improvement by multi-stream aggregation. Therefore, in our model, the networks are represented by different queueing systems in order to indicate networks with opposite quality of service provisioning, capacity and delay variations. Furthermore, services with different traffic characteristics in terms of quality of service requirements are considered. The simulation results show the advantages of our scheme with respect to efficient increase in data rate and delay performance compared to traditional schemes.

General information

State: Published Organisations: Department of Photonics Engineering, Networks Technology and Service Platforms Authors: Popovska Avramova, A. (Intern), Iversen, V. B. (Intern) Number of pages: 6 Publication date: 2015

Host publication information

Title of host publication: Proceedings of IEEE GLOBECOM'15 Publisher: IEEE Main Research Area: Technical/natural sciences Conference: IEEE GLOBECOM 2015, San Diego, California, United States, 06/12/2015 - 06/12/2015 Multiple stream aggregation, Traffic allocation, Delay, Heterogeneous networks, Queueing models DOIs: 10.1109/GLOCOMW.2015.7414029

Source: PublicationPreSubmission Source-ID: 118855056

Publication: Research - peer-review > Article in proceedings - Annual report year: 2015