

Technical University of Denmark



## Life Cycle Assessment of Injection Molding Inserts: Additively Manufactured, in Brass, and in Steel

Mischkot, Michael; Hofstätter, Thomas; Bey, Niki; Lunzer, Andreas

*Publication date:*  
2015

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Mischkot, M., Hofstätter, T., Bey, N., & Lunzer, A. (2015). Life Cycle Assessment of Injection Molding Inserts: Additively Manufactured, in Brass, and in Steel. Poster session presented at DTU Sustain Conference 2015, Lyngby, Denmark.

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Life Cycle Assessment Injection Mold Inserts: Additively Manufactured, in Brass, and in Steel

Michael Mischkot\*<sup>1</sup>, Thomas Hofstätter<sup>1</sup>, Niki Bey<sup>2</sup>, David Bue Pedersen<sup>1</sup>, Hans Nørgaard Hansen<sup>1</sup>, Michael Z. Hauschild<sup>2</sup>

1: DTU Mechanical Engineering;

2: DTU Management Engineering

\*Corresponding author email: [micmi@mek.dtu.dk](mailto:micmi@mek.dtu.dk)

3D printing applied to Manufacturing Engineering is known as Additive Manufacturing (AM) Polymer AM can be used to produce soft tooling inserts for injection molding. As life time of such inserts is significantly shorter than the life time of traditional brass, aluminum, or steel inserts, soft inserts are mainly used for pilot production and prototyping. The short lived nature of these molds renders little allowance for run-in errors, and as such, a Life Cycle Assessment study has been carried out in order to provide for the maximum yield throughout the development and pilot phase. Spite a short life-span, and depending on the insert geometry, AM inserts can be made cheaper and quicker than traditional pre-production tooling, which is particularly advantageous for pilot production and small production sizes.

In this research, Life Cycle Assessment (LCA) is used to compare the environmental impact Soft Tooling by AM to two traditional methods for the manufacture of inserts for injection molds during the pre-production phase:

- 3D printing of a photopolymer using Digital Light Processing (DLP)
- Milling of a brass insert
- Milling of a steel insert

References:

[1] Curran M A, Life Cycle Assessment Handbook – A Guide for Environmentally Sustainable Products, Scrivener Publishing LLC 2012, ISBN 978-1-118-09972-8

[2] Gibson I, Rosen D, and Stucker B, Additive Manufacturing Technologies – 3D Printing, Rapid Prototyping, and Direct Digital Manufacturing, Springer New York 2015, ISBN 978-1-4939-2112-6

[3] Wohlers Report 2015 – 3D Printing and Additive Manufacturing State of the Industry Annual Worldwide Progress Report, Wohlers Associates, Fort Collins Colorado

[4] Kreiger M, and Pearce J M, Environmental life cycle analysis of distributed three-dimensional printing and conventional manufacturing of polymer products, ACS Sustainable Chem. Eng. 2013, 1, 1511–1519, [dx.doi.org/10.1021/sc400093k](https://doi.org/10.1021/sc400093k)