

Technical University of Denmark



LAR-potentiale: a new planning tool to support sustainable stormwater management

Lerer, Sara Maria; Sørup, Hjalte Jomo Danielsen; Arnbjerg-Nielsen, Karsten; Mikkelsen, Peter Steen

Published in:

Book of Abstracts. DTU's Sustain Conference 2015

Publication date:

2015

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Lerer, S. M., Sørup, H. J. D., Arnbjerg-Nielsen, K., & Mikkelsen, P. S. (2015). LAR-potentiale: a new planning tool to support sustainable stormwater management. In Book of Abstracts. DTU's Sustain Conference 2015 [L-10] Lyngby: Technical University of Denmark (DTU).

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LAR-potentiale: a new planning tool to support sustainable stormwater management

Sara Maria Lerer*¹, Hjalte Jomo Danielsen Sørup¹², Karsten Arnbjerg-Nielsen¹² and Peter Steen Mikkelsen¹³

1: DTU Environment; 2: DTU GDSI, 3: Water DTU

*Corresponding author email: smrl@env.dtu.dk

Stormwater management systems are essential for creating and maintaining safe and healthy cities. Current challenges to these systems include climate change, growth and densification of cities, and an increase in demands for sustainability and livability. Among the suggested solutions is a suite of decentralized stormwater control measures known as e.g. Water Sensitive Urban Design (WSUD), which aim at improving the sustainability of stormwater management by applying a more holistic and multifunctional approach. Unlike traditional stormwater planning, WSUD must bring together drainage engineers with city planners, architects and other professionals. We have developed a new tool to support this interdisciplinary collaboration.

The tool facilitates a fast and simple quantification of the core hydrologic effects of a suggested WSUD retrofitting plan. We use the following two key indicators to represent the hydrologic effects of WSUD: 1) the runoff volume/return period at the single event scale, and 2) the water balance impact at the annual scale. The significance of the first indicator is illustrated using the “Three Points Approach”, which has a proven ability to improve conversations about how well different drainage solutions meet expectations. The significance of the second indicator is illustrated against typical annual water budgets, emphasizing the potential for restoring a more natural hydrological cycle and managing pollution on site.

The tool includes simple methods for assessing these effects for a number of different WSUD techniques including permeable paving, rain gardens and detention basins. Local constraints, such as the available area for collection of rainwater and the soils infiltration capacity, are taken into account. We will present the tool using an example application on a case study in Copenhagen. Danish cities are investing large amounts of resources in urban infrastructure renewal, and actors are eagerly waiting for tools like this to more effectively prioritize their spending.




Figure 1: Example outputs. To the left: Key indicator 1 – volume of runoff/return period at the single event scale. To the right: Key indicator 2 - annual water budget before and after.