Distribution Line Parameter Estimation Under Consideration of Measurement Tolerances - DTU Orbit (08/11/2017)

Distribution Line Parameter Estimation Under Consideration of Measurement Tolerances

State estimation and control approaches in electric distribution grids rely on precise electric models that may be inaccurate. This work presents a novel method of estimating distribution line parameters using only root mean square voltage and power measurements under consideration of measurement tolerances, noise, and asynchronous timestamps. A measurement tolerance compensation model and an alternative representation of the power flow equations without voltage phase angles are introduced. The line parameters are obtained using numeric methods. The simulation demonstrates in case of the series conductance that the absolute compensated error is -1.05% and -1.07% for both representations, as opposed to the expected uncompensated error of -79.68%. Identification of a laboratory distribution line using real measurement data grid yields a deviation of 6.75% and 4.00%, respectively, from a calculation based on the manufacturer's cable specifications and estimated line length. The transformed power flow equations deliver similar results despite the reduced problem complexity.

General information

State: Published

Organisations: Department of Electrical Engineering, Center for Electric Power and Energy, Energy system operation and management, Department of Informatics and Mathematical Modeling, Risø National Laboratory for Sustainable Energy, Austrian Institute of Technology

Authors: Prostejovsky, A. (Intern), Gehrke, O. (Intern), Kosek, A. M. (Intern), Strasser, T. (Ekstern), Bindner, H. W. (Intern) Pages: 726-735

Publication date: 2016 Main Research Area: Technical/natural sciences

Publication information

Journal: I E E E Transactions on Industrial Informatics Volume: 12 Issue number: 2 ISSN (Print): 1551-3203 Ratings: BFI (2017): BFI-level 1 Web of Science (2017): Indexed Yes BFI (2016): BFI-level 1 Scopus rating (2016): CiteScore 8.62 SJR 2.446 SNIP 3.339 Web of Science (2016): Indexed yes BFI (2015): BFI-level 1 Scopus rating (2015): SJR 2.557 SNIP 3.331 CiteScore 7.57 BFI (2014): BFI-level 1 Scopus rating (2014): SJR 2.298 SNIP 3.992 CiteScore 8.17 Web of Science (2014): Indexed yes BFI (2013): BFI-level 1 Scopus rating (2013): SJR 2.204 SNIP 4.664 CiteScore 9.38 ISI indexed (2013): ISI indexed yes Web of Science (2013): Indexed yes BFI (2012): BFI-level 1 Scopus rating (2012): SJR 1.038 SNIP 3.259 CiteScore 5.56 ISI indexed (2012): ISI indexed yes Web of Science (2012): Indexed yes BFI (2011): BFI-level 1 Scopus rating (2011): SJR 0.875 SNIP 2.514 CiteScore 4.08 ISI indexed (2011): ISI indexed yes Web of Science (2011): Indexed yes BFI (2010): BFI-level 1 Scopus rating (2010): SJR 0.615 SNIP 2.072 BFI (2009): BFI-level 1 Scopus rating (2009): SJR 0.99 SNIP 2.3 BFI (2008): BFI-level 1 Scopus rating (2008): SJR 1.012 SNIP 2.59

Scopus rating (2007): SJR 0.803 SNIP 1.734 Scopus rating (2006): SJR 1.433 SNIP 1.738 Original language: English Grid topology, Measurement uncertainty, Monitoring, Parameter estimation, Parameter uncertainty, Smart grids (SGs), State estimation (SE) DOIs: 10.1109/TII.2016.2530620 Source: FindIt Source-ID: 277405940 Publication: Research - peer-review > Journal article – Annual report year: 2016