Elsevier Editorial System(tm) for Journal of Chromatography A Manuscript Draft

Manuscript Number: JCA-10-2200R1

Title: Solid-phase extraction using molecularly imprinted polymer for selective extraction of natural and synthetic estrogens from aqueous samples

Article Type: ISC 2010

Keywords: Estrogens; molecularly imprinted polymers; ultra high performance liquid chromatography; mass spectrometry; water samples.

Corresponding Author: Dr Paolo Lucci,

Corresponding Author's Institution: University of Barcelona

First Author: Paolo Lucci

Order of Authors: Paolo Lucci; Oscar Núñez, Ph.D.; Maria Teresa Galceran, Professor

Solid-phase extraction using molecularly imprinted polymer for selective extraction of natural and synthetic estrogens from aqueous samples

4 5678 Paolo Lucci^{*}, Oscar Núñez, M.T. Galceran Department of Analytical Chemistry, University of Barcelona, Av. Diagonal 647, 08028 Barcelona, Spain

9 Abstract

10 A method is proposed for the clean-up and preconcentration of natural and synthetic estrogens 11 from aqueous samples employing molecularly imprinted polymer (MIP) as selective sorbent 12 for solid-phase extraction (SPE). The selectivity of the MIP was checked toward several 13 selected natural and synthetic estrogens such as estrone (E1), 17β -estradiol (β -E2), 17α -14 estradiol (α -E2), estriol (E3), 17 α -ethinylestradiol (EE2), dienestrol (DIES) and diethylstilbestrol (DES). Ultrahigh pressure liquid chromatography (UHPLC) coupled to a 15 16 TSQ triple quadrupole mass spectrometry (QqQ) was used for analysis of target analytes. The chromatographic separation of the selected compounds was performed in less than 2 min 17 18 under isocratic conditions. The method was applied to the analysis of estrogens in spiked river 19 and tap water samples. High recoveries (>82%) for estrone, 17β -estradiol, 17α -estradiol, 20 estriol and 17α -ethinylestradiol were obtained. Lower but still satisfactory recoveries (>48%) were achieved for dienestrol and diethylstilbestrol. The method was validated and found to be 21 linear in the range 50-500 ng L⁻¹ with correlation coefficients (R^2) greater than 0.995 and 22 23 repeatability relative standard deviation (RSD) below 8% in all cases. For analysis of 100-ml sample, the method detection limits (LOD) ranged from 4.5 to 9.8 ng L⁻¹ and the limit of 24 quantitation (LOQ) from 14.9 to 32.6 ng L⁻¹. To demonstrate the potential of the MIP 25 26 obtained, a comparison with commercially available C₁₈ SPE was performed. Molecularly 27 imprinted SPE showed higher recoveries than commercially available C₁₈ SPE for most of the 28 compounds.

29 These results showed the suitability of the MIP-SPE method for the selective extraction of a

30 class of structurally related compounds such as natural and synthetic estrogens.

31

32 KEYWORDS: Estrogens; molecularly imprinted polymers; ultrahigh pressure liquid chromatography; mass
 33 spectrometry; water samples.

^{*} Corresponding author. Tel. 34-93-4021286:; Fax :34-93-4021233.

E-mail address : paololucci2001@yahoo.it (Paolo Lucci)

35 **1. Introduction**

36

37 Endocrine disrupting compounds (ECDs) are a heterogeneous group of substances that may 38 interact with the endocrine system of organisms. Estrogens are important members of the 39 ECDs group and they have been often recognized as the major contributors to the endocrine-40 disrupting activity observed in aquatic environments [1]. They are excreted into the aquatic 41 environment through human and animal urine and the use of natural and synthetic estrogens 42 in medicine or in veterinary have caused their presence in aquatic ecosystems. Although the environmental concentrations of estrogens are very low (up to 105 ng L⁻¹) [2,3,4], their 43 44 adverse effect on the reproduction of wildlife and humans is not negligible [5]. To assess the 45 ecological risk of these compounds, sensitive determination of estrogens in environment is 46 needed.

Several analytical methods have been developed to identify and quantify ECDs in water
samples [6], including high-performance liquid chromatography with several detection
systems such as UV [7,8], fluorescence [9] and coupled to mass spectrometry [10,11,12,13],
gas-chromatography after derivatization [14] and enzyme-linked immunosorbent assay [15].

51 Currently, liquid chromatography coupled with tandem mass spectrometry is the most 52 common approach. However, as the concentrations of the estrogenic compounds in 53 environmental matrices are very low, a clean-up and preconcentration step is usually required 54 in order to minimize interferences and improve method accuracy and sensitivity. Solid-phase 55 extraction (SPE) is a well-established method routinely used for clean-up and 56 preconcentration step of this compounds [16]. The main drawback of conventional SPE 57 sorbents is their lack of selectivity resulting in co-extraction of interfering matrix components, 58 which can negatively affect quantitation. Selectivity can be obtained using sorbents based on 59 molecularly imprinted polymers (MIP). These types of sorbents are synthetic materials 60 possessing an artificially generated three-dimensional network that is able to specifically 61 rebind a target analyte, or class of structurally related compounds. MIP has the advantages of 62 being very selective, cost-effective, and not suffering from storage limitations and stability 63 problems regarding organic solvents. MIPs have been proposed in recent years as sorbent for 64 the extraction and/or removal of endocrine disrupting compounds [17,18,19]. In addition, the 65 potential of MIP as SPE sorbent for extraction of diethylstilbestrol [20,21], 17β -estradiol [22] 66 and 17α -ethinylestradiol [23] from aqueous samples has also been demonstrated. The aim of 67 this work was to develop for the first time a group-selective extraction method based on 68 molecularly imprinted polymer for the analysis of natural (estrone, 17β-estradiol, 17α69 estradiol, estriol) estrogens (17 α -ethinylestradiol, and synthetic dienestrol and diethylstilbestrol) in aqueous samples. For analysis of the selected analytes ultrahigh pressure 70 71 liquid chromatography (UHPLC) coupled to a TSQ triple quadrupole mass spectrometry 72 (QqQ) with atmospheric pressure chemical ionization (APCI) was used. The applicability of 73 the method was evaluated analyzing estrogens in river and tap water samples spiked at 74 concentrations similar to those found in the aquatic environment.

75

77

76 2. Experimental

78 2.1 Materials and chemicals79

HPLC-grade methanol, water and acetonitrile for the UHPLC analysis were purchased from 80 81 Riedel-de Haën (Seelze, Germany). Acetonitrile, acetone, chloroform and methanol used for 82 the synthesis and chromatographic evaluation of the polymers were supplied by Carlo Erba 83 (Val de Reuil, France). Estrone (E1), 17 β -estradiol (β -E2), 17 α -estradiol (α -E2), estriol (E3), 84 17α -ethinylestradiol (EE2), dienestrol (DIES) and diethylstilbestrol (DES) (structures shown 85 in Fig.1) were from Sigma-Aldrich (Steinheim, Germany). Nitrogen (99.8% pure) supplied by Claind Nitrogen Generator N2 FLO (Lenno, Italy) was used for the mass spectrometry 86 87 ionization source. High-purity Argon (Ar₁) and helium, purchased from Air Liquide (Madrid, Spain), were used as a collision-induced gas (CID gas) in the triple quadrupole mass 88 89 spectrometer.

Molecularly imprinted polymer (product code: AFFINIMIP) and non-imprinted polymer (NIP) were provided by POLYINTELL (Val de Reuil, France). MIPs are obtained by radical polymerization using initiatior 2,2'-azobis-isobutyronitrile from Sigma–Aldrich (Steinheim, Germany) and based on difunctional acrylic cross-linker monomers (Sigma–Aldrich, Steinheim, Germany). Isolute cartridges (3 mL) packed with 100 mg of C₁₈ material were purchased from IST (Mid Glamorgan, UK).

96 97

98 2.2 Instrumentation

99

100 Chromatographic evaluation of the imprinted polymers was performed in an LC system from 101 Gilson (Villiers le Bell, France) that consisted of a Pump 322 and a UV/VIS detector 102 (UV/VIS-155). Stainless steel LC columns (250 mm x 2.1 mm) filled with molecularly 103 imprinted and non-imprinted polymers were packed using 1666 HPLC column Slurry Packer 104 (Alltech Associates Applied Science Ltd, Lancashire, UK). The UHPLC system used for the

105 MIP-SPE evaluation consisted of an Accela liquid chromatograph system (Thermo Fisher 106 Scientific, San José, CA, USA) coupled to a triple quadrupole mass spectrometer TSQ Quantum Ultra AM (Thermo Fisher Scientific, San José, CA, USA) equipped with 107 108 atmospheric pressure chemical ionization (APCI) source. The column used to analyze the 109 various MIP-SPE fractions was an Ascentis Express Phenyl-Hexyl HPLC Column (150 mm \times 110 2.1 mm i.d., 2.7 µm particle size) from Supelco (Bellefonte, PA, USA) Sigma-Aldrich). The 111 Xcalibur software version 2.0 (Thermo Fisher Scientific, San José, CA, USA) was used to 112 control the LC/MS system and to process data.

113114

116

118

115 **2.3 Procedure**

117 2.3.1 Chromatographic evaluation of the imprinted polymers

119 Imprinted and non imprinted polymers (25-45 µm particles) were slurry-packed in 120 chloroform/methanol (80:20, v/v) into LC columns using a slurry packer. The LC was carried out at 21 °C and the flow rate was kept constant at 1 mL min⁻¹. The analytical wavelength was 121 122 set at 220 nm. Acetone was used as a void volume marker and the retention factor (k) for each analyte was calculated as $k = (t-t_0) t_0^{-1}$, where t and t_0 are the retention times of the analyte and 123 the void marker (acetone), respectively. The imprinted factor (IF) was calculated as IF = k_{MIP} 124 k_{NIP}^{-1} , *i.e.* the ratio of the retention factor of each analyte in the MIP column to that in the NIP 125 126 column. The elution times of the void marker on MIP and NIP columns were 0.6 and 0.58 127 min, respectively.

128

130

129 2.3.2 Extraction and clean-up using MIP-SPE

Empty SPE cartridges of 4-mL capped with fritted polypropylene disks at the bottom and on 131 132 the top were packed with 100 mg of each polymer particles (imprinted and non-imprinted). 133 Before each use, sorbents were conditioned with acetonitrile (5 mL) followed by water (5 134 mL). For the MIP-SPE experiments, 100mL of Milli-Q, river and tap water samples free from 135 analytes were filtered using 0.45µm pore size cellulose filters and spiked with different amounts of estrogens to reach a final concentration of 50, 100, 150 and 200 ng L⁻¹. The 136 samples were percolated through the MIP-SPE cartridge at the flow rate of 2 ml min⁻¹. The 137 138 sorbent was washed with 4 mL of water/acetonitrile (80:20, v/v) followed by 2 mL of water. 139 Full vacuum was applied for 5 min to ensure the polymer was completely dry. Then, the 140 sorbent was washed with acetonitrile (2 mL) followed by 2 mL of acetonitrile/methanol

141 mixture (95:5, v/v). Estrogenic compounds were finally eluted from the cartridges with three 142 aliquots (3 x 1 mL) of methanol.

Each fraction eluted from the MIP-SPE cartridge was evaporated to dryness under a stream of nitrogen and the residues were reconstituted in 500 μ L of the UHPLC mobile phase. Extraction recovery was calculated by comparing the peak areas of the analytes from extracted samples with those of control samples corresponding to 100%. Recovery experiments were performed in triplicate.

148 149

151

150 2.3.3 Extraction using C_{18} SPE

152 C_{18} SPE columns were pre-treated with 4 mL of methanol followed by 10 mL of Milli-Q 153 water. Then, spiked river water samples (100 ml) was loaded on the cartridge with a flow rate 154 of 10 mL min⁻¹ after which the column was dried under vacuum for 20 min. Acetone (3 mL) 155 was used to elute the analytes from the extraction column [24]. The extract was evaporated 156 under a gentle stream of nitrogen and redissolved in 500 µL of the ultrahigh pressure LC 157 mobile phase.

- 158
- 159

161

160 2.3.4 2.33 *LC-MS conditions*

162 The chromatographic separation of estrogens was performed at 35 °C using isocratic elution. 163 A mobile phase consisting of a mixture of water/acetonitrile/methanol (51:44:5, v/v/v) at 450 µL min⁻¹ flow rate was used. Injection volume was set to 10µL. Atmospheric pressure 164 chemical ionization (APCI) interface in the positive (PI) ionization mode was used. Nitrogen 165 166 (purity > 99.98%) was used as a sheath gas, ion sweep gas and auxiliary gas at flow rates of 167 50, 0 and 40 a.u. (arbitrary units), respectively. The vaporizer temperature was set at 350°C 168 and corona discharge current at 10µA. Quantitative analysis was performed using selected 169 reaction-monitoring mode (SRM). Argon was used as collision gas at 1.5mtorr and the 170 optimum collision energy (CE) and the SRM transition with the best signal intensity was used 171 for quantification (Tab.1).

Matrix-matched standard calibration curves, at seven concentration levels (5 to 1000 ng mL⁻¹) for each compound were obtained by spiking analytes into sample extracts. Good linearity of response by direct injection was obtained for all compounds. The resulting correlation coefficients (R^2) were higher than of 0.999 in all cases. The instrumental detection limits ranged from 8.3 to 25.1 pg injected, based on a signal to noise ratio of 3:1 (**Tab.1**).

180

182

179 **3. Results and discussions**

181 *3.1 Evaluation of the MIP by LC*

183 Chromatographic evaluation of the imprinted polymer was performed in order to assess the 184 MIP activity. For this purpose, the chromatographic behaviour of β -E2 on the molecularly 185 imprinted polymer packed column was compared with that of the column filled with non 186 imprinted polymer. The choice of the mobile phase is crucial to identify the nature of the 187 interactions involved in the retention process. Thus, different ACN/MeOH mixtures (MeOH 188 content ranging from 0 to 10%) were used as mobile phases to characterize the MIP before 189 SPE applications. β -E2 was totally retained on MIP when using acetonitrile as mobile phase 190 (no elution of β -E2 after 75 min), whereas in NIP control, β -E2 has a retention time of 43 min 191 (data not shown). These results reveal the successful imprinted process. Then, to obtain the 192 optimal selectivity, a further set of experiments was performed using acetonitrile/methanol 193 mixtures. In all polymers, the addition of methanol in the mobile phase resulted in a decrease 194 in retention of β -E2. The highest imprinting factor (IF=3.9) was obtained using a mixture of 195 ACN/MeOH (95:5, v/v), indicating that a moderate increase of the methanol content 196 enhanced the selectivity of the MIP. As it is shown in Fig.2, a NIP retention time of 3.2 min 197 for β -E2 whereas this compound was more strongly retained when the MIP polymer was used 198 $(t_{\text{MIP}} = 11.2 \text{ min})$. This behavior reveals the difference in the strength of the interactions 199 between the analyte and the two sorbents. The strong retention of the MIP for β -E2 results 200 from the presence of cavities with high affinity binding sites whereas β -E2 was adsorbed by 201 the NIP through non-specific relative weak interactions which was easily eluted by a mobile 202 phase containing low amounts of a polar protic solvent. This result was further supported by 203 MIP-SPE procedure described below.

- 204
- 205

207

206 *3.2 Study of the SPE retention mechanism*

To develop the MIP-SPE method for the selective extraction of the selected estrogens in water, experiments for the optimization of conditioning, loading, washing and elution steps were performed. First, MIP performance was evaluated using Milli-Q water. After conditioning the imprinted polymer with 5mL of ACN followed by 5mL of water, a volume of 100 mL of Milli-Q water spiked with 200 ng L⁻¹ of each estrogenic compound were 213 percolated through the MIP. The same experiment was carried out on NIP. Under aqueous 214 condition estrogens are principally retained on the polymer by non-specific interactions such 215 as ionic and hydrophobic. In order to generate specific interactions between the target 216 compounds and the MIP and to disrupt the non-specific interactions between the polymer and 217 apolar matrix components that can be present in real samples, the sorbents were completely 218 dried in vacuum during 5 min and, once the drying step was carried out, 2mL of acetonitrile 219 were applied. A partial elution of the compounds (2-8%) was observed for NIP, while in MIP 220 most of the compounds were completely retained (Fig.3-w1). The use of acetonitrile, a polar 221 non protic solvent with a high dielectric constant, allowed the formation of specific 222 interactions via hydrogen bonds between the molecules and the functional monomers. Each 223 molecule displays at least one hydroxyl group able to interact specifically with imprinted 224 cavities. In order to clearly demonstrate the real imprinting effect of the MIP, 2mL of a 225 mixture of acetonitrile/methanol (95:5, v/v) were applied to the polymer in order to disrupt 226 the residual non-specific interactions formed on the MIP and NIP by hydrogen bonds. 227 Estrogens were completely desorbed in the non-imprinted polymer during the 228 acetonitrile/methanol (95:5, v/v) washing step (Fig.3-w2) due to the presence of a protic polar 229 solvent such as methanol and to the lack of MIP cavities. In contrast in the MIP most of the 230 compounds were manly mainly retained and only DIES and DES were partially eluted. This 231 can be explained because this analytes, besides the hydroxyl groups at para positions of the 232 two benzene rings, have quite different chemical structure with a different number of aromatic 233 rings (Fig.1). Finally, estrogens were eluted from MIP-SPE with 3x1mL of methanol. The 234 results obtained from the analysis of the elution fractions showed a good recovery for all 235 estrogenic compounds (Fig.3-E). High extraction recoveries (>95%) were obtained for E1, β -236 E2, α -E2, E3, and EE2 demonstrating the effectiveness of the newly prepared MIP. For DES 237 and DIES, lower recoveries were found between 50% and 60%. Although these two 238 compounds were more easily removed than the other estrogenic compounds during the 239 acetonitrile/methanol (95:5, v/v) organic washing step, their MIP recoveries were relatively 240 high. Thus, even if MIP exhibited a lower affinity for these compounds, it is clear that the 241 synthesized polymer can recognize structurally related compounds.

242

243

244

245

246

3.3 Application of MIP-SPE procedure

250 To check the applicability of the developed MIP-SPE for the extraction of the selected 251 estrogens in real matrices, river and tap water samples were collected and submitted to the 252 MIP extraction procedure. In real samples an additional washing step was used in order to 253 remove non-selectively bounded polar matrix components. Thus, after loading, 4mL of a 254 mixture water/acetonitrile (80:20, v/v) followed by 2mL of water were applied to the 255 polymers. As expected, there was no desorption from the MIP-SPE of estrogens during the 256 additional aqueous washing steps (data not shown). Then, the same procedure as described 257 above was applied. Figure 4 shows the SRM chromatogram corresponding to the injection of the elution fraction after the purification of river water spiked at 100 ng L^{-1} on MIP. All 258 259 compounds, including the two isomers of estradiol, were successfully separated in less then 2 260 min.

The linearity of the total analytical method, including the MIP-SPE step, was checked by 261 262 analyzing water samples spiked at different concentrations ranging from 50 to 500 ng L^{-1} . 263 Good linearity of the seven analytes was achieved in both river and tap water with correlation 264 coefficients greater than 0.995 (Tab.3). The limits of detection (LODs), defined as the 265 concentrations that yielded S/N ratios greater than or equal to 3, and the limits of 266 quantification (LOQs), defined as the concentrations that yielded S/N ratios greater than or 267 equal to 10, were determined through MIP-SPE extractions of spiked water samples. The LODs ranged from 4.5 to 9.8 ng L⁻¹ whereas LOQs were in the range of 14.9-32.6 ng L⁻¹ 268 (Tab.3). The recovery, accuracy and precision of the developed MIP-SPE method were 269 270 calculated in Milli-Q, river and tap water samples at four concentration levels. The recovery 271 values obtained are presented in **Tab.2**. Comparable average recoveries at the different 272 fortification levels were founded in Milli-Q and river water samples varying from 82 (E1) to 106% (EE2). Similar results were observed for tap water samples with a mean recovery in the 273 274 elution fractions ranging from 82 (E1) to 95% (α -E2). For DES and DIES, recoveries between 275 48 and 63% were obtained. These results revealed the ability of MIP to extract estrogens in 276 real water samples without suffering from matrix interferences during the rebinding process 277 of the target compounds. The precision and linearity of the method were satisfactory with 278 repeatability relative standard deviation (RSD) below 8% in all cases.

To demonstrate further the potential of the MIP obtained for the extractions of the selected estrogens in real matrices, a comparison between the MIP-SPE and commercially available C_{18} SPE was performed. The retention of the estrogenic compounds on both sorbents was evaluated under optimal conditions by percolating a river water samples spiked at 50 ng L⁻¹. Resulting elution profiles are described in **Fig.5**. The recoveries of MIP extraction were higher compared with C_{18} SPE and only DIES and DES were strongly retained on the C_{18} cartridges. However it should be pointed out that the MIP-SPE procedure included also a clean-up step.

The results obtained showed that the imprinted sorbent can be a good substitute of the traditional C_{18} sorbent, revealing the suitability of the method for the selective extraction of natural and synthetic estrogens from river and tap water samples.

290

292

4. Conclusions

293 In this work, we propose a MIP-SPE procedure for the group-selective extraction of natural 294 and synthetic estrogens (estrone, 17β -estradiol, 17α -estradiol, estrol, 17α -ethinylestradiol, 295 dienestrol and diethylstilbestrol) employing a new molecularly imprinted polymer (MIP) as 296 selective sorbent. The new MIP has high specific recognition selectivity for estrogenic 297 compounds with similar structure. Recovery, precision and accuracy found for the selective 298 extraction of the target analytes from river and tap water samples spiked at concentrations 299 similar to those observed in the aquatic environment allowed to propose this method for the determination of the selected estrogenic compounds at concentrations down to the ng L^{-1} 300 301 level.

302

307

309

303 Acknowledgments:

This work has been supported by CARBOSORB project [(FP7 Marie Curie Industry-Academia Partnerships and Pathways (IAPP)]. Thanks to POLYINTELL team for their donation of MIP and NIP polymers and SPE cartridges.

308 **References:**

- 310 [1] M. Holger, K. Ballschmiter, K. Ballschmiter. M. Environ. Sci. Technol. 35 (2001) 3201-3206
- 311 [2] K. Wanami, T. Shimazu, T. Miyashita, T. Ohara, Bulletin of Tokyo Metropolitan Research
- 312 Institute for Environmental Protection, (2003) pp 55–62.
- 313 [3] K. Wanami, T. Shimazu, T. Miyashita, T. Yamamoto, K. Thukada, T. Yoshioka, Bulletin of Tokyo
- 314 Metropolitan Research Institute for Environmental Protection (2004) pp101-109.
- 315 [4] T.A. Ternesa, U, M. Stumpfa, J. Muellera, K. Haberera, R.-D. Wilkena, M. Servos, Sci Total
- 316 Environ 225 (1999) 81-90
- [5] CE. Purdoma, PA. Hardimana, VVJ.Byea, NC. Enoa, CR. Tylerb, JP Sumpterb. Chem. Ecol. 1994,
 8, 275.
- 319 [6] V. Pacáková, L. Loukotková, Z. Bosáková, K. Štulík, J. Sep. Sci. 32 (2009) 867-882

- 320 [7] JA. Russell, R. K. Malcolm, K. Campbell. J. Chromatogr. B 744 (2000) 157.
- 321 [8] DW. Choi, J. Y. Kim, S. H. Choi, Food Chrm 96 (2006) 562
- 322 [9] S. Weber, P. Leushner, P. Kampfer. Appl. Microbiol. Biotechnol. 67 (2005) 106.
- 323 [10] S. Wang, W. Huang, G. Fang, Y. Zhang, H. Qiao, Intern. J. Environ. Anal. Chem. 88 (2008) 1.
- 324 [11] M.S. Díaz-Cruz, M.J. López de Alda, R. López, D. Barceló, J. Mass Spectrom. 38 (2003) 917.
- 325 [12] Y.H. Lin, C.Y. Chen, G.S. Wang, Rapid Commun. Mass Spectrom. 21 (2007)1973.
- [13] H.C. Chena, H.W. Kuoa, W.H. Ding, Chemosphere 74 (2009) 508.
 [14] G. Saravanabhavan, R. Helleur, J. Hellou, Chemosphere 76 (2009) 1156.
 [15] M. Farré, M. Kuster, R. Brix, F. Rubio, M.J. López de Alda, D. Barceló. J. Chromatogr. A. 1160 (2007) 166.
- 327 [16] L. Sun, W. Yong, X. Chu and J.M. Lin, J. Chromatogr. A 28 (2009) 5416.
- 328 [17] Z. Meng, W. Chen, A. Mulchandani, Environ. Sci. Technol. 39 (2005) 8958.
- 329 [18] Y. Lin, Y. Shi, M. Jiang, Y. Jin, Y. Peng, B. Lu, K. Dai, Environ. Pollut. 153 (2008) 489.
- [19] H. Sanbe, J. Haginaka, J. Pharm. Biomed. Anal. 30 (2002) 1835.
 [20] J.C. Bravo, R.M. Garcinuño, P. Fernández, J.S. Durand. Anal Bioanal Chem 388 (2007) 1039.
- 331 [21] C. Zhao, Y. Ji, Y. Shao, X. Jiang, H. Zhang, J Chromatogr A 1216 (2009) 7546.
- 332 [22] M.D. Celiz, D.S. Aga, L.A. Colón, Microchemical J 92 (2009) 174.

[23] J.C. Bravo, R.M. Garcinuño, P. Fernández, J.S. Durand, Anal Bioanal Chem. 393 (2009) 1763.

- [24] T. Benijts, R. Dams, W. Günther, W. Lambert, A. De Leenheer, Rapid Commun. Mass Spectrom.
 16 (2002) 1358.
- 335 336
- 337

338 Figure captions

- 339
- 340 Fig.1. Selected estrogenic compounds
- 341
- 342 **Fig. 2.** Chromatograms of 17β-estradiol (2.2mM mM) on LC columns filled with non-
- 343 imprinted (NIP) and imprinted polymer (MIP). Sample volume: 20 µL. Mobile phase:
- ACN/MeOH (95:5, v/v). Flow rate:1 mL min⁻¹. Column dimension: 250 mm \times 2.1 mm. Detection at 220 nm. T: 21 °C.
- 346
- Fig.3 Elution profiles of the estrogenic compounds obtained on MIP and NIP (100mg of
 sorbent) in MilliQ-water. W1: 2mL ACN, W2: 2mL ACN/MeOH (95/5, v/v), E: 3mL MeOH
- Fig. 4. SRM Chromatogram of estrogens extracted from 100 mL river water spiked at 100 ng
 L⁻¹
- **Fig. 5.** Comparison of extraction performance between the MIP and C_{18} in river water
- samples spiked at 50 ng L^{-1} of each compound. **Table 1.** LC/APCI-MS-MS parameters for the acquisition of the estrogenic compounds in positive ionization mode
- 356

357	Table 1. LC/APCI-MS-MS parameters for the acquisition of the estrogenic compounds in positive ionization mode
358	
359	

Compound	Precursor ion (m/z)	Quantitation ion (m/z)	CE (eV)	Tube lens (V)	Confirmation ion (<i>m</i> / <i>z</i>)	CE (eV)	Tube lens (V)	IDL (pg injected)	Linearity range (ng mL ⁻¹)
Estriol	271.2	253.0	12	54	157.0	21	54	24.0	5-1000
17β-estradiol	255.2	159.0	18	76	133.0	20	76	8.3	5-1000
17α-estradiol	255.2	159.0	18	76	133.0	20	76	8.5	5-1000
17α-ethynilestradiol	279.2	133.0	16	50	159.0	19	50	12.5	5-1000
Estrone	271.2	253.0	12	52	133.0	25	52	18.0	5-1000
Diethylstilbestrol	269.2	107.0	32	44	135.0	12	44	25.1	5-1000
Dienestrol	267.2	107.0	23	62	173.0	15	62	24.0	5-1000

Diene	estrol	267.2	107.0	23	62	1/3.0	15
360							
361							
362							
363 '	Table 2. Reco	overies of selected	estrogens in	MilliQ,	river and	tap water samp	oles (n=3)
364							
					n	(0.4)	

						Recove	ery (%)					
		MilliQ	-water			River	water			Tap	water	
	Spike (ng L ⁻¹)				Spike ($(ng L^{-1})$)		Spike (ng L ⁻¹)			
Compound	50	100	150	200	50	100	150	200	50	100	150	200
Estriol	83	87	87	82	82	82	94	93	88	91	82	89
17β-estradiol	96	89	98	101	85	93	91	92	86	93	89	90
17α-estradiol	95	92	97	104	88	93	90	89	95	87	89	89
17α-ethynilestradiol	97	92	98	96	92	99	92	106	92	89	90	87
Estrone	98	94	103	96	94	89	88	95	94	92	85	94
Diethylstilbestrol	47	42	54	60	53	54	49	51	54	48	52	51
Dienestrol	56	53	69	71	50	54	61	63	63	57	61	63

MilliQ-water			Ri	ver wate	r	Tap water				
Compound	$LOD LOQ R^2$			LOD (ng I^{-1})	LOQ (ng L	R^2	LOD (ng L	LOQ (ng L ⁻	R^2	Linearity range $(ng L^{-1})$
	$\frac{1}{1}$	$^{1})$		(115 L)	$\binom{11}{1}$		$\frac{1}{1}$	$\binom{1}{1}$		(lig L)
Estriol	6.1	20.3	0.998	7.5	25.0	0.998	7.3	24.3	0.998	50-500
17β-estradiol	4.3	14.3	0.996	5.0	16.6	0.995	4.9	16.3	0.996	50-500
17α-estradiol	4.2	13.9	0.997	4.6	15.3	0.997	4.5	14.9	0.995	50-500
17α-ethynilestradiol	6.1	20.3	0.998	6.5	21.6	0.998	6.4	21.3	0.998	50-500
Estrone	5.7	18.9	0.996	6.0	19.9	0.996	5.8	19.3	0.996	50-500
Diethylstilbestrol	8.5	28.3	0.997	9.8	32.6	0.996	9.8	32.6	0.997	50-500
Dienestrol	8.3	27.6	0.996	9.5	31.6	0.995	9.4	31.2	0.995	50-500

Table 3. Linearity, detection and quantification limits of the MIP-SPE method in MilliQ, river and tap water samples (n=3)
 370

Figure 1







469	
470	Figure 3
471	









Figure 4



