Table of Contents

| 1. Molecule Microscopy | 1 |
|--|---|
| 1.1 Scanning Desorption Molecule Microscopy (SDMM) 1.2 Scanning Micropipette Molecule Microscopy (SMMM) | 1 3 |
| 2. Semiconductor Surface Studies | 6 |
| 2.1 Excitations at Surfaces and Interfaces of Solids 2.2 Surface and Defect Excitations in Covalently Bonded Solids | 6 7 |
| 3. Atomic Resonance and Scattering | 8 |
| 3.1 Atomic Physics Program 3.2 Atoms in Strong Magnetic Fields 3.3 Structural Studies - Nonadiabatic Effects in Calcium 3.4 Rydberg Atoms and Radiation 3.5 Inhibited Spontaneous Emission 3.6 Rotationally Inelastic Collisions 3.7 Two Basic Ideas 3.8 Fitting Laws 3.9 Velocity Dependence 3.10 Doppler Probe of Energy Transfer in Adiabatically Expanding Gas Scientific Objective 3.11 Scientific Background | 8 9 9 10 11 12 12 13 13 15 |
| 4. Reaction Dynamics at Semiconductor Surfaces | 19 |
| 5. X-Ray Diffuse Scattering | 20 |
| 5.1 Structure and Transitions of Rare Gas Atoms on Graphite 5.2 Smectic Liquid Crystals | 20 21 |
| 6. Phase Transitions in Chemisorbed Systems | 23 |
| 6.1 Multicritical Phase Diagrams of Chemisorbed Systems on Nickel 6.2 Improved Renormalization-group Calculations of Critical Exponents in Surface Systems | 23 23 |
| 7. Quantum Electronics | 25 |
| 7.1 Ultrahigh-Resolution Spectroscopy and Frequency Standards in the Microwave and MM Wave Regions Using Optical Lasers | 25 |
| 7.2 Resonant Light Diffraction by an Atomic Beam | 26 |
| 7.3 Precision Atomic Beam Studies of Atom-Field Interactions 7.4 Passive Ring Resonator Method for Sensitive Inertial Rotation Measurements in Geophysics and Relativity | 27 27 |
| 7.5 Closed Loop, Low Noise Eiberoptic Botation Sensor | 28 |
| 7.6 Intensity-Induced Nonreciprocity in a Fiberoptic Gyroscope | 29 |
| 7.7 Measurement of Natural Predissociation Effects in Iodine Molecules | 29 |
| 7.8 Picosecond Optical Signal-Sampling Device | 31 |
| 7.9 Devices for High-Rate Optical Communications | 34 |
| 7.10 Picosecond Optics | 36 |
| 7.11 Surface Acoustic Wave Gratings | 39 |
| 8. Time-Resolved Spectroscopy of Condensed Matter | 42 |
| 9. Infrared Nonlinear Optics | 45 |
| 9.1 Infrared Nonlinear Processes in Semiconductors | 45 |

| 10. Quantum Optics and Electronics | 47 |
|--|--|
| 10.1 Nonlinear Optical Interactions in Semiconductors 10.2 Picosecond Dye Laser Optics 10.3 Nonlinear Spectroscopy of Atoms and Molecules | 47 48 48 |
| 11. Microwave and Millimeter Wave Techniques | 51 |
| 11.1 Research Objectives | 51 |
| 12. Microwave and Quantum Magnetics | 53 |
| 12.1 Tutorial Review of MSW 12.2 Magnetostatic Modes Bound by DC Field Gradients 12.3 Optical and Inductive Probing of Magnetostatic Resonances 12.4 Mode Synthesis 12.5 New Techniques to Guide and Control Magnetostatic Waves 12.6 Magnetostatic Wave Dispersion Theory 12.7 Velocity of Energy Circulation of Magnetostatic Modes 12.8 Magnetoelastic Waves and Devices 12.9 Short Millimeter Wave Magnetics | 55 61 63 65 67 69 70 71 72 |
| 13. Radio Astronomy | 73 |
| 13.1 Microwave Spectroscopy of the Interstellar Medium 13.2 Research Objectives 13.3 Long-Baseline Astrometric Interferometer 13.4 Controlled Thin-Film Antenna 13.5 Improved Microwave Retrieval Techniques 13.6 Communications Satellites 13.7 Video-Bandwidth Compression Techniques 13.8 Scanning Multichannel Microwave Radiometer (SMMR) 13.9 Tiros-N Satellite Microwave Sounder 13.10 Advanced Microwave Sounding Unit 13.11 Jovian Decametric Radiation | 73 74 75 76 76 76 77 78 78 79 80 80 81 |
| 14. Electromagnetic Wave Theory and Remote Sensing | 82 |
| 14.1 Electromagnetic Waves 14.2 Remote Sensing with Electromagnetic Waves 14.3 Acoustic Wave Propagation Studies 14.4 Effect of Earth Terrain on Millimeter Wave Propagation 14.5 Theories for Microwave Remote Sensing of Snow 14.6 SAR Image Prediction, Simulation, and Analysis 14.7 Remote Sensing of Vegetation and Soil Moisture | 82 82 83 83 83 84 84 84 |
| 15. Electronic Properties of Amorphous Silicon Dioxide | 87 |
| 16. Photon Correlation Spectroscopy and Applications | 90 |
| 16.1 Research Program | 90 |
| 17. Submicron Structures Fabrication and Research | 92 |
| 17.1 Submicron Structures Fabrication 17.2 Submicron-Period Gold Transmission Gratings for Soft X-ray Spectroscopy | 92 93 |
| 17.3 Spatial Period Division | 93 |

| 17.4 Fabrication of X-ray Masks Using Anisotropic Etching of (110) SI and Shadowing Techniques | 94 |
|--|--|
| 17.5 Reactive Sputter Etching of Si, SiO ₂ , Cr. and Al with Gas Mixtures Based on CF ₄ , Cl ₂ , and SiCl, | 95 |
| 17.6 Studies of Graphoepitaxy by CVD and Solution Growth 17.7 Graphoepitaxy for Solar Cells 17.8 Liquid Phase Epitaxy of InP 17.9 Filters Based on the Coupling of Surface Acoustic Waves in Gratings to Bulk Plate Modes | 96 97 98 99 |
| 17.10 Fabrication of Corrugated-Gate MOS Structures 17.11 Narrow Inversion Layers in Silicon 17.12 Collaborative Projects | 99 100 101 |
| 18. Plasma Dynamics | 105 |
| 18.1 Relativistic Electron Beams and Generation of Coherent Electromagnetic Radiation 18.2 Nonlinear Wave Interactions - RF Heating and Current Generation in Plasmas 18.3 Tokamak Research: RF Heating and Current Drive 18.4 Physics of Thermonuclear Plasmas 18.5 Tokamak Research: RF Heating and Current Drive 18.6 Preparation of Ozone | 105 112 118 121 124 125 |
| 19. Optical Propagation and Communication | 127 |
| 19.1 Improved Low-Visibility Optical Communication 19.2 Atmospheric Propagation Effects on Infrared Radars 19.3 Improved Millimeter-Wave Communication Through Rain 19.4 Fiber-Coupled External-Cavity Semiconductor High-Power Laser | 127 129 131 133 |
| 20. Digital Signal Processing | 137 |
| 20.1 Introduction 20.2 The Parabolic Wave Equation 20.3 Knowledge-Based Signal Processing 20.4 MEM Spectral Estimation for Non-uniformly Sampled Signals 20.5 Geophysical Inversion by Velocity Spectra Migration and Joint Travel-time and Amplitude Techniques | 137 139 140 140 141 |
| 20.6 A Comparison of Power Spectrum Estimation Techniques for Array Data 20.7 Characterization of a Atherosclerosis Using Pulse Doppler Ultrasound 20.8 Pole-Zero Modelling and Classification of Phonocardiograms 20.9 Reflection Coefficient Estimation in the Borehole Environment 20.10 One and Two Dimensional Maximum Entropy Spectral Estimation 20.11 Investigation of the Importance of Phase of the Residual Error Signal in the Linear | 142 143 144 144 145 145 |
| 20.12 The Determination of the Acoustic Reflection Coefficient of the Ocean Bottom from its Response to a Point Source | 146 |
| 20.13 Optimal Signal Reconstruction and ARMA Model Identification Given Noisy and Incomplete Observation Data | 146 |
| 20.14 Artificial Intelligence and Signal Processing in Scene Analysis | 147 |
| 20.15 Signal Reconstruction from the Short-Time Fourier Transform Magnitude | 148 |
| 20.10 MEM Power Spectral Estimation with Uncertainty in Correlation Measurements 20.17 Linimportance of Phase in Speech | 148 148 |
| 20.18 Comparison of Fast Hankel Transforms | 149 |

.

| 21. Speech Communication | 150 |
|--|--|
| 22. Linguistics | 152 |
| 23. Cognitive Information Processing | 154 |
| 23.1 Picture Coding 23.2 Digital Wirephoto ²⁰ System | 154 |
| 23.3 Graphic Arts Applications | 156 |
| 23.4 Graphics Processing for Yearbook Production | 157 158 |
| 24. Custom Integrated Circuits | 159 |
| 24.1 Conversion of Algorithms to Custom Integrated Circuits 24.2 VERY LARGE-SCALE INTEGRATED CIRCUIT RESEARCH | 159 162 |
| 25. Communications Biophysics | 164 |
| 25.1 Basic and Clinical Studies of the Auditory System 25.2 Middle Ear 25.3 Inner Ear Transduction 25.4 Coding in the Cochlear Nerve 25.5 Central Nervous System 25.6 Intensity Perception and Loudness 25.7 Hearing Aid Research 25.8 Tactile Communication of Speech 25.9 Acoustic Emissions from Human Ears 25.10 Investigation of the Mechanical Basis of Frequency Selectivity and Tonotopic | 164 164 165 165 166 167 169 174 177 179 |
| 26. Neurophysiology | 182 |
| 26.1 Studies of Optical Properties of Biological Materials | 182 |
| 27. Publications and Reports | 185 |
| 27.1 Meeting Papers Presented 27.2 Journal Papers Published 27.3 Journal Papers Accepted for Publication 27.4 Letters to the Editor Published 27.5 Letters to the Editor Accepted for Publication 27.6 Special Publications 27.7 Technical Reports Published | 185 201 211 213 215 215 215 216 |
| 28. Personnel | 217 |
| 29. Research Support Index | 226 |

List of Figures

| Figure 1-1: So co gi ui in (c ai | equential view of reversible uncoupling experiment. (a) Interference ontrast view (4OX water-immersion objective) of apical surface of Necturus all bladder before impalement. (b) Epifluorescent view of injected cell in ncoupled epithelium (80% CO ₂ , 32 mM bicarbonate buffer) 10 minutes after njection with the fluorescent dye, Lucifer Yellow. No dye spreading is visible. c) Epifluorescent view of epithelium showing dye coupling after switching to ir-saturated buffer. Scale bar, 10 μ m. | 4 |
|--|---|----|
| Figure 7-1: In | nterferometric sampler with strip-line resonator | 32 |
| Figure 7-2: D | emultiplexer | 33 |
| Figure 7-3: In | nterferometer with 5-Waveguide "Y" | 35 |
| Figure 7-4: S | chematic vies of the integrated XOR gate | 37 |
| Figure 12-1: | Comparison between SAW and MSW normalized frequency dispersion. For a given wavelength λ , the MSW frequency ω_2 can be much higher than the SAW frequency ω_1 . Moreover, since $\omega(0)$ depends upon the dc bias, ω is magnetically tunable. | 54 |
| Figure 12-2: | Equivalent arithmetic operations provided by various analog signal- processing devices. | 55 |
| Figure 12-3: | Transverse section of a thin ferrite strip placed between ground planes. Longitudinal propagation of MSFVW, MSBVW, and MSSW results when, respectively, the dc bias is parallel to the x_3 , x_2 , x_1 axis. | 58 |
| Figure 12-4: | Normalized MSW frequency dispersion for the geometry of Figure 12.2 when the dc magnetic bias is oriented parallel to (a) x_3 , (b) x_2 , and (c) x_1 axis. The respective modes are termed MSFVW, MSBVW, and MSSW. | 60 |
| Figure 12-5: | MSSW mode potentials of a finite slab for opposite directions of propagation. Localization occures near the surface for which the mode is more nearly positive-circularly polarized and is termed field-displacement nonreciprocity. The solid curve is for β out of the paper. | 61 |
| Figure 12-6: | Geometry of curved-path experiment | 62 |
| Figure 12-7: | Transmission characteristics of curved path delay line | 63 |
| Figure 12-8: | Probe tips of induction probe | 64 |
| Figure 12-9: | Schematic of Induction Probe | 65 |
| Figure 12-10: | Probe tip on LPE-YIG thin film | 65 |
| Figure 12-11: | MSSW profiles | 66 |
| Figure 12-12: | Schematic Diagram of microstrip transducer geometry | 68 |
| Figure 12-13: | Experimental diplexer with YIG film removed | 68 |
| Figure 12-14: | a. Channel 1, MSSW b. Channel 2, MSBVW | 09 |
| Figure 17-1. | Left: End view of PMMA exposed by x-ray lithography and developed 0.2 | 04 |
| - 1901¢ 17-1. | um period 0.7 um thick | |
| Right | End view of gold grating 0.3 µm period 0.6 µm thick. The gold was plated | |
| rugit. | up between the PMMA grating lines shown in the top view and then the | |
| | PMMA was dissolved away | |
| Figure 17-2. | Ton view of DMMA v.ray exposed with crystallographic mask. The seried of | 05 |
| 1 Igute 17-2. | the grating is 0.3 μ m and the lines are smooth to + 4 nm. | 90 |

- Figure 19-1: Scattered-to-Direct-Beam Power Ratio vs. Extinction Thickness
- Figure 19-2: Optical layout of experiments. External-cavity laser components are shown 133 in a top, cutaway view through the four-bar Super-Invar supporting structure. The labeled elements are: PM plane mirror; SL spherical collimating lens; D diode gain element; CL 40-mm diameter cylindrical lens; GL graded-index (GRIN) rod lens; F 14-cm-long optical fiber; P polarizer; SM spherical mirror. The polarizer was removed for some experiments. The plane mirror (PM) was replaced by a grating in the Littrow configuration in other experiments (the output in this case was the zero order of the grating).
- Figure 19-3: (a) Spectrum of stimulated emission output of external cavity containing 134 series combination of a diode gain element and a multimode fiber. (b) Fabry-Perot scan of this spectrum. Top trace shows entire 1500-MHz instrument resolution. These results are typical for output powers up to the 2-mW level set by diode life considerations.
- Figure 19-4: Concept of fiber-coupled external cavity semiconductor high-power laser 135 illustrating from left-to-right: the semiconductor-diode gain element whose left facet is coated for near-unity reflectivity and whose right facet is antireflection coated; electrooptic element for phase shifting; focusing lens; the appropriate spatial filter to assure coherence of wavefront across entire fiber bundle emitter (illustrated schematically as a stop); focusing lens to recollimate beam; and a partially reflecting mirror. The external cavity is bounded on the left by the reflecting facets of the semi-conductor gain elements and the right by the partially reflecting mirror.

131