Author(s): Galhardo, A (Galhardo, A.); Goes, J (Goes, J.); Paulino, N (Paulino, N.)

Title: Design of improved rail-to-rail low-distortion and low-stress switches in advanced CMOS technologies

Source: Analog Integrated Circuits and Signal Processing, 64 (1): 13-22 Sp. Iss. SI JUL 2010 **Language:** English

Document Type: Proceedings Paper

Conference Title: 14th IEEE International Conference on Electronics, Circuits and Systems **Conference Date:** DEC 11-14, 2007

Conference Location: Marrakech, MOROCCO

Conference Sponsors: IEEE.

Author Keywords: Switch linearization; Reliability; Switched-capacitor linearization control circuit (SLC); Bootstrapped switch; Clock boosting

KeyWords Plus: LOW-VOLTAGE

Abstract: This paper describes the efficient design of an improved and dedicated switchedcapacitor (SC) circuit capable of linearizing CMOS switches to allow SC circuits to reach low distortion levels. The described circuit (SC linearization control circuit, SLC) has the advantage over conventional clock-bootstrapping circuits of exhibiting low-stress, since large gate voltages are avoided. This paper presents exhaustive corner simulation results of a SC sample-and-hold (S/H) circuit which employs the proposed and optimized circuits, together with the experimental evaluation of a complete 10-bit ADC utilizing the referred S/H circuit. These results show that the SLC circuits can reduce distortion and increase dynamic linearity above 12 bits for wide input signal bandwidths.

Addresses: [Galhardo, A.] DEEA Inst Super Engn Lisboa, Lisbon, Portugal; [Goes, J.; Paulino, N.] Univ Nova Lisboa, Fac Ciencias & Tecnol, DEE FCT UNL CTS UNINOVA, Monte De Caparica, Portugal

Reprint Address: Galhardo, A, DEEA Inst Super Engn Lisboa, Lisbon, Portugal.

E-mail Address: galhardo@deea.isel.ipl.pt; jg@uninova.pt

Publisher: Springer
Publisher Address: VAN GODEWIJCKSTRAAT 30, 3311 GZ DORDRECHT, NETHERLANDS
ISSN: 0925-1030
DOI: 10.1007/s10470-009-9357-z
29-char Source Abbrev.: ANALOG INTEGR CIRCUIT SIGNAL

ISI Document Delivery No.: 605KS