Title: Stacked pin Devices for Imaging Applications

Author(s): Louro, P (Louro, P.); Fantoni, A (Fantoni, A.); Fernandes, M (Fernandes, M.); Vieira, M (Vieira,

M.)

**Book Group Author(s):** IEEE

Source: 2009 6TH International Multi-Conference on Systems, Signals and Devices, Vols 1 and 2

Pages: 880-883 Published: 2009

**Abstract:** In this paper we present results on the optimization of device architectures for colour and imaging applications, using a device with a TCO/pinpi'n/TCO configuration.

The effect of the applied voltage on the color selectivity is discussed. Results show that the spectral response curves demonstrate rather good separation between the red, green and blue basic colors. Combining the information obtained under positive and negative applied bias a colour image is acquired without colour filters or pixel architecture. A low level image processing algorithm is used for the colour image reconstruction.

Language: English

**Document Type:** Proceedings Paper

Conference Title: 6th International Multi-Conference on Systems, Signals and Devices

Conference Date: MAR 23-26, 2009 Conference Location: Djerba, TUNISIA

**Conference Sponsor(s):** Univ Sfax, ENIS, Univ Chemnitz, Philadelphia, Univ, Amman, CISEN comp, SEIMENS, QUNDIS, British Gas, Etudes Realisat Elect, Meubles Samet, IEEE Instrumentat & Measurements

Soc, IEEE German Chapter, Instrumentat & Measurement Soc

Author Keywords: Optical Devices; a-SiC Heterostructures; Colour Sensors

Reprint Address: Louro, P (reprint author), ISEL, Elect Telecommun & Comp Dept, P-1949014 Lisbon,

Portugal

E-mail Address: plouro@deetc.isel.pt

**Publisher: IEEE** 

Publisher Address: 345 E 47TH ST, NEW YORK, NY 10017 USA

ISBN: 978-1-4244-4345-1