



# Modeling the concurrent development of speech perception and production in a Bayesian framework

Marie-Lou Barnaud, Julien Diard, Pierre Bessière, Jean-Luc Schwartz

## ► To cite this version:

Marie-Lou Barnaud, Julien Diard, Pierre Bessière, Jean-Luc Schwartz. Modeling the concurrent development of speech perception and production in a Bayesian framework: COSMO, a Bayesian computational model of speech communication: Assessing the role of sensory vs. motor knowledge in speech perception. EPIROB-ICDL, Aug 2015, Providence, United States. 2015, <<http://www.icdl-epirob.org/>>. <hal-01202418>

**HAL Id: hal-01202418**

**<https://hal.archives-ouvertes.fr/hal-01202418>**

Submitted on 23 Sep 2015

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



It is widely accepted that both **auditory** and **motor representations** intervene in the perceptual processing of speech units. However, the question of the functional role of each of these systems remains seldom addressed and poorly understood.


This is where computational models can play a crucial role. We developed **COSMO**, a Bayesian model comparing **sensory** and **motor** processes in the form of probability distributions which enable both theoretical developments and quantitative simulations.

## Context and Bayesian model


### Issues

- Question of interest:** Why perceptuo-motor units ?  
**Hypothesis:** The **auditory** and the **motor** systems would be complementary.

### COSMO: from a model of communication...




### COSMO: ... to a model of communicating agent (the internalization hypothesis)




## Model learning and simulation of perception processes

### Model learning




### Simulation of perception processes




## Results

### Learning pace: Comparison of the entropy of the sensory and motor learning




The entropy of the **sensory model** converges quickly to a level close to the entropy of the stimuli produced by the **master** (in less than 200 learning steps), while the entropy of the **motor model** converges more slowly (in more than 20,000 learning steps).

### Evaluation of perception: Comparison of recognition rates of the three perception processes in noisy conditions



The **sensory system** provides good recognition scores without noise, with a quick degradation of performance when noise is added. The **motor system** is better than the sensory model in noise, though still being poorer without noise. The **perceptuo-motor system** performs better than both isolated systems in all conditions.

## Discussion



The **sensory model** is of lower variance than the **motor model** and yields a less uncertain categorization probability distribution than the motor categorization process. By contrast, the **motor model** is of larger variance than the **sensory model** and generalizes better.

Consequently, in **nominal condition**, both systems are able to categorize the stimulus but the **sensory system** is better than the **motor system**. In **adverse condition**, the **sensory system** performs a random categorization whereas the **motor system** succeeds to correctly categorize.

## Conclusion and perspectives

### Conclusion

We have compared and illustrated in detail the behavior and the performance of the learned **sensory** and **motor** models. We have shown that the **sensory model** directly *exploits* the associations between objects and stimuli to learn the sensory classifier in a quick and efficient way. In contrast, the **motor model** needs to build both motor repertoires and an internal model of the sensory-motor mapping. In order to do so the Learning Agent *explores* its motor space. As a result, the **motor model** is less efficient for the processing of stimuli typical of the learning set ("nominal conditions") but more robust to degradations and adverse conditions. The **motor model** has some generalization capacities thanks to its exploration phase, when the **sensory model**, in some sense, overlearned. This is what we summarize as the "**sensory narrow-band vs. motor wide-band**" property.

### Perspectives

- We have already extended COSMO to more complex configurations in multi-dimensional spaces involving synthetic plosive-vowel sequences.
- We are currently exploring further the learning algorithm and its ability to produce "idiosyncrasies" which are variations in learned motor and sensory strategies in the learning agent.