



Titre: Title:	Effect of ozonation on anaerobic digestion sludge activity and viability
Auteurs: Authors:	Jaime Alexis Chacana Olivares, Sanaz Alizadeh, Marc-André Labelle, Antoine Laporte, Jalal Hawari et Yves Comeau
Date:	2017
Туре:	Article de revue / Journal article
Référence: Citation:	Chacana Olivares, J. A., Alizadeh, S., Labelle, MA., Laporte, A., Hawari, J. & Comeau, Y. (2017). Effect of ozonation on anaerobic digestion sludge activity and viability. <i>Chemosphere</i> , <i>176</i> , p. 405-411. doi: <u>10.1016/j.chemosphere.2017.02.108</u>



Document en libre accès dans PolyPublie

Open Access document in PolyPublie

URL de PolyPublie: PolyPublie URL:	https://publications.polymtl.ca/9075/
Version:	Version finale avant publication / Accepted version Révisé par les pairs / Refereed
Conditions d'utilisation: Terms of Use:	CC BY-NC-ND



Document publié chez l'éditeur officiel

Document issued by the official publisher

Titre de la revue: Journal Title:	Chemosphere (vol. 176)
Maison d'édition: Publisher:	Elsevier
URL officiel: Official URL:	https://doi.org/10.1016/j.chemosphere.2017.02.108
Mention légale: Legal notice:	

Ce fichier a été téléchargé à partir de PolyPublie, le dépôt institutionnel de Polytechnique Montréal This file has been downloaded from PolyPublie, the institutional repository of Polytechnique Montréal

http://publications.polymtl.ca

1 EFFECT OF OZONATION ON ANAEROBIC DIGESTION SLUDGE ACTIVITY

2 AND VIABILITY

- 3 *Chemosphere*, 176: 405-411. dx.doi.org/10.1016/j.chemosphere.2017.02.108
- 4 Jaime Chacana^{1*}, Sanaz Alizadeh¹, Marc-André Labelle^{1,2}, Antoine Laporte³, Jalal
- 5 Hawari¹, Benoit Barbeau¹, Yves Comeau¹
- ¹Polytechnique Montreal, ²WSP, ³City of Repentigny
- 7 <u>*jaime.chacana@polymtl.ca</u>

8 ABSTRACT

9 The effect of ozonation of anaerobic sludge on methane production was studied as 10 a means to increase the capacity of municipal anaerobic digesters. Ozone doses 11 ranging between 0 to 192 mg O₃/g sludge COD were evaluated in batch tests with 12 a bench scale ozonation unit. Ozonation initially, and temporarily, reduced biomass 13 viability and acetoclastic methanogenic activity, resulting in an initial lag phase 14 ranging from 0.8 to 10 days. Following this lag phase, ozonation enhanced 15 methane production with an optimal methane yield attained at 86 mg O_3/g COD. 16 Under these conditions, the yield of methane and the rate of its formation were 17 52% and 95% higher, respectively, than those measured without ozonation. A 18 required optimal ozone dose could be feasible to improve the anaerobic digestion 19 performance by increasing the methane production potential with a minimum 20 impact on microbial activity; thus, it would enable an increase in the capacity of 21 anaerobic digesters.

Keywords: Anaerobic digestion, sludge, ozone, extracellular polymeric substances,
 mechanisms.

24 **1. Introduction**

25 Anaerobic digestion (AD) of primary and secondary sludge is commonly used for 26 sludge reduction, stabilization and energy recovery at municipal water resource 27 recovery facilities (WRRFs) (Appels et al., 2008). Sludge consists of a polymeric 28 network of organic and inorganic compounds, however, its actual composition 29 depends on the source of the sludge (Sheng et al., 2010). The presence of these 30 chemicals, including extracellular polymeric substances (EPS), e.g. 31 polysaccharides, proteins, lipids strongly influence the hydrolysis of sludge during 32 anaerobic digestion (Sheng et al., 2010). The hydrolysis of sludge requires long 33 hydraulic retention times (20 to 30 days), leading to moderate degradation 34 efficiencies (30 to 50%), translating into large volume digesters and high capital 35 expenditures (Foladori et al., 2010a).

36 Usually, the main factor limiting anaerobic digestion is the hydrolysis of particulate 37 matter. Improving anaerobic digestion through enhancing rate-limiting hydrolysis 38 can increase the degradability leading to improve anaerobic digestion performance 39 (Appels et al., 2008). A variety of treatment techniques have been studied to 40 enhance sludge hydrolysis by using thermal, chemical, mechanical and other 41 biological processes (Appels et al., 2008). Ozonation is one of the preferred 42 chemical treatments, which permits sludge reduction and it is effective in 43 enhancing methane production via the oxidation and solubilisation of sludge 44 (Weemaes et al., 2000). Ozonation of activated sludge prior to anaerobic digestion

45 (pre-ozonation) effectively enhances its anaerobic biodegradability, but it is not
46 effective with primary sludge (Carrère et al., 2010). Alternatively, the ozonation of
47 digested sludge in the recirculation loop of the anaerobic digester (post-ozonation)
48 has been shown to produce a significant increase in methane production (Battimelli
49 et al., 2003).

50 Previous studies demonstrated that ozonation has great potential to increase 51 biodegradation of activated sludge (Appels et al., 2008), but other studies showed 52 evidence of biomass destruction (Labelle et al., 2011; Chiellini et al., 2014). Further 53 investigation is required to establish the potential linkage between ozonation of 54 anaerobic digested sludge, methane production, and its biological response. A 55 better understanding of the mechanisms of sludge ozonation and its impact on 56 methane production and biological response may allow for better operational 57 control and design of an anaerobic digestion process integrated with post-58 ozonation.

The objective of this study was to evaluate the effect of ozonation on the methane production of anaerobic digested sludge, including the mechanisms involved in this process. The specific objectives were to evaluate the impact of ozonation on the methane yield and methane production rate in batch tests, and to evaluate the microbial response of ozonated sludge by monitoring the microbial cell integrity, the metabolism behaviour (key enzyme), the acetoclastic methane activity and the intracellular reactive oxygen species (ROS) formed for various ozone dosages.

66

67 **2. Material and method**

68 2.1. Sludge ozonation

Anaerobic digested sludge was obtained from the Repentigny WRRF (Quebec) which treats 25 000 m³/d using a chemically enhanced primary treatment (CEPT) process and stabilizes the sludge in a completely mixed mesophilic (35°C) anaerobic digester with a hydraulic retention time of 19 days. The collected sludge was passed through a 5 mm sieve to remove large debris, and then stored at 4°C until further use.

75 Ozone was generated by a pure oxygen ozone generator (Peak 2X, Pinnacle, 76 USA). Ozonation of digested sludge was performed in a batch reactor. The gas 77 flow rate was 6 L STP/min with an ozone mass concentration of about 12% by 78 weight. The transferred ozone dose (mg/L) was calculated from the difference 79 between the mass of ozone transferred (mass fed to the reactor minus the mass in 80 the off gas) divided by the volume of sludge. Ozone dosages were normalized as 81 mg O₃/mg COD by dividing the transferred ozone dosage by the initial total COD 82 content of the sample.

Sludge ozonation was conducted on volumes of 2.2 L of digested sludge fed in a
3.8 L column and operated at room temperature. Using a peristaltic pump
operating at a flowrate of 6 L/min, the sludge was recirculated through a venturi
(484X, Mazzei, USA) where ozone was injected continuously. Higher ozone
dosages required longer recirculation time. The contact time ranged from 0.0 to 6.1
minutes for ozone doses between 0 to 192 mg O₃/g COD. Sludge samples were

- 89 periodically collected during the operation of the ozonation system. Additionally, a
- 90 control was prepared to evaluate the effect of treatment without ozone injection.

91 2.2. Analytical methods

92 2.2.1. Ozone measurements

93 The inlet ozone concentration was measured using an ultraviolet ozone meter 94 (BMT 964, BMT Messtechnik GmbH, Germany) while ozone in the off gas was 95 measured using the standard KI method (Rakness, 2005). Dissolved ozone was 96 not measured; it was considered negligible as it was never detected during 97 preliminary tests.

98 2.2.2. EPS extraction and quantification

99 EPS were extracted from the control and ozonated samples based on the method 100 of EPS extraction of Liu and Fang. (2002) and Yu et al. (2008). First, 15 mL of the 101 sample was centrifuged at 2 000 g for 15 min at 4°C. The supernatant was 102 collected and filtered (S-Pak 0.45 µm filter, Millipore, USA) to measure soluble 103 EPS. The sludge pellet was re-suspended to its original volume using a phosphate 104 buffer saline (PBS) solution supplemented with 90 μ L of formaldehyde (36.5% v/v) 105 and then incubated at 4°C for 1 hour under agitation. The suspension was 106 centrifuged at 5 000 g for 15 min at 4°C and the supernatant was collected and 107 filtered (0.45 µm) for measuring the loosely bound EPS (LB-EPS). The remaining 108 sludge pellet was re-suspended again with a PBS solution to its original volume 109 and incubated for 3 h at 4°C after the addition of 6 mL of a 1 M NaOH solution. The 110 suspension was then centrifuged at 12 000 g for 15 min at 4°C, the decanted

supernatant contained the tightly bound EPS fraction (TB-EPS). The residual
sludge pellet was re-suspended once again with a PBS solution to its original
volume (pellet fraction).

114 Proteins and polysaccharides were then measured in the samples before 115 extraction and in soluble EPS, LB-EPS, TB-EPS and pellet fraction. The protein 116 content in the samples was determined using the bicinchoninic acid (BAC) method 117 (Pierce© BCA Protein Assay Kit, Thermo Scientific, USA) with bovine serum 118 albumin (BSA) as the standard. The polysaccharide content of the extracts was 119 analyzed by the phenol-sulfuric acid method using glucose as a standard. Proteins 120 and polysaccharides were measured by a microplate reader (Synergy-HT, BioTek, 121 USA). Excitation-emission matrix (EEM) fluorescence spectra were obtained from 122 the extracts using a luminescence spectrometry (RF-5301pc, Shimadzu, Japan). 123 Samples for EEM analysis were diluted to a final COD of 30 mg COD/L with Milli-Q 124 water. The EEM spectra were collected with the scanning emission spectra (Em) 125 from 220 to 550 nm at 1 nm intervals by varying the excitation wavelengths (Ex) 126 from 220 to 400 nm at 10 nm sampling intervals. Excitation and emission slits were 127 set to 5 nm.

128 2.2.3. Biochemical methane potential

Methane yield and acetoclastic activity were evaluated by measuring the biochemical methane potential (BMP) in 160 mL serological bottles incubated at 35°C based on Saha et al. (2011). A gas manometer (DG25, Ashcroft, USA) was used to measure the biogas production and the methane gas content was quantified with a gas chromatograph (GC-456, Bruker, USA) equipped with a

thermal conductivity detector (150°C). The modified Gompertz model was applied
to the cumulative methane production data to determine the maximum methane
production rate in the samples (Lay et al., 1996). Methane yield was evaluated
without substrate addition, and the acetoclastic activity test was fed with sodium
acetate solution. The methane production was evaluated at the standard
temperature and pressure (STP) of 0°C and 1 atm.

140 2.2.4. Characterization of biological response

141 Bacterial viability of anaerobic sludge was evaluated using the Live/Dead Baclight 142 bacterial viability kit (Molecular Probes, Invitrogen, Kit L13152) and the microplate 143 reader (Synergy-HT, BioTek, USA) using the modified protocol of Chen et al. 144 (2012). The fluorescence intensity of the stained bacterial suspensions (F_{cell}) was 145 determined at an excitation of 488 nm and detection at 635 nm (red) and 530 nm 146 (green), for red-fluorescent nucleic acid stain propidium iodide (PI) and green-147 fluorescent nucleic acid stain SYTO 9, respectively. The green/red fluorescence 148 ratios (R_{G/R}) were used to compare the bacterial inactivation triggered by different 149 doses of ozone. Different proportions of fresh sludge (optimal viable cells) and 150 positive control, inactivated cells with alcohol treatment (2-propanol, 70%), were 151 used as standards. The viability calibration curve was obtained by linear regression 152 of the green/red fluorescence ratio ($R_{G/R}$) vs the percentage of viable cells.

The dehydrogenase activity was quantified by the protocol described by Von Mersi and Schinner (1991). The technique uses soluble and colorless 2-(4-lodophenyl)-3-(4-nitrophenyl)-5-phenyl-2H-tetrazolium chloride (INT) reduction to the red insoluble iodonitrotetrazolium formazan (INF) as a tracer of active bacterial

157 electron transport systems (Caravelli et al., 2004). Briefly, triplicates of sludge 158 samples (0.5 g) were spiked with 0.75 mL of TRIS buffer (1M; pH 7.0) and 1 mL of 159 0.5% INT solution (9.88 mM), slightly mixed using a vortex for 30 seconds. After 2 160 hours incubation at 40 °C in the dark, the intracellular INF crystals were extracted 161 with 5 mL ethanol/N,N-dimethylformamide solution (1/1 v/v) and incubated for 1 h 162 at 40 °C in the dark. The concentration of developed formazan in the retained 163 supernatant of sludge was determined by a UV/vis spectrophotometer at 464 nm 164 using the extraction solution, ethanol/N,N-dimethylformamide solution (1/1 v/v) as 165 reference blank. INT-electron transport system activity was calculated using the 166 modified equation proposed by Yin et al. (2005) (equation 1)

$$INT-ETSA = D_{464} \cdot V/k_i \cdot W \cdot t$$
 (1)

Where INT-ETSA is the INT-electron transport system activity (mg INTF/g biomass/h), D₄₆₄ is the absorbance of the supernatant at 464 nm; V is volume of solvent (mL), k_i is the slope of standard curve of absorbance at 485 nm vs INTF concentration (O.D. mL/mg INTF), W is the weight of biomass (g) and t is the incubation time (h).

172 ROS was determined using an established fluorescence assay (You et al., 2015). 173 The sludge samples were rinsed three times with 0.1 M phosphate buffer (pH 7.4) 174 and the pellets were re-suspended in 0.1 M phosphate buffer containing 50 μ M 175 dichlorodihydrofluorescein diacetate (H2DCF-DA, Molecular Probes, Invitrogen). 176 The resulting mixture was incubated at 25 ± 1°C in the dark for 30 min. The

177 generated fluorescent fluorescein DCF was measured using a microplate reader

178 (Synergy-HT, BioTek, USA) at excitation of 488 nm and emission of 525 nm.

179 2.2.5. Other analytical methods

180 Chemical oxygen demand (COD) was measured using the HACH method (HACH

181 Reactor Digestion Method 8000). Soluble COD was determined on centrifuged
182 (10 000 g, 10 min) and filtered (S-Pak 0.45 µm filter, Millipore, USA) samples.

The morphology of blank and ozonated sludge were visualized using a scanning electron microscope (SEM, JEOL JSM7600F). The sample preparation procedure was adapted from Sheng et al. (2011). Sludge sample preparation included the fixation with 2.5% glutaraldehyde in phosphate buffer for 30 min, followed by serial ethanol dehydration. The gold-coated samples were observed with a highresolution SEM equipped with a field emission gun at a resolution of 1.4 nm at 1 kV and an accelerating voltage of 0.1 to 30 kV.

190 2.6. Statistical analysis

Anaerobic biodegradability tests and EPS extraction were conducted in duplicate, 3D-EEM tests without replication and the other analyses in triplicate. The Student's t-test was used to compare the quantitative variables considering a p value < 0.05 to be statistically significant. A nonlinear optimization by least squares procedure was applied to calculate the maximum methane production by the Modified Gompertz model (Lay et al., 1996).

197

198 3. Results and discussion

199 3.1. Effect of ozonation on COD solubilization and mineralization

200 The impact of ozonation on total COD was shown in Figure 1A. During ozonation, 201 total COD was reduced from 15.0 to 12.3 g COD/L. This was a decrease of 202 approximately 18% at 192 mg O₃/g COD. The decrease of COD by ozonation 203 could be attributed mostly to the complete oxidation of a portion of the organic 204 compounds to CO₂ and water (mineralization); this is based on previous studies for 205 ozonation of activated sludge that reported a decrease of total organic carbon 206 (TOC) similar to the reduction of COD, and also an increase of CO_2 in the residual 207 gas of ozone reactor (Weemaes et al., 2000; Déléris, 2001).

208 Soluble COD increased significantly from 1.13 to 3.31 g COD/L (157 mg O₃/g 209 COD) during ozonation, representing a solubilization of 15.7% (Figure 1A). Higher 210 ozone doses resulted in an apparent decrease in the solubilized COD which may 211 be due to increased mineralization. Solubilization effects observed in this study are 212 consistent with the study of Weemaes et al. (2000) who reported 29% increase in 213 COD solubilization of sludge exposed to 200 mg O₃/g COD. A comparison of the 214 efficiency of sludge solubilization and mineralization in different studies is difficult 215 since the performance depends on several factors including ozone injection 216 conditions, ozone dosage and sludge characteristics (Foladori et al., 2010a). No 217 significant solubilization and COD decrease were observed in the control.



Figure 1: Effect of ozone dose and contact time on COD and methane production – (A) total COD (\bullet) and (\blacktriangle) soluble COD; (B) Methane yield of ozonated sludge (\bullet) and Gompertz maximum production rate (\blacktriangle).

225 3.2. Effect of ozonation on methane production

226 The efficiency of ozonation on methane yield was evaluated in BMP assays using 227 ozonated sludges and controls (Figure 1B). Ozonation leads to a significant 228 increase in methane production and reaching a maximum yield of 123 mL STP 229 CH_4/g COD for an ozone dose of 86 mg O₃/g COD. In the absence of ozone, 230 methane production did not exceed 81 mL STP CH₄/g COD. The composition of 231 the biogas was not impacted significantly during ozonation. The average 232 composition of the biogas in both ozonated sludges and controls was 71.3%, 28.6, 233 and 0.05% for CH₄, CO₂ and H₂, respectively. These experimental findings 234 demonstrated that ozonation could increase methane production. Interestingly, 235 using doses of ozone higher than 86 mg O₃/g COD reduced the improvement in 236 methane production. Similar behavior was reported by Weemaes et al. (2000), who 237 found an optimal methane production for an ozone dose of 100 mg O₃/g COD 238 (80%), but also a higher ozone dose reduced the possitve effect on methane 239 production (30%) for activated sludge mixed with primary sludge.

240 The maximum methane production rate of samples was determined by fitting the 241 cumulative methane production data to the modified Gompertz model (Lay et al., 242 1996). A good agreement between the experimental data and the modified 243 Gompertz model ($R^2 > 0.95$) was obtained. The maximum methane production rate 244 was 2.2 mL STP CH₄ g COD⁻¹ d⁻¹ for an ozone dose of 86 mg O₃/g COD, 245 representing an increase of 94.5% relative to the untreated sludge (Figure 1B). 246 Ozone doses between 122 to 192 mg O_3/g COD did not change significantly the 247 maximum methane production rate compared to the untreated sample. The

maximum methane production rates of the current study are low compared to Weemaes et al. (2000). These authors observed a methane production rate of 4.3 mL STP $CH_4 \cdot g COD^{-1} \cdot d^{-1}$ for untreated sludge, while for the optimal ozone dose, the production rate was 9.1 mL STP $CH_4 \cdot g COD^{-1} \cdot d^{-1}$. This difference may be due to the type of sludge used. Digested sludge has a low biodegradability since the anaerobic digester has already removed readily biodegradable matter.

254 Ozonation can induce the release of soluble substances into the aqueous phase, 255 this phenomenon increases the accessibility of compounds to microorganisms, and 256 therefore, improves the anaerobic biodegradability of ozonated samples. The 257 maximum ozone dose tested (192 mg O₃/g COD) reduced methane yield and the 258 methane production rate, probably due to the complete oxidation of solubilized matter caused by the mineralization. Therefore, mineralization should be 259 260 minimized, while organic matter solubilization should be maximised to enhance 261 methane production (Weemaes et al. 2000; Carballa et al., 2007).

262 3.3. Effect of ozonation on EPS

The effect of ozonation on the protein and polysaccharide content from different extracted EPS fractions and pellets of anaerobic digested sludge is shown in Figure 2A. For the un-ozonated sludge, the total content of proteins and polysaccharides were 6.6 and 1.8 g/L, respectively, with almost 85% of both polymer substances found in the pellet remaining after centrifugation, while the bound EPS and soluble EPS accounted for only 8.6% and 6.2%, respectively. The ratio of proteins and polysaccharides of extracted EPS (soluble EPS and bound

- EPS) was 1.84, as compared with the reported ratios of 1.1 to 2.8 for digested
- 271 sludge (Morgan et al., 1990).



273





Figure 2: (A) Determination and distribution of EPS (proteins and polysaccharides) in extracted EPS fractions and pellet of digested sludge for an ozone dose between 0 to 192 mg O_3/g COD, (B) effect of ozonation on protein and polysaccharide content, (C) Correlation between soluble EPS and soluble COD.

280 A non-significant change in protein concentration was observed for ozone doses 281 between 0 to 157 mg O₃/g COD (Figure 2B). However, the protein content was 282 reduced by 27% for an ozone dose of 192 mg O₃/g COD. Oxidation can cause 283 structural modification of proteins ranging from fragmentation of the polypeptide 284 backbone to aggregation by cross-linking between amino acid residues (Davies, 285 2005). Furthermore, ozone can oxidize amino acid residues, such as cysteine, 286 tryptophan and tyrosine (Cataldo, 2003; Meng et al., 2016) which should usually be 287 quantified by the BCA method (Wiechelman et al., 1988). However, the by-288 products of oxidation could not be quantified as proteins.

289 As for polysaccharides, no significant decrease in content was noted for doses up 290 to 192 mg O₃/g COD (Figure 2B). Polysaccharides were reported to react weakly 291 with ozone (Bablon et al., 1991). This is expected knowing that proteins have more 292 reactive functional groups (-NH₂, -SH, -COOH, amide linkages) than 293 polysaccharides (mostly –OH and ether linkages). Ozonation of β -D-glycosidic 294 linkages in polysaccharides leads to selective depolymerisation into short chain 295 polysaccharides and oligosaccharides (Wang et al., 1999). Using the phenol-296 sulfuric acid method, these oligosaccharides will be detected as polysaccharides, 297 thereby, the total sugar content will remain constant.

For the pellet residues, measured amounts of proteins and polysaccharides were significantly reduced during ozonation from 7.1 to 3.8 g/L at 192 mg O_3/g COD. Total content of proteins and polysaccharides reduced from 8.3 to 6.5 g/L using an ozone dose of 192 mg O_3/g COD. TB-EPS, LB-EPS and soluble-EPS content of the sludge changed significantly upon exposure to ozone compared to the non

303 ozonated sample. TB-EPS decreased from 0.37 to 0.29 g/L for an ozone dose of 304 192 mg O₃/g COD whereas the amount of LB-EPS and soluble-EPS increased 305 linearly from 0.34 to 0.52 g/L ($R^2 = 0.71$) and 0.52 to 1.9 g/L ($R^2 = 0.98$), 306 respectively.

307 Ozonation was found to have a significant effect on the distribution of proteins and 308 polysaccharides in various fractions of the digested sludge. Initially, 85% of 309 proteins and polysaccharides were concentrated in the pellet fraction, but after 310 ozonation 59% remained in the pellet (192 mg O_3/g COD). On the other hand, 311 proteins and polysaccharides in the soluble fraction increased from 6.2 to 29% 312 after ozonation (192 mg O_3/g COD).

313 During ozonation, the concentration of EPS in the soluble layer increased while the 314 amount of proteins and polysaccharides from the pellet was reduced as the ozone 315 dose was increased suggesting that ozonation causes the release of EPS from the 316 inner layer to the outer layer. Protein release to the soluble phase was higher than 317 that of polysaccharides. The increase in EPS content in the soluble layer correlated 318 with the COD solubilization (Figure 2C). These results suggest that ozonation 319 disintegrates sludge flocs and releases COD, proteins and polysaccharides from 320 the pellet into the soluble phase. The control showed that mechanical friction of the 321 pump did not cause any significant effect on the protein and polysaccharide 322 content and its distribution in the different fractions.

323 Three-dimensional EEM spectroscopy was applied to characterize the EPS 324 extracted from untreated and treated sludge (192 mg O_3/g COD). Peaks at four 325 different locations were identified according to the literature (Chen et al., 2003).

326 The fluorescence peak positions and fluorescence intensity of the different EPS 327 fractions are detailed in Table 1 and Figure S1 (Supplementary Information). The 328 peaks were associated with the presence of aromatic amino acids, e.g. 329 tryptophane in proteins (peak A), fulvic acid-like (peak B), soluble microbial by-330 products-like (peak C) and humic acid-like (peak D). EEM intensities of peaks 331 tended to decrease after ozonation. Intensity reduction of the fluorescence peaks 332 can be an indication of oxidation and removal of some of the molecular 333 functionalities responsible for fluorescence. Although protein content increased in 334 soluble EPS and LB-EPS, tryptophan and tyrosine are susceptible to oxidation by 335 ozone, thus, reducing the intensity of fluorescence peaks A and C (Figure S1).

Table 1: Impact of ozonation on peak intensities of the fluorescence spectra for soluble EPS, LB-EPS, and TB-EPS fractions of anaerobic digested sludge (A = tryptophan, B = fulvic acid-like, C = soluble microbial by-products-like, and

EPS	Ozone dose	Peak intensities			
fractions	mg O₃/g COD	А	В	С	D
Soluble	0	340	1000	270	880
	192	200	540	140	720
LB-EPS	0	220	440	200	300
	192	67	180	140	180
TB-EPS	0	860	970	910	570
	192	490	590	650	430

339 D=humic acid-like)

340 3.4. Observations of samples by scanning electron microscopy

341 SEM observations revealed a distinct difference in the morphology of the control 342 and the ozone treated sludge floc (Figure S2, Supplementary Information). The 343 untreated sludge samples consisted of smooth, dense and integrated structures. 344 with embedded cells in the sludge matrix. As the ozone dose increased, more 345 irregular porous and rough surface structures were observed in the treated 346 samples. Surface deformation and sludge floc disaggregation were observed in 347 sludge samples treated with a dose higher than 86 mg O₃/g COD. The morphology 348 modification of sludge agrees with the alteration of sludge properties, such as EPS, 349 which was confirmed by the release of soluble proteins.

350 3.5. Effect of ozonation on viability, enzymatic activity, ROS production and351 acetoclastic activity of anaerobic sludge

352 3.5.1. Viability and dehydrogenase activity assay

353 Modified microbial activity of anaerobic sludge following ozonation was 354 characterized by the determination of the biomass viability and the dehydrogenase 355 activity (Figure 3A). The primary ozone dose of 49 mg O_3/g COD inhibited by 57% 356 the relative viability of cells. Ozone treatment between 49 and 122 mg O₃/g COD 357 significantly tailed off the viable biomass with intact membrane, coupled with a 358 higher ratio of inactivated cells. The ozone treatment at doses higher than 157 mg 359 O₃/g COD resulted in significant lysis of biomass with a relative viability of less 360 than 5%. Therefore, significant inactivation of active biomass was observed by 361 ozonation at all tested doses. Membrane integrity defines the potential metabolic 362 activity of the intact cells; therefore, cells with damaged membranes can be 363 classified as permeabilized/dead cells (Foladori et al., 2010b). The influence of

364 ozonation on bacterial viability consists of progressive degradation initiated with the 365 physical alteration of membrane permeability and cell integrity, followed by the lysis 366 reaction (Thanomsub et al., 2002). The bacterial cell membrane is comprised 367 dominantly of lipids with abundant C=C double bonds as well as proteins (Winter et 368 al., 2008; Arts et al., 2015). Ozone is a strong electrophile and thus, can easily 369 react with unsaturated lipids via their nucleophilic -C=C- functionality leading to 370 cellular membrane decomposition and the release of cellular components, 371 including EPS. It has been reported that oxidation of C=C double bonds in lipids 372 forms malondialdehyde (MDA) (Han et al., 2016) causing decomposition of the 373 cellular membranes resulting in cell disruption and subsequent leakage of cellular 374 contents (Foladori et al., 2010b).



Figure 3: Effect of ozone dose on (A) relative viability, dehydrogenase activity, and
(B) intracellular ROS production.

380 3.5.2. Intracellular ROS production

381 Ozonation induced ROS in treated sludge at each ozone dose (Figure 3B). 382 Intracellular ROS augmented with an increase in ozone dosage. The ROS 383 concentration was 46 times higher than the control at the highest ozone 384 concentration of 192 mg O₃/g COD. The phenolic and olefinic groups and proteins 385 in the lipid bilayers of the bacterial cell wall are the primary oxidative sites leading 386 to the formation of ROS, such as hydroxyl radicals (OH), peroxides (RCOO) and 387 superoxide radical anions (O-O-) (Pryor et al., 1991). Subsequent reactions of 388 ROS with cellular components, such as lipids, proteins and nucleic acid leads to 389 cell disruption and decomposition and causing the release of intracellular 390 components (Baier et al., 2005). Thus, the significantly higher intracellular ROS 391 above 86 mg O_3/q COD confirms the potential of oxidative stress to trigger cell 392 membrane damage and enzyme inhibition for ozonated sludge.

393 3.5.3. Acetoclastic methane activity

394 The acetoclastic methanogenic activity of sludge was used to determine the effect 395 of ozonation on the anaerobic biodegradability of sludge. The acetoclastic 396 methanogenic yield of control and ozonated sludge are illustrated in Figure 4A. 397 Acetoclastic activity after short-term exposure to ozone showed a lag phase, which 398 increased as ozone dose increased. The initial inhibition of acetoclastic activity was 399 consistent with the significant decrease of dehydrogenase enzymatic activity and 400 loss of intact viable cells measured at the beginning of experiment. Similarly, the 401 complete inhibition of respiratory activity of activated sludge has been reported at 402 100 mg O₃/g TSS (Chu et al., 2008). However, approximately 95% of the

403 theoretical methane production (350 mL STD CH₄/g COD) was achieved in the 404 samples over 14 days despite the presence of a lag phase of 0.8 to 10 days in the 405 initiation of activity for all ozonated sludge. Furthermore, the dehydrogenase 406 activity of sludge increased during the incubation (192 mg O_3/g COD) (Figure 4B). 407 The cell membrane disintegration, alteration of permeability and interaction of 408 membrane proteins and lipids with ozone can inhibit the acetoclastic activity of 409 sludge. The extension of the activity test, up to 80 days, demonstrated the recovery 410 of microbial activity of ozonated sludge due to the potential recovery of the 411 bacterial community.



Figure 4: (A) Impact of exposure to ozone on acetoclastic methanogenic activity of
anaerobic sludge, and (B) comparison of dehydrogenase activities and acetoclastic
activity for D0 and D5 (D0=0 mg O₃/g COD, D1=49 mg O₃/g COD, D2=86 mg O₃/g
COD, D3=122 mg O₃/g COD, D4=157 mg O₃/g COD, D5=192 mg O₃/g COD, B5=
control).

420 3.6. Potential mechanisms of improving of anaerobic biodegradability

421 Ozonation was shown to increase the solubilization of sludge mainly via partial 422 disintegration/solubilization of the sludge matrix and damage to the cell membrane 423 integrity. Ozonation can disintegrate the sludge matrix and release COD, proteins 424 and polysaccharides from the pellet into the soluble phase, thereby, promoting the 425 enhancement of methane production during anaerobic digestion. Furthermore, the 426 reduction in viability of the sample suggests that the broken cells can release 427 intracellular matter into the solution. The enhancement in methane production may 428 not only be ascribed to solubilization and it also can be influenced by the increase 429 of the biodegradability of organic products generated during ozonation, e.g. the 430 products of oxidation by ozone of olefins and aromatic compounds are more 431 biodegradable than their parent compounds (Hübner et al., 2015). As a result of 432 the increase in solubilization and biodegradability, anaerobic degradation can be 433 enhanced, improving methane yield and accelerating digestion time. An overdose 434 of ozone can reduce the methane production potential, probably due to the 435 potential mineralization of the solubilization matter. Additionally, an overdose of 436 ozone can minimize the viability of anaerobic biomass and enzymatic activity which 437 could have a negative impact on the stability of anaerobic digesters in a post-438 treatment configuration.

440 4. Conclusions

441 The effect of ozonation on anaerobic digested sludge and its impact on microbial 442 response were evaluated by monitoring methane production, EPS, microbial 443 activity, viability and ROS. The EPS matrix was impacted by ozonation, resulting in 444 the release of COD, proteins and polysaccharides into the soluble phase. 445 Ozonation, initially and temporarily, reduced biomass viability and activity, but 446 following this lag phase, ozonation enhanced methane production. The optimized 447 ozone dose of 86 mg O₃/g COD increased the methane yield up to 52% and the 448 methane production rate up to 95%. Therefore, ozonation could be used to 449 increase the capacity of anaerobic digesters.

450 Acknowledgements

This study was funded by the Natural Sciences and Engineering Research Council of Canada (NSERC), Veolia, EnviroSim and the City of Repentigny. We thank the Comisión Nacional de Investigación Científica y Tecnológica (CONICYT, Chile) for the awarded Ph.D. fellowship. The authors also thank Pinnacle LLC (USA) for their technical contribution and for providing the ozone generator required to perform this study.

457

458

459

461 **References**

- Appels, L., Baeyens, J., Degrève, J., & Dewil, R. (2008). Principles and potential of
 the anaerobic digestion of waste-activated sludge. *Progress in Energy and Combustion Science, 34*(6), 755-781.
- Arts, I. S., Gennaris, A., & Collet, J.-F. (2015). Reducing systems protecting the
 bacterial cell envelope from oxidative damage. *FEBS Letters*, 589(14), 15591568.
- Bablon, G., Bellamy, W. D., Bourbigot, M. M., Daniel, F. B., Doré, M., Erb, F.,
 Gordon, G., Langlais, B., Laplanche, A., Legube, B., Martin, G., Masschelein,
 W. J. Pacey, G., Reckhow, D. A., & Ventresque, C. (1991). Fundamental
 aspects. In B. Langlais, D. A. Reckhow, & D. R. Brink, Ozone in water
 treatment: application and engineering : cooperative research report (pp. 11132). Chelsea, Michigan: Lewis Publishers.
- 474 Baier, M., Kandlbinder, A., Golldack, D., & Dietz, K. J. (2005). Oxidative stress and
 475 ozone: perception, signalling and response. *Plant, Cell & Environment, 28*(8),
 476 1012-1020.
- 477 Battimelli, A., Millet, C., Delgenes, J., & Moletta, R. (2003). Anaerobic digestion of
 478 waste activated sludge combined with ozone post-treatment and recycling.
 479 Water Science and Technology, 48(4), 61-68.
- 480 Caravelli, A., Giannuzzi, L., & Zaritzky, N. (2004). Effect of chlorine on filamentous
 481 microorganisms present in activated sludge as evaluated by respirometry and
 482 INT-dehydrogenase activity. *Water Research, 38*(9), 2395-2405.
- 483 Carballa, M., Manterola, G., Larrea, L., Ternes, T., Omil, F., & Lema, J. M. (2007).
 484 Influence of ozone pre-treatment on sludge anaerobic digestion: removal of
 485 pharmaceutical and personal care products. *Chemosphere, 67*(7), 1444486 1452.
- 487 Carrère, H., Dumas, C., Battimelli, A., Batstone, D. J., Delgenes, J. P., Steyer, J. P.,
 488 & Ferrer, I. (2010). Pretreatment methods to improve sludge anaerobic
 489 degradability: a review. *Journal of Hazardous Materials, 183*(1-3), 1-15.
- 490 Cataldo, F. (2003). On the action of ozone on proteins. *Polymer Degradation and*491 *Stability*, 82(1), 105-114.
- Chen, W., Westerhoff, P., Leenheer, J. A., & Booksh, K. (2003). Fluorescence
 excitation Emission matrix regional integration to quantify spectra for
 dissolved organic matter. *Environmental Science & Technology*, *37*(24), 57015710.
- Chen, Y., Chen, H., Zheng, X., & Mu, H. (2012). The impacts of silver nanoparticles
 and silver ions on wastewater biological phosphorous removal and the
 mechanisms. *Journal of Hazardous Materials,* 239, 88-94.
- Chiellini, C., Gori, R., Tiezzi, A., Brusetti, L., Pucciarelli, S., D'Amato, E., Chiavola,
 A., Sirini, P., Lubello, C., & Petroni, G. (2014). Ozonation effects for excess

- 501 sludge reduction on bacterial communities composition in a full-scale 502 activated sludge plant for domestic wastewater treatment. *Environmental* 503 *technology*, *35*(12), 1462-1469.
- 504 Chu, L. B., Yan, S. T., Xing, X. H., Yu, A. F., Sun, X. L., & Jurcik, B. (2008).
 505 Enhanced sludge solubilization by microbubble ozonation. *Chemosphere*, 506 72(2), 205-212.
- 507 Davies, M. J. (2005). The oxidative environment and protein damage. *Biochimica* 508 *et Biophysica Acta (BBA)-Proteins and Proteomics, 1703*(2), 93-109.
- 509 Déléris, S. (2001). *Réduction de la production de boue lors du traitement des eaux*510 *résiduaires urbaines. Analyse du traitement combiné : ozonation et traitement*511 *biologique.* (PhD thesis, Institut National des Sciences Appliquées de
 512 Toulouse, Trance).
- 513 Foladori, P., Andreottola, G., & Ziglio, G. (2010a). *Sludge reduction technologies in* 514 *wastewater treatment plants*. London, U.K:, IWA Publishing.
- Foladori, P., Tamburini, S., & Bruni, L. (2010b). Bacteria permeabilisation and
 disruption caused by sludge reduction technologies evaluated by flow
 cytometry. *Water Research, 44*(17), 4888-4899.
- Han, X., Wang, Z., Wang, X., Zheng, X., Ma, J., & Wu, Z. (2016). Microbial
 responses to membrane cleaning using sodium hypochlorite in membrane
 bioreactors: Cell integrity, key enzymes and intracellular reactive oxygen
 species. *Water Research, 88*, 293-300.
- Hübner, U., von Gunten, U., & Jekel, M. (2015). Evaluation of the persistence of
 transformation products from ozonation of trace organic compounds A
 critical review. *Water Research, 68*, 150-170.
- Labelle, M. A., Ramdani, A., Deleris, S., Gadbois, A., Dold, P., & Comeau, Y.
 (2011). Ozonation of endogenous residue and active biomass from a
 synthetic activated sludge. *Water Science and Technology*, *63*(2), 297-302.
- Lay, J.-J., Li, Y.-Y., & Noike, T. (1996). Effect of moisture content and chemical
 nature on methane fermentation characteristics of municipal solid wastes. *Journal of Environmental Systems and Engineering*, 552, 101-108.
- Liu, H., & Fang, H. H. P. (2002). Extraction of extracellular polymeric substances (EPS) of sludges. *Journal of Biotechnology, 95*(3), 249-256.
- Meng, L., Xi, J., & Yeung, M. (2016). Degradation of extracellular polymeric
 substances (EPS) extracted from activated sludge by low-concentration
 ozonation. *Chemosphere, 147*, 248-255.
- Morgan, J., Forster, C., & Evison, L. (1990). A comparative study of the nature of
 biopolymers extracted from anaerobic and activated sludges. *Water Research, 24*(6), 743-750.
- 539 Pryor, W. A., & Church, D. F. (1991). Aldehydes, hydrogen peroxide, and organic
 540 radicals as mediators of ozone toxicity. *Free Radical Biology and Medicine*,
 541 *11*(1), 41-46.

- 542 Rakness, K. L. (2005). Ozone in drinking water treatment: process design,
 543 operation, and optimization. Denver, Colorado: American Water Works
 544 Association.
- Saha, M., Eskicioglu, C., & Marin, J. (2011). Microwave, ultrasonic and chemomechanical pretreatments for enhancing methane potential of pulp mill
 wastewater treatment sludge. *Bioresource technology*, 102(17), 7815-7826.
- 548 Sheng, G.-P., Yu, H.-Q., & Li, X.-Y. (2010). Extracellular polymeric substances
 549 (EPS) of microbial aggregates in biological wastewater treatment systems: a
 550 review. *Biotechnology Advances, 28*(6), 882-894.
- Sheng, Z., & Liu, Y. (2011). Effects of silver nanoparticles on wastewater biofilms.
 Water Research, *45*(18), 6039-6050.
- Thanomsub, B., Anupunpisit, V., Chanphetch, S., Watcharachaipong, T.,
 Poonkhum, R., & Srisukonth, C. (2002). Effects of ozone treatment on cell
 growth and ultrastructural changes in bacteria. *The Journal of General and Applied Microbiology, 48*(4), 193-199.
- 557 Von Mersi, W., & Schinner, F. (1991). An improved and accurate method for
 558 determining the dehydrogenase activity of soils with iodonitrotetrazolium
 559 chloride. *Biology and Fertility of Soils*, *11*(3), 216-220.
- Wang, Y., Hollingsworth, R. I., & Kasper, D. L. (1999). Ozonolytic depolymerization
 of polysaccharides in aqueous solution. *Carbohydrate Research*, *319*(1), 141147.
- Weemaes, M., Grootaerd, H., Simoens, F., & Verstraete, W. (2000). Anaerobic
 digestion of ozonized biosolids. *Water Research*, *34*(8), 2330-2336.
- Wiechelman, K. J., Braun, R. D., & Fitzpatrick, J. D. (1988). Investigation of the
 bicinchoninic acid protein assay: identification of the groups responsible for
 color formation. *Analytical Biochemistry*, *175*(1), 231-237.
- Winter, J., Ilbert, M., Graf, P., Özcelik, D., & Jakob, U. (2008). Bleach activates a
 redox-regulated chaperone by oxidative protein unfolding. *Cell*, *135*(4), 691701.
- 571 Yin, J., Tan, X., Ren, N., Cui, Y., & Tang, L. (2005). Evaluation of heavy metal
 572 inhibition of activated sludge by TTC and INT-electron transport system
 573 activity tests. *Water Science and Technology, 52*(8), 231-239.
- You, G., Hou, J., Xu, Y., Wang, C., Wang, P., Miao, L., Ao, Y., Li, Y., & Lv, B.
 (2015). Effects of CeO 2 nanoparticles on production and physicochemical characteristics of extracellular polymeric substances in biofilms in sequencing batch biofilm reactor. *Bioresource Technology*, *194*, 91-98.
- Yu, G. H., He, P. J., Shao, L. M., & Zhu, Y. S. (2008). Extracellular proteins,
 polysaccharides and enzymes impact on sludge aerobic digestion after
 ultrasonic pretreatment. Water Research, 42(8), 1925-1934.
- 581



Figure S1: EEM spectra of the extracted EPS fractions for untreated and treated
sludge (192 mg O₃/g COD).



Figure S2: Scanning electron micrographs imaging of anaerobic sludge exposed to 0 mg O_3/g COD (A), 86 mg O_3/g COD (B), and 192 mg O_3/g COD (C).