

CHEMICALLY ACTIVATED CARBON USING PEAT SOIL FOR HEAVY  
METALS ADSORPTION IN INDUSTRIAL WASTEWATER

FAHRULRAZI BIN MD JAMIEN

A Thesis submitted in fulfilment of the  
requirement for the award of the degree of  
Masters of Science

Faculty of Applied Sciences and Technology  
Universiti Tun Hussein Onn Malaysia

JANUARY 2019

For my beloved mother, Dalina binti Kariban. My late father which I miss every day, Allahyarham Md Jamien bin Salman, family members and friends. Not forgetting my best friend Khawarizmi bin Mohd Jafery and Abdul Jalil bin Abdul Rahim who have continuously supporting me all time long.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ACKNOWLEDGEMENT

The author would like to express his sincere appreciation to his inspiring and desirable Project Supervisor, Assoc. Prof. Dr. Zaidi Bin Embong and his wife, Pn Salawati Binti Ahmad for the support given throughout the duration for this research.

The cooperation given by the Faculty of Mechanical and Manufacturing Engineering (FKMP), Faculty of Civil and Environment Engineering (FKAAS) and Microelectronics and Nanotechnology – Shamsuddin Research Center (MiNT – SRC), Universiti Tun Hussein Onn Malaysia (UTHM) are also appreciated for providing the consultancies, equipments and space to run out the analysis. Appreciation also goes to everyone who has been involved directly and indirectly towards the compilation of this thesis. A thousand thanks to Research Centre for Soft Soil (RECESS), UTHM for providing a working station to do this research.



PERPUSTAKAAN TUNKU TUNJALINAH

## ABSTRACT

The present work is aimed to produce peat soil activated carbon (PSAC) for the removal of heavy metal ions in industrial wastewater. Activated carbon from peat has successfully produced by chemical activation process using sulphuric acid as activating agents. The effect of heating temperature on the carbon content, the physical and chemical characterizations of peat activated carbons were studied. From this study, peat soil heated at 400°C possess the highest carbon content with concentration of 95.44 % due to the complete degradation of organic matter. The thermogravimetric analysis (TGA) and its derivative thermogravimetric (DTG) confirm the finding where at temperature  $\approx 400^\circ\text{C}$ , peat undergo complete degradation of matter. The heating temperature was set to constant at 400°C for activation process. The BET specific surface area of the activated carbon obtained was  $1298.84\text{ m}^2\text{ g}^{-1}$ . The Raman spectrum gave to main peaks at 1368 and 1590  $\text{cm}^{-1}$  which is attributed to diamond, D and graphitic, G band, respectively. FTIR spectrum analysis showed the carboxyl, ketone, aldehyde, methylene and hydroxyl groups are present on the surface of PSAC due to the activation process with  $\text{H}_2\text{SO}_4$ . Point of zero charge ( $\text{pH}_{\text{pzc}}$ ) of activated carbon is 5.60 which available for heavy metal adsorption due to the adsorbent surface charge was negative. The heavy metal adsorption capacity is evaluate by using an adsorption test. The heavy metal elemental compositions (Cu, Zn, Al, Cr, Pb and Fe) in the industrial wastewater were analysed using ICP – MS. The adsorption test was conducted using batch experiment method where various dosage of PSAC (0.0, 0.2, 0.4, 0.6, 0.8, 1.0 g) mixed to 25 ml water samples. From the adsorption test, the PSAC can be used as adsorbent for industrial waste water treatment.

## ABSTRAK

Kajian terikini bertujuan untuk menghasilkan karbon teraktif tanah gambut bagi penyingkiran ion-ion logam berat yang terkandung dalam air sisa industri. Karbon teraktif yang terhasil dari tanah gambut ini berjaya dihasilkan melalui kaedah rawatan pengaktifan kimia yang menggunakan asid sulfurik sebagai bahan pengaktifan. Antara kajian yang dijalankan dalam penyelidikan ini adalah kesan suhu pemanasan terhadap kandungan karbon dalam tanah gambut, dan percirikan fizikal dan kimia karbon teraktif. Dalam kajian ini, tanah gambut yang dipanaskan pada suhu 400°C menghasilkan kandungan karbon yang amat tinggi iaitu sebanyak 95.44%, yang disebabkan oleh penguraian lengkap bahan organik. Analisis termogravimetri (TGA) dan derivatifnya (DTG) mengesahkan dapatan tersebut dimana penguraian lengkap berlaku pada suhu sekitar 400°C. Suhu pemanasan tersebut adalah ditetapkan sebagai pemalar bagi proses pengaktifan. Luas permukaan spesifik BET karbon teraktif adalah 1298.84 m<sup>2</sup> g<sup>-1</sup>. Spektrum Raman menunjukkan puncak utama pada 1368 dan 1590 cm<sup>-1</sup> yang masing-masing mewakili jalur berlian, D dan grafit, G. Analisis spectrum inframerah FTIR menunjukkan bahawa kumpulan karboksil, ketone, aldehida, metilena dan hidroksil terhasil pada permukaan yang terjadi semasa proses pengaktifan Bersama H<sub>2</sub>SO<sub>4</sub>. Nilai titik bercaj sifar (pH<sub>pzc</sub>) karbon teraktif adalah 5.60 dimana sesuai untuk serapan logam berat dimana caj permukaan bahan serapan adalah negatif. Ujikaji penyerapan dijalankan untuk mengkaji muatan serapan logam berat. Logam berat (Cu, Zn, Al, Cr, Pb and Fe) dalam spesimen air sisa industri dianalisis menggunakan ICP – MS. Ujikaji penyerapan ini dijalankan dengan dos karbon teraktif iaitu jisim bahan bagi setiap 25 ml spesimen air. Maka hasil dari kajian ini, karbon teraktif terhasil dari tanah gambut sesuai digunakan sebagai bahan penyerap untuk merawat air sisa industri.

## CONTENTS

	<b>TITLE</b>	<b>i</b>
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>CONTENTS</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>xi</b>
	<b>LIST OF FIGURES</b>	<b>xii</b>
	<b>LIST OF LIST OF EQUATIONS</b>	<b>xvi</b>
	<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xvii</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Background of study	1
	1.2 Problems statement	3
	1.3 Objectives	4
	1.4 Significance of study	5
	1.5 Scopes of study	5
<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	<b>7</b>
	2.1 Peat soil	7
	2.2 Activated carbon	8
	2.3 The preparation of activated carbon from different precursors	8
	2.4 Activating agent for the preparation of AC	12
	2.5 Application of peat soil activated carbon	14

2.5.1	Application of peat soil activated carbon on metal and non-metal adsorption	14
2.6	Porous structure in activated carbon	15
2.7	Characterization of activated carbon	16
2.7.1	Elemental composition and morphology study of activated carbon via SEM-EDX	16
2.7.2	Thermoanalysis study	27
2.7.3	Surface area using N <sub>2</sub> adsorption-desorption test	28
2.7.4	Graphitic properties using laser Raman spectroscopy	31
2.7.5	Surface functional group using FTIR spectroscopy	36
2.7.6	Point of zero Charge (pH <sub>pzc</sub> ) of activated carbon	40
2.8	Elemental composition of heavy metals in wastewater	42
2.9	Error calculation	44
<b>CHAPTER 3</b>	<b>METHODOLOGY</b>	<b>45</b>
3.1	Peat soil sampling	46
3.2	Peat soil sample preparation	48
3.3	Carbon extraction at various heating temperature	48
3.4	Preparation of peat soil activated carbon (PSAC)	49
3.5	Industrial waste water sampling	50
3.6	Adsorption test	51
3.7	Characterization methods	52
3.7.1	Elemental composition analysis and microscopic studies using SEM - EDX	52
3.7.2	Graphitic content investigation using laser Raman	53
3.7.3	The specific surface area and porosity and determination using BET surface analyzer	54



3.7.4	Surface functional group study using Infrared Spectrophotometry (FTIR)	55
3.7.5	Elemental composition analysis of water samples using ICP - MS	56
3.7.6	Determination of point of zero charge ( $\text{pH}_{\text{pzc}}$ )	57
3.8	Thermal analysis	57
<b>CHAPTER 4</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>58</b>
4.1	The optimum heating temperature and physical characteristics of peat	58
4.1.1	The optimum heating temperature	58
4.1.2	The evolution of carbon and silica content under pyrolysis process at various heating temperatures	60
4.1.3	Surface morphology study of raw, heat treated peat and peat soil activated carbon	62
4.1.4	Pore structure of the carbon	64
4.2	The molecular structure of heat treated peat and peat soil activated carbon	67
4.2.1	Laser Raman analysis of carbon species at various heating temperatures (200-700°C)	67
4.2.2	The deconvolution of Raman spectrum for raw peat, peat carbon at optimum temperature and peat soil activated carbon (PSAC)	69
4.3	Surface functional groups of heat treated peat and peat soil activated carbon	74
4.3.1	FTIR analysis of carbon species at various heating temperature (200-700 °C)	74
4.3.2	The comparison of FTIR shifts for raw peat soil, at optimum temperature (400°C) and peat soil activated carbon (PSAC)	76
4.3.3	Point of zero charge ( $\text{pH}_{\text{pzc}}$ )	79



4.4	Elemental composition of heavy metal in polluted water sample from industrial area	81
4.5	The heavy metal concentration on polluted water between pre and post absorption test	84
<b>CHAPTER 5</b>	<b>CONCLUSIONS</b>	<b>89</b>
5.1	Summary	89
5.2	Recommendations for Future Work	90
	<b>REFERENCES</b>	<b>92</b>
	<b>APPENDICES</b>	<b>108</b>
	<b>VITA</b>	



**PTTA UTHM**  
PERPUSTAKAAN TUNKU TUN AMINAH

**LIST OF TABLES**

2.1	The preparation of AC from different precursors and activation process	11
2.2	The application of activated carbon from peat for metal and non-metal adsorption	15
2.3	The point of zero charge for different activated carbon	41
3.1	Soil sample labelling	48
3.2	Water samples labelling	51
4.1	Characteristics of the porous structure of carbon	64
4.2	The intensity ratio, $R$ of specimens	72
4.3	The heavy metals concentration at pre and post-adsorption test with WHO limitation	88



## LIST OF FIGURES

2.1	The working principle of SEM	17
2.2	A schematic diagram of EDX system in SEM	18
2.3	A typical EDX spectrum	19
2.4	The micrographs of AC of olive cake obtained from SEM at different magnifications	20
2.5	SEM images of the (a) peat soil, (b) AC peat soil	20
2.6	SEM micrographs of jackfruit peel at T = 350°C	21
2.7a	SEM micrograph of a raw jute fiber	21
2.7b	SEM micrograph of CO <sub>2</sub> activated jute fiber	22
2.8	SEM micrographs of (a) raw date stone, (b) pyrolised date stone at 500°C, (c) pyrolised date stone at 600°C, (d) pyrolised date stone at 700°C, (e) activated date stone at 700°C with 1 hour combustion, and (f) activated date stone at 700°C with 3 hours combustion	23
2.9a	SEM micrograph of coconut button AC at x2000	24
2.9b	SEM micrograph of coconut button AC at x5000	24
2.10	The micrograph of untreated peat (top) and HCl-treated peat (bottom)	25
2.11	Dried peat micrograph (x500)	26
2.12	SEM image of peat	26

2.13	TGA (red) and DTG (blue) curves	27
2.14	IUPAC classification of adsorption isotherms	29
2.15	Linearised BET plot	30
2.16	Effect of the chemical (KOH) to precursor (corn) ratio on BET surface area	31
2.17	The diagram of Raman spectrometer showing essential features	32
2.18	Raman transition diagram	33
2.19	Raman spectra of PSAC	34
2.20	(a) $sp^3$ -hybrid and (b) $sp^2$ -hybrid orbital	35
2.21	The graphite structure	35
2.22	An example of armchair – edge and zigzag – edge	36
2.23	FTIR spectrometer optical layout	37
2.24	FTIR spectra of peat soil and PSAC	38
2.25	The oxygen – containing functional groups from PSAC	39
2.26	Determination of $pH_{pzc}$	41
2.27	Components of an ICP –MS	43
2.28	Positive ions generation in the plasma	43
3.1	Overall research flowchart	45
3.2	Marked point shows the peat soil sampling location at Kampung Parit Nipah, Senggarang, Johor (top), and five sampling sites (bottom)	47
3.3	An electric furnace for carbon extraction from peat soil	49
3.4	Arrow marks show Sri Sulong, Sri Gading and Parit Raja industrial park, respectively	50
3.5	The PSAC dosage per 25 ml water sample	51
3.6	SEM – EDX instrument	52
3.7	Laser Raman spectroscopy	53
3.8	BET instrumentation (left) and degasser equipment (right)	54

3.9	Infrared Spectrophotometry (FTIR) instrument	55
3.10	ICP – MS instrument	56
4.1	The variation of C-Si composition at various heating temperature	59
4.2	(a) TGA and (b) DTG curve of the peat	61
4.3	Surface morphology of raw peat (x850 magnification)	62
4.4	Surface morphology of peat heated at optimum temperature (400°C) (x850 magnification)	63
4.5	Surface morphology of peat soil activated carbon (x850 magnification)	63
4.6	N <sub>2</sub> adsorption-desorption isotherm of raw peat, peat at an optimum heating temperature (400°C), and PSAC	66
4.7	Laser Raman spectrum of peat soil at various heating temperatures	68
4.8	The comparison of Raman shift for raw peat soil, heated at 400°C, PSAC and post-adsorption PSAC	70
4.9	Raman spectrum of the original raw peat soil (left) and spectrum deconvolution of D and G band (right)	71
4.10	Raman spectrum of the original heated peat soil at 400°C (left) and spectrum deconvolution of D and G band (right)	73
4.11	Raman spectrum of the PSAC (left) and spectrum deconvolution of D and G band (right)	73
4.12	FTIR spectrum for raw peat and peat baked at various temperatures	75
4.13	FTIR spectra for raw peat, peat carbon at an optimum temperature (400°C) and PSAC	78
4.14	Determination of pH <sub>pzc</sub> using pH drift method	79



PT TANA UTAMA  
PERPUSTAKAAN TUNKU TUN AMINAH

4.15	The changes in pH of wastewater samples at post-adsorption test	80
4.16	The distribution of elemental composition of heavy metal in polluted water at different sampling sites	84
4.17	Comparative evaluation of different heavy metal elemental composition	85



**LIST OF EQUATIONS**

2.1	BET equation	29
2.2	Monolayer adsorbed gas quantity	29
2.3	BET constant	29
2.4	Total surface area	30
2.5	Specific surface area	30
2.6	Standard deviation	44



**PTTA UTHM**  
PERPUSTAKAAN TUNKU TUN AMINAH

**LIST OF SYMBOLS AND ABBREVIATIONS**

AC	- Activated carbon
Al	- Aluminium
As	- Arsenic
at %	- Atomic percentage
C	- Carbon
C <sub>e</sub>	- Equilibrium concentration of adsorbate in solution
CO	- Carbon monoxide
CO <sub>2</sub>	- Carbon dioxide
COOH	- carboxyl
COT	- Carbon extracted at an optimum temperature
Cr	- Chromium
Cu	- Copper
D - band	- Diamond band
Fe	- Iron
FTIR	- Fourier Transformed Infrared Spectroscopy
G - band	- Graphitic band
H <sub>2</sub> SO <sub>4</sub>	- Sulphuric acid
H <sub>3</sub> PO <sub>4</sub>	- Phosphoric acid
HCl	- Hydrochloric acid
HNO <sub>3</sub>	- Nitric acid
ICP - MS	- Inductively Coupled Plasma – Mass Spectrometry
I <sub>D</sub>	- Intensity of diamond band
I <sub>G</sub>	- Intensity of graphitic band
K <sub>2</sub> CO <sub>3</sub>	- Potassium carbonate
K <sub>2</sub> O	- Potassium oxide



KBr	- Potassium bromide
keV	- Kilo electron volt
m	- Mass of specimen
$m^2 g^{-1}$	- Squared meter per gram
$m^3 h^{-1}$	- Cubic meter per hour
$mg g^{-1}$	- Milligram per gram
$mg L^{-1}$	- Milligram per litre
$N_2$	- Nitrogen gas
$N_A$	- Avogadro's number
NaOH	- Sodium hydroxide
Ni	- Nickel
nm	- Nanometer
$O_2$	- Oxygen
OH	- hydroxyl
P	- Phosphorus
P	- Equilibrium pressure
$P_0$	- Saturation pressure
Pb	- Lead
$pH_{pzc}$	- Point of zero charge
$pH_{sol}$	- pH of solution
ppb	- Part per billion
PSAC	- Peat soil activated carbon
PSAC - PA	- Peat soil activated carbon after adsorption test (post adsorption)
$q_e$	- Metal uptake capacity
$q_m$	- Maximum capacity of adsorbent
R	- Intensity ratio
s	- Molecular cross section of adsorbing materials
$S_{BET}$	- Specific surface area
SEM - EDX	- Scanning Electron Microscope – Energy Dispersive X – Ray spectroscopy
Si	- Silicon
$S_{total}$	- Total surface area
v	- Adsorbed gas quantity

$V_m$	- Monolayer adsorbed gas quantity
Zn	- Zinc
ZnCl <sub>2</sub>	- Zinc chloride
°C min <sup>-1</sup>	- Degree Celcius per minute
μm	- micrometer



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background of study

Economic bloom and high living standards causes the industrial revolution to increase. Rapid industrialization causes the heavy metal contaminants being discharged into the environment from their wastewater (Amuda, Giwa, & Bello, 2007a). One of the key topics that have attracted attention globally is the water contaminant released from industrial wastewater due to the negative impact in environment and biological systems (Sabela et al., 2016). Heavy metal pollution may come from many industries such as electronic fabrications, paints and pigments and manufacturing processes. Wastewater commonly includes aluminium, chromium, lead, zinc, iron and copper (Amuda, Giwa, & Bello, 2007b; Salam, Reiad, & Elshafei, 2011).

Al compound is shown to be neurotoxic if it enters the bloodstream. Bone mineralization disorder and defects of the brain may be occur for the people who receive an excessive exposure of Al (Al-Muhtaseb, El-Naas, & Abdallah, 2008). Cr is suspected to be a carcinogenic as it affects the kidney, liver and causes diarrhea and dermatitis (Rai et al., 2016). According to El-Wakil, El-Maaty, & Awad, (2014), Pb is the most toxic element even in a low concentration. Pb toxicity may lead to the nephritic syndrome, hepatitis, anaemia and several diseases such as nervous system, kidney and liver problems. Zn is essential to physiological functions of living tissue and regulate many bio-chemical processes. However, excessive consumption of Zn might cause vomiting, kidney and stomach damage, and skin problems (Amuda et. al., 2007b). Fe is essential for human as it plays a main role for oxygen transportation in red blood cell. But there are some consideration that makes water is un-usable like metallic taste, stains and odour (Myalowenkosi, Kwanele, & Suvadhan, 2015). In contrast, the Fe may precipitate a dark sludge when Fe in water exposed to air in

atmospheric pressure and becomes oxidised or ferric form that will not dissolved in water, and influence the ferruginous bacteria resulting in neurological disorder (A. Akl, Yousef, & AbdElnasser, 2013). Heavy metal such as Cu tends to accumulate in living organism resulting various diseases and health disorder. The excessive exposure of Cu whether direct or indirect causes Cu to accumulate in the liver and produces gastrointestinal problems (Imamoglu & Tekir, 2008). Because of the above factors, there is a significance to remove these metals from wastewater in conjunction with prevention of metal pollutant by effluents of toxic properties.

There are several ways to remove heavy metal composition from wastewater such as oxidation (Gunatilake SK, 2015), reverse osmosis (Aljendeel, 2011), membrane filtration (Qdais & Moussa, 2004) and adsorption (I. A. W. Tan, Chan, Hameed, & Lim, 2016).

Adsorption of heavy metal on activated carbon conforms to be the effective and efficient technique in this application (Myalowenkosi et al., 2015). Adsorption of heavy metal on adsorbents such as activated carbon has been used as an effective adsorbent. Activated carbon has unique characteristics such as highly developed porosity, large internal surface area, surface charge, surface functional groups and the adsorption capabilities of metal ion in activated carbon (El-Wakil et al., 2014).

There are several ways to produce activated carbon such as physical, chemical and also microwave assisted activation method. Physical activation method refers to a mechanism that include pyrolysis process under atmospheric pressure, followed by an activation process using oxidizing gas such as steam, CO<sub>2</sub>, N<sub>2</sub> or air at high temperature ranges from 800 to 1100°C. On the other hand, chemical activation process is a process that includes mixing step of chemical agent and precursor upon heat treatment in at temperature ranges from 400 to 600°C under atmospheric condition. High carbon yield obtained from chemical activation method compared to physical one (Rashidi & Yusup, 2017). It provides economical viable as it has lower activation temperature and shorter processing time. Additionally, activated carbon prepared from microwave heating also undergoes chemical treatment. Microwave heating approach was used as it provide rapid heating rate compared to conventional electric furnace. However, there were different in physiochemical properties of activated carbon from microwave heating where the surface area of activated carbon using furnace was exceptionally higher than microwave assisted (Rashidi & Yusup, 2017).

Generally, raw materials from various agricultural by-products have been used such as tamarind seed (Mopoung, Moonsri, Palas, & Khumpai, 2015), oil palm bunch (Wahyuningsih & Yusri, 2016), olive stone (Gautam et al., 2015), rice husk (Manoj Kumar Reddy, Krushnamurthy, K Mahammadunnisa, Dayamani, & Ch Subrahmanyam, 2014), coconut button (Anirudhan & Sreekumari, 2011), apple wastes (Hesas, Arami-Niya, Mohd, Daud, & Sahu, 2013) and jackfruit peel (Prahas, Kartika, Indraswati, & Ismadji, 2008).

From those raw materials, peat is one of the rich sources of carbon and abundant. Compared to other soils such as acrisols and fluvisols, peat has the greater carbon content. Acrisols is a kaolinitic-content soil which has mean pH of 4.5 and high mineral salt element such as Mg, Ca, Na and K (Tho & Hoa, 2017). On the other hand, fluvisols is an acid-sulphate soils which dominant in sea sediment. Fluvisols has greater amount of Al with low pH value of 3.5 (Kluiving, De Ridder, Van Dasselaar, Roozen, & Prins, 2016). Acrisols and fluvisols have low carbon content. Thus peat offer little economic value and wide range of applications. The carbon content from peat is contributed from the decaying plant residues. Furthermore, peat has high carbon and organic matter that make it important for metal uptake by the sorbent. Thus, peat can be modified in order to improve the sorption capacity since biosorption of peat is inexpensive and large spectrum of applications. Peat also consists of variety of surface functional groups such as hydroxyl, lactone, phenolic and carboxyl groups that plays a main role in complexation and metal ion exchange during ion fixation (Batista et al., 2009; Hartman, Chen, & Hatcher, 2015; Xiong & Mahmood, 2010). The study of activated peat as adsorbent material for heavy metal adsorption is still lack and less information could be obtained on the adsorption properties. Thus, the study on activated peat from different activation method, type of pollutant and activating agent. The previous work on peat will be discussed in Literature Review.

## **1.2 Problems statement**

The industrial wastewater such as electronic factories contribute the heavy metal contaminants that may lead to hazardous effect for biological life and environment. Wastewater polluted by heavy metal should undergo treatment before being discharged into the drainage systems. Adsorption method using activated carbon is one of the effective way to remove heavy metal contaminants in wastewater (Kumar

& Jena, 2017). However, the materials used as precursors have different capability to adsorb different type of metal ions due to its high adsorption capacities and the functional groups on the surface of activated carbon (Sabela et al., 2016). The effective and inexpensive technologies capable of treating wastewater rich in metal contaminants and biosorption has emerged as a viable technique for metal removal. Biosorption offers advantages including minimal production of chemical or biological sludge and efficient removal and no nutrient requirement (Batista et al., 2009). In previous work on peat as adsorbent for metal removal in wastewater, there are some activation reagent used to activate peat such as HCl (Batista et al., 2009),  $\text{H}_2\text{PO}_3$  (Mudjijati et al., 2000), iron coated peat (Kasiulienė et al., 2018) and  $\text{ZnCl}_2$  (Varila et al., 2017). However in this study,  $\text{H}_2\text{SO}_4$  was used as an activating agent. In previous study on metal sorption by activated peat, less type of metal concerned such as Cr, Cu, Ni, Cd, and As. However, in present work, a several type of metals that has different kind of toxicity such as Al, Fe, Zn and Pb will be study and comprehend their sorption capability.

### 1.3 Objectives

The aim of this research is to generate activated carbon from peat soil activated with sulphuric acid for adsorption of heavy metal contaminants. To achieve the aim of the research, a study was carried out with the following objectives:

1. To determine the optimum heating temperature of carbon extraction from peat soil.
2. To determine the graphitic contents and functional group on peat soil activated carbon.
3. To evaluate the adsorption efficiency of heavy metal contaminants from wastewater on peat soil activated carbon.

#### **1.4 Significance of study**

Activated carbon is used as an adsorbent to remove organic and inorganic pollutant from liquid and gas phase. Activated carbon is used in the wastewater treatment of variety heavy metal contaminants. The development of activated carbon in industrial scales could approach towards controlling the discharge of heavy metal contaminants hence reducing water pollution. The adsorption of heavy metal contaminants using activated carbon were done from previous research with significant outcome. However, the study on chemically prepared peat soil activated carbon for metal adsorption is lack. A study reported by Batista et al., (2009) found that the activation agent used was HCl and this study was focus on Cr adsorption. There were no varieties of the chemical agents and metal species. Another study on peat soil activated carbon reported by Mudjijati et al., (2000), shows the production of activated carbon was success but there were no study on metal species except more focus on its characterisation. At a glance, the studies on the metal adsorption using activated carbon were using standardised initial concentration of metal contaminant which was synthetically produced in laboratories.

This study has its betterment of research area in terms of the initial concentration of metal contaminant. The contaminated wastewater was taken from the selected industrial parks which provide actual concentration and varieties metal elements from the real polluted environment. The heating temperature of peat soil were manipulated as well as to determine the optimum temperature in order produce high carbon concentration. Next, the comparison of graphitic content in raw peat soil, peat soil heated at optimum temperature and peat soil activated carbon were conducted in this study.

#### **1.5 Scopes of the study**

This research was conducted in order to produce activated carbon prepared from peat for the removal of metal contaminants in industrial wastewater. The aspects looked into were the number of sampling points (5 sampling point at Kg Pt Nipah, Senggarang), heavy metal contaminants in wastewater, facilities used for investigation and analysis, and method used during this study. Some limitations for this study are as follow;

1. Heating up peat soil as precursor from 200°C to 700°C. Chemical activation method was used to produce peat soil activated carbon.
2. H<sub>2</sub>SO<sub>4</sub> was used as activating agent with mixing ratio 1:1 and heated up to 400°C for an hour at atmospheric pressure.
3. This work also focuses on the physical and chemical characteristics of activated peat.
4. Chemical characteristics of activated peat would be analysed using Laser Raman spectroscopy for graphitic content and FTIR spectroscopy for the surface functional groups identification.
5. Industrial waste water specimen would be taken from three different industrial parks which were located at Sri Sulong, Sri Gading and Parit Raja industrial park. The water specimen was taken using physical method as describe in ISO 5667. The heavy metal in this study would be focused on Al, Cr, Pb, Zn, Fe and Cu. These metals are analysed using ICP-MS.
6. This study also carried out the adsorption test using different dosage (0.0, 0.2, 0.4, 0.6, 0.8, 1.0 g) of activated peat for every 25 ml of waste water. The removal efficiency analysis conducted using the remaining (final) concentration of heavy metal in water specimens.
7. Langmuir and Freundlich adsorption isotherm would be used for adsorption capacity on different type of metal species.





## REFERENCES

- A. Akl, M., Yousef, A. M., & AbdElnasser, S. (2013). Removal of Iron and Manganese in Water Samples Using Activated Carbon Derived from Local Agro-Residues. *Journal of Chemical Engineering & Process Technology*, 04(04).
- Adamczyk, Z. (2013). Electrostatic Interactions. In *Encyclopedia of Colloid and Interface Science* (pp. 362–362). Berlin, Heidelberg: Springer Berlin Heidelberg.
- Adamson, A. W., & Gast, A. P. (1997). *Physical chemistry of surfaces* (6th ed.). Canada: John Wiley & Sons Inc. Chemistry-of-Surfaces
- Aguayo-Villarreal, I. A., Bonilla-Petriciolet, A., & Muñiz-Valencia, R. (2017). Preparation of activated carbons from pecan nutshell and their application in the antagonistic adsorption of heavy metal ions. *Journal of Molecular Liquids*, 230,
- Al-Muhtaseb, S. A., El-Naas, M. H., & Abdallah, S. (2008). Removal of aluminum from aqueous solutions by adsorption on date-pit and BDH activated carbons. *Journal of Hazardous Materials*, 158(2–3), 300–307.
- Aljendeel, H. A. (2011). Removal of Heavy Metal Using Reverse Osmosis. *Journal of Engineering*, 17.
- Aljundi, I. H., & Jarrah, N. (2008). A study of characteristics of activated carbon produced from Jordanian olive cake. *Journal of Analytical and Applied Pyrolysis*, 81(1), 33–36.
- Allwar, A., Hartati, R., & Fatimah, I. (2017). Effect of nitric acid treatment on activated carbon derived from oil palm shell. *AIP Conference Proceedings*, 1823.
- Almarri, M., Ma, X., & Song, C. (2009). Role of Surface Oxygen-Containing Functional Groups in Liquid-Phase Adsorption of Nitrogen Compounds on Carbon-Based Adsorbents. *Energy & Fuels*, 23(8), 3940–3947.
- Amuda, O. S., Giwa, A. A., & Bello, I. A. (2007a). Removal of heavy metal from industrial wastewater using modified activated coconut shell carbon. *Biochemical Engineering Journal*, 36(2), 174–181.
- Amuda, O. S., Giwa, A. A., & Bello, I. A. (2007b). Removal of heavy metal from

- industrial wastewater using modified activated coconut shell carbon. *Biochemical Engineering Journal*, 36(2), 174–181.
- Anirudhan, T. S., & Sreekumari, S. S. (2011). Adsorptive removal of heavy metal ions from industrial effluents using activated carbon derived from waste coconut buttons. *Journal of Environmental Sciences*, 23(12), 1989–1998.
- Anwar, J., Shafique, U., Uz-Zaman, W., Salman., M., & Dar, A. (2010). Removal of Pb(II) and Cd(II) from water by adsorption on peels of banana. *Bioresource Technology*, 101(6), 1752–1755.
- Appel, C., Ma, L. Q., Rhue, R. D., & Kennelley, E. (2003). Point of zero charge determination in soils and minerals via traditional methods and detection of electroacoustic mobility. *Geoderma*, 113, 77–93.
- Arneli, Pangestika, fauziah, Wahyuningrum, & Astuti. (2017). The influence of activating agents on the performance of rice husk-based carbon for sodium lauryl sulfate and chrome (Cr) metal adsorptions. *IOP Conference Series: Materials and Science Engineering*, 1(172), 1–8.
- Bagheri, N., & Abedi, J. (2009). Preparation of high surface area activated carbon from corn by chemical activation using potassium hydroxide. *Chemical Engineering Research and Design*, 87(8), 1059–1064.
- Balasubramanian, R., Perumal, S. V., & Vijayaraghavan, K. (2009). Equilibrium Isotherm Studies for the Multicomponent Adsorption of Lead, Zinc, and Cadmium onto Indonesian Peat. *Industrial & Engineering Chemistry Research*, 48(4), 2093–2099.
- Barde, M. P., & Barde, P. J. (2012). What to use to express the variability of data: Standard deviation or standard error of mean? *Perspectives in Clinical Research*, 3(3), 113–116.
- Bartczak, P., Norman, M., Klapiszewski, Ł., Karwańska, N., Kawalec, M., Baczyńska, M., Jesionowski, T. (2015). Removal of nickel(II) and lead(II) ions from aqueous solution using peat as a low-cost adsorbent: A kinetic and equilibrium study. *Arabian Journal of Chemistry*.
- Batista, A. P. S., Romão, L. P. C., Arguelho, M. L. P. M., Garcia, C. A. B., Alves, J. P. H., Passos, E. A., & Rosa, A. H. (2009). Biosorption of Cr(III) using in natura and chemically treated tropical peats. *Journal of Hazardous Materials*, 163(2–3), 517–523.
- Beauchemin, D. (2017). Inductively Coupled Plasma Mass Spectrometry Methods. In

*Encyclopedia of Spectroscopy and Spectrometry* (pp. 236–245). Elsevier.

- Belhachemi, M., & Addoun, F. (2011). Comparative adsorption isotherms and modeling of methylene blue onto activated carbons. *Applied Water Science*, 1(3–4), 111–117.
- Bendou, S., & Amrani, M. (2014). Effect of Hydrochloric Acid on the Structural of Sodic-Bentonite Clay. *Journal of Minerals and Materials Characterization and Engineering*, 2(2), 404–413.
- Bezak-Mazur, E., Widłak, M., & Ciupa, T. (2001). A Speciation Analysis of Aluminium in the River Silnica. *Polish Journal of Environmental Studies*, 10(4), 263–267.
- Bin Jusoh, A., Cheng, W. H., Low, W. M., Nora 'aini, A., Megat, M. J., & Noor, M. (2005). Study on the removal of iron and manganese in groundwater by granular activated carbon. *Desalination*, 182, 347–353.
- Bouchelta, C., Medjram, M. S., Bertrand, O., & Bellat, J.-P. (2008). Preparation and characterization of activated carbon from date stones by physical activation with steam. *Journal of Analytical and Applied Pyrolysis*, 82(1), 70–77.
- Bradley, M. (2007). *Curve Fitting in Raman and IR Spectroscopy: Basic Theory of Line Shapes and Applications*. Wisconsin.
- Brunauer, S., Emmett, P. H., & Teller, E. (1938). Adsorption of Gases in Multimolecular Layers. *Journal of the American Chemical Society*, 60(2), 309–319.
- Capeletti, L. B., & Zimnoch, J. H. (2016). Fourier Transform Infrared and Raman Characterization of Silica-Based Materials. In *Applications of Molecular Spectroscopy to Current Research in the Chemical and Biological Sciences*. InTech.
- Cazetta, A. L., Vargas, A. M. M., Nogami, E. M., Kunita, M. H., Guilherme, M. R., Martins, A. C., Almeida, V. C. (2011). NaOH-activated carbon of high surface area produced from coconut shell: Kinetics and equilibrium studies from the methylene blue adsorption. *Chemical Engineering Journal*, 174(1), 117–125.
- Chaffai, R., Seybou, T., Marzouk, B., & Ferjani, E. (2009). A comparative analysis of fatty acid composition of root and shoot lipids in *Zea mays* under copper and cadmium stress. *Acta Biologica Hungarica*, 60(1), 109–125.
- Chambon, Lund, Galal-Gorchev, Ohanian, Marla, & Kenny. (2003). *Aluminium in Drinking-water Background document for development of WHO Guidelines for*

*Drinking-water Quality*. Geneva.

- Chaturvedi, S., & Dave, P. N. (2012). Removal of iron for safe drinking water. *Desalination*, 303, 1–11. <https://doi.org/10.1016/j.desal.2012.07.003>
- Cheng, N. (2013). *Application of Fourier-transform Infrared for Quality Control of Swiss Cheese*. The Ohio State University.
- Cho, H., Oh, D., & Kim, K. (2005). A study on removal characteristics of heavy metals from aqueous solution by fly ash. *Journal of Hazardous Materials*, 127(1–3), 187–195.
- Chung, C. K., & Wu, B. H. (2006). Effect of amorphous Si layer on the reaction of carbon and silicon in the C/Si multilayer by high vacuum annealing. *Thin Solid Films*, 515(4), 1985–1991.
- Chung, C. K., & Wu, B. H. (2008). Reaction of carbon and silicon at high temperature deposition. In *2008 3rd IEEE International Conference on Nano/Micro Engineered and Molecular Systems* (pp. 136–139).
- Chwastowski, J., Staroń, P., Kołoczek, H., & Banach, M. (2017). Adsorption of hexavalent chromium from aqueous solutions using Canadian peat and coconut fiber. *Journal of Molecular Liquids*, 248, 981–989.
- Connelly, A. (2017). BET surface area – Andy Connelly.
- Cuhadaroglu, D., & Uygun, O. A. (2008). Production and characterization of activated carbon from a bituminous coal by chemical activation. *African Journal of Biotechnology*, 7(20), 3703–3710.
- Delicato, D. (1996). *Physical - Chemical Properties and Sorption Characteristics of Peat*. Dublin City University.
- Demirak, A., Yilmaz, F., Levent Tuna, A., & Ozdemir, N. (2006). Heavy metals in water, sediment and tissues of *Leuciscus cephalus* from a stream in southwestern Turkey. *Chemosphere*, 63(9), 1451–1458.
- Dias, J. M., Alvim-Ferraz, M. C. M., Almeida, M. F., Rivera-Utrilla, J., & Sánchez-Polo, M. (2007). Waste materials for activated carbon preparation and its use in aqueous-phase treatment: A review. *Journal of Environmental Management*, 85(4), 833–846.
- Ding, J., Wang, H., Li, Z., Kohandehghan, A., Cui, K., Xu, Z., ... Mitlin, D. (2013). Carbon Nanosheet Frameworks Derived from Peat Moss as High Performance Sodium Ion Battery Anodes. *ACS Nano*, 7(12), 11004–11015.
- Dodevski, V., Janković, B., Stojmenović, M., Krstić, S., Popović, J., Pagnacco, M.

- C., Pašalić, S. (2017). Plane tree seed biomass used for preparation of activated carbons (AC) derived from pyrolysis. Modeling the activation process. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 522, 83–96.
- Donohue, M., & Aranovich, G. (1998). Classification of Gibbs adsorption isotherms. *Advances in Colloid and Interface Science*, 76–77, 137–152.
- Dychalska, A., Fabisiak, K., Paprocki, K., Makowiecki, J., Iskaliyeva, A., & Szybowski, M. (2016). A Raman spectroscopy study of the effect of thermal treatment on structural and photoluminescence properties of CVD diamond films. *Materials & Design*, 112, 320–327.
- El-Wakil, El-Maaty, A., & Awad. (2014). Removal of Lead from Aqueous Solution on Activated Carbon and Modified Activated Carbon Prepared from Dried Water Hyacinth Plant. *J Anal Bioanal Tech*, 5(2). Retrieved from
- Escribano, R., Sloan, J. J., Siddique, N., Sze, N., & Dudev, T. (2001). Raman spectroscopy of carbon-containing particles. *Vibrational Spectroscopy*, 26(2), 179–186.
- Fawell, J., Lund, Mintz, Galal-Gorchev, Helmer, Bonnefoy, & Espinoza. (2003). *Iron in Drinking-Water*.
- Fawell, Lund, Mintz, Galal-Gorchev, Helmer, Bonnefoy, ... Marla. (2003). *Chromium in Drinking-water Background document for development of WHO Guidelines for Drinking-water Quality*. Geneva.
- Fu, F., & Wang, Q. (2011). Removal of heavy metal ions from wastewaters: A review. *Journal of Environmental Management*, 92(3), 407–418.
- G. Maahs, H. (1972). Oxidation Of Carbon At High Temperatures: Or Transport Control Reaction-Rate Control. *National Aeronautics and Space Administration*. Washington D.C.
- Gaur, V., & Shankar. (2012). Surface modification of activated carbon for the removal of water impurities | Water Technology.
- Gautam, P. K., Gautam, R. K., Banerjee, S., Lofrano, G., Sanroman, M. A., Chattopadhyaya, M. C., & Pandey, J. D. (2015). Preparation of activated carbon from Alligator weed ( *Alternanthera philoxeroides* ) and its application for tartrazine removal: Isotherm, kinetics and spectroscopic analysis. *Journal of Environmental Chemical Engineering*, 3(4), 2560–2568.
- Geşikiewicz-Puchalska, A., Zgrzebnicki, M., Michalkiewicz, B., Narkiewicz, U., Morawski, A. W., & Wrobel, R. J. (2017). Improvement of CO<sub>2</sub> uptake of



activated carbons by treatment with mineral acids. *Chemical Engineering Journal*, 309, 159–171.

- Glaser, R. E., Hampton, C., & Demoin, D. (2010). *Vibrational Spectroscopy Tutorial: Sulphur and Phosphorus*. Missouri.
- Gunatilake SK. (2015). Methods of Removing Heavy Metals from Industrial Wastewater. *Journal of Multidisciplinary Engineering Science Studies (JMESS)*, 1(1), 2912–1309.
- Gupta, A., Dhakate, S. R., Pal, P., Dey, A., Iyer, P. K., & Singh, D. K. (2017). Effect of graphitization temperature on structure and electrical conductivity of polyacrylonitrile based carbon fibers. *Diamond and Related Materials*, 78, 31–38.
- Hafsa, M. N., Ibrahim, M., & Sharif, S. (2013). Investment Casting Using Multi-Jet Modeling Patterns: The Thermogravimetric Analysis Of Visijet® Sr200 Uv Curable Acrylate Plastic. *International Conference on Mechanical Engineering Research Bukit Gambang Resort City*, 1–3.
- Hartman, B. E., Chen, H., & Hatcher, P. G. (2015). A non-thermogenic source of black carbon in peat and coal. *International Journal of Coal Geology*, 144–145, 15–22.
- Hemati, S., Arbabi, M., & Amiri, M. (2015). Removal of lead ions from industrial wastewater: A review of Removal methods. *International Journal of Epidemiologic Research*, 2(2), 105–109.
- Hesas, R. H., Arami-Niya, A., Mohd, W., Daud, A. W., & Sahu, J. N. (2013). Preparation and Characterization of Activated Carbon from Apple Waste by Microwave-Assisted Phosphoric Acid Activation: Application in Methylene Blue Adsorption. *BioResources*, 8(2), 2950–2966.
- Hong, Y., Wang, Z., & Jin, X. (2013). Sulfuric acid intercalated graphite oxide for graphene preparation. *Scientific Reports*, 3, 3439.
- Hesas, R., Arami-Niya, A., Wan Daud, W. M. A., & Sahu, J. N. (2013). Comparison of oil palm shell-based activated carbons produced by microwave and conventional heating methods using zinc chloride activation. *Journal of Analytical and Applied Pyrolysis*, 104, 176–184.
- Ide, M. S., & Davis, R. J. (2014). The Important Role of Hydroxyl on Oxidation Catalysis by Gold Nanoparticles. *Accounts of Chemical Research*, 47(3), 825–833.
- Imamoglu, M., & Tekir, O. (2008). Removal of copper (II) and lead (II) ions from aqueous solutions by adsorption on activated carbon from a new precursor

- hazelnut husks. *Desalination*, 228(1–3), 108–113.
- Ing Teong, T. (2015). *Characterization of Soil Organic Matter in Peat Soil with Different Humification Levels using FTIR. Material Science and Engineering*.
- Jiang, Y. (2017). Preparation of activated carbon from walnut shell and its application in industrial wastewater, 20063–20064.
- Jinming, H., & Xuehui, M. (2009). Physical And Chemical Properties Of Peat. *Coal , Oil Shale, Natural Bitumen, Heavy Oil and Peat*, 2(1), 452.
- Jirakarn, N., Apanee, L., & Sujitra, W. (2013). A Comparison of Dilute Sulfuric and Phosphoric Acid Pretreatments in Biofuel Production from Corncobs. *International Journal of Chemical and Molecular Engineering*, 7(4), 197–201.
- Joshi, S., & Pokharel, B. P. (n.d.). Preparation and Characterization of Activated Carbon from Lapsi (*Choerospondias axillaris*) Seed Stone by Chemical Activation with Potassium Hydroxide. *Journal of the Institute of Engineering*, 9(1), 79–88.
- Jung, C., Heo, J., Han, J., Her, N., Lee, S.-J., Oh, J., ... Yoon, Y. (2013). Hexavalent chromium removal by various adsorbents: Powdered activated carbon, chitosan, and single/multi-walled carbon nanotubes. *Separation and Purification Technology*, 106, 63–71.
- Kalaitzidis, S., & Christanis, K. (2003). Scanning electron microscope studies of the Philippi peat (NE Greece): initial aspects. *International Journal of Coal Geology*, 54(1–2), 69–77.
- Kalpana, D., & Lee, Y. S. (2016). Effects of Temperature and Pore Structure on High Surface Area-Activated Carbon Obtained from Peanut Shells. *Journal of Nanoscience and Nanotechnology*, 16(3), 2950–2955.
- Kasiulienė, A., Carabante, I., Bhattacharya, P., Caporale, A. G., Adamo, P., & Kumpiene, J. (2018). Removal of metal(oid)s from contaminated water using iron-coated peat sorbent. *Chemosphere*, 198, 290–296.
- Kaya, M., Şahin, Ö., & Saka, C. (2017). Preparation and TG/DTG, FT-IR, SEM, BET Surface Area, Iodine Number and Methylene Blue Number Analysis of Activated Carbon from Pistachio Shells by Chemical Activation. *International Journal of Chemical Reactor Engineering*.
- Khadiran, T., Hussein, M. Z., Zainal, Z., & Rusli, R. (2015). Activated carbon derived from peat soil as a framework for the preparation of shape-stabilized phase change material. *Energy*, 82, 468–478.

- Kimbrough, D. E. (2009). Source identification of copper, lead, nickel, and zinc loading in wastewater reclamation plant influents from corrosion of brass in plumbing fixtures. *Environmental Pollution*, *157*, 1310–1316.
- Kluiving, S., De Ridder, T., Van Dasselaar, M., Roozen, S., & Prins, M. (2016). Soil archives of a Fluvisol: subsurface analysis and soil history of the medieval city centre of Vlaardingen, the Netherlands-an integral approach, *2*, 271–285.
- Kok, D. (2017). *Raman spectroscopy: Principle, key elements and application*. Kuala Lumpur.
- Kormin, S., Zafiah, A., Rus, M., Shafiq, M., & Azahari, M. (2017). Thermal properties of biopolyol from oil palm fruit fibre (OPFF) using solvolysis liquefaction technique.
- Kumar, A., & Jena, H. M. (2017). Adsorption of Cr(VI) from aqueous phase by high surface area activated carbon prepared by chemical activation with ZnCl<sub>2</sub>. *Process Safety and Environmental Protection*, *109*, 63–71.
- Lallanilla, M. (2014). What Is Dew Point? | Relative Humidity.
- Legrouri, K., Khouya, E., Ezzine, M., Hannache, H., Denoyel, R., Pallier, R., & Naslain, R. (2005). Production of activated carbon from a new precursor molasses by activation with sulphuric acid. *Journal of Hazardous Materials*, *118*(1–3), 259–263.
- Leiviskä, T., Khalid, M. K., Gogoi, H., & Tanskanen, J. (2018). Enhancing peat metal sorption and settling characteristics. *Ecotoxicology and Environmental Safety*, *148*, 346–351
- Lenntech, B. . (2015). Chromium (Cr) and water: Reaction Mechanisms, Environmental impact and Health Effects. Retrieved November 6, 2017, from <https://www.lenntech.com/periodic/water/chromium/chromium-and-water.htm>
- Lenntech, B. . (2016a). Aluminum (Al) and water: reaction mechanisms, environmental impact and health effects. Retrieved November 6, 2017, from <https://www.lenntech.com/periodic/water/aluminium/aluminum-and-water.htm>
- Lenntech, B. V. (2016b). Lead (Pb) and water: Reaction Mechanisms, Environmental Impact and Health Effects. Retrieved November 4, 2017, from <https://www.lenntech.com/periodic/water/lead/lead-and-water.htm>
- Li, B. (2012). *Characterization of Pore Structure and Surface Chemistry of Activated Carbons – A Review*. (Dr Salih Salih, Ed.), *INTECH* (Vol. 3). Shanghai: InTech China.



- Lim, H. K., Teng, T. T., Ibrahim, M. H., Ahmad, A., & Chee, H. T. (2012). Adsorption and Removal of Zinc (II) from Aqueous Solution Using Powdered Fish Bones. *APCBEE Procedia*, 1, 96–102.
- Linares-Solan, Lillo-Ródenas, Marco-Lozar, Kunowsky, & Romero-Anaya. (2006). NaOH and KOH for Preparing Activated Carbons Used In Energy and Environmental Applications (pp. 355-387).
- Linntech, B. . (2017). Zinc (Zn) and water: reaction mechanism, environmental impact and health effects. Retrieved November 6, 2017, from <https://www.lenntech.com/periodic/water/zinc/zinc-and-water.htm>
- Liu, H., Chen, T., Chang, J., Zou, X., & Frost, R. L. (2013). The effect of hydroxyl groups and surface area of hematite derived from annealing goethite for phosphate removal. *Journal of Colloid and Interface Science*, 398, 88–94.
- Liu, W., & Zhao, G. (2012). Effect Of Temperature And Time On Microstructure And Surface Functional Groups Of Activated Carbon Fibers Prepared From Liquefied Wood. *BioResources*, 7(4), 5552–5567.
- LIU, Z., ZHOU, L., WEI, P., ZENG, K., WEN, C., & LAN, H. (2008). Competitive adsorption of heavy metal ions on peat. *Journal of China University of Mining and Technology*, 18(2), 255–260.
- Ljupković, R. B., Mitrović, J., Radović, M., Kostić, M., Bojić, D., Mitić-Stojanović, D.-L., & Lj Bojić, A. (2011). Removal Cu(II) ions from water using sulphuric acid treated *Lagenaria vulgaris* Shell (Cucurbitaceae). *Biologica Nyssana*, 2(2), 85–89.
- Lu, C., & Liu, C. (2006). Removal of nickel(II) from aqueous solution by carbon nanotubes. *Journal of Chemical Technology & Biotechnology*, 81(12), 1932–1940.
- Lund, Fawell, Mintz, Galal-Gorchev, Helmer, Espinoza, & Marla. (2003). *Zinc in Drinking-water Background document for development of WHO Guidelines for Drinking-water Quality*. Geneva.
- M. M. Rahman, M. Awang, B. S. Mohosinaa, B. Y. Kamaruzzaman, W. B. Wan Nik, & C. M. C. Adnan. (2012). Waste Palm Shell Converted to High Efficient Activated Carbon by Chemical Activation Method and Its Adsorption Capacity Tested by Water Filtration. *Procediaa APCBEE*, 1(1), 293–298.
- Ma, X., Yang, H., Chen, Y., & Li, Y. (2004). Preparation, Surface and Pore Structure of High Surface Area Activated Carbon Fibers from Bamboo by Steam

Activation. *Journals of Materials*, 7(1), 4433–4441.

- Manoj Kumar Reddy, P., Krushnamurty, B. K., K Mahammadunnisa, B. S., Dayamani, B. A., & Ch Subrahmanyam, B. (2014). Preparation of activated carbons from bio-waste: effect of surface functional groups on methylene blue adsorption.
- Maurya, S., Paunikar, A., Warang, A., & Sajeevan, S. (2016). *Automotive Fasteners Defects and Failure Analysis*. Mumbai.
- Misutsu, M. Y., Cavalheiro, L. F., Ricci, T. G., Viana, L. H., de Oliveira, S. C., Machulek, A., & de Oliveira, L. C. S. (2015). Thermoanalytical Methods in Verifying the Quality of Biodiesel. In *Biofuels - Status and Perspective*. InTech. <https://doi.org/10.5772/59479>
- Miyazawa, M., Pavan, M. A., Oliveira, E. L. de, Ionashiro, M., & Silva, A. K. (2000). Gravimetric determination of soil organic matter. *Brazilian Archives of Biology and Technology*, 43(5), 475–478.
- Moghtaderi, B., Meesri, C., & Wall, T. F. (2004). Pyrolytic characteristics of blended coal and woody biomass. *Fuel*, 83(6), 745–750.
- Mohamed, E. G., Mohamed, H. A., Ali, M. H., Ibrahim, A. A.-M., Ayman, H. F., & Seliem, M. E. (2015). Removal of aluminum, iron and manganese ions from industrial wastes using granular activated carbon and Amberlite IR-120H. *The Egyptian Journal of Aquatic Research*, 41(2), 155–164.
- Mopoung, S., Amornsakchai, P., & Somroop, S. (2016). Characterization of phosphoric acid modified activated carbon fiber from fiber waste of pineapple leaf fiber production processing. *Carbon - Science and Technology*, 8(1), 1–12.
- Mopoung, S., Moonsri, P., Palas, W., & Khumpai, S. (2015). Characterization and Properties of Activated Carbon Prepared from Tamarind Seeds by KOH Activation for Fe(III) Adsorption from Aqueous Solution. *The Scientific World Journal*, 2015, 1–9.
- Moreno-Castilla, C., Álvarez-Merino, M. A., Pastrana-Martínez, L. M., & López-Ramón, M. V. (2010). Adsorption mechanisms of metal cations from water on an oxidized carbon surface. *Journal of Colloid and Interface Science*, 345(2), 461–466.
- Moreno-Tovar, R., Terrés, E., & Rangel-Mendez, J. R. (2014). Oxidation and EDX elemental mapping characterization of an ordered mesoporous carbon: Pb(II) and Cd(II) removal. *Applied Surface Science*, 303, 373–380. <https://doi.org/10.1016/j.apsusc.2014.03.008>

- Mudjijati, Indraswati, N., Wicaksana, F., Herman, Harsono, I., & Ismadji, S. (2000). Activated Carbon Produced From Kalimantan Peat By Chemical Activation. In *Adsorption Science and Technology* (pp. 446–450).
- Muniz, A. M. V. (2011). *Material characterization techniques : SEM and EDS*. Ohio.
- Myalowenkosi, I. S., Kwanele, K., & Suvardhan, K. (2015). Removal of Iron(II) from Aqueous Solution using Activated Carbon Derived from Pods of *Acacia Nilotica* Var *Astringens* (Sunt tree) by Chemical Activation with ZnCl<sub>2</sub>. *International Journal of Emerging Technology and Advanced Engineering Website: Wwww.Ijetae.Com ISO Certified Journal*, 9001(10).
- Nunes, C. A., & Guerreiro, M. C. (2011). Estimation of surface area and pore volume of activated carbons by methylene blue and iodine numbers. *Química Nova*, 34(3), 472–476.
- Ohanian, Fawell, Giddings, Toft, Magara, Jackson., (2004). *Copper in Drinking-water Background document for development of WHO Guidelines for Drinking-water Quality*. New York.
- Okman, I., Karagöz, S., Tay, T., & Erdem, M. (2014). Activated Carbons From Grape Seeds By Chemical Activation With Potassium Carbonate And Potassium Hydroxide. *Applied Surface Science*, 293, 138–142.
- Ong, S.-E., Zhang, S., Du, H., & Tan, G. (2007). Temperature effect on bonding structures of amorphous carbon containing more than 30at.% silicon. *Diamond and Related Materials*, 16, 1823–1827.
- Onishchenko, D. V., & Reva, V. P. (2013). Physicochemical properties of carbon nanotubes obtained from peat moss. *Journal of Engineering Physics and Thermophysics*, 86(2), 363–369.
- Panich, M., Shames, A. ., & Nakajima, T. (2001). On paramagnetism in fluorinated graphite: EPR and solid state NMR study. *Journal of Physics and Chemistry of Solids*, 62(5), 959–964.
- Peschel, G. (2011). *Carbon-Carbon Bonds: Hybridization*. Berlin.
- Peter, M. (2016, March 24). Researchers produce graphene nanoribbon with perfect zigzag edge.
- Petsch, S. T. (2011). Carbon (Organic, Degradation) (pp. 234–238). Springer Netherlands. [https://doi.org/10.1007/978-1-4020-9212-1\\_46](https://doi.org/10.1007/978-1-4020-9212-1_46)
- Phan, N. H., Rio, S., Faur, C., Le Coq, L., Le Cloirec, P., & Nguyen, T. H. (2006). Production of fibrous activated carbons from natural cellulose (jute, coconut)

- fibers for water treatment applications. *Carbon*, 44(12), 2569–2577.
- Pimenta, Dresselhaus, Dresselhaus, Cancado, Jorio, & Saito. (2007). Studying disorder in graphitic-based systems by Raman spectroscopy. *Physical Chemistry*, 9, 1276–1291.
- Pradhan, S., & Mishra, S. (2011). *Production and characterization of Activated Carbon produced from a suitable Industrial sludge*. National Institute of Technology Rourkela.
- Prahas, D., Kartika, Y., Indraswati, N., & Ismadji, S. (2008). Activated carbon from jackfruit peel waste by H<sub>3</sub>PO<sub>4</sub> chemical activation: Pore structure and surface chemistry characterization. *Chemical Engineering Journal*, 140(1–3), 32–42.
- Qdais, H. A., & Moussa, H. (2004). Removal of heavy metals from wastewater by membrane processes: a comparative study. *Desalination*, 164(2), 105–110.
- Quideau, S. A., McIntosh, A. C. S., Norris, C. E., Lloret, E., Swallow, M. J. B., & Hannam, K. (2016). Extraction and Analysis of Microbial Phospholipid Fatty Acids in Soils. *Journal of Visualized Experiments : JoVE*, (114).
- Radetić, T. (2011). *Fundamentals of Scanning Electron Microscopy and Energy Dispersive X-ray Analysis in SEM and TEM*. Beograd.
- Rai, Shahi, Meena, Chakraborty, Singh, & Rai. (2016). Removal of hexavalent chromium Cr (VI) using activated carbon prepared from mango kernel activated with H<sub>3</sub>PO<sub>4</sub>. *Resource-Efficient Technologies*, 2, S63–S70.
- Rashidi, N. A., & Yusup, S. (2017). A review on recent technological advancement in the activated carbon production from oil palm wastes. *Chemical Engineering Journal*, 314, 277–290. <https://doi.org/10.1016/j.cej.2016.11.059>
- Rezanezhad, F., Price, J. S., Quinton, W. L., Lennartz, B., Milojevic, T., & Van Cappellen, P. (2016). Structure of peat soils and implications for water storage, flow and solute transport: A review update for geochemists. *Chemical Geology*, 429, 75–84.
- Roh, J.-S. (2008). Structural Study of the Activated Carbon Fiber using Laser Raman Spectroscopy. *Carbon Letters*, 9(2), 127–130.
- Sabela, M., Kunene, K., Kanchi, S., M.Xhakaza, N., Bathinapatla, A., Mdluli Phumlane, ... Bisetty, K. (2016). Removal of copper (II) from wastewater using green vegetable waste derived activated carbon: An approach to equilibrium and kinetic study. *Arabian Journal of Chemistry*, 1(1), 1–9.
- Sahira, J., Mandira, A., Bhadra Prasad, P., & Raja Ram, P. (2013). Effects of

- Activating Agents on the Activated Carbons Prepared from Lapsi Seed Stone. *Research Journal of Chemical Sciences Res. J. Chem. Sci*, 3(5), 2231–2606.
- Salam, O. E. A., Reiad, N. A., & Elshafei, M. M. (2011). A study of the removal characteristics of heavy metals from wastewater by low-cost adsorbents. *Journal of Advanced Research*, 2, 297–303.
- Saskatchewan, G. (2008). *Zinc for Private water and Health Regulated Public Water Supplies*. Canada. Retrieved from <http://www.agriculture.gov.sk.ca/AKC>
- Selvanathan, N., & Subki, N. S. (2015). Dye Adsorbent By Pineapple Activated Carbon: H<sub>3</sub>po<sub>4</sub> And Naoh Activation, 10(20). Retrieved from [www.arpnjournals.com](http://www.arpnjournals.com)
- Sepúlveda-Cuevas, L. A., Contreras-Villacura, E. G., & Palma-Tolozá, C. L. (2008). Magellan Peat (*Sphagnum Magallanicum*) As Natural Adsorbent Of Recalcitrant Synthetic Dyes. *J. Soil Sc. Plant Nutr*, 8(82), 31–4331.
- Sert, Y., Mahendra, M., Keskinoglu, S., Chandra, Srikantamurthy, N., Umesha, K. B., & Çırak, Ç. (2015). FT-IR, Laser-Raman spectra and computational analysis of 5-Methyl-3-phenylisoxazole-4-carboxylic acid. *Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy*, 139, 145–155.
- Shi, Q., Zhang, J., Zhang, C., Li, C., Zhang, B., Hu, W., Zhao, R. (2010). Preparation of activated carbon from cattail and its application for dyes removal. *Journal of Environmental Sciences*, 22(1), 91–97.
- Shim, J.-W., Park, S.-J., & Ryu, S.-K. (2001). Effect of modification with HNO<sub>3</sub> and NaOH on metal adsorption by pitch-based activated carbon fibers. *Carbon*, 39(11), 1635–1642.
- Shimodaira, N., & Masui, A. (2002). Raman spectroscopic investigations of activated carbon materials. *Journal of Applied Physics*, 92(2), 902–909.
- Shrestha, S. (2016). Chemical, Structural and Elemental Characterization of Biosorbents Using FE-SEM, SEM-EDX, XRD/XRPD and ATR-FTIR Techniques. *Journal of Chemical Engineering & Process Technology*, 7(3).
- Sing, K. (2001). The use of nitrogen adsorption for the characterisation of porous materials. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 187(188), 3–9.
- Sing, K. S. W., Haul, R. A. W., Pierotti, R. A., Siemieniowska, T., Everett, D. H., Moscou, L., & Rouquerol, J. (1985). Reporting Physisorption Data for Gas/Solid Systems with Special Reference to the Determination of Surface Area and



- Porosity. *Pure and Applied Chemistry*, 57(4), 603–619.
- Steele, W. A. (1966). Adsorbate Equation of State. In E. A. Flood (Ed.), *The Gas - Solid Interface* (pp. 307–367). Ottawa: Marcel Dekker Inc.
- Subramaniam, A., & Rodriguez - Saona, L. (2009). Fourier transform infrared (FTIR) spectroscopy. In D.-W. Sun (Ed.), *Infrared Spectroscopy for Food Quality Analysis and Control* (1st ed., p. 424). Oxford: Academic Press/Elsevier.
- Sutcu, H. (2007). Pyrolysis by thermogravimetric analysis of blends of peat with coals of different characteristics and biomass. *Journal of the Chinese Institute of Chemical Engineers*, 38(3–4), 245–249.
- Sutejo, Y., Saggaff, A., & Rahayu, W. (2017). Physical and Chemical Characteristics of Fibrous Peat. *American Institute of Physics*, 1903.
- Tan, I. A. W., Chan, J. C., Hameed, B. H., & Lim, L. L. P. (2016). Adsorption behavior of cadmium ions onto phosphoric acid-impregnated microwave-induced mesoporous activated carbon. *Journal of Water Process Engineering*, 14, 60–70.
- Tan, Y. L., Islam, M. A., Asif, M., & Hameed, B. H. (2014). Adsorption of carbon dioxide by sodium hydroxide-modified granular coconut shell activated carbon in a fixed bed. *Energy*, 77, 926–931.
- Tangsathitkulchai, M., Tangsathitkulchai, C., Wongsooksin, K., & Chutingsakuntip, S. (2012). Removal of Residual Aluminium-Dye Complex and Aluminium Ion from Spent Natural-Dye Solution Using Activated Carbons. *Engineering Journal*, 16(5), 29–43.
- Tham, Y. J., Latif, P. A., Abdullah, A. M., Shamala-Devi, A., & Taufiq-Yap, Y. H. (2011). Performances of toluene removal by activated carbon derived from durian shell. *Bioresource Technology*, 102(2), 724–728.
- Tho, N., & Hoa, N. T. (2017). Characteristics of soil acidification of haplic Acrisols on ancient alluvial deposits under intensive cassava cultivation in Chau Thanh district, Tay Ninh province. *Vietnam Journal of Earth Sciences*, 39(2), 130–138.
- Thomas, R. (2008a). An overview of ICP Mass Spectrometry. In *Practical Guide to ICP-MS: A tutorial for beginners* (2nd ed., pp. 1–5). Florida: CRC Press.
- Thomas, R. (2008b). Principles of Ion Formation. In *Practical Guide to ICP-MS: A tutorial for beginners* (2nd ed., pp. 7–11). Florida: CRC Press.
- Toronto. (2016). Raman Band Correlation Table. Retrieved December 2, 2017, from [http://www.utoronto.ca/~traceslab/raman correlation table.pdf](http://www.utoronto.ca/~traceslab/raman%20correlation%20table.pdf)
- Tsang, D. C. W., Lai, K. C. K., & Lo, I. M. C. (2007). *Conversion Of Wood Waste*

- Into Activated Carbon And Its Application*. Canterbury. Retrieved from <https://www.wasteminz.org.nz/wp-content/uploads/Daniel-Tsang.pdf>
- Uraki, Y., Tamai, Y., Ogawa, M., Gaman, S., & Tokura, S. (2008). Preparation Of Activated Carbon From Peat. *BioResources*, 4(1), 205–213.
- US EPA. (1997). *SOIL SAMPLING*. New York. Retrieved from <https://archive.epa.gov/region9/toxic/web/pdf/ee-soilsampling-sop-env-3-13.pdf>
- Vaiopoulou, E., & Gikas, P. (2012). Effects of chromium on activated sludge and on the performance of wastewater treatment plants: A review. *Water Research*, 46, 549–570.
- Varila, T., Bergna, D., Lahti, R., Romar, H., Hu, T., & Lassi, U. (2017). Activated carbon production from peat using ZnCl<sub>2</sub>: Characterization and applications. *BioResources*, 12(4), 8078–8092.
- Vranova, V., Rejsek, K., & Formanek, P. (2013). Aliphatic, cyclic, and aromatic organic acids, vitamins, and carbohydrates in soil: a review. *TheScientificWorldJournal*, 2013, 524239.
- Wahyuningsih, P., & Yusri, N. (2016). Characterization of Activated Carbon Prepared from Oil Palm Empty Fruit Bunch by Chemical Activation using Sulphuric Acid (H<sub>2</sub>SO<sub>4</sub>). *International Conference on Engineering and Science for Research and Development*, 1(1), 239–244.
- Wang, X., Liang, X., Wang, Y., Wang, X., Liu, M., Yin, D., Zhang, Y. (2011). Adsorption of Copper (II) onto activated carbons from sewage sludge by microwave-induced phosphoric acid and zinc chloride activation. *Desalination*, 278(1–3), 231–237.
- Weitao, Z., Haixiang, C., Naian, L., & Jianjun, Z. (2014). Thermogravimetric analysis of peat decomposition under different oxygen concentration. *Journal of Thermal Analysis & Calorimetry*, 117(1), 489–497.
- Wilhelm Scherer, H. (2009). Sulfur in soils. *Journal of Plant Nutrition and Soil Science*, 172(3), 326–335.
- Wolff, A. (2014). Why is hydrochloric acid stronger than sulphuric acid even though sulphuric acid should dissociate to produce more hydrogen ions? - Quora. Retrieved March 15, 2018, from <https://www.quora.com/Why-is-hydrochloric-acid-stronger-than-sulphuric-acid-even-though-sulphuric-acid-should-dissociate-to-produce-more-hydrogen-ions>
- Xiong, J. B., & Mahmood, Q. (2010). Adsorptive removal of phosphate from aqueous

- media by peat. *Desalination*, 259(1), 59–64.
- Yakout, S. M., & Sharaf El-Deen, G. (2016). Characterization of activated carbon prepared by phosphoric acid activation of olive stones. *Ara*, 9, 1155–1162. <https://doi.org/10.1016/j.arabjc.2011.12.002>
- Yang, K., Peng, J., Srinivasakannan, C., Zhang, L., Xia, H., & Duan, X. (2010). Preparation of high surface area activated carbon from coconut shells using microwave heating. *Bioresource Technology*, 101(15), 6163–6169.
- Yoder, C. (2017). Common Bond Energies. Retrieved December 2, 2017, from [http://www.wiredchemist.com/chemistry/data/bond\\_energies\\_lengths.html](http://www.wiredchemist.com/chemistry/data/bond_energies_lengths.html)
- Yorgun, S., & Yıldız, D. (2015). Preparation and characterization of activated carbons from Paulownia wood by chemical activation with H<sub>3</sub>PO<sub>4</sub>. *Journal of the Taiwan Institute of Chemical Engineers*, 53, 122–131.
- Zhou, L., Yu, Q., Cui, Y., Xie, F., Li, W., Li, Y., & Chen, M. (2017). Adsorption properties of activated carbon from reed with a high adsorption capacity. *Ecological Engineering*, 102, 443–450.

