# Turbulent Friction in Rough Pipes and the Energy Spectrum of the Phenomenological Theory<sup>\*</sup>

G. Gioia and Pinaki Chakraborty

Department of Theoretical and Applied Mechanics University of Illinois at Urbana-Champaign, Urbana, IL 61801

(Dated: December 20, 2005)

### Abstract

The classical experiments on turbulent friction in rough pipes were performed by J. Nikuradse in the 1930's. Seventy years later, they continue to defy theory. Here we model Nikuradse's experiments using the phenomenological theory of Kolmogórov, a theory that is widely thought to be applicable only to highly idealized flows. Our results include both the empirical scalings of Blasius and Strickler, and are otherwise in minute qualitative agreement with the experiments; they suggest that the phenomenological theory may be relevant to other flows of practical interest; and they unveil the existence of close ties between two milestones of experimental and theoretical turbulence.

<sup>\*</sup> arXiv:physics/0507066 v1 8 Jul 2005; also Physical Review Letters, in press, 2005.

Turbulence is the unrest that spontaneously takes over a streamline flow adjacent to a wall or obstacle when the flow is made sufficiently fast. Although most of the flows that surround us in everyday life and in nature are turbulent flows over rough walls, these flows have remained amongst the least understood phenomena of classical physics [1, 2]. Thus, one of the weightier experimental studies of turbulent flows on rough walls, and the most useful in common applications, is yet to be explained theoretically 70 years after its publication. In that study [3], Nikuradse elucidated how the friction coefficient between the wall of a pipe and the turbulent flow inside depends on the Reynolds number of the flow and the roughness of the wall. The friction coefficient, f, is a measure of the shear stress (or shear force per unit area) that the turbulent flow exerts on the wall of a pipe; it is customarily expressed in dimensionless form as  $f = \tau / \rho V^2$ , where  $\rho$  is the density of the liquid that flows in the pipe and V the mean velocity of the flow. The Reynolds number is defined as  $Re = VR/\nu$ , where R is the radius of the pipe and  $\nu$  the kinematic viscosity of the liquid. Last, the roughness is defined as the ratio r/R between the size r of the roughness elements (sand grains in the case of Nikuradse's experiments) that line the wall of the pipe and the radius of the pipe.

Nikuradse presented his data in the form of six curves, the log-log plots of f versus Re for six values of the roughness [3]. These curves are shown in Fig. 1. At the onset of turbulence [4], at a Re of about 3,000, all six curves rise united in a single bundle. At a Re of about 3,500, the bundle bends downward to form a marked hump and then it plunges in accord with Blasius's empirical scaling [5],  $f \sim \text{Re}^{-1/4}$ , as one by one in order of decreasing roughness the curves start to careen away from the bundle. After leaving the bundle, which continues to plunge, each curve sets out to trace a *belly* [6] as it steers farther from the bundle with increasing Re, then flexes towards a terminal, constant value of f that is in keeping with Strickler's empirical scaling [7],  $f \sim (r/R)^{1/3}$ . For seventy years now, our understanding of these curves has been aided by little beyond a pictorial narrative of roughness elements being progressively exposed to the turbulent flow as Re increases [8].

In our theoretical work, we adopt the phenomenological imagery of "turbulent eddies" [9–11] and use the spectrum of turbulent energy [12] at a lengthscale  $\sigma$ ,  $E(\sigma)$ , to determine the velocity of the eddies of size s,  $u_s$ , in the form  $u_s^2 = \int_0^s E(\sigma)\sigma^{-2}d\sigma$ , where  $E(\sigma) = A \varepsilon^{2/3}\sigma^{5/3}c_d(\eta/\sigma)c_e(\sigma/R)$ . Here A is a dimensionless constant,  $\varepsilon$  is the turbulent power per unit mass,  $\eta = \nu^{3/4}\varepsilon^{-1/4}$  is the viscous lengthscale, R is the largest lengthscale in the flow,




FIG. 1: Nikuradse's data. Up to a Re of about 3,000 the flow is streamline (free from turbulence) and  $f \sim 1/\text{Re}$ . Note that for very rough pipes (small R/r) the curves do not form a belly at intermediate values of Re. Inset: verification of Strickler's empirical scaling for f at high Re,  $f \sim (r/R)^{1/3}$ .

 $A \varepsilon^{2/3} \sigma^{5/3}$  is the Kolmogórov spectrum (which is valid in the inertial range,  $\eta \ll \sigma \ll R$ ), and  $c_d$  and  $c_e$  are dimensionless corrections for the dissipative range and the energetic range, respectively. For  $c_d$  we adopt an exponential form,  $c_d(\eta/\sigma) = \exp(-\beta\eta/\sigma)$  (which gives  $c_d \approx 1$  except in the dissipative range, where  $\sigma \approx \eta$ ), and for  $c_e$  the form proposed by von Kármán,  $c_e(\sigma/R) = (1 + \gamma(\sigma/R)^2)^{-17/6}$  (which gives  $c_e \approx 1$  except in the energetic range, where  $\sigma \approx R$ ), where  $\beta$  and  $\gamma$  are dimensionless constants [12]. To obtain expressions for  $u_s$  and  $\eta$  in terms of Re, r/R, and V, we invoke the usual scalings [13],  $\varepsilon = \kappa_{\varepsilon} u_R^3/R$ (Taylor's scaling [14], where  $u_R$  is the characteristic velocity of the largest eddies and  $\kappa_{\varepsilon}$ a dimensionless constant) and  $u_R = \kappa_u V$  (where  $\kappa_u$  is a dimensionless constant). Then, we can write  $\eta = bR \operatorname{Re}^{-3/4}$ , where  $b \equiv (\kappa_{\varepsilon} \kappa_u^3)^{-1/4}$ , and (after changing the integration variable to  $x \equiv \sigma/R$ )  $u_s^2 = A \kappa_{\varepsilon}^{2/3} u_R^2 \int_0^{s/R} x^{-1/3} c_d (b \operatorname{Re}^{-3/4}/x) c_e(x) dx$ . For  $s \ll R$  we can set  $c_e = 1$ , compute the integral, and let  $\operatorname{Re} \to \infty$  to obtain  $u_s^2 = (3/2)A \kappa_{\varepsilon}^{2/3} u_R^2 (s/R)^{2/3}$ , or  $u_s^2 \sim u_R^2 (s/R)^{2/3}$ , a well-known result of the phenomenological theory. Further, for consistency with Taylor's scaling we must have  $A \kappa_{\varepsilon}^{2/3} = 2/3$  (so that  $u_s = u_R$  for s = R) and therefore  $u_s^2 = \kappa_u^2 V^2 (2/3) \int_0^{s/R} x^{-1/3} c_d (b \operatorname{Re}^{-3/4}/x) c_e(x) dx$ .

We now seek to derive an expression for  $\tau$ , the shear stress on the wall of the pipe. We assume a viscous layer of constant thickness  $a\eta$ , where a is a dimensionless constant, and call W a wetted surface parallel to the peaks of the viscous layer (Fig. 2). Then,  $\tau$  is effected by momentum transfer across W. Above W, the velocity of the flow scales with V, and the fluid carries a high horizontal momentum per unit volume (~  $\rho V$ ). Below W, the velocity of the flow is negligible, and the fluid carries a negligible horizontal momentum per unit volume. Now consider an eddy that straddles the wetted surface W. This eddy transfers fluid of high horizontal momentum downwards across W, and fluid of negligible horizontal momentum upwards across W. The net rate of transfer of momentum across W is set by the velocity normal to W, which velocity is provided by the eddy. Therefore, if  $v_n$  denotes the velocity normal to W provided by the *dominant* eddy that straddles W, then the shear stress effected by momentum transfer across W scales in the form  $\tau \sim \rho V v_n$ .

In order to identify the dominant eddy that straddles W, let us denote by  $s = r + a\eta$  the size of the largest eddy that fits the coves between successive roughness elements. Eddies much larger than s can provide only a negligible velocity normal to W. (This observation is purely a matter of geometry.) On the other hand, eddies smaller than s can provide a sizable velocity normal to W. Nevertheless, if these eddies are much smaller than s, their velocities are overshadowed by the velocity of the eddy of size s. Thus,  $v_n$  scales with  $u_s$ , which is the velocity of the eddy of size s, and the dominant eddy is the largest eddy that fits the coves between successive roughness elements. We conclude that  $\tau \sim \rho V u_s$ , or  $\tau = \kappa_{\tau} \rho V u_s$ (where  $\kappa_{\tau}$  is a dimensionless constant of order 1), and therefore  $f = \kappa_{\tau} u_s/V$  or

$$f = K \left( \int_0^{s/R} x^{-1/3} c_d (b \operatorname{Re}^{-3/4}/x) c_e(x) dx \right)^{1/2},$$
(1)

where  $K \equiv \kappa_{\tau} \kappa_u \sqrt{2/3}$ ,  $s/R = r/R + ab \operatorname{Re}^{-3/4}$ , and  $b \equiv (\kappa_{\varepsilon} \kappa_u^3)^{-1/4}$ . Equation (1) gives f as an explicit function of the Reynolds number Re and the roughness r/R.

To evaluate computationally the integral of (1), we set  $\beta = 2.1$ ,  $\gamma = 6.783$  (the values given in [12]), a = 5 ( $5\eta$  being a common estimation of the thickness of the viscous layer),  $\kappa_{\varepsilon} = 5/4$  (a value that follows from Kolmogórov's four-fifth law [15]),  $\kappa_u = 0.036$  (0.036  $\pm$ 0.005 being the value measured in pipe flow by Antonia and Pearson [16]),  $b \equiv (\kappa_{\varepsilon} \kappa_u^3)^{-1/4} =$ 11.4, and treat  $\kappa_{\tau}$  as a free parameter (albeit a parameter constrained by theory to be of order 1). With  $\kappa_{\tau} = 0.5$  (and therefore K = 0.015), (1) gives the plots of Fig. 3. (Note that a different value of  $\kappa_{\tau}$  would give the same plots except for a vertical translation.) These plots show that (1) is in excellent qualitative agreement with Nikuradse's data, right from the onset of turbulence, including the hump and, for relatively low roughness, the bellies. These plots remain qualitatively the same even if the value of any of the parameters is changed widely. In particular, there is always a hump and there are always bellies: these are robust




FIG. 2: Schematic of the immediate vicinity of the wall with roughness elements of size r covered by a viscous layer of uniform thickness  $a\eta$ . The distance between roughness elements is about equal to the height of the roughness elements, as in Nikuradse's experiments [20]. The horizontal line is the trace of a wetted surface W tangent to the peaks of the viscous layer.

features closely connected with the overall form of the spectrum of turbulent energy. The connections will become apparent after the discussion that follows.

To help interpreting our results, we compute f without including the correction for the energetic range—that is, setting  $\gamma = 0$ . In this case, the integral of (1) may be evaluated analytically, with the result

$$f = K(r/R + ab \operatorname{Re}^{-3/4})^{1/3} \sqrt{F(y)},$$
(2)

where  $F(y) = y^{2/3}\Gamma_{-2/3}(y)$ ,  $\Gamma_{-2/3}$  is the gamma function of order -2/3, and  $y = \beta \eta/s = \beta b \operatorname{Re}^{-3/4}(r/R+ab \operatorname{Re}^{-3/4})^{-1}$ . With the same values of  $\kappa_{\tau}$ ,  $\kappa_u$ , a, b, and  $\beta$  as before, (2) gives the solid-line plots in the inset of Fig. 3. The hump is no more. We conclude that the hump relates to the energetic range. Further, with the exception of the hump at relatively low Re, the plots of (1) coincide with the plots of (2); thus, we can study (2) to reach conclusions about (1) at intermediate and high Re. For example, (2) gives  $f \sim (r/R)^{1/3}$  for  $r \gg a\eta$  and  $f \sim \operatorname{Re}^{-1/4}$  for  $r \ll a\eta$ . It follows that both (2) and (1) give a gradual transition between the empirical scalings of Blasius and Strickler [17], in accord with Nikuradse's data.

If we set  $\beta = 0$  in addition to  $\gamma = 0$ , (2) simplifies to  $f = \kappa_{\tau}\kappa_u (r/R + ab \operatorname{Re}^{-3/4})^{1/3}$ . With the same values of  $\kappa_{\tau}$ ,  $\kappa_u$ , a, and b as before, this expression gives the dashed-line plots in the inset of Fig. 3. Now the bellies are no more. We conclude that the bellies relate to the dissipative range. The dissipation depresses the values of f at relatively low and intermediate Re, leading to the formation of the bellies of Nikuradse's data.

We are ready to explain the unfolding of Nikuradse's data in terms of the varying habits of momentum transfer with increasing Re (Fig. 4). At relatively low Re, the inertial range is immature, and the momentum transfer is dominated by eddies in the energetic range,




FIG. 3: Plot of (1). Inset: Plot of (2) (no correction for the energetic range: solid lines) and plot of (2) with  $\gamma = 0$  (no correction for the energetic range and the dissipative range: dashed lines).

whose velocity scales with V, and therefore with Re. Consequently, an increase in Re leads to a more vigorous momentum transfer—and to an increase in f. This effect explains the rising part of the hump. At higher Re, the momentum transfer is dominated by eddies of size  $s \approx a\eta \gg r$ . Since  $\eta \sim \text{Re}^{-3/4}$ , with increasing Re the momentum transfer is effected by ever smaller (and slower) eddies, and f lessens as Re continues to increase. This effect explains the plunging part of the hump—the part governed by Blasius's scaling. At intermediate Re,  $s = r + a\eta$  with  $r \approx a\eta$ . Due to the decrease in  $\eta$ , s continues to lessen as Re continues to increase, but at a lower rate than before, when it was  $s \approx a\eta \gg r$ . Thus, the curve associated with r deviates from Blasius's scaling and starts to trace a belly. As  $\eta$  continues to decrease, the dominant eddies become decidedly larger than the smaller eddies in the inertial range, which is well established now, and any lingering dissipation at lengthscales larger than s must cease. This effect explains the rising part of the belly. Last, at high Re,  $s \approx r \gg a\eta$ . As Re increases further,  $\eta$  lessens and new, smaller eddies populate the flow and become jumbled with the preexisting eddies. Yet the momentum transfer continues to be dominated by eddies of size r, and f remains invariant. This effect explains Nikuradse's data at high Re, where f is governed by Strickler's scaling.

We have predicated equation (1), on the assumption that the turbulent eddies are governed by the phenomenological theory of turbulence. The theory was originally derived for isotropic and homogeneous flows, but recent research [18] suggests that it applies to much




FIG. 4: Schematic of the relations among a generic Nikuradse curve, the spectrum of turbulent energy, the size of the roughness elements, the thickness of the viscous layer, and the size of the dominant eddies.

more general flows as well. Our results indicate that even where the flow is anisotropic and inhomogeneous—as is the case in the vicinity of a wall—the theory gives an approximate solution that embodies the essential structure of the complete solution (including the correct scalings of Blasius and Strickler) and is in detailed qualitative agreement with the observed phenomenology. Remarkably, the qualitative agreement holds starting at the very onset of turbulence, in accord with experimental evidence that "in pipes, turbulence sets in suddenly and fully, without intermediate states and without a clear stability boundary" [4]. The deficiencies in quantitative agreement point to a need for corrections to account for the effect of the roughness elements on the dissipative range as well as for the effect of the overall geometry on the energetic range.

In conclusion, to a good approximation the eddies in a pipe are governed by the spectrum of turbulent energy of the phenomenological theory. The size of the eddies that dominate the momentum transfer close to the wall is set by a combination of the size of the roughness elements and the viscous lengthscale. As a result, the dependence of the turbulent friction on the roughness and the Reynolds number is a direct manifestation of the distribution of turbulent energy given by the phenomenological theory. This close relation between the turbulent friction and the phenomenological theory [19] may be summarized in the following observation: the similarity exponents of Blasius and Strickler are but recast forms of the exponent 5/3 of the Kolmogórov spectrum.

We are thankful to F. A. Bombardelli, N. Goldenfeld, and W. R. C. Phillips for a number of illuminating discussions. We are also thankful to Referee C, whose pointed criticism resulted in a much stronger paper. J. W. Phillips kindly read our manuscript and made suggestions for its improvement.

- [1] J. Jiménez, Annu. Rev. Fluid Mech. 36, 173 (2004).
- [2] M. R. Raupach, R. A. Antonia, S. Rajagopalan, Appl. Mech. Rev. 44, 1 (1991).
- [3] Reprinted in English in J. Nikuradse, NACA TM 1292 (1950).
- [4] B. Hof et al., Science **305**, 1594 (2004).
- [5] L. Prandtl, Essentials of Fluid Dynamics, (Blackie & Son, London, 3rd ed., 1953), chap. III.11.
- [6] In Nikuradse's experiments the average distance between roughness elements, λ, was about the same as the height of the roughness elements, r. This is the type of single-lengthscale roughness that concerns us here. For this type of roughness, there are always bellies in the log-log plots of f vs. Re. (For similar results on open channels, see Varwick's data in, e.g., O. Kirshmer, Revue générale de l'hydraulique **51**, 115 (1949); in French.) For more complicated types of roughness, where roughness elements of many different sizes are present (as is commonly the case in commercial pipes), the bellies may be absent (see, e.g., the paper by Kirshmer cited above) or perhaps present after all (see, e.g., C. F. Colebrook, C. M. White, Proc. Roy. Soc. London A **161**, 367 (1937)). For the latest experimental data and discussion of this issue see J. J. Allen, M. A. Shockling, and A. J. Smits, Evaluation of a universal transitional resistance diagram for pipes with honed surfaces (to appear in Phys. Fluids) and M. A. Shockling, Turbulent flow in a rough pipe, MSE Dissertation (Princeton University, 2005).
- [7] Reprinted in English in A. Strickler, Contribution to the question of a velocity formula and roughness data for streams, channels and close pipelines, translation by T. Roesgen, W. R. Brownlie (Caltech, Pasadena, 1981). The value 1/3 of the exponent of r/R in Strickler's scaling can be derived by dimensional analysis from the value 2/3 of the exponent of the hydraulic radius in Manning's empirical formula for the average velocity of the flow in a rough open channel. Manning obtained his formula independently of Strickler, on the basis of different experimental data.
- [8] See, e.g., V. T. Chow, Open-Channel Hydraulics (McGraw-Hill, New York, 1988).
- [9] L. F. Richardson, Proc. Roy. Soc. London A 110, 709 (1926).
- [10] Reprinted in English in A. N. Kolmogórov, Proc. R. Soc. London A 434, 9 (1991).
- [11] U. Frisch, *Turbulence* (Cambridge Univ. Press, Cambridge, 1995).

- [12] S. B. Pope, *Turbulent Flows* (Cambridge Univ. Press, Cambridge, 2000).
- [13] See, e.g., H. Tennekes, J. L. Lumley, A First Course in Turbulence (MIT Press, 1972).
- [14] G. I. Taylor, Proc. Roy. Soc. London A 151, 421 (1935); D. Lohse, Phys. Rev. Lett. 73, 3223 (1994). The existence of an upper bound on ε that is independent of the viscosity has been proved *mathematically*; see Doering, Ch. R. and P. Constantin, Phys. Rev. Lett. 69, 1648 (1992).
- [15] Kolmogorov's four-fifth law reads  $\overline{u_r^3} = -(4/5) \varepsilon r$ , where the left-hand side is the third-order structure function. Substituting r = R and estimating  $|\overline{u_r^3}| = u_R^3$  leads to  $\varepsilon = (5/4) u_R^3/R$ , or  $\kappa_{\varepsilon} = 5/4$ . Experimental estimates of  $\kappa_{\varepsilon}$  are O(1); see K. R. Sreenivasan, Phys. Fluids **10**, 528 (1998).
- [16] R. A. Antonia and B. R. Pearson, Flow, Turbulence and Combustion **64**, 95 (2000). For comparison, Tennekes and Lumley give  $\kappa_u = 0.033$  for the atmosphere's turbulent boundary layer [13].
- [17] G. Gioia, F. A. Bombardelli, Phys. Rev. Lett. 88, 014501 (2002).
- [18] B. Knight, L. Sirovich, Phys. Rev. Lett. 65, 1356 (1990); T. S. Lundgren, Phys. Fluids 14, 638 (2002); T. S. Lundgren, ibid. 15, 1024 (2003). Yet the view of anisotropy as a perturbation superposed on the isotropic flow (see, e.g., L. Biferale, I. Procaccia, Anisotropy in turbulent flows and in turbulent transport, arXiv:nlin.CD/0404014 (2004)) might break down close to a wall, where the exponents themselves might change (see M. Casciola, P. Gualtieri, B. Jacob, R. Piva, Phys. Rev. Lett. 95, 024503 (2005)). Nevertheless, note (i) that the exponent of the second-order structure function appears to change only by little and (ii) that the Kolmogórov exponent does give the exact scalings of Blasius and Strickler, whereas any modified exponent would not.
- [19] The close connection between the turbulent friction and the phenomenological spectrum suggests that in turbulence, just as in phase transitions, large-scale phenomena are direct manifestations of the small-scale statistics. The parallel with phase transitions has been adduced by N. Goldenfeld, who was prompted by our results to reanalyze Nikuradse's data and conclude that (2) is consistent with a turbulent analogue of Widom scaling near critical points. See N. Goldenfeld, Roughness-induced critical phenomena in a turbulent flow, arXiv:cond-mat/0509439 (2005).
- [20] Our schematic of Fig. 2 may seem to resemble the "d-type roughness" of A. E. Perry, W.

H. Schofield, and P. N. Joubert, J. Fluid Mech. **37**, 383 (1969). According to these authors, for this type of roughness the turbulent friction does not asymptotically approach a constant value at high Re. Nevertheless, as pointed out by Jimenez [1], the distinction between k-type roughness (including the type of roughness in Nikuradse's pipes) and d-type roughness appears to have been predicated on limited experimental data, and must be regarded with caution. In any case, the schematic of Fig. 2 represents the rough walls of Nikuradse's experiments [6] and does lead to predictions that are in accord with those experiments.

## List of Recent TAM Reports

No.	Authors	Title	Date
987	Phillips, W. R. C.	Langmuir circulations – <i>Surface Waves</i> (J. C. R. Hunt and S. Sajjadi, eds.), in press (2002)	Nov. 2001
988	Gioia, G., and F. A. Bombardelli	Scaling and similarity in rough channel flows – <i>Physical Review</i> <i>Letters</i> 88, 014501 (2002)	Nov. 2001
989	Riahi, D. N.	On stationary and oscillatory modes of flow instabilities in a rotating porous layer during alloy solidification – <i>Journal of Porous Media</i> 6, 1–11 (2003)	Nov. 2001
990	Okhuysen, B. S., and D. N. Riahi	Effect of Coriolis force on instabilities of liquid and mushy regions during alloy solidification – <i>Physics of Fluids</i> (submitted)	Dec. 2001
991	Christensen, K. T., and R. J. Adrian	Measurement of instantaneous Eulerian acceleration fields by particle-image accelerometry: Method and accuracy – <i>Experimental Fluids</i> (submitted)	Dec. 2001
992	Liu, M., and K. J. Hsia	Interfacial cracks between piezoelectric and elastic materials under in-plane electric loading – <i>Journal of the Mechanics and Physics of</i> <i>Solids</i> <b>51</b> , 921–944 (2003)	Dec. 2001
993	Panat, R. P., S. Zhang, and K. J. Hsia	Bond coat surface rumpling in thermal barrier coatings – <i>Acta Materialia</i> <b>51</b> , 239–249 (2003)	Jan. 2002
994	Aref, H.	A transformation of the point vortex equations – <i>Physics of Fluids</i> <b>14</b> , 2395–2401 (2002)	Jan. 2002
995	Saif, M. T. A, S. Zhang, A. Haque, and K. J. Hsia	Effect of native $Al_2O_3$ on the elastic response of nanoscale aluminum films – <i>Acta Materialia</i> <b>50</b> , 2779–2786 (2002)	Jan. 2002
996	Fried, E., and M. E. Gurtin	A nonequilibrium theory of epitaxial growth that accounts for surface stress and surface diffusion – <i>Journal of the Mechanics and Physics of Solids</i> <b>51</b> , 487–517 (2003)	Jan. 2002
997	Aref, H.	The development of chaotic advection – <i>Physics of Fluids</i> <b>14</b> , 1315–1325 (2002); see also <i>Virtual Journal of Nanoscale Science and Technology</i> , 11 March 2002	Jan. 2002
998	Christensen, K. T., and R. J. Adrian	The velocity and acceleration signatures of small-scale vortices in turbulent channel flow – <i>Journal of Turbulence</i> , in press (2002)	Jan. 2002
999	Riahi, D. N.	Flow instabilities in a horizontal dendrite layer rotating about an inclined axis – <i>Journal of Porous Media</i> , in press (2003)	Feb. 2002
1000	Kessler, M. R., and S. R. White	Cure kinetics of ring-opening metathesis polymerization of dicyclopentadiene – <i>Journal of Polymer Science A</i> <b>40</b> , 2373–2383 (2002)	Feb. 2002
1001	Dolbow, J. E., E. Fried, and A. Q. Shen	Point defects in nematic gels: The case for hedgehogs – <i>Archive for Rational Mechanics and Analysis</i> <b>177</b> , 21–51 (2005)	Feb. 2002
1002	Riahi, D. N.	Nonlinear steady convection in rotating mushy layers – <i>Journal of Fluid Mechanics</i> <b>485</b> , 279–306 (2003)	Mar. 2002
1003	Carlson, D. E., E. Fried, and S. Sellers	The totality of soft-states in a neo-classical nematic elastomer – <i>Journal of Elasticity</i> <b>69</b> , 169–180 (2003) with revised title	Mar. 2002
1004	Fried, E., and R. E. Todres	Normal-stress differences and the detection of disclinations in nematic elastomers – <i>Journal of Polymer Science B: Polymer Physics</i> <b>40</b> , 2098–2106 (2002)	June 2002
1005	Fried, E., and B. C. Roy	Gravity-induced segregation of cohesionless granular mixtures – Lecture Notes in Mechanics, in press (2002)	July 2002
1006	Tomkins, C. D., and R. J. Adrian	Spanwise structure and scale growth in turbulent boundary layers – <i>Journal of Fluid Mechanics</i> (submitted)	Aug. 2002
1007	Riahi, D. N.	On nonlinear convection in mushy layers: Part 2. Mixed oscillatory and stationary modes of convection – <i>Journal of Fluid Mechanics</i> <b>517</b> , 71–102 (2004)	Sept. 2002
1008	Aref, H., P. K. Newton, M. A. Stremler, T. Tokieda, and D. L. Vainchtein	Vortex crystals – <i>Advances in Applied Mathematics</i> <b>39</b> , in press (2002)	Oct. 2002

## List of Recent TAM Reports (cont'd)

No.	Authors	Title	Date
1009	Bagchi, P., and S. Balachandar	Effect of turbulence on the drag and lift of a particle – <i>Physics of Fluids</i> , in press (2003)	Oct. 2002
1010	Zhang, S., R. Panat, and K. J. Hsia	Influence of surface morphology on the adhesive strength of aluminum/epoxy interfaces – <i>Journal of Adhesion Science and Technology</i> <b>17</b> , 1685–1711 (2003)	Oct. 2002
1011	Carlson, D. E., E. Fried, and D. A. Tortorelli	On internal constraints in continuum mechanics – <i>Journal of Elasticity</i> <b>70</b> , 101–109 (2003)	Oct. 2002
1012	Boyland, P. L., M. A. Stremler, and H. Aref	Topological fluid mechanics of point vortex motions – <i>Physica D</i> <b>175</b> , 69–95 (2002)	Oct. 2002
1013	Bhattacharjee, P., and D. N. Riahi	Computational studies of the effect of rotation on convection during protein crystallization – <i>International Journal of Mathematical</i> <i>Sciences,</i> in press (2004)	Feb. 2003
1014	Brown, E. N., M. R. Kessler, N. R. Sottos, and S. R. White	<i>In situ</i> poly(urea-formaldehyde) microencapsulation of dicyclopentadiene – <i>Journal of Microencapsulation</i> (submitted)	Feb. 2003
1015	Brown, E. N., S. R. White, and N. R. Sottos	Microcapsule induced toughening in a self-healing polymer composite – <i>Journal of Materials Science</i> (submitted)	Feb. 2003
1016	Kuznetsov, I. R., and D. S. Stewart	Burning rate of energetic materials with thermal expansion – <i>Combustion and Flame</i> (submitted)	Mar. 2003
1017	Dolbow, J., E. Fried, and H. Ji	Chemically induced swelling of hydrogels – <i>Journal of the Mechanics and Physics of Solids,</i> in press (2003)	Mar. 2003
1018	Costello, G. A.	Mechanics of wire rope – Mordica Lecture, Interwire 2003, Wire Association International, Atlanta, Georgia, May 12, 2003	Mar. 2003
1019	Wang, J., N. R. Sottos, and R. L. Weaver	Thin film adhesion measurement by laser induced stress waves – Journal of the Mechanics and Physics of Solids (submitted)	Apr. 2003
1020	Bhattacharjee, P., and D. N. Riahi	Effect of rotation on surface tension driven flow during protein crystallization – <i>Microgravity Science and Technology</i> <b>14</b> , 36–44 (2003)	Apr. 2003
1021	Fried, E.	The configurational and standard force balances are not always statements of a single law – <i>Proceedings of the Royal Society</i> (submitted)	Apr. 2003
1022	Panat, R. P., and K. J. Hsia	Experimental investigation of the bond coat rumpling instability under isothermal and cyclic thermal histories in thermal barrier systems – <i>Proceedings of the Royal Society of London A</i> <b>460</b> , 1957–1979 (2003)	May 2003
1023	Fried, E., and M. E. Gurtin	A unified treatment of evolving interfaces accounting for small deformations and atomic transport: grain-boundaries, phase transitions, epitaxy – <i>Advances in Applied Mechanics</i> <b>40</b> , 1–177 (2004)	May 2003
1024	Dong, F., D. N. Riahi, and A. T. Hsui	On similarity waves in compacting media – <i>Horizons in World Physics</i> <b>244</b> , 45–82 (2004)	May 2003
1025	Liu, M., and K. J. Hsia	Locking of electric field induced non-180° domain switching and phase transition in ferroelectric materials upon cyclic electric fatigue – <i>Applied Physics Letters</i> <b>83</b> , 3978–3980 (2003)	May 2003
1026	Liu, M., K. J. Hsia, and M. Sardela Jr.	In situ X-ray diffraction study of electric field induced domain switching and phase transition in PZT-5H— <i>Journal of the American</i> <i>Ceramics Society</i> (submitted)	May 2003
1027	Riahi, D. N.	On flow of binary alloys during crystal growth – <i>Recent Research Development in Crystal Growth</i> , in press (2003)	May 2003
1028	Riahi, D. N.	On fluid dynamics during crystallization – <i>Recent Research Development in Fluid Dynamics,</i> in press (2003)	July 2003
1029	Fried, E., V. Korchagin, and R. E. Todres	Biaxial disclinated states in nematic elastomers – <i>Journal of Chemical Physics</i> <b>119</b> , 13170–13179 (2003)	July 2003
1030	Sharp, K. V., and R. J. Adrian	Transition from laminar to turbulent flow in liquid filled microtubes – <i>Physics of Fluids</i> (submitted)	July 2003

## List of Recent TAM Reports (cont'd)

No.	Authors	Title	Date
1031	Yoon, H. S., D. F. Hill, S. Balachandar, R. J. Adrian, and M. Y. Ha	Reynolds number scaling of flow in a Rushton turbine stirred tank: Part I – Mean flow, circular jet and tip vortex scaling – <i>Chemical</i> <i>Engineering Science</i> (submitted)	Aug. 2003
1032	Raju, R., S. Balachandar, D. F. Hill, and R. J. Adrian	Reynolds number scaling of flow in a Rushton turbine stirred tank: Part II – Eigen-decomposition of fluctuation – <i>Chemical Engineering</i> <i>Science</i> (submitted)	Aug. 2003
1033	Hill, K. M., G. Gioia, and V. V. Tota	Structure and kinematics in dense free-surface granular flow – <i>Physical Review Letters</i> <b>91</b> , 064302 (2003)	Aug. 2003
1034	Fried, E., and S. Sellers	Free-energy density functions for nematic elastomers – <i>Journal of the Mechanics and Physics of Solids</i> <b>52</b> , 1671–1689 (2004)	Sept. 2003
1035	Kasimov, A. R., and D. S. Stewart	On the dynamics of self-sustained one-dimensional detonations: A numerical study in the shock-attached frame – <i>Physics of Fluids</i> (submitted)	Nov. 2003
1036	Fried, E., and B. C. Roy	Disclinations in a homogeneously deformed nematic elastomer – <i>Nature Materials</i> (submitted)	Nov. 2003
1037	Fried, E., and M. E. Gurtin	The unifying nature of the configurational force balance – <i>Mechanics of Material Forces</i> (P. Steinmann and G. A. Maugin, eds.), in press (2003)	Dec. 2003
1038	Panat, R., K. J. Hsia, and J. W. Oldham	Rumpling instability in thermal barrier systems under isothermal conditions in vacuum – <i>Philosophical Magazine</i> , in press (2004)	Dec. 2003
1039	Cermelli, P., E. Fried, and M. E. Gurtin	Sharp-interface nematic-isotropic phase transitions without flow – <i>Archive for Rational Mechanics and Analysis</i> <b>174</b> , 151–178 (2004)	Dec. 2003
1040	Yoo, S., and D. S. Stewart	A hybrid level-set method in two and three dimensions for modeling detonation and combustion problems in complex geometries – <i>Combustion Theory and Modeling</i> (submitted)	Feb. 2004
1041	Dienberg, C. E., S. E. Ott-Monsivais, J. L. Ranchero, A. A. Rzeszutko, and C. L. Winter	Proceedings of the Fifth Annual Research Conference in Mechanics (April 2003), TAM Department, UIUC (E. N. Brown, ed.)	Feb. 2004
1042	Kasimov, A. R., and D. S. Stewart	Asymptotic theory of ignition and failure of self-sustained detonations – <i>Journal of Fluid Mechanics</i> (submitted)	Feb. 2004
1043	Kasimov, A. R., and D. S. Stewart	Theory of direct initiation of gaseous detonations and comparison with experiment – <i>Proceedings of the Combustion Institute</i> (submitted)	Mar. 2004
1044	Panat, R., K. J. Hsia, and D. G. Cahill	Evolution of surface waviness in thin films via volume and surface diffusion— <i>Journal of Applied Physics</i> (submitted)	Mar. 2004
1045	Riahi, D. N.	Steady and oscillatory flow in a mushy layer – <i>Current Topics in Crystal Growth Research,</i> in press (2004)	Mar. 2004
1046	Riahi, D. N.	Modeling flows in protein crystal growth – <i>Current Topics in Crystal Growth Research,</i> in press (2004)	Mar. 2004
1047	Bagchi, P., and S. Balachandar	Response of the wake of an isolated particle to isotropic turbulent cross-flow – <i>Journal of Fluid Mechanics</i> (submitted)	Mar. 2004
1048	Brown, E. N., S. R. White, and N. R. Sottos	Fatigue crack propagation in microcapsule toughened epoxy – <i>Journal of Materials Science</i> (submitted)	Apr. 2004
1049	Zeng, L., S. Balachandar, and P. Fischer	Wall-induced forces on a rigid sphere at finite Reynolds number – <i>Journal of Fluid Mechanics</i> (submitted)	May 2004
1050	Dolbow, J., E. Fried, and H. Ji	A numerical strategy for investigating the kinetic response of stimulus-responsive hydrogels – <i>Computer Methods in Applied Mechanics and Engineering</i> <b>194</b> , 4447–4480 (2005)	June 2004
1051	Riahi, D. N.	Effect of permeability on steady flow in a dendrite layer – <i>Journal of Porous Media</i> , in press (2004)	July 2004

List of Recent TAM Reports (cont'd)

No.	Authors	Title	Date
	Cermelli, P., E. Fried, and M. E. Gurtin	Transport relations for surface integrals arising in the formulation of balance laws for evolving fluid interfaces – <i>Journal of Fluid Mechanics</i> (submitted)	Sept. 2004
	Stewart, D. S., and A. R. Kasimov	Theory of detonation with an embedded sonic locus – <i>SIAM Journal on Applied Mathematics</i> (submitted)	Oct. 2004
]	Stewart, D. S., K. C. Tang, S. Yoo, M. Q. Brewster, and I. R. Kuznetsov	Multi-scale modeling of solid rocket motors: Time integration methods from computational aerodynamics applied to stable quasi-steady motor burning – <i>Proceedings of the 43rd AIAA Aerospace</i> <i>Sciences Meeting and Exhibit</i> (January 2005), Paper AIAA-2005-0357 (2005)	Oct. 2004
	Ji, H., H. Mourad, E. Fried, and J. Dolbow	Kinetics of thermally induced swelling of hydrogels – <i>International</i> <i>Journal of Solids and Structures</i> (submitted)	Dec. 2004
	Fulton, J. M., S. Hussain, J. H. Lai, M. E. Ly, S. A. McGough, G. M. Miller, R. Oats, L. A. Shipton, P. K. Shreeman, D. S. Widrevitz, and E. A. Zimmermann	Final reports: Mechanics of complex materials, Summer 2004 (K. M. Hill and J. W. Phillips, eds.)	Dec. 2004
	Hill, K. M., G. Gioia, and D. R. Amaravadi	Radial segregation patterns in rotating granular mixtures: Waviness selection – <i>Physical Review Letters</i> <b>93</b> , 224301 (2004)	Dec. 2004
1058 ]	Riahi, D. N.	Nonlinear oscillatory convection in rotating mushy layers – <i>Journal of Fluid Mechanics</i> (submitted)	Dec. 2004
	Okhuysen, B. S., and D. N. Riahi	On buoyant convection in binary solidification – <i>Journal of Fluid Mechanics</i> (submitted)	Jan. 2005
9	Brown, E. N., S. R. White, and N. R. Sottos	Retardation and repair of fatigue cracks in a microcapsule toughened epoxy composite – Part I: Manual infiltration – <i>Composites Science and Technology</i> (submitted)	Jan. 2005
9	Brown, E. N., S. R. White, and N. R. Sottos	Retardation and repair of fatigue cracks in a microcapsule toughened epoxy composite – Part II: <i>In situ</i> self-healing – <i>Composites Science and Technology</i> (submitted)	Jan. 2005
]	Berfield, T. A., R. J. Ong, D. A. Payne, and N. R. Sottos	Residual stress effects on piezoelectric response of sol-gel derived PZT thin films – <i>Journal of Applied Physics</i> (submitted)	Apr. 2005
] ]	Anderson, D. M., P. Cermelli, E. Fried, M. E. Gurtin, and G. B. McFadden	General dynamical sharp-interface conditions for phase transformations in viscous heat-conducting fluids – <i>Journal of Fluid Mechanics</i> (submitted)	Apr. 2005
	Fried, E., and M. E. Gurtin	Second-gradient fluids: A theory for incompressible flows at small length scales – <i>Journal of Fluid Mechanics</i> (submitted)	Apr. 2005
	Gioia, G., and F. A. Bombardelli	Localized turbulent flows on scouring granular beds – <i>Physical Review Letters,</i> in press (2005)	May 2005
1066 ]	Fried, E., and S. Sellers	Orientational order and finite strain in nematic elastomers – <i>Journal of Chemical Physics</i> <b>123</b> , 044901 (2005)	May 2005
	Chen, YC., and E. Fried	Uniaxial nematic elastomers: Constitutive framework and a simple application – <i>Proceedings of the Royal Society of London A</i> (submitted)	June 2005
1068 ]	Fried, E., and S. Sellers	Incompatible strains associated with defects in nematic elastomers – <i>Physical Review Letters</i> (submitted)	Aug. 2005
1069 (	Gioia, G., and X. Dai	Surface stress and reversing size effect in the initial yielding of ultrathin films – <i>Journal of Applied Mechanics,</i> in press (2005)	Aug. 2005
	Gioia, G., and P. Chakraborty	Turbulent friction in rough pipes and the energy spectrum of the phenomenological theory – <i>arXiv:physics</i> 0507066 v1 8 Jul 2005	Aug. 2005