

#### Purdue University Purdue e-Pubs

LARS Symposia

Laboratory for Applications of Remote Sensing

1-1-1980

# Interactive Processing of Landsat Image for Morphopedological Studies

Denis Chaume

Nguyen Phu Thien

Follow this and additional works at: http://docs.lib.purdue.edu/lars\_symp

Chaume, Denis and Thien, Nguyen Phu, "Interactive Processing of Landsat Image for Morphopedological Studies" (1980). LARS Symposia. Paper 358. http://docs.lib.purdue.edu/lars\_symp/358

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

### Symposium on

### **Machine Processing of**

### **Remotely Sensed Data**

and

### **Soil Information Systems**

and

### **Remote Sensing and Soil Survey**

June 3-6, 1980

## **Proceedings**

The Laboratory for Applications of Remote Sensing

Purdue University West Lafayette Indiana 47907 USA

IEEE Catalog No. 80CH1533-9 MPRSD

Copyright © 1980 IEEE The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

#### INTERACTIVE PROCESSING OF LANDSAT IMAGE FOR MORPHOPEDOLOGICAL STUDIES

DENIS CHAUME AND NGUYEN PHU THIEN Scientific Center of IBM-France

#### I/ INTRODUCTION

With the increasing amount of data made available from Landsat there is a clear need for an integrated method of soil mapping in which these data can be exploited to provide valuable information for the various stages of conventional soil mapping:

- preliminary study

- detail mapping

- verification of the results of photo-interpretation

- updating of soil map by temporal study

A joint research study was initiated between the Scientific Center of IBM France and IRAT, the Tropical Agriculture Research Institute to investigate these possible contributions.

#### II/ BACKGROUND and OBJECTIVES

In developping their soil map, IRAT adopts a working method consisting of a study of the overall pedogenesis and morphology of the region followed by an in-situ soil survey and profile sampling. The soil is then classified into morphopedological units according both to the nature of the soil and the final usage of the map.

In the present study following morphopedological units (fig. 1) were studied to determine the possible land use and the danger of erosion:

1/ Sandstone hill
2/ Ferrite hardpan
3/ Low glacis
4/ Cultivated area

A method of analysing the Landsat image was then seeked:

to characterise the radiometric signatures of these morphopedological units

- to study the variation of these signatures in space and in time.

- and finally to obtain a working method of image processing and a number of keys for interpreting Landsat images.

CH1533-9/80/0000-0195 \$00.75 © 1980 IEEE

1980 Machine Processing of Remotely Sensed Data Symposium

Contraction of the second



Figure 2 : Morphopedological Map



Figure 1 : Principal landscape-units of the Mandingue plateau in Mali.

III/ METHODOLOGY

The study was carried out by using ERMAN II (Earth Resource Management System ) and a new interactive image processing system the developped at Scientific Center, IBM France. These two systems and their interface provided the necessary tools for displaying, manipulating, and processing of the image.

The area chosen for the study was in Gale on the Mandingue plateau in Mali. This area had been studied previously by IRAT (Raunet, 1975 and Brouwers, 1976) and a morpho pedological map was produced (fig. 2). Images from 1972, 1973 and 1976 for this area were used.

Training fields belonging to different morphopedological the units were determined from a series of 4 aerial photographs coverring the central part of the studied (fig. 3). A model of zone transformation between corresponding co-ordinates on photograph and image was then calculated from a set of landmarks. The co-ordinates of the subimages were obtained by applying the model transformation of to the

co-ordinates on photographs. The image to UTM (Universal Tranverse Mercator projection) registration was avoided two important normally used intentionally for reasons. Firstly to avoid errors from the interpolation required in image re-sampling, and secondly to reduce the errors due to the use of a global model of deformation for the whole image. In our study, separate models of deformation were calculated for smaller areas corresponding to each aerial photograph.

The first operation was then the principal component analysis of the original Landsat channels (fig. 4a-b). Since most of the information was contained in the first two channels (95 percent of the total variance), they were used instead of the original channels These facts, mentioned also by other researcher (Lowitz, 1976) and are illustrated clearly in fig 4c.

The representation on color TV screen of the first component (CF1) as brightness and the second (CF2) as color also gave a better visualisation for the pedologists to indentify the different morphopedological units than the normal false color visualisation of the original channels (Chaume, 1977).

1980 Machine Processing of Remotely Sensed Data Symposium

And Address of the Ad



Figure 3 : Examples of training fields drawn on an aerial photograph.

1980 Machine Processing of Remotely Sensed Data Symposium

198

![](_page_6_Picture_0.jpeg)

a, rirst component

![](_page_6_Picture_2.jpeg)

b) Second component

![](_page_6_Figure_4.jpeg)

c) Distribution of the original bands in plans F1/F2 and F3/F4.

Figure 4 : Principal component analysis

The distribution domains of the morphopedological units were then determined in the two-dimensional histogram of the two components CF1 and CF2 (fig 5). Each pixel in the study area was then classified according to their respective position in the distribution domains

The classified image was then deskewed and re-sampled at the same scale as the morphopedological map of IRAT. The classified image was then compared with the groundtruth map and the aerial photographs. The subimages corresponding to the training fields were re-adjusted, the distribution domains re-calculated and the classified image re-produced accordingly. The process was repeated interactively until a good fit was obtained between classified image and groundtruth map for the study area

The final distribution domains as obtained were then used to extrapolate the result into a larger area around the study area The final classified image produced at the same scale as the morpho-pedological map and the photographs was then viewed on the color or TV screen (fig. 6) or produced as gray level map by the IBM 3800 printer.

IV/ RESULTS AND DISCUSSIONS.

The results obtained proved that it was possible to localise the distribution domains of different morphopedological units due to:

- The separation of the distribution domains in the two-dimensional histogram

- The consistant location of these distribution domains in areas surrounding the study area

These are valuable assets for the spatial extrapolation of the results. An attempt was made to study the same area using images available at different dates but there existed two main difficulties: the poor quality of the Landsat-I images taken on 31 OCT 1972 and 29 APR 1973, the presence of haze in the rainy season also had an unacceptable influence on the orientation of the principal component axes.

The image used (02 FEB 1976) corresponds to the dry season in Mali, and a small percentage of the area studied(40x30 km) was covered with bush fire. These bush fires were however clealy indentified. The morphopedological units classified most accurately was the ferrite hardpan, particularly where sharp cliff exist. On the contrary, the ferrite hardpan slope were in some areas classified as low-glacis, the limit between the as hardpan and the low-glacis are difficult to locate accurately. The low-glacis extending from the riverside up to the hardpan slope are in general well classified. Cultivated areas were detected by the presence of bare soil (characterized by their extreme values in the first and second principal components), these areas also revealed the humain activities in nearby villages. The sandstone hills were very similar in their spectral signature with the river but their presence was detected by their massive grouping.

Low-glacis with erosion was the most difficult unit to characterise because of their small dimensions (1 to 3 pixels wide). It was difficult to locate these fields and to obtain a reasonable population to represent the unit accurately. Another approach in which their textural properties are analysed was neccessary to study these small. Works in this direction are being followed at the IBM Scientific Center at Paris.

V/ CONCLUSIONS

With the encouraging results, the present study has now passed on to the second phase where

![](_page_8_Figure_0.jpeg)

Figure 5 : Two-dimensionnal histogram with landscape unit distribution domains. (1: low-glacis, 2: ferrite hardpan, 3: transition area, 4: cultivated area)

1980 Machine Processing of Remotety Sensed Data Symposium

201

![](_page_9_Picture_0.jpeg)

Figure 6 : Classified image as window TV screen (blank: low-glacis, dark grey: ferrite hardpan, black: cultivated area, light grey: unclassified).

the established procedures will be applied to another region of Africa - Upper Volta. In this study the area to be studied will cover a more extensive area including an area where detail soils map is not available.

It remains to improve the accuracy and the generality of the method and two parrallel aproaches are required.

Firstly to exploit fully the satellite image the choice of the morphopedological units proved to be vital. These units should be orientated to the properties of the soil surface such 35 the vegetation, soil moisture, humain activities, erosion ог other factors which can be revealed by their different reflectances.

On the other hand, a further study of the distribution domains of typical morphopedological units should be followed and a method of transforming these distribution domains according to the variation of the principal component axes should be derived to make these keys of interpretation applicable both for spatial and temporal extrapolation. Some encouraging results obtained in this direction are presented in another paper (Oudin M.F, 1980).

ACKNOWLEDGEMENTS						
T	he	results	of	this	research	
were	ac	hieved	from	the	common	

effort of all the members of the Image Proceesing Research Group at the Scientific Center and the Departement of Pedology of IRAT, to whom the authors are most gratefull in particular Messrs J. Kilian and G. Savary.

#### REFERENCE

- Brouwers M. and Raunet M. (1976) Etude morphologique du Plateau Mandingue en vue de son developpement agricole. IRAT, 1976.
- Chaume D. (1977) Image visualisation on TV screen Digital Image Processing and Analysis (ed. JC Simon & A Rosenfeld) NATO-ASI. Noordhoff Leyden 1977.
- Lowitz G.E (1976) Traitement des Images Multispectrales. Automatisme,XXI,3-4,Mars/Avril 1976.
- Oudin M.F & Chaume D. (1980) Une aide a la photo interpretation des images Landsat XIV Congress of ISP -Hamburg 13-26 july 1980
- Raunet M. (1975) Plateau Mandingue (Mali)-Reconnaissance geomorphologique. IRAT, 1975.