



Virginia Commonwealth University  
VCU Scholars Compass

---

Biology and Medicine Through Mathematics  
Conference

2016

---

May 21st, 5:30 PM - 8:00 PM

# A computational model of neurons in the Thalamic Reticular Nucleus

Xinxuan Li

*University of Maryland - Baltimore County, [xl1@umbc.edu](mailto:xl1@umbc.edu)*

Follow this and additional works at: <http://scholarscompass.vcu.edu/bamm>

---

<http://scholarscompass.vcu.edu/bamm/2016/May21/32>

This Event is brought to you for free and open access by the Dept. of Mathematics and Applied Mathematics at VCU Scholars Compass. It has been accepted for inclusion in Biology and Medicine Through Mathematics Conference by an authorized administrator of VCU Scholars Compass. For more information, please contact [libcompass@vcu.edu](mailto:libcompass@vcu.edu).

# A computational model of neurons in the Thalamic Reticular Nucleus

XINXUAN LI<sup>1</sup>, KATHLEEN HOFFMAN<sup>1</sup>, ANTHONY PARK<sup>2</sup>, AND ASAF KELLER<sup>2</sup>

<sup>1</sup>*University of Maryland, Baltimore County.*

<sup>2</sup>*University of Maryland, Baltimore.*

## ABSTRACT

The thalamic reticular nucleus (TRN), a shell of GABAergic neurons that surrounds the dorsal thalamus, generates and sustains rhythmic oscillations called sleep spindles. Recent evidence has shown that TRN neurons are connected by chemical synapses and gap junctions. Moreover, the primary chemical synapses in TRN modulated by GABA<sub>A</sub> receptors, have recently been shown to be excitatory instead of inhibitory, as previously suggested. In order to understand how TRN neurons generate and sustain sleep spindles, we develop a Hodgkin-Huxley based computational model of a TRN neuron with the currents and parameters supported by recent experimental data. The resulting computational model of a single TRN neuron demonstrates bistable behavior. We also introduce the large T-window current model and the small T-window current model as a means of reflecting the known heterogeneity of TRN neurons. To understand the network properties of TRN, we connect two model neurons with excitatory GABA<sub>A</sub>, inhibitory GABA<sub>B</sub> synapses, and gap junctions. The computational model of excitatory GABA<sub>A</sub> synapses and gap junction are consistent with experimental results. We also explore computational models of GABA<sub>B</sub> synapses in TRN neuron. Both computational simulations and experimental results indicate that TRN requires input from the thalamocortical circuit to generate oscillations.