

APPLICABILITY OF FEM FOR NONLINEAR SEISMIC ANALYSIS OF URM STRUCTURES WITH TIMBER DIAPHRAGMS ACCOUNTING FOR WALL-TO-FLOOR/ROOF CONNECTIONS

Maria Pia Ciocci¹, Rui Marques² and Paulo B. Lourenço²

1: Institute for Sustainability and Innovation in Structural Engineering (ISISE)
Department of Civil Engineering, University of Minho
e-mail: mariapiaciocci@gmail.com

2: Institute for Sustainability and Innovation in Structural Engineering (ISISE) and
Institute of Science and Innovation for Bio-Sustainability (IB-S)
Department of Civil Engineering, University of Minho
e-mail: marquesmnc@sapo.pt, pbl@civil.uminho.pt

Keywords: Unreinforced masonry buildings, finite element modelling, timber diaphragms, wall-to-floor/roof connections, benchmark shaking table test, seismic response

Abstract. *The seismic behaviour of unreinforced masonry (URM) structures is generally governed by a complex interaction between the out-of-plane and in-plane responses of the walls, depending on the in-plane stiffness of timber diaphragms and the efficiency of wall-to-floor/roof connections. The presence of timber diaphragms, which are typically characterized by low in-plane stiffness and poor connection to the masonry walls, adds hindrances to the numerical modelling and analysis as well as to the structural assessment of URM structures under seismic actions. This work aims at developing a numerical study to investigate the seismic behaviour of URM buildings with timber diaphragms accounting for wall-to-floor/roof connections.*

The reference model used in this study is a full-scale two-storey prototype building which was subjected to shaking table tests at the European Centre for Training and Research in Earthquake Engineering (EUCENTRE), in Italy. Refined finite element (FE) models have been developed in DIANA software under different modelling assumptions for the timber diaphragms and their connections to the masonry walls. Eigenvalue, nonlinear static and nonlinear dynamic analyses have been carried out to calibrate and validate the models with respect to the experimental data. The results are discussed in terms of: (1) suitable modelling assumptions for the vertical structure and timber diaphragms; (2) derivation of mechanical properties for the timber diaphragms from available experimental data; (3) accuracy in predicting the experimental behaviour of the prototype building when refined FE modelling is used; and (4) advantages and limitations of applying nonlinear static and dynamic analyses.

Acknowledgement. The first author gratefully acknowledges the financial support from the Portuguese Foundation for Science and Technology (FCT) within the InfraRisk- doctoral programme, through the grant PD/BD/127910/2016. This work was further supported by FCT through ISISE (project UID/ECI/04029) and the grant SFRH/BPD/94677/2013 to the second author.